

HEADING EXPLANATIONS :

Avail = Actual AVAILABLE stock for sale (include stock to arrive, stock in production, less customers forward order)
Un = Unit of supply / pricing (M = Metre, M2 = Square Metre, Kg = Kilogram etc.)
Price = List Price for 1 Unit in NZ\$ (quantity prices will be supplied based upon customer requirements)
TypeNo = CASA's Product reference number (either the manufacturers OEM Number or produced from CASA's Part Number Composer see separate chart/table for explanation of the rules and nomenclature)

Cables : LOOK UP & ALPHA Listing

	P2I	P3I	TypeNo	Description	Price	Un	Avail
1	C	MC	SUNDRY-MULTICORE	Sundry Multicore Cable - not elsewhere listed	9.56	M	0
2	C	MC	NK2-2-6-Y	Microphone Cable 2 core flexible screened PROFESSIONAL Audio Quality, Yellow	2.29	M	0
3	C	MC	NK2-2-6	Microphone Cable 2 core flexible screened PROFESSIONAL Audio Quality, Black	2.29	M	0
4	C	MC	MIC-2C+S-GR	Microphone Cable 2 core flexible screened Audio Lead Quality, Grey	3.75	M	0
5	C	MC	LSMHOF-44-M24643/7-08UN	Multicore cable 44 way to M24643/7-08UN	45.02	FT	0
6	C	MC	FC-12P-COL	12 Twisted Pair FLAT Ribbon Signal Cable 28mm Wide	9.10	M	0
7	C	MC	AC-2C+S-BK	Audio Cable, 2 core + Braided screen 3mm OD Black (100m reels)	0.96	M	700
8	C	MC	9841(BELDEN)	Shielded Twisted Pair 120 Ohm Data Cable for RS-485 (Braid + Screen) etc.	6.27	M	0
9	C	MC	9783(R)	60 Way Screened Signal/Control Cable, Conductors = 0.63mm0 Solid Copper, Insulation = Multicolour PVC, Screen = Tinned Copper, Jacket = Blac	0.00	D	0
10	C	MC	9783(M)	60 Way Screened Cable 15mm OD	17.29	M	0
11	C	MC	8C+FW&DW-24AWG	8 Core Screened (Foil & Drain Wire), Flexible, 6.6mm OD, Beige	2.80	M	78
12	C	MC	8+S(M)	8 Way Screened Flexible Signal Cable 6~9mm OD	9.56	M	6.8
13	C	MC	6C-0.2MM(WHITE)	6 Way Stranded 7x0.2mm colourcoded Flexible Security Cable - 100M drums	22.17	R	57
14	C	MC	6C	6 Way Flexible Signal/Control Cable	0.00	M	200
15	C	MC	60F+S(R)	60 Way Screened Flexible Signal Cable, Conductord = 14/0.0076" (16/0.2mm) CU, Screening = Tinned Copper, Insulation = Multicolour PVC, Jac	0.00	D	0
16	C	MC	60F+S(M)	60 Way Screened Flexible Signal Cable	0.00	M	0
17	C	MC	5P+S(R)	5 Individual Twisted Pair s 1/0.063 (1.6mm) Grey PVC Shieth 8mm OD	5.73	D	250
18	C	MC	50/0.4-PCW	50 Pair Jelly Filled Telecom cable on wooden drum	5.26	M	250
19	C	MC	4x0.06mm(Gy)	Grey 4 core circular signal 2/0.10 Screened	1.00	M	50
20	C	MC	4x0.06mm(C)	Grey 4 core Individual Screen Signal 100m	63.70	C	8
21	C	MC	4P+FW+DW(VW-1SC)	4 Pair Signal/Control Cable 24AWG Foil Wrap + DW - Beigue 6.35 dia	3.82	M	242
22	C	MC	4C-2.5MMTRS(M)	4 Way Tough RUBBER Sheathed Cable 10A (Cut lengths)	7.64	M	0
23	C	MC	4C-2.5MM-TPS(M)	4 Way Tough Plastic Sheathed Cable 10A (Cut lengths)	4.78	M	0
24	C	MC	4C+S-18/0.2MM-SP(BLACK)	4 Way Screened Cable 18x0.2mm SILVER plated colourcoded Flexible - 100M drums	4.87	M	265
25	C	MC	4C+S-18/0.2MM(BLACK)	4 Way Screened Cable 18x0.2mm colourcoded Flexible - 100M drums	3.25	M	300
26	C	MC	4131B	Black 15 core circular flex with strain, wire Vulcanised India Rubber Jacket 25mm0, 40/0076 Tinned Copper + 49/0076 HT Strain	7.28	M	0
27	C	MC	4131B	Black 15 core circular flex with strain, wire Vulcanised India Rubber Jacket 25mm0, 40/0076 Tinned Copper + 49/0076 HT Strain	7.28	M	45
28	C	MC	3x0.5mm(Gy)	Grey 3 Core Circular Flex on 250m Drums	91.00	D	8
29	C	MC	3x0.5mm(Bk)	Black 3 core Circular Flex on 250m Drums	91.00	D	7
30	C	MC	3X1.0MM-CUT(GY)	Grey 3 Core Circular Flex 1mm (cut from 2Km drum)	1.27	M	0
31	C	MC	3X1.0MM-2K(GY)	Grey 3 core Circular Flex on Drum of 2000m	1,930.11	D	2
32	C	MC	3P+S(R)	3 Individual Twisted Pairs + Foil Wrap and Drain wire 1/0.063 Beige PVC Shieth 6mm OD	2.12	D	200
33	C	MC	3C-10AWG-TRS(C)	3 Way Rubber Flexible Power Cable, Conductors 10AWG Stranded Tinned Copper, Voltage Rating = 600 RMS, Insulation = Vulcanised India Rubber	5.30	M	750
34	C	MC	36+S(M)	36 Way Screened Flexible Signal Cable 9mm OD	23.41	M	6.8
35	C	MC	3105A(DC)	Shielded (Foil+DW+Braid) Twisted Pair 120 Ohm Data Cable	7.93	M	0
36	C	MC	3105A(AC)	Shielded Twisted Pair 120 Ohm Data Cable for RS-485 etc.	8.73	M	0
37	C	MC	3+STRS(R)	3 Way Plus Neutral Screen(or earth), Neoprene Insulated Flexible Power Cable, Conductors = 80/0.3mm (42 Amps) Tinned CU, Screen = 80/0.3mm T	0.00	C	0
38	C	MC	3+STRS(M)	3 Way Plus Neutral Screen Power Cable 42A	7.28	M	0
39	C	MC	2x0.5mm(GR)	Twin Tru-rip Speaker Cable (Red on Grey)	0.00	M	0
40	C	MC	2x0.5mm(GB)	Twin Tru-rip Speaker Cable (Black on Grey)	0.00	M	0
41	C	MC	2CX0.75MM(BK)	Black 2 core Circular Flex (on 500m Drums)	1.15	M	1200
42	C	MC	2CX0.5MM+S(BR)	Bown 2 core 0.5mm + Lapped Screen tinned copper Circular Flex cable on 200m coils	0.96	D	12
43	C	MC	2C-0.75(B)	2 Core 0.75mm Circular Flex on 50m reels	0.00	R	0
44	C	MC	2C+S-0.5(GR)	2 Core Screened 0.5mm Circular Braided on 150m reels	2.12	R	0

Cables : LOOK UP & ALPHA Listing

Report Name:- CAB_LS1.RSL (23/12/95)YI

	P2I	P3I	TypeNo	Description	Price	Un	Avail
45	C	MC	25C(R)	25 Way Screened Signal/Control Cable, Conductors = 0.81mm 0 Solid Copper, Insulation = Multicolour PVC, Jacket = Black PVC 16mm 0	0.00	D	0
46	C	MC	25C(M)	25 Way Screened Signal/Control Cable	5.68	M	0
47	C	MC	2546-F	12 Way Grey Flexible with Braid/Screen	0.00	M	440
48	C	MC	24C-FW-DW(1424A)	24 Way Signal Cable, Foil Wrap and Drain Wire Stranded 7/0.2mm individually Colour Coded (random lengths) 10.62 mm OD	9.34	M	0
49	C	MC	20P+FW+DW	20 Pair Signal/Control Cable plus Screen+DW	0.00	M	20
50	C	MC	1P+S(APEXSP-2A)	1 pair 0.5mm Screened (braided) Flexible cable, Brown, (Cools of 200m)	0.96	M	600
51	C	MC	1C-8AWG-TRS(M1348/1-8)	Single Core 8AWG Prestolite 3-85 M13486/1-8 Stranded Flexible Rubber Covered Cable 19/0.3x7=133 strands	7.64	M	55
52	C	MC	16C(M)	16 Way Signal/Control Cable, 0.81mm Stranded & Colour Coded (random lengths) 9.1mm OD	5.31	M	91
53	C	MC	15P+S(R)	15 Individual Twisted Pair s 1/0.063 Grey PVC Shieth 11mm OD	0.00	D	10
54	C	MC	151(R)	2 Core Automotive Cable 2/14/0.3mm(1mm) to NZS-6403 RED (with Black stripe)	0.00	M	0
55	C	MC	15/0.63-PEFUT-U/A	15 Pair Jelly Filled Telecom cable on wooden drum	4.78	M	288
56	C	MC	12+S(R)	12 Way Screened Cable 0.74 Cu + 0.15 Braid	0.00	D	20
57	C	MC	12+S(R)	12 Way Screened Signal/Control Cable, Conductors = 0.81mm Solid Copper, Screen = Tinned Copper, Insulation = Multicolour PVC, Jacket = Black	0.00	D	0
58	C	MC	12+S(M)	12 Way Screened Signal/Control Cable	4.00	M	91
59	C	MC	11609(R)	15 Pair Screened Signal/Control Cable, Conductors = 0.630 Solid Copper, Screen = Tinned Copper, Insulation = Multicolour PVC, Jacket = Black	0.00	D	0
60	C	MC	11609(M)	15 Pair Signal/Control Cable 13mm OD	9.10	M	0
61	C	MC	10S+S	10 Core Screened (copper tape or SWA)	0.00	M	0
62	C	MC	10P+S(R)	10 Individual Twisted Pair s 1/0.063 Grey PVC Shieth 9mm OD	0.00	D	13
63	C	MC	10P+FW+DW	10 Pair Signal/Control Cable Foil Wrap + DW	7.64	M	242
64	C	MC	10/3TRS(M)	3 Way Rubber Flexible Power Cable 10 AWG	2.73	M	0