

The QMS 860 Print System

The QMS® 860 Print System supports 600 dpi resolution for the highest quality output, and offers the flexibility to print on paper sizes as large as 11"x17"/A3. It also provides direct connectivity to all popular networks. Everything to make the QMS 860 the best price/performance printer available.

At the heart of the 860 is QMS Crown™

architecture. This unique combination of hardware and software gives the printer superior throughput, greater networkability, and many advanced features that distinguish it from the competition.

The QMS 860 Print System. The first affordable way to get 600 dpi, 11"x17"/A3 printing with all the network connectivity you'll need.



FEATURES AND BENEFITS

- 11" x 17"/A3 printing capabilities give users more flexibility in page layout and design.
- 600 DPI resolution supports printing of PostScript® and HP-GL emulations. This higher resolution produces extremely clean output that can be used as camera-ready originals or as accurate prepress proofs.
- The QMS 860 offers the capabilities of PostScript Level 1 and Level 2, giving it the same features and functionality offered by Adobe's "second generation" of PostScript software.
- An Intel® 80960CA RISC-based internal controller, running at 25 MHz and utilizing proprietary QMS Crown™ technology, processes PostScript files at speeds unsurpassed by other printers in its class.
- Standard and optional interfaces provide compatibility with PCs, Macintosh® computers, UNIX® workstations, DEC® systems, and IBM® mainframes
- Emulation Sensing Processor[†] (ESP) technology, which works with most popular commerciallyavailable applications, analyzes incoming file data from any of the printer's interfaces, and selects the appropriate printer language from those installed on the printer.

RESIDENT TYPEFACES

Times®* Helvetica®* Courier*

Helvetica Condensed Helvetica Narrow^{*} ITC Bookman® Light*

Palatino®* New Century Schoolbook* ITC Avant Garde® Gothic Book* ITC Zapf Chancery® Medium Italic σψμβολ (Symbol Set)

●〇******* (ITC Zapf Dingbats®)

* Includes Regular, Italic, Bold, and Bold Italic type styles.

TECHNICAL SPECIFICATIONS PRINT ENGINE

- Print Method Electrophotographic recording with semiconductor laser. Dry toner, image transfer to paper.
- Resolution Standard 12 MB RAM supports printing at 600 x 600 dots per inch on all paper
- Toner Single component, dry toner.
 Toner Cartridge Life 6,000 pages at normal (4%) coverage.
- Warm-up Time Less than 90 seconds.
- Recommended Duty Cycle 10,000 prints per month.

 Print Speed – Up to 8 pages per minute using letter/A4 paper; up to 4.6 pages per minute using ledger/A3 paper.

CONTROLLER

- Type Intel 80960CA RISC-based controller operating at 25 MHz and utilizing QMS Crown technology.
- Memory 12 MB RAM, 4 MB ROM standard. RAM Úpgrades (optional) – 4 and 8 MB SIMMs
- increase printer memory up to 32 MB. QMS SCSI Hard Drives (optional) – 20 and 45 MB external hard drives expand the printer's spooling and font cache capabilities and provide permanent storage of downloadable typefaces,
- emulations, and programs. Printer Emulations – PostScript Level 1, PostScript Level 2, HP PCL® Level 4 and HP-GL 7475A/7550A. LN03™ PLUS emulation is provided with the DECnet® interface option.
- Emulation Sensing Processor (ESP) Technology.
 - Graphics Standard memory provides up to a full ledger/A3-size page bitmapped at 600 x 600 dpi.
- Typefaces 39 licensed, resident typefaces for PostScript language printing. Adobe's PostScript Type 1 downloadable typefaces are supported. All these typefaces have multilingual character sets. The standard HP® fonts resident on the HP LaserJet IIP are also included for the HP PCL emulation.
- Two Cartridge Slots Accommodate optional plug-in cartridges for additional typefaces and

INTERFACES

- Standard Interfaces LocalTalk™, RS-232C serial, and Centronics® parallel interfaces. The printer is equipped with an external SCSI port that supports up to seven hard disks
- Simultaneous Interface Operation (SIO) -Allows all of the printer's interfaces, standard and optional, to receive data simultaneously.
- Optional Interfaces Provide direct connectivity to Ethernet, supporting DECnet and TCP/IP protocols concurrently or any one of the following protocols: TCP/IP, EtherTalk™, and NetWare®. An optional Token-Ring interface also supports the NetWare protocol.

PAPER HANDLING

- Paper Sizes Supported Letter, legal, ledger, A4, B4, A3, A5, B5, A6, B6, Executive, and
- Special Stocks Printer can handle approved envelopes, label stock, and transparency film. Paper Weights – 16 to 36 lbs. (60 to 135 g/m²).
- Standard Paper Input 250-sheet paper cassette and a 100-sheet multi-purpose tray.
- Optional Paper Input An optional paper feeder allows the addition of a 250-sheet paper cassette. When used with a cassette supporter, the paper feeder supports a 500-sheet letter/A4-size paper
- Paper Output 250 sheets maximum, facedown.
- Automatic Jam Recovery Printer automatically reprints jammed pages.

PHYSICAL

- Type Laser printer with internal controller.
- Dimensions (W x D x H) 18.07" x 20.55" x 11.81" (459 mm x 522 mm x 300 mm)
- Weight 50 lbs. (22.68 kg).
- Warranty One year, return-to-factory.

ELECTRICAL

- Power Requirements 90 to 130 VAC, 48-62 Hz; or 200 to 260 VAC, 50 Hz.
- Power Consumption 650 VA maximum.

ENVIRONMENT

- Temperature 50° to 90° F (10° to 32° C).
- Humidity 20% to 80% RH (operating).
- Noise Level Not more than 49 dB (A).

REGULATORY/ SAFETY CONFORMITY

- FCC-A and VFG 1046 regulatory.
- UL,CSA and TUV/GS safety approvals.

Specifications subject to change without notification. patent pending



QMS, Inc. QMS-PS 860/8-92

One Magnum Pass Mobile, Alabama 36618 USA Telephone: (205) 633-4300 Product Information: (800) 523-2696 Fax: (205) 633-4866 Int'l Fax: (205) 633-0020 For consumables call: (800) 777-7782 (U.S.)

QMS Canada Inc. 9630 Rte Trans-Canadienne Saint-Laurent, Québec H4S 1V9 Canada Telephone: (514) 333-5940 Fax: (514) 333-5949

Calgary, Edmonton, Ottowa, Québec City, Toronto, Vancouver, Winnipeg

QMS Europe Amsterdam Tel.: (31) 20/662-3936 Düsseldorf London Maarssen München

Winterthur

(49) 211-32 42 00 (44) 784 430900 (31) 3465 51 333 (49) 89-922002-0 (33).1.40 83 01 01 Paris Stockholm (46)-8/700 62 33 (31) 30-41 46 46 Utrecht (41) 52 28 46 16

QMS Australia Pty Ltd Melbourne, Tel.: 61 (3) 899 5777 Sydney, Tel.: 61 (2) 901 3235

QMS New Zealand Limited Auckland, Tel.: 64 (9) 630 7912

OMS Japan Inc. Tokyo, Tel.: (81) 3-3457-1185