



Zebra® Z Series™ Metal

Thermal, On-Demand, Metal Bar Code Printers

Z4Mplus™ and Z6Mplus™—Sleek with Speed

Processing labels fast is a breeze with the Z4Mplus and Z6Mplus industrial and commercial bar code printers. At 10 inches (254 mm) per second, these Zebra printers output labels quickly and efficiently, maximizing production and minimizing wait time for demanding jobs like variable-information applications. The Z4Mplus and Z6Mplus die-cast metal construction means reliability and top performance for industrial environments and distribution centers.

Competitive Performers, Competitive Price

Z Series printers stand up to the competition, in terms of both performance and price. Rely on these top-of-the-line performers to get the job done, cost-effectively. Up to twice as fast as CompactFlash, Zebra's powered up Flash memory option drives productivity farther than ever before! The Z Series offers many standard features per dollar, including ZebraLink™ with Alert and WebView for centralized printer management. With an internal Ethernet option, super-fast external memory options, industry-leading throughput, and complex multi-language font support, the Z4Mplus and Z6Mplus are unbeatable commercial printers.

On top of the hard-working durability and easy use of these die-cast metal frame printers, the newly speed-optimized Z4Mplus and Z6Mplus are perfect for:

- Work in process
- Order fulfillment
- Compliance labeling
- Distribution
- Shipping/Receiving
- Hospitality/Transportation ticketing



Connect with it. Count on it.™

Z4Mplus Z6Mplus



Specifications at a Glance*

Quicker first label out and shorter print times make the Z Series printers up to **five times faster** than before when processing most variable-information labels.

MAXIMUM PRINT AREA

(STANDARD MEMORY, CONTINUOUS MEDIA)

Z4Mplus

Width: 4.09"/104 mm
Length with 203 dpi: 174"/4,420 mm
Length with 300 dpi: 73"/1,851 mm

Z6Mplus

Width: 6.6"/168 mm
Length with 203 dpi: 116"/2,946 mm
Length with 300 dpi: 49"/1,254 mm

PHYSICAL CHARACTERISTICS

Z4Mplus

Width: 10.93"/278 mm
Depth: 18.69"/475 mm
Height: 13.32"/338 mm
Weight: 32.4 lbs/15 kg

Z6Mplus

Width: 13.43"/341 mm
Depth: 18.69"/475 mm
Height: 13.32"/338 mm
Weight: 34.7 lbs/16 kg

MEDIA SPECIFICATIONS

Z4Mplus

Label and liner width:
Min: 1"/25.4 mm—
Max (Tear/Cutter): 4.5"/114 mm
Max (Peel/Rewind): 4.25"/108 mm
Ribbon width:
2"/51 mm—
4.33"/110 mm

Z6Mplus

Label and liner width:
Min: 2"/51 mm—
Max (Tear/Cutter): 7"/178 mm
Max (Peel/Rewind): 6.75"/171 mm
Ribbon width:
2"/51 mm—
6.85"/174 mm

RESOLUTION

203 dpi/8 dots per mm; 300 dpi/12 dots per mm

MAXIMUM PRINT SPEED

203 dpi/10 ips; 300 dpi/6 ips

MEMORY

Standard: 2 MB Flash, 8MB DRAM
Optional: Up to 32 MB additional Flash via PCMCIA; Up to 256 MB additional ATA format via PCMCIA or CompactFlash cards

*Specifications subject to change without notice. Copyright 2003 ZIH Corp. Z4Mplus, Z6Mplus, ZBI and ZebraLink are trademarks and Zebra, BAR-ONE, ZebraNet, ZPL, ZPL II and E³ are registered trademarks of ZIH Corp. All rights reserved. All other trademarks are the property of their respective owners.

STANDARD FEATURES

Print methods: Thermal transfer or direct thermal
Construction: Die-cast aluminum base, frame and printhead mechanism
ZebraLink™
Metal media cover with large clear window
Zebra E³™ Printhead Energy Control
Auto-calibration
Real-time clock
Auto-ranging (110 V–220 V) power supply
Color-coded operator cues
Back-lit LCD control panel

Zebra Programming Language

ZPL® & ZPL II®—universal language for Zebra® printers
ZBI™—works with ZPL to control and interpret text and data streams from peripherals and non-ZPL printer programming languages. Transmits captured data over LAN, WAN, or wireless network via e-mail or TCP/IP messaging.

OPERATING CHARACTERISTICS

Environment

Operating Temp. 32° F/0° C to 104° F/40° C (Direct Thermal)
Operating Temp. 40° F/5° C to 104° F/40° C (Thermal Transfer)
Storage Temp. -40° F/-40° C to 140° F/60° C
Operating Humidity 20-85% non-condensing
Storage Humidity 5-85% non-condensing

Electrical

Universal auto-ranging (PFC-compliant) power supply 90-265 VAC; 48-62 Hz; 5A fused

Communication Interface Capabilities

RS-232C serial port
High-speed, IEEE1284, bi-directional parallel interface
ZebraNet® PrintServer II

Agency Approvals and Product Markings

Agencies: IEC60950, EN55024 Class B, EN55024, EN61000-3-2, EN61000-3-3,
Markings: cULus, CE Marking, FCC-B, ICES-003, VCCI, C-Tick, NOM, IRAM, CCC, GOST-R, BSMI

MEDIA CHARACTERISTICS

Labels

Max. Roll Size: 8"/203 mm O.D. on a 3"/76 mm I.D. core
Thickness (label & liner): .0023"/.058 mm to .01"/.25 mm
Maximum non-continuous label length 39"/991 mm
Media Types: Continuous or fanfold, die-cut, notched, tag stock, black mark, perforated
For optimum print quality and print engine performance, use Genuine Zebra Supplies.

Ribbons

Max. Roll Size: 3.2"/81.3 mm O.D. on a 1"/25.4 mm I.D. core
Standard Lengths: 1476'/450 m; provides 3:1 media roll to ribbon ratios
Ribbon Setup: Ribbon wound ink side out
Ribbon is recommended to be at least as wide as media.

FONTS/GRAPHICS/SYMBOLOLOGIES

Fonts and Character Sets

7 bitmapped, 1 smooth scalable (CG Triumvirate™ Bold Condensed)
Sets: International character sets supporting the following code pages:
IBM® Code Page 850 International character set
Optional European and Asian font sets

Graphic Features

Supports user-defined fonts and graphics—including custom logos
ZPL II drawing commands—including boxes and lines

Bar Code Symbolologies

Linear Bar Codes: Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case C Codes, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2 or 5 digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, Planet Code, RSS
2-Dimensional: Codablock, PDF417, Code 49, Data Matrix, MaxiCode, QR Code, Micro PDF417, TLC 39, RSS

OPTIONS AND ACCESSORIES

Standard Memory: 2 MB Flash, 8MB DRAM
Optional Memory: Up to 32 MB additional Flash via PCMCIA; Up to 256 MB additional ATA format via PCMCIA or CompactFlash cards
Cutter with catch tray
Peel—a front mount, passive peel option with no liner take-up
Liner take-up (works with peel option)—full roll liner take-up spindle (fits standard base; Z4Mplus only)
Rewind—internally rewinds full label roll on three-inch core (comes with taller, non-standard printer base)
Memory Socket Card PCMCIA: Supports PCMCIA cards up to 32 MB
CompactFlash: Supports CompactFlash cards up to 256 MB
Adjustable transmissive sensor
ZebraNet® PrintServer II
BAR-ONE® 6.04 software
RS-422/485 serial port adapter
European and Asian font sets



HEADQUARTERS

Zebra Technologies International, LLC T: +1 847 793 2600 or +1 800 423 0442 F: +1 847 913 8766
ADDRESS: 333 Corporate Woods Parkway, Vernon Hills, IL 60061-3109 U.S.A. WEB: www.zebra.com

OTHER LOCATIONS

USA: California, Florida, Rhode Island, Wisconsin EUROPE: Denmark, France, Germany, Italy, South Africa, United Kingdom ASIA-PACIFIC: Australia, China, Japan, Singapore, South Korea LATIN AMERICA: Argentina, Brazil, Mexico MIDDLE EAST: United Arab Emirates



An ISO 9001 registered company
GSA#: GS-35F-0268N
©2003 ZIH Corp. Printed in U.S.A.
#13391L Rev. 1 (9/03) xLM



BarcodesInc

BarcodesInc
200 West Monroe Street
Suite 1050
Chicago, Illinois 60606
Ph: 1-800-351-9962
Fax: 1-312-212-1800
www.barcodesinc.com

About BarcodesInc

I ZaI V3dW

BarcodesInc is North America's leading provider of barcode, mobile computing, point of sale and RFID products and solutions. For over fifteen years, we have worked hard to earn a reputation for being dedicated, reliable and customer-oriented.

I VAI VAgdEgUWteFa Kag

BarcodesInc continues to grow year after year. We have one overriding objective: Focus on you, the customer. We work hard to listen carefully and tailor our solutions to meet your needs. Then, we make ordering easy for you while providing a great value. Our goal is to build a growing relationship with you, and we appreciate the opportunity to serve you.

Why Choose BarcodesInc?

Dedicated Account Team

Our Account Managers will not compromise when it comes to providing you top-notch service. Your Account Manager is the primary point of contact for your business and makes it a priority to get to know you, your company and all your needs.

: [YZ'kZ'cS] W FWZ` [US^Egbbad`

Our technical staff has the broadest knowledge and every significant certification in the industry. One of our friendly experts is always available to suggest products and solutions for any situation.

;` UaW[T'VHS'gW

Our purchasing power means big savings for you. Whatever your project, our team will work hard to deliver a solution that fits your budget.

>ScVaf;` hWfack [fZW` Vgefck S` VES_ V6Sk EZ[bb[Y

Whatever your barcoding, mobile computing, or printing needs, we will fill your order and ship it the same day.

BdW [Vd3UWtefa Fab? S` gXUfgdWte

BarcodesInc maintains strong strategic partnerships with the leading manufacturers in barcoding, mobile computing, printing and RFID.

DVba` e[hW5gefa_ VdEVh[UW

Every phone call and email is responded to promptly, completely and accurately by our customer service team.

7Sek DVfgd e

Damaged, defective or incorrectly ordered goods may be returned without hassle.

BRANDS



AND MORE