



























Adobe Acrobat 5.0 Bundled! for Microsoft Windows 98/Me/2000/XP







■ Compact design: Hopper and stacker can be folded in when the equipment is not in use.





The fi-4860C image scanner (Ultra Wide SCSI interface) offers high speed, duplex color scanning capabilities. Fujitsu is proud of these excellent features, which will ensure this product is used well into the future.

- Most efficient in color/duplex scanning: Scanning speed is steadily high 60ppm/120ipm (A4,150dpi/200dpi) regardless of color/grayscale/ binary, or simplex/duplex documents.
- Superior paper transport function: ADF function minimizes paper double-feed and
- CCD (Charge Coupled Device): CCD image sensor has accelerated scanning speed, and realized simultaneous duplex, high-resolution scanning. Now, users can overcome massive filing task.
- Imprinter fi-486PRFR (Front)



■ Imprinter fi-486PRRE (Rear)



Note: Imprinter is the device for recognizing scanned documents by imprinting numbers on each document. fi-486PRFR enables users to store image data with imprint numbers on.

TECHNICAL SPECIFICATIONS

Operating method		ADF (Automatic document feeder) / MF(Manual feed)	
Image sensor		Color CCD (charge-coupled device) Image sensor x 2	
Light source		White fluorescent lamp	
Document size	Maximum	A3 or 11in. x 17in.	
	Minimum	74 x 74 mm	
Optical resolution		400dpi	
Video output		Color (24 bit/pixel)	
		Monochrome binary (1 bit/pixel)	
		Grayscale (8bit/pixel)	
Output resolution	Color	100 ^{*1} ,150 ^{*1} ,200,300,400 ^{*2} dpi	
	Binary	100, 150, 200, 240, 300, 400 dpi	
	Grayscale	100, 150, 200, 240, 300, 400 dpi	
Scanning speed	Color	60 ppm / 120 ipm*³(150 dpi / 200 dpi, A4 portrait)	
	Binary	60 ppm / 120 ipm*³(200 dpi, A4 portrait)	
	Grayscale	60 ppm / 120 ipm*3(200 dpi, A4 portrait)	
Image memory (Standard)		256 Mbytes (128MB x 2)	
Interface		Ultra Wide SCSI	
Capacity of Hopper/Stacker		Maximum 500 sheets 80g/m² (20lb) , A4	
Power requirements		100-240 VAC ±10%, 50/60Hz + 2%-4%	
Operation environment		Temperature	15 ℃-35 ℃ (59°F-95°F)
		Relative Humidity	20%-80% RH
Dimensions (W x D x H)		520 x 431x 523mm (When Hopper and Stacker are closed)	
Weight		45 Kg (99 lb)	
Option		Imprinter fi-486PRFR (for printing before scanning)*4	
		Imprinter fi-486PRRE (for printing after scanning)*4	
Attachments		Scanner Driver (CD-ROM) containing TWAIN Driver, ISIS Driver, and Image Capturing Software "ScandAll 21"	
		User Manual (CD-ROM) containing Operator's Guide and Installation Guide	
		Installation Guide	
		Adobe Acrobat 5.0 (CD-ROM) containing Adobe User Registration and Support Guide	
		AC power cable	

- *1 100/150 output (sub scanning): Output at 100/150dpi after decimating the image(line) which is scanned at 200dpi.
- *2 Output of 400dpi does not support A3 and 11in. x 17in. size document.
- *3 Scanning speed may vary depending upon scanning mode and working environment.
- *4 Imprinter options fi-486PRFR and fi-486PRRE do not operate at the same time

Microsoft®, Windows® and Windows NT® are registered trademarks of Microsoft Corporation of the USA and other respective countries.

ISIS® is a registered trademark of Pixel Translations, A Division of Actionpoint Inc.

"Adobe", "Acrobat" and "Adobe PDF logo" are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Other company/product names mentioned may be trademarks or registered trademarks of their respective holders.

Specifications are subject to change without notice. For the latest information, contact your local Fujitsu representative. First edition July 2002

North American contact FUJITSU CANADA, INC. 2800 Matheson Boulevard East, Mississauga, Ontario L4W 4X5, Canada Phone: (1-905)602-5454 Fax:602-5457 http://www.fujitsu.ca/

FUJITSU COMPUTER PRODUCTS OF AMERICA, INC. 2904 Orchard Parkway, San Jose, CA95134-2009, U.S.A. Phone:(1-408)432-6333 Fax:894-1709 http://www.fcpa.com/

European contact

FrullTSU DEUTSCHLAND GmbH.
Frankfurter Ring 211,
80807 München, Germany
Phone:(49-89)32378-0 Fax:32378-100
http://de.fujitsu.com/

FUJITSU EUROPE LTD.

Hayes Park Central, Hayes End Road, Hayes, Middlesex UB4 8FE, U.K. Phone:(44-208)573-4444 Fax:8573-2643 http://www.fujitsu-europe.com/

FUJITSU ICL ESPAÑA, S.A. Camino Cerro de los Gamos, 1 28224 Pozuelo de Alarcon, Madrid, Spain Phone:(34-91)784-9000 Fax:784-9379

FUJITSU ITALIA S.p.A Via Nazario Sauro, 38 20099 Sesto S, Giovanni (MI), Italy Phone:(39-2)26294-1 Fax:(39-2)26294-201

Australian contact

Fujitsu AustraLla LTD.
Fujitsu House 2 Julius Avenue
North Ryde, NSW 2113 Australia
Phone: (61-2)9776-4555 Fax:9776-4019
http://au.fujitsu.com/

Asian contact FUJITSU ASIA PTE LTD. 20 Science Park Road #03-01, Tele Teck Park Singapore Science Park II, Singapore 117674 Republic of Singapore Phone:(65)777-6577 Fax:771-5499 http://sg.fujitsu.com/

FUJITSU HONG KONG LTD. 10F., Lincoln House, 979 King's Road, Taikoo Place, Island East, Hong Kong Phone:(852)2827-5780 Fax:2827-4724 http://hk.fujitsu.com/

FUJITSU KOREA LTD.

23-6, Youido-dong, Youngdungpo-gu, Seoul, Republic of Korea Phone: (82)2-3787-6159 Fax:3787-6164 http://kr.fujitsu.com/

FUJITSU (MALAYSIA) SDN. BHD. 7th Floor Wisma Damansara, Jalan Semantan 50490 Kuala Lumpur, MALAYSIA Phone:(603)254-3644 Fax:253-3940 http://my.fujitsu.com/

FUJITSU SYSTEMS BUSINESS (THALLAND) LTD. 12th Fl., Olympia Thai Tower, 444 Rachadapisek Road, Samsennok, Huay Kwang, Bangkok 10320, Thailand Phone:(662)512-6066 Fax:512-6068

FUJITSU TAIWAN LTD.

19F, No. 39, Sec. 1, Chung-hwa Rd., Taipei, Taiwan, R.O.C. Phone:(886-2)2311-2255 Fax:2311-2277



PFU LIMITED

Image Products Sales Dept., Imaging Products Division, Products Group Solid Square East Tower, 580 Horikawa-cho, Saiwai-ku, Kawasaki 212-8563, Japan Phone: (81-44)540-4538 Fax:(81-44)540-4639 http://imagescanner.fujitsu.com/

Corporate Headquarters 98-2, Nu, Unoke-machi, Kahoku-gun Ishikawa-ken 929-1192, Japan

©2002 PFU LIMITED Printed in Japan 2002.7 U-017 MCS-100S