



HP COMPAQ T5000 THIN CLIENT SERIES

Simple, dependable, manageable, and more secure solutions for your business environment.



Gain a competitive edge with the help of HP's affordable thin clients, featuring Microsoft® Windows® and Linux operating systems. Give your workers the processing power they need for a great server-based computing experience, whether running general office applications or a specific line of business software.

With proven business technology and a great price-performance ratio, HP thin clients are easy to buy, deploy, and manage.

Lower total cost of ownership

HP thin clients help you lower your total ownership costs with improved overall reliability and industry-standard components. See the benefits of lower costs through:

- Reduced risk of lost or damaged data: Secure your data on a centralized network server.
 Additional customizable security options are also available.
- Controlled environment: Eliminate tedious PC setup and management. Upgrade applications quickly by updating servers rather than clients.
- Highly reliable clients: No moving parts result in less maintenance and downtime than PCs.

Desktop-like features

Enjoy a true desktop experience with enough processor speed, and flash, system, and graphics memory to run multiple windows and process local applications faster. Select HP thin client models feature legacy support and options for security, wireless, and local storage.

Simplified IT management

HP thin clients run "out of the box" taking only a matter of minutes to set up. Easily establish your client network with automated HP setup and configuration tools. A full license of Altiris Deployment Solution is included with every thin client. Full integration with and a license for HP OpenView Client Configuration Manager simplify deployment and management along with built-in HP exclusive HP ThinState Tools.

HP advantage

HP is a global leader in thin client sales, successfully deploying thousands of solutions for business and providing a single source for servers, monitors, peripherals, and services.

HP's highly reliable thin clients are backed by HP Global Service and Support through our network of 50,000 IT professionals in over 100 countries.

HP COMPAQ T5000 THIN CLIENT SERIES

Model	t5135 Thin Client	t5530 Thin Client	t5720 Thin Client	t5725 Thin Client		
Hardware and operating	VIA Eden 400 MHz	VIA Eden 800 MHz	AMD Geode NX 1500	AMD Geode NX 1500		
system	64 MB Flash, 128 MB RAM ¹	64 MB Flash, 128 MB RAM ¹	Up to 1GB Flash and RAM ¹	512 MB Flash, 256 MB RAM ¹		
	Maximum video resolution is	Maximum video resolution is	Maximum video resolution is	Maximum video resolution is		
	1600x1200, 24 bit @60 Hz	1600x1200, 32 bit @60 Hz	2048x1536, 32 bit @60 Hz	1600x1200, 24 bit @85 Hz		
	HP ThinConnect	Microsoft® Windows® CE 5.0	Microsoft Windows XPe, SP2	Debian Linux 3.1 (Kernel 2.6)		
Supported hardware and			support, VGA-type video output (DB-1			
ports	2 USB 2.0 ports in secure compartment (t5135/t5530); 2 USB 2.0 ports in front; 4 USB 2.0 ports in back					
	Optional PCI expansion module (t5720/t5725); 1 Serial, 1 Parallel, 2 PS/2, 1 RJ-45, Cable Lock;					
			and Modem support (varies by mode	l)		
1.0			Release support			
Manageability and	Full license of Altiris Deployment Solution included with every thin client					
deployment	Fully integrated with and licensed for HP OpenView Client Configuration Manager for quick deployment of images and client managemen					
	Automatic image and The state of th		Automatic settings upgrade from	n FIP		
	settings upgrade from FTP	add-ons upgrade from FTP				
	Stateless mode: store settings					
	on server, download only for the duration of session					
HP ThinState Tools		ings on "master" this client then do	loy to multiple "target" clients: Built ir	a casu ta usa danlaymant taalal		
Data captured:	1 .	Image and settings		1		
Capture changes from	Settings USB flash drive	USB flash drive;	Image and settings USB flash drive	Image and settings USB flash drive		
master thin client to:	USB flash arive	Internal memory of thin client	USB flash drive	USB flash arive		
Deploy changes to	USB flash drive	USB flash drive	USB flash drive	USB flash drive		
target thin clients with:	OSB IIdsii drive	Network ("Master" thin client	OSB IIdsii diive	OSB ilasti arive		
· 5 ····· ····		acts as FTP server)				
		PC (using SMB protocol)				
Terminal emulations	None	TeemTalk for Windows	TeemTalk for Windows	TeemTalk for Linux		
Security	Admin/User passwords	Admin/User passwords	HP Sygate Security Agent (SSA)	Admin/User passwords		
occom,	Remotely configurable BIOS	Remotely configurable BIOS	including an application-centric	Remotely configurable BIOS		
	Smart card support	Smart card support	firewall, application control,	Smart card support		
	Lockable USB ports	Lockable USB ports	intrusion prevention, and policy	Configurable local storage		
	'	Configurable local storage,	enforcement	3		
		(USB mass storage	Symantec Embedded Security			
		configurability)	Configurable local storage,			
			(NTFS security and USB mass			
			storage configurability			
			 Prevent unauthorized 			
			installation and viruses with			
			enhanced Write Filter			
			 Disable local storage 			
			Lock user profiles to limit OS			
			vulnerability			
Brokers	Not applicable HP PC Session Allocation Manager Software for the HP Consolidated Client Infrastructure (CCI)					
	Citrix Desktop Broker for VMware Virtual Desktop Infrastructure (VDI) usin					
Server OS support	Support for latest terminal servers from Citrix and Microsoft. For details, refer to product datasheets.					
Dimensions (h x w x d)						
Without stand:	185 7 × 105 7 × 50 4	mm (7.31 v 7.31 v 2.04 :n)	250 18 v 45 70 v 205 40	mm (0.85 v 2.50 v 9.00 :a)		
	185.7 x 185.7 x 52.4 mm (7.31 x 7.31 x 2.06 in)		250.18 x 65.78 x 205.48 mm (9.85 x 2.59 x 8.09 in)			
With stand:	Stand adds 19 mm (0.75 in) to height 271.09 x 110 x 237.1 mm (10.67 x 4.33 x 9.33 in)					
Power	Worldwide, Auto-sensing 100-240 VAC, 50-60 Hz, 40W power supply					
Temperature range	50° to 104° F (10° to 40° C) (operating)					
iomporatoro rango		-22° to 140° F (-30° to 60° C) (non-operating)				
romporatoro rango		`	50° to 95° F (10° to 35° C) (operating, HP Quick Release with a flat panel monitor or PCl expansion module) t5720/t5725 only			
	50° to 95° F (10° to 35° C	•	n a flat panel monitor or PCI expansion	n module) t5720/t5725 only		
Warranty	<u> </u>	C) (operating, HP Quick Release with	n a flat panel monitor or PCI expansion apply. Visit the HP Customer Support	· · · · · · · · · · · · · · · · · · ·		