



INDUSTRIAL HANDHELD LINEAR IMAGER BAR CODE READER WITH BLUETOOTH® WIRELESS TECHNOLOGY

The PowerScan 7100 product series are Datalogic ADC's value line of rugged industrial handheld data collection products. The PowerScan PBT7100 linear imaging bar code reader with Bluetooth® wireless technology offers operator freedom from cable entanglement, rugged durability and extremely snappy reading performance all at an affordable price.

Datalogic ADC's innovative and unique optical design of the PowerScan 7100 series of readers combines features that are normally available on different models into a single device: up to 3 mils maximum code resolution; contact to over 3.0 m / 9.8 ft reading distance on standard paper labels; and wide angle code reading. The result is a versatile, easy to use and intuitive scanner that simplifies any code reading activity.

Together high-speed digital hardware and Datalogic ADC's advanced decoding algorithms produce read rates up to 390 scans per second, making the PowerScan 7100 readers the fastest industrial scanners available. This is why the 7100's are especially suitable for "high-speed" applications where thousands of codes have to be read in a very short period of time.

Bluetooth® wireless technology can be implemented through the base station or by connecting the scanner directly to any commercial or embedded Bluetooth® compliant device allowing an operator mobility range of up to 100 m / 328 ft.

The base station is offered with two different multi-interface combinations; the Standard multi-interface includes RS-232, Keyboard Wedge, Wand Emulation and USB; the POS multi-interface set includes RS-232, IBM 46xx and USB.

A loud beeper and Datalogic's exclusive patented 'Green Spot' directly on the code, provide intuitive good read feedback in noisy environments. The Datalogic Aladdin™ configuration program provides user-friendly features that simplify the start-up procedure, even for inexperienced users.

Light weight and instinctive usage combined with outstanding speed-to-read makes the PowerScan 7100 product series the ideal solution for intensive code reading applications.

FEATURES

- Fastest speed-to-read - 390 scans/second
- Datalogic 'Green Spot' and loud beeper for good read feedback
- Bluetooth Wireless Technology with up to 100 m / 328 ft range
- Connectivity through the Base Station or directly to other Bluetooth devices
- Water and particulate sealing rating: IP65
- Drop resistance to 2.0 m / 6.5 ft
- 25kV Electrostatic protection (air discharge)
- Model option with aimer for optimal code pointing



SPECIFICATIONS

POWERSCAN™ PBT7100

CORDLESS COMMUNICATIONS

BLUETOOTH WIRELESS TECHNOLOGY	Protocol: Bluetooth 2.0 Certified Class 1 Radio Frequency: 2.40 to 2.48 GHz Radio Range (Open Air): 100.0 m / 328.1 ft
-------------------------------	--

DECODING CAPABILITY

1D / LINEAR CODES	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.
POSTAL CODES	China Post
STACKED CODES	GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional

ELECTRICAL

BATTERY	Battery Type: Lithium-Ion, 2400 mAh Charge Time: External Power: 4 Hours Reads per Charge: 22,000 in 16 Hours
CURRENT	Operating (Typical): BC70X0: 280 mA @ 5 VDC Standby/Idle (Typical): BC70X0: 210 mA @ 5 VDC
INPUT VOLTAGE	5 VDC +/- 5% ; 7 - 14 VDC

ENVIRONMENTAL

AMBIENT LIGHT	100,000 lux
DROP RESISTANCE	Withstands 50 drops from 2.0 m / 6.6 ft onto a concrete surface
ESD PROTECTION (AIR DISCHARGE)	25 kV
HUMIDITY (NON-CONDENSING)	5 - 95%
PARTICULATE AND WATER SEALING	IP65
TEMPERATURE	Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -40 to 60 °C / -40 to 140 °F

INTERFACES

INTERFACES	RS-232 / IBM 46XX / USB Multi-Interface RS-232 / USB / Keyboard Wedge / Wand Multi-Interface
------------	---

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE	Black; Yellow/Black
DIMENSIONS	Cradle: 23.9 x 11.7 x 4.8 cm / 9.4 x 4.6 x 1.9 in Reader: 20.3 x 7.6 x 11.4 cm / 8.0 x 3.0 x 4.5 in
WEIGHT	Cradle: 326.2 g / 11.5 oz Reader: 354.4 g / 12.5 oz

READING PERFORMANCE

LIGHT SOURCE	Aiming: 630 - 680 nm VLD
ILLUMINATION	LED Array 630 - 670 nm
PRINT CONTRAST RATIO (MINIMUM)	15%
READ RATE (MAXIMUM)	390 reads/sec.
READING ANGLE	Pitch: +/- 65°; Roll (Tilt): +/- 30°; Skew (Yaw): +/- 65°
READING INDICATORS	Beeper (Adjustable Tone and Volume); Datalogic 'Green Spot' Good Read Feedback; Good Read LED
RESOLUTION (MAXIMUM)	0.076 mm / 3 mils

READING RANGES

TYPICAL DEPTH OF FIELD	Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent. 5 mils: 1.5 to 14.0 cm / 0.6 to 5.5 in 7.5 mils: 0 to 44.0 cm / 0 to 17.3 in 10 mils: 0 to 60.0 cm / 0 to 23.6 in 13 mils: 0 to 80.0 cm / 0 to 31.5 in 20 mils: 0 to 119.0 cm / 0 to 46.9 in 40 mils: 2.0 to 240.0 cm / 0.8 to 94.5 in Reflective - 55 mils: 5.0 to 300.0 cm / 2.0 to 118.1 in Reflective - 100 mils: 13.0 to 530.0 cm / 5.1 to 208.7 in
------------------------	--

SAFETY & REGULATORY

AGENCY APPROVALS	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
ENVIRONMENTAL COMPLIANCE	Complies to China RoHS; Complies to EU RoHS
LASER CLASSIFICATION	Caution Laser Radiation - Do not stare into beam; EN 60825-1 Class 1

UTILITIES

DATALOGIC ALADDIN™	Datalogic Aladdin configuration program is available for download at no charge.
REMOTE HOST DOWNLOAD	Lowers service costs and improves operations.

WARRANTY

WARRANTY	3-Year Factory Warranty
----------	-------------------------

ACCESSORIES



Base Stations/Chargers

- BC7010 Base/Charger, RS-232 / IBM 46XX / USB Multi-Interface
- BC7030 Base/Charger, RS-232 / USB / Keyboard Wedge / Wand Multi-Interface



Batteries/Battery Chargers

- 11-0202 Battery Charger, 4 Station, US T&L
- 11-0203 Battery Charger, 4 Station, US Std
- 11-0204 Battery Charger, 4 Station, Europe
- 11-0205 Battery Charger, 4 Station, UK
- 11-0234 Battery Pack



Cases/Holsters

- 11-0138 Heated Holder, 36 VDC
- 11-0139 Heated Holder, 24 VDC
- 11-0140 Heated Holder, 48 VDC



Mounts/Stands

- 11-0110 Hands Free Stand
- 11-0111 Universal Mounting Kit for PowerScan
- 7-0404 Industrial Take Up Reel

© 2009 - 2012 Datalogic ADC, Inc. • All rights reserved. • Protected to the fullest extent under U.S. and international laws. • Copying, or altering of this document is prohibited without express written consent from Datalogic ADC, Inc. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. and the Datalogic Automatic Data Capture logo is a trademark of Datalogic S.p.A. • Datalogic Aladdin is a trademark of Datalogic Scanning Group S.r.l. • PowerScan is a registered trademark of Datalogic ADC, Inc. in many countries, including the U.S. and the E.U. • The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Datalogic ADC, Inc. is under license. • All other brand and product names are trademarks of their respective owners. All other brand and product names are trademarks of their respective owners. • DS-POWERSCANPBT7100-ENA4 20120101