

Data & Signal, Plug, 6.3 mm, 2-pole, solder terminal, insulated, angled



Description

- Solder terminal:
for cable mounting
- Data and Signal transfer
- Data and Signal Connectors 2-pole, insulated, angled

References

Alternative: Housing shielded 4803.1200

Weblinks


pdf-datasheet, html-datasheet, General Product Information, RoHS, CHINA-RoHS, REACH, Mating Connectors, e-Shop, SCHURTER-Stock-Check, Distributor-Stock-Check

Technical Data

Diameter	6.3 mm
Number of Poles	2-pole
Ratings DC	2 A / 12 VDC
Ratings AC	2 A / 12 VAC
Dielectric Strength	1000VDC
Insulation Resistance	> 10000 MΩ @ 500VDC

Allowable Operation Temp.	-20 °C to 70 °C
Terminal	solder terminal
Housing	insulated
Style	angled
Lifetime	10000 Insertions

Dimensions



All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
Data and Signal Plug/ Sockets	6.3	2-pole	solder terminal	4803.1220

Most Popular.

Availability for all products can be searched real-time: <http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging unit 100 Pcs

Mating Outlets/Connectors

Category / Description



[Data and Signal Plug/Socket Overview complete](#)

4803, Socket, solder terminal, screened, 6.3 mm, 2-pole, straight, , UK-Connector	4803.2200
4803, Socket, solder terminal, insulated, 6.3 mm, 2-pole, straight, , UK-Connector	4803.2210
4803, Socket, PCB terminals, screened, 6.3 mm, 2-pole, straight, , UK-Connector	4803.2220
4803, Socket, PCB terminals, insulated, 6.3 mm, 2-pole, straight, , UK-Connector	4803.2230
4803, Line Socket, solder terminal, screened, 6.3 mm, 2-pole, straight, , UK-Connector	4803.3200

[Data and Signal Plug/Socket further types to 4803 UK-Stecker, D=6,5mm](#)