



SUHNER® COAXIAL CONNECTOR DATA SHEET

TYPE 31_N-716-50-1/---_U

Description

Adaptor jack/jack



General Information

1st Interface / 2nd Interface:

N / 7/16

Interface dims acc. to:

IEC 60169-16_MIL-STD-348A/304_CECC 22210

Weight:

0.0879 Kg / 3.1002 oz

Electrical Data

Impedance:

50Ω

Interface frequency max.:

7.5GHz

Frequency range:

0 ... 7.5 GHz

Piece Parts N

Centre contact:

Material

Copper Beryllium Alloy

Outer contact:

Brass

Body:

Brass

Other Body Part:

Insulator:

PFA / PTFE

Plating

Gold Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

Piece Parts 7/16

Centre contact:

Material

Bronze

Outer contact:

Brass

Body:

Brass

Insulator:

PFA / PTFE

Plating

Silver Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

Attachments

Catalogue drawing: DCA-00014603

Notes

Order as **31_N-716-50-1/---_UE** for Single

WAIVER!
While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Issued: 24.03.04 11:04

Document: DOC-0000195579

RF_Ad_B_S_PDF

uncontrolled copy

Page 1



HUBER+SUHNER

HUBER+SUHNER AG

Interconnect Division

CH-9100 Herisau

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

<http://www.hubersuhner.com>