

# HUBER+SUHNER® DATA SHEET

## Between Series Adapter: 32\_N-SMA-50-1/11-\_N

Rev.: G



### Description

Adaptor plug/plug  
N plug (male) / SMA plug (male)

Interface standards  
IEC 60169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	18 GHz
VSWR	DC - 12.4 GHz $\leq 1.05 + 0.017 f$

#### Mechanical Data

Number of matings	500
Weight	0.0316 kg

#### Environmental Data

Operating Temperature 2002/95/EC (RoHS)	-65 °C to 165 °C compliant
--	-------------------------------

#### Material Data

##### Piece Parts (N)

Centre contact	Copper Beryllium Alloy
Outer contact	Copper Beryllium Alloy
Body	Brass
Insulator	PTFE
Coupling nut	Brass
Gasket	MVQ (Silicone Rubber)

##### Piece Parts (SMA)

Centre contact	Copper Beryllium Alloy
Outer contact	Copper Beryllium Alloy
Body	Brass
Insulator	PTFE
Coupling nut	Bronze
Gasket	MVQ (Silicone Rubber)

##### Surface Plating

Hard Au min. 1.3  $\mu\text{m}$   
Gold Plating (without Nickel underplating)  
SUCOPLATE min. 0.5  $\mu\text{m}$  over Ag min. 2  $\mu\text{m}$

SUCOPLATE min. 2  $\mu\text{m}$

##### Surface Plating

Gold Plating (without Nickel underplating)  
Gold Plating (without Nickel underplating)  
SUCOPLATE (R) Plating

Gold Plating (without Nickel underplating)

### Related Documents

#### Ordering Information

Single package	32_N-SMA-50-1/11-_NE
----------------	----------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**