

Between Series Adaptor 32_PC35-QMA-50-1/1--_N

Description

Adaptor plug/plug
PC 3.5 plug (male) / QMA plug (male)

QuickLock Interface
For Test & Measurement applications

Interface standards
Series PC 3.5 - IEC 60169-23
Series QMA - QMA QLF compliant



Technical Data

Electrical Data

Impedance	50 Ω			
Interface frequency max.	18 GHz			
Frequency range	DC to 1.5 GHz	1.5 to 6 GHz	6 to 18 GHz	
Return loss	≥ 35 dB	≥ 30 dB	≥ 20 dB	
Electrical length	25.4 mm			

Mechanical Data

Number of matings	500
Weight	0.0101 kg

Environmental Data

Operating temperature	-60 °C to 100 °C
2011/65/EC (RoHS)	compliant

Material Data

Interface - PC 3.5 plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PS	
Coupling nut	Stainless Steel	Passivated (Plating)

Interface - QMA plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Copper Beryllium Alloy	SUCOPRO Plating
Body	Stainless Steel / Brass	
Insulator	Air Dielectric - Bead - PS	

Related Documents

Outline drawing	DOU-00014037
-----------------	--------------

Ordering Information

Single package	32_PC35-QMA-50-1/1--_NE
----------------	-------------------------