



SUHNER® COAXIAL CONNECTOR DATA SHEET

TYPE 37_N-SMA-50-1/1--_U

Description

Panel adaptor jack/jack, flange mount



General Information

1st Interface / 2nd Interface: N / SMA
 Interface dims acc. to: IEC 60169-16_MIL-STD-348A/304_CECC 22210
 Weight: 0.0264 Kg / 0.9311 oz

Electrical Data

Impedance: 50Ω
 Interface frequency max.: 18GHz
 Frequency range: 0 ... 12.4 GHz

Piece Parts N

Centre contact:
 Outer contact:
 Body:
 Other Body Part:
 Insulator:

Material

Copper Beryllium Alloy
 Brass
 Brass
 PFA / PTFE

Plating

Gold Plating
 SUCOPLATE (R) Plating
 SUCOPLATE (R) Plating

Piece Parts SMA

Centre contact:
 Outer contact:
 Body:
 Insulator:

Material

Copper Beryllium Alloy
 Copper Beryllium Alloy
 Copper Beryllium Alloy
 PFA / PTFE

Plating


Gold Plating
 Gold Plating
 Gold Plating

Attachments

Catalogue drawing: DCA-00014077

Notes

Mounting hole: DOU-00013979
 Order as **37_N-SMA-50-1/1--_UE** for Single

WAIVER! While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.		 HUBER+SUHNER HUBER+SUHNER AG Interconnect Division CH-9100 Herisau Phone +41 (0)71 353 41 11 Fax +41 (0)71 353 45 90 http://www.hubersuhner.com
Issued: 31.03.04 10:12	Document: DOC-0000195102	
RF_Ad_B_S_PDF	<i>uncontrolled copy</i> Page 1	