



SERIES C

COAXIAL CONNECTORS

Description

SUHNER C connectors are available with 50 Ω impedance. The useful frequency range extends from DC to 11 GHz.

These connectors are robust and owing to their bayonet coupling mechanism are simple and quick to use.

Contents

	page
Technical Data	200
Connectors for Flexible Cables	202
Receptacles with Solder End	204
Within-Series Adaptors	205
Protective Caps	207

Further Information


Cable Entries	15
Adaptors	234
Accessories	261

Standards


Interface dimensions conform to:
IEC 169-7, MIL-STD-348A/302,
DIN 47222

Interface Dimensions

Plug



Jack



C/UHF

Technical Data

Electrical Data	Requirements
Impedance	50 Ω
Frequency range	DC ... 11 GHz
RF-leakage	≥ 55 dB
Dielectric withstanding voltage (at sea level)	3.0 kV rms, 50 Hz
Working voltage (at sea level)	≤ 1.0 kV rms, 50 Hz
Insulation resistance	$\geq 5 \cdot 10^3$ M Ω
Contact resistance – inner conductor – outer conductor	≤ 1.0 m Ω ≤ 1.0 m Ω

Mechanical Data	Requirements
Coupling nut torque	≤ 0.45 Nm
Coupling nut retention force	≥ 450 N
Contact captivation	≥ 27 N
Cable retention force ¹⁾ – cable group U7 – cable groups U9, U10, U11 – cable groups U28, U29 – cable groups U32, U33	≥ 125 N ≥ 250 N ≥ 415 N ≥ 530 N
Durability (matings)	≥ 500

1) value considers maximum load of the cables without irreversible variations of specifications.

Environmental Data	Requirements/tests
Temperature range	$-65^\circ\text{C} \dots +165^\circ\text{C}$
Climatic category acc. to IEC	55/155/21
Thermal shock	MIL-STD-202, Method 107, Condition B
Moisture resistance	MIL-STD-202, Method 106
Corrosion	Saltspray test acc. to MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition D
Shock	MIL-STD-202, Method 213, Condition I
Sealing	connectors with clamp type cable entry are moisture proof

Materials

Connector part	Standards	Material	Surface/plating
Bodies, Contact pins	QQ-B-626, ISO CuZn 38 Pb2	brass	Sucoplate® gold plated
Outer contacts	CuSn 4 Te	spring bronze	Sucoplate®
Contact sockets	QQ-C-530/MIL-H-7199, CuBe2	beryllium-copper, hardened	gold plated
Crimp ferrules	SUHNER specification	copper	nickel plated
Insulators, standard version	ASTM-D-1457, BS 4271 Grade B	PTFE	
Rubber gaskets	ASTM-E-1418 PS 1	silicone rubber 70 shore	

Some connectors may have a specification that differs from above mentioned data.

Connectors for Flexible Cables

straight plugs

cable entry clamp





Fig. 1



Fig. 2



SUHNER TYPE	Ident. no.	US-MIL M 39012/	Cable group (example)	Fig.	Weight	AI	Notes
11 C-50-3-12	646602		U7, U10 (RG 58 C/U)	1	31.5 g	MAP 256	
11 C-50-7-6c	541137	6-0015	U28, U33 (RG 214/U)	2	45.5 g	3008	

cable entry
SUHNER full crimp

taper sleeves
see page 262



SUHNER TYPE	Ident. no.	US-MIL M 39012/	Cable group (example)	Crimp insert	Weight	AI	Notes
11 C-50-3-7c	541103		U7 (RG 58 C/U)	2B	27.5 g	3063	L = 35.0 mm
11 C-50-3-8c	541104		U9 (RG 223/U)	2B	26.5 g	3063	L = 35.0 mm
11 C-50-7-14c	541142	6-0022	U29 (RG 213/U)	3D	29.5 g	3061	L = 37.0 mm
11 C-50-7-15c	541144	6-0023	U32 (RG 214/U)	3D	29.5 g	3061	L = 37.0 mm

right angle plugs

cable entry clamp

fully PTFE insulated





Fig. 1

Fig. 2





SUHNER TYPE	Ident. no.	US-MIL M 39012/	Cable group (example)	Fig.	Weight	AI	Notes
16 C-50-3-3	642051		U7, U10 (RG 58 C/U)	1	54.5 g	3016	
16 C-50-7-6	541185	10-0001	U28, U33 (RG 214/U)	2	76.5 g	3007	replaces UG-710/U

AI = assembly instruction
cable groups see page 17

mounting holes see page 269
assembly tools see page 251

straight jacks



cable entry clamp



SUHNER TYPE	Ident. no.	US-MIL	Cable group (example)	Weight	Al	Notes
21 C-50-3-4	541197		U7, U10 (RG 58 C/U)	29.0 g	3016	L = ~ 31.0 mm
21 C-50-7-3	541214		U28, U33 (RG 214/U)	36.5 g	3007	L = ~ 36.0 mm

cable entry
SUHNER full crimp

taper sleeves
see page 262



SUHNER TYPE	Ident. no.	US-MIL	Cable group (example)	Crimp insert	Weight	Al	Notes
21 C-50-3-6c	543976		U7 (RG 58 C/U)	2B	29.0 g	3015	L = ~ 38.0 mm
21 C-50-3-7c	643033		U9 (RG 223/U)	2B	29.0 g	3015	L = ~ 38.0 mm

bulkhead jacks

cable entry clamp





Fig. 1

Fig. 2

Fig. 3



SUHNER TYPE	Ident. no.	Cable group (example)	Mounting hole	Fig.	Weight	Al	Notes
24 C-50-3-2c	644448	U7, U10(RG 58 C/U)	ML 25	1	56.0 g	3017	
24 C-50-3-5c	543622	U7, U10(RG 58 C/U)	ML 24	3	30.0 g	3017	front mounting
24 C-50-7-3	541256	U28,U33 (RG 214/U)	ML 25	2	48.0 g	3007	replaces UG 570 A/U

panel thickness 3.5 mm max.

Al = assembly instruction
cable groups see page 17

mounting holes see page 269
assembly tools see page 251

panel jacks

cable entry clamp





Fig. 1

Fig. 2





SUHNER TYPE	Ident. no.	Cable group (example)	Mounting hole	Fig.	Weight	Al	Fastening hole d
25 C-50-3-3c	641096	U7, U10(RG 58 C/U)	ML 14	1	29.0 g	3017	6-32 UNC
25 C-50-3-4c	541265	U7, U10(RG 58 C/U)	ML 14	1	29.0 g	3017	3.4 mm dia.
25 C-50-7-3	541277	U28,U33(RG 214/U)	ML 37	2	40.0 g	3007	6-32 UNC

cable entry

SUHNER full crimp

taper sleeves
see page 262





SUHNER TYPE	Ident. no.	US-MIL	Cable group (example)	Crimp insert	Weight	Al	Notes
25 C-50-7-15c	541288		U29 (RG 213/U)	3D	32.0 g	3061	L = 40.0 mm
25 C-50-7-16c	643964		U32 (RG 214/U)	3D	32.0 g	3061	L = 40.0 mm

mounting hole ML 14

Receptacles with Solder End

receptacles, male

panel mounting





SUHNER TYPE	Ident. no.	US-MIL	Mounting hole	Weight	Fastening hole d
13 C-50-0-2	541163		ML 47	35.0 g	3.4 mm dia.

Al = assembly instruction
cable groups see page 17

mounting holes see page 269
assembly tools see page 251



receptacles, female

panel mounted



SUHNER TYPE	Ident. no.	US-MIL M 39012/	d =	Mounting hole	Weight	Notes
23 C-50-0-1	541226	12-0001	6-32 UNC	ML 36	22.5 g	replaces UG-568/U
23 C-50-0-2	541230		3.4 mm dia.	ML 36	22.5 g	

bulkhead mounted





SUHNER TYPE	Ident. no.	Mounting hole	Weight	Panel thickness
22 C-50-0-3	541222	ML 25	33.5 g	2.5 mm max.

Within-Series Adaptors



straight adaptors

jack to jack



SUHNER TYPE	Ident. no.	US-MIL 55339/	Weight	Notes
31 C-50-0-1	541292	08-00643	30.0 g	replaces UG-643/U

plug to plug



SUHNER TYPE	Ident. no.	US-MIL 55339/	Weight	Notes
32 C-50-0-1	541301	09-00642	46.5 g	replaces UG-642 A/U



AI = assembly instruction
cable groups see page 17

mounting holes see page 269
assembly tools see page 251

straight adaptors

jack to jack



bulkhead mounted



SUHNER TYPE	Ident. no.	US-MIL	Mounting hole	Weight	Panel thickness
34 C-50-0-1	541327		ML 25	45.5 g	2.5 mm max.

jack to jack

panel mounted





SUHNER TYPE	Ident. no.	US-MIL	Mounting hole	Weight	Panel thickness
37 C-50-0-2	541333		ML 14	31.0 g	3.5 mm max.

T-adaptor

2 jacks



1 plug



SUHNER TYPE	Ident. no.	US-MIL 55339/	Weight	Notes
43 C-50-0-1	541336	11-00566	48.5 g	replaces UG-566 A/U

L-adaptor



plug to jack



SUHNER TYPE	Ident. no.	US-MIL 55339/	Weight	Notes
53 C-50-0-1	541338	10-00567	50.0 g	replaces UG-567 A/U



Protective Caps

for plugs



SUHNER TYPE	Ident. no.	US-MIL 55339/	Weight	Notes
61 C-0-0-1	541341	25-0003	17.5 g	replaces MX-1143 A/U


for jacks



SUHNER TYPE	Ident. no.	US-MIL 55339/	Weight	Notes
62 C-0-0-1	541344	25-0001	20.0 g	replaces MX-1142 A/U

AI = assembly instruction
cable groups see page 17

mounting holes see page 269
assembly tools see page 251



Section 1: [Illegible text] Section 2: [Illegible text]



Section 3: [Illegible text] Section 4: [Illegible text]



Section 5: [Illegible text] Section 6: [Illegible text]

