

HUBER+SUHNER® DATA SHEET

RF ATTENUATORS: SERIES 68XX.01.A (BNC, 4 GHz)



Description

Standard Attenuator, Low Power

Type 68XX.01.A, for XX insert attenuation value in dB

For example for 3 dB attenuation insert "03" in the type code and write 6803.01.A



Product Configuration

Connectors (side 1 / side2) BNC plug (male) / BNC jack (female)

Technical Data

Electrical Data

Nominal impedance	50 Ω
Attenuation values	from 1 up to 30 dB
Frequency range	DC to 4 GHz ^{*)}
Power rating	2 Watt ^{*)} average power to 30°C ambient temperature , linearly derated to 0 Watt at 130°C ambient temperature. 500 Watt peak power during max. 5 μ s
Power Coefficient	0.001 dB/dB/W
Temp. Coefficient	0.0001 dB/dB/°C

Environmental Data

2002/95/EC (RoHS) compliant

Mechanical Data

Dimensions	12.5 / 12.5 / 44.4 (height / width / length coaxial in mm)
Weight	0.069 kg / 2.43 oz

Material Data

Piece Part

Centre contacts
Outer contacts
Body
Coupling Nut

Material

Copper-Beryllium Alloy
Brass
Brass
Brass

Surface Plating

Gold Plating (not nickel underplated)
SUCOPLATE® Plating
SUCOPLATE® Plating
SUCOPLATE® Plating

Related Documents

Outline Drawing DOU-00005238

Ordering Information

Single Packing 68XX.01.A ^{*)}

Additional Information

Remarks

Interface dimensions acc. to IEC 60169-8_MIL-STD-348A/301_CECC 22120

^{*)} for complete type code identification and detail specifications see page 2.

HUBER+SUHNER® DATA SHEET

RF ATTENUATORS: SERIES 68XX.01.A (BNC, 4 GHz)



Type 68XX.01.A, for XX insert attenuation value in dB

For example for 3 dB attenuation insert "03" in the type code and write 6803.01.A

Nominal attenuation (dB)	Attenuation deviation max. over frequency (GHz) (dB)		VSWR max. over frequency (GHz)		Power	H+S type	Item number
	DC - 2	2 - 4	DC - 2	2 - 4			
1	+/-0.3	+/-0.5	1.10	1.20	2 W	6801.01.A	22641542
2					2 W	6802.01.A	22641543
3					2 W	6803.01.A	22550177
4					2 W	6804.01.A	22641544
6					2 W	6806.01.A	22550178
7					2 W	6807.01.A	22641546
10					1 W	6810.01.A	22550179
20	+/-0.5	+/-1.0	1.10	1.20	1 W	6820.01.A	22550180
30	+/-1.0	+/-1.0	1.10	1.20	1 W	6830.01.A	22550181

The HUBER+SUHNER group is certified according to ISO 9001 and ISO 14001

WAIVER!
It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions