

			REVISIONS																																													
			REV	DESCRIPTION	DATE	APPROVED																																										
			02 ₀	REVISED	JD 6/6/95	JD 6/13/95																																										
<table><tr><td>ELECTRICAL</td><td>MECHANICAL</td><td>ENVIRONMENTAL</td></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Force to Engage (Lbs MAX) 3.4</td><td>Temperature Rating -65° to +165°C</td></tr><tr><td>Frequency Range (GHz) DC to 4.0</td><td>& Disengage (Lbs) 1.77MIN, 4.5MAX</td><td>Vibration MIL-STD-202, Method 204, Condition B</td></tr><tr><td>Volt Rating (VRMS MAX) @ Sea Level 335</td><td></td><td>Thermal Shock MIL-STD-202, Method 102, Condition C</td></tr><tr><td>VSWR 1.15:1 MAX</td><td></td><td>Moisture Resistance MIL-STD-202, Method 106D, 10 Cycles, 24 Hours</td></tr><tr><td>Insertion Loss .1dB MAX x fGHz</td><td></td><td>Corrosion - MIL-STD-202, Method 101, Condition b</td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 250</td><td></td><td></td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1000</td><td></td><td></td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td></td><td></td></tr><tr><td>Center Contact 5.0</td><td></td><td></td></tr><tr><td>Outer Contact 1.0</td><td></td><td></td></tr><tr><td>Cable to Housing 1.0</td><td></td><td></td></tr><tr><td>RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670</td><td></td><td></td></tr><tr><td>I.R.(Megohms MIN) 10,000</td><td></td><td></td></tr></table>			ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Force to Engage (Lbs MAX) 3.4	Temperature Rating -65° to +165°C	Frequency Range (GHz) DC to 4.0	& Disengage (Lbs) 1.77MIN, 4.5MAX	Vibration MIL-STD-202, Method 204, Condition B	Volt Rating (VRMS MAX) @ Sea Level 335		Thermal Shock MIL-STD-202, Method 102, Condition C	VSWR 1.15:1 MAX		Moisture Resistance MIL-STD-202, Method 106D, 10 Cycles, 24 Hours	Insertion Loss .1dB MAX x fGHz		Corrosion - MIL-STD-202, Method 101, Condition b	Corona, 70,000 Ft (VRMS MIN) 250			Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1000			Contact Resistance (Milliohms MAX)			Center Contact 5.0			Outer Contact 1.0			Cable to Housing 1.0			RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670			I.R.(Megohms MIN) 10,000			HOUSING BRASS PER QQ-B-626 COMP. 360, HALF HARD		NICKEL PLATE PER QQ-N-290	
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																														
Nominal Impedance (Ohms) 50	Force to Engage (Lbs MAX) 3.4	Temperature Rating -65° to +165°C																																														
Frequency Range (GHz) DC to 4.0	& Disengage (Lbs) 1.77MIN, 4.5MAX	Vibration MIL-STD-202, Method 204, Condition B																																														
Volt Rating (VRMS MAX) @ Sea Level 335		Thermal Shock MIL-STD-202, Method 102, Condition C																																														
VSWR 1.15:1 MAX		Moisture Resistance MIL-STD-202, Method 106D, 10 Cycles, 24 Hours																																														
Insertion Loss .1dB MAX x fGHz		Corrosion - MIL-STD-202, Method 101, Condition b																																														
Corona, 70,000 Ft (VRMS MIN) 250																																																
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1000																																																
Contact Resistance (Milliohms MAX)																																																
Center Contact 5.0																																																
Outer Contact 1.0																																																
Cable to Housing 1.0																																																
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670																																																
I.R.(Megohms MIN) 10,000																																																
DIELECTRIC TFE FLUOROCARBON PER ASTM-D-1457		N/A																																														
CENTER CONTACT CONTACT FINGERS BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H		GOLD PLATE PER MIL-G-45204																																														
COMPONENT		MATERIAL		FINISH																																												
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1°		DRAWN BY <i>QRL</i> DATE 10/9/91 CHECKED BY MY 10-11-91 APPD BY <i>QRL</i> 10-11-91		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599																																												
These drawings and specifications are the property of M/A-COM Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.		USE ASS'Y PROCEDURE NO. AP. N/A		TITLE OSX PRINTED WIRING BOARD PLUG RECEPTACLE STRAIGHT TERMINAL																																												
SIZE B		CODE IDENT NO. 26805		5863-0000-10																																												
SCALE 10:1				REV 02 ₀																																												
				SHEET 1 OF 1																																												