



SUHNER® COAXIAL CONNECTOR DATA SHEET

TYPE 11_N-50-6-5/133_N

Description

Straight cable plug for flexible cable



SUHNER full crimp cable attachment

General Information

N Interface dims acc. to: IEC 60169-16_MIL-STD-348A/304_CECC 22210
 Weight: 0.0317 Kg / 1.12 oz

Cable Cable type: S_06132D-10

Cable Entry Centre contact: crimped
 Outer contact: crimped

Electrical Data

Impedance: 50Ω
 Interface frequency max.: 11 GHz

Piece Parts

Center contact:
 Outer contact:
 Body:

Material

Brass
 Brass
 Brass
 PFA / PTFE
 Brass
 MQ (Silicon Rubber)
 Copper

Surface Plating

Gold Plating (Nickel underplated)
 SUCOPLATE (R) Plating
 SUCOPLATE (R) Plating
 SUCOPLATE (R) Plating
 SUCOPLATE (R) Plating

Insulator:

Coupling nut:

Gasket:

Crimp ferrule:

Attachments

Outline drawing: DOU-00008103
 Assembly instruction: DOC-0000179009

Notes

Order as **11_N-50-6-5/133_NE** for Single

WAIVER!
 While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Issued: 17.12.2003 17:50

Document: DOC-0000183795

RF_Ca_C_PDF

uncontrolled copy

Page 1



HUBER+SUHNER

HUBER+SUHNER AG
 Interconnect Division
 CH-9100 Herisau
 Phone +41 (0)71 353 41 11
 Fax +41 (0)71 353 45 90
<http://www.hubersuhner.com>