

Coaxial Cable Connector 11_SMA-50-5-2/199_N

Description

Straight cable plug

Interface standards

IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 18 GHz |

Mechanical Data

| | |
|----------------|-----------|
| Centre contact | soldered |
| Outer contact | clamped |
| Weight | 0.0089 kg |

Environmental Data

| | |
|--|------------------|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|--|
| Centre contact | Copper Beryllium Alloy | Gold Plating (without Nickel underplating) |
| Outer contact | Stainless Steel | Passivated (Plating) |
| Body | Stainless Steel | Passivated (Plating) |
| Insulator | PFA / PTFE | |
| Coupling nut | Stainless Steel | |
| Gasket | VMQ (Silicone rubber) | |

Related Documents

| | |
|----------------------|----------------|
| Catalogue drawing | DOU-00008080 |
| Assembly instruction | DOC-0000181417 |

Ordering Information

| | |
|----------------|----------------------|
| Single package | 11_SMA-50-5-2/199_NE |
|----------------|----------------------|

Additional Information

| | |
|-----------------|---------------|
| Suitable cables | EZ_250_TP_M17 |
|-----------------|---------------|

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[11_SMA-50-5-2/199_NE](#)