



SUHNER® COAXIAL CONNECTOR DATA SHEET

TYPE 23_SMA-50-0-13/111_N

Description

Straight panel receptacle jack, flange mount



General Information

SMA Interface dims acc. to: IEC 60169-15_MIL-STD-348A/310_CECC 22110
 Weight: 0.0023 Kg / 0.08

Electrical Data

Impedance: 50Ω
 Interface frequency max.: 18 GHz

Piece Parts

Centre contact:
 Outer contact:
 Body:
 Insulator:

Material

Copper Beryllium Alloy
 Copper Beryllium Alloy
 Copper Beryllium Alloy
 PFA / PTFE

Surface Plating

Gold Plating (Nickel underplated)
 Gold Plating (Nickel underplated)
 Gold Plating (Nickel underplated)

Attachments

Catalogue drawing: DCA-00010327

Notes

Order as **23_SMA-50-0-13/111_NE** for Single
 Order as **23_SMA-50-0-13/111_NH** for Bulk 100 pcs

WAIVER! While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.		 HUBER+SUHNER HUBER+SUHNER AG Interconnect Division CH-9100 Herisau Phone +41 (0)71 353 41 11 Fax +41 (0)71 353 45 90 http://www.hubersuhner.com
Issued: 23.03.04 13:52	Document: DOC-0000187987	
RF_Pa_C_PDF <i>uncontrolled copy</i>	Page 1	