

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_UHF-0-3-18/023_-



Description

Straight cable plug

Interface Standards
IEC 60169-12



Technical Data

Electrical Data

Impedance other Ω
Interface frequency max. 0.2 GHz

Mechanical Data

Centre contact crimped
Outer contact crimped
Weight 0.0206 kg

Environmental Data

Operating Temperature -55 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Piece Parts	Material
Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PSU
Coupling nut	Brass
Crimp ferrule	Copper

Surface Plating

Silver Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
Nickel Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00181573
Catalogue drawing	DCA-00045041
Assembly instruction	DOC-0000201061

Ordering Information

Single package 11_UHF-0-3-18/023_-E

Additional Information

Suitable cables RG_223_/U, RG_142_B/U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions