

COAXIAL CONNECTOR, UHF, X Ohm, Straight cable jack (female)  
21\_UHF-0-7-4/033\_

Properties

- Mateable with 4 mm banana plugs
- Applicable in frequencies up to 200 MHz



| Product configuration       |                     |                       |
|-----------------------------|---------------------|-----------------------|
| Interface type              | Gender              | Standard              |
| UHF                         | jack                | IEC 60169-12          |
|                             |                     |                       |
| Interface and material data |                     |                       |
| Piece parts                 | Material            | Plating               |
| Centre contact              | Brass               | Silver Plating        |
| Outer conductor             | Brass               | SUCOPLATE (R) Plating |
| Body                        | Brass               | SUCOPLATE (R) Plating |
| Insulator                   | PFA / PTFE          |                       |
| Crimp ferrule               | Copper              | SUCOPLATE (R) Plating |
|                             |                     |                       |
| Electrical data             |                     |                       |
| Interface frequency         |                     | 0.2 GHz               |
|                             |                     |                       |
| Mechanical data             |                     |                       |
| Weight                      |                     | 0.0324 kg             |
| Mating cycles               |                     | 500                   |
| Cable entry centre contact  |                     | crimped               |
| Cable entry outer contact   |                     | crimped               |
|                             |                     |                       |
| Environmental data          |                     |                       |
| Operation temperature       |                     | -55 °C ... 165°C      |
|                             |                     |                       |
| Ordering Information Table  |                     |                       |
| Item number                 | Item description    |                       |
| 22542775                    | 21_UHF-0-7-4/033_-E |                       |

**COAXIAL CONNECTOR, UHF, X Ohm, Straight cable jack (female)**

21\_UHF-0-7-4/033\_

| Suitable cables        |                     |
|------------------------|---------------------|
| Cable group            | U42 - 7 mm / 50 Ohm |
|                        | U29 - 7 mm / 50 Ohm |
| Suitable cables        | GX_07272            |
|                        | RG_213_/U           |
| Additional cables      | G_07272             |
|                        | RADOX_RF_213        |
| Additional Information |                     |
| Only as assembly       | No                  |

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2825 / Date of publication: 25.11.2023 / uncontrolled copy