

Product Specifications



L4.5PNM-RC

Type N Male RingFlare™ for 5/8 in LDF4.5-50 cable



CHARACTERISTICS

General Specifications

Interface	N Male
Body Style	Straight
Mounting Angle	Straight

Electrical Specifications

Operating Frequency Band	0 – 6100 MHz
Average Power	0.6 kW @ 900 MHz
Cable Impedance	50 ohm
Connector Impedance	50 ohm
dc Test Voltage	2000 V
Inner Contact Resistance	1.50 mOhm
Insulation Resistance, minimum	5000 MOhm
Outer Contact Resistance	1.50 mOhm
Peak Power, maximum	40.00 kW
RF Operating Voltage, maximum (vrms)	707.00 V
Shielding Effectiveness	-110 dB

Mechanical Specifications

Outer Contact Attachment Method	Self-flare
Attachment Durability	25 cycles
Connector Retention Tensile Force	200 lbf 890 N
Connector Retention Torque	48 in lb 5 N·m
Coupling Nut Proof Torque	40.00 in lb 4.52 N·m
Coupling Nut Retention Force	100.00 lbf 444.82 N
Coupling Nut Retention Force Method	MIL-C-39012C-3.25, 4.6.22
Inner Contact Attachment Method	Captivated
Insertion Force	15.00 lbf 66.72 N
Insertion Force Method	MIL-C-39012C-3.12, 4.6.9
Interface Durability	500 cycles
Interface Durability Method	IEC 169-16:9.5
Pressurizable	No

Dimensions

From North America, toll free
Telephone: 1-800-255-1479
Fax: 1-800-349-5444

Outside North America
Telephone: +1-708-873-2307
Fax: +1-779-435-8579

© 2007 Andrew Corporation, Westchester, IL 60154 US
All designs, specifications, and availabilities of products and
services presented are subject to change without notice

page 1 of 2
5/16/2007

Product Specifications



Nominal Size	5/8 in
Diameter, maximum	1.40 in 35.56 mm
Length	3.20 in 81.28 mm
Weight	181.44 g 0.40 lb

Environmental Specifications

Corrosion Test Method	MIL-STD-1344A, Method 1001.1, Test Condition A
Immersion Depth	1 m
Immersion Test Mating	Mated
Immersion Test Method	IEC 529:1989, IP68
Mechanical Shock Test Method	MIL-STD-202F, Method 213B, Test Condition C
Moisture Resistance Test Method	MIL-STD-202F, Method 106F
Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Thermal Shock Test Method	MIL-STD-202F, Method 107G, Test Condition A-1, Low Temperature -55 °C
Vibration Test Method	IEC 68, Part 2-6
Water Jetting Test Mating	Mated
Water Jetting Test Method	IEC 529:1989, IP66

Standard Conditions

Attenuation, Ambient Temperature	20 °C 68 °F
Average Power, Ambient Temperature	40 °C 104 °F

* Footnotes

Immersion Depth	Immersion at specified depth for 24 hours
-----------------	---