

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 21\_N-50-3-12/133\_N

Rev.: D



### Description

Straight cable jack

Interface Standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance 50 Ω

Interface frequency max. 11 GHz

#### Mechanical Data

Centre contact crimped

Outer contact crimped

Weight 0.0348 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C

2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact

Outer contact

Body

Insulator

Crimp ferrule

##### Material

Copper Beryllium Alloy

Brass

Brass

PFA / PTFE

Copper

##### Surface Plating

Gold Plating (Nickel underplated)

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

SUCOPLATE (R) Plating

#### Related Documents

Outline drawing DOU-00006765

Catalogue drawing DCA-00066584

Assembly instruction DOC-0000179851

#### Ordering Information

Single package 21\_N-50-3-12/133\_NE

#### Additional Information

Suitable cables RG\_400\_U, ENVIROFLEX\_400, ASNE 0293 XF

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**

**RF Technology**

**9100 Herisau, Switzerland**

Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90

www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**