



SUHNER® COAXIAL CONNECTOR DATA SHEET

TYPE 21_N-50-9-9/003_-

Description

Straight cable jack for corrugated cable

QUICK-FIT connector

For outdoor applications

Water protection according to IP 68



General Information

N Interface dims acc. to:

IEC 60169-16_MIL-STD-348A/304_CECC 22210

Weight:

0.1121 Kg / 3.95 oz

Cable

Cable type:

SUCOFEED_1/2HF

Cable type:

SUCOFEED_1/2HF-FR

Cable type:

SUCOFEED_1/2HF-FR-UL

Cable type:

FSJ4-50

Cable Entry

Centre contact:

plugged

Outer contact:

clamped

Electrical Data

Impedance:

50Ω

Interface frequency max.:

11 GHz

Frequency range:

0 ... 2.5 GHz

Return loss:

30 dB

VSWR:

1.065

Piece Parts

Center contact:

Material

Bronze

Outer contact:

Brass

Body:

Brass

Surface Plating

Silver Plating

Silver Plating

Silver / SUCOPLATE (R) Plating

Insulator:

PFA / PTFE

Coupling nut:

Brass

SUCOPLATE (R) Plating

Gasket:

NR (Natural Rubber)

Attachments

Outline drawing:

DOU-00007995

Assembly instruction:

DOC-0000179418

WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.



HUBER+SUHNER

HUBER+SUHNER AG
Interconnect Division
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
<http://www.hubersuhner.com>

Issued: 19.12.2003 11:16

Document: DOC-0000183612

RF_Ca_C_PDF

uncontrolled copy

Page 1



SUHNER® COAXIAL CONNECTOR DATA SHEET

Notes

Order as **21_N-50-9-9/003_-E**

for Single

WAIVER!
While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

Issued: 19.12.2003 11:16

Document: DOC-0000183612

RF_Ca_C_PDF

uncontrolled copy

Page 2



HUBER+SUHNER

HUBER+SUHNER AG
Interconnect Division
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
<http://www.hubersuhner.com>