

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 22\_N-50-0-2/133\_N

Rev.: D 

### Description

Straight bulkhead receptacle jack

Interface standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance 50 Ω  
Interface frequency max. 11 GHz

#### Mechanical Data

Weight 0.0457 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

|                |                        |
|----------------|------------------------|
| Centre contact | Copper Beryllium Alloy |
| Outer contact  | Brass                  |
| Body           | Brass                  |
| Insulator      | PFA / PTFE             |
| Gasket         | MVQ (Silicone Rubber)  |
| Fastening nut  | Brass                  |
| Washer         | Bronze                 |

##### Surface Plating

|                                   |
|-----------------------------------|
| Gold Plating (Nickel underplated) |
| SUCOPLATE (R) Plating             |

#### Related Documents

|                   |              |
|-------------------|--------------|
| Outline drawing   | DOU-00011585 |
| Catalogue drawing | DCA-00010169 |

#### Ordering Information

|                |                    |
|----------------|--------------------|
| Single package | 22_N-50-0-2/133_NE |
|----------------|--------------------|

#### Remarks

With panel seal

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**