

## Within Series Adaptor 32\_N-50-0-51/193\_N

### Description

Adaptor plug/plug  
N-precision plug (male) / N-precision plug (male)

Precision adaptor  
For Test & Measurement applications

Interface standard  
Series N-precision - IEC 60169-16\_MIL-STD-348A/402\_CECC 22210



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	18 GHz
VSWR	DC - 18 GHz ≤ 1.03 + 0.01 f (GHz)
Electrical length	52.9 mm

#### Mechanical Data

Number of matings	500
Weight	0.0625 kg

#### Environmental Data

Operating temperature	-55 °C to 70 °C
2011/65/EU (RoHS)	compliant

#### Material Data

Interface - N-precision plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PPH	
Coupling nut	Brass	SUCOPLATE (R) Plating

Interface - N-precision plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PPH	
Coupling nut	Brass	SUCOPLATE (R) Plating

### Related Documents

Catalogue drawing	DCA-00013723
-------------------	--------------

### Ordering Information

Single package	32_N-50-0-51/193_NE
----------------	---------------------

### Remarks

Operating specification acc. IEEE Std 287: temperature 13 °C to 33 °C