

## Typ BU02..

- 5,08 mm pin spacing
- with cage clamp
- 2 .. 16-poles single mold
- wire entry on locking tab side
- 2,7 x 3,5 mm clamp opening



|                                 | <b>cULus</b>                | <b>VDE</b>          |
|---------------------------------|-----------------------------|---------------------|
| Rated voltage                   | 300 V                       | 250 V               |
| Rated current                   | 15 A                        | 12 A                |
| Wire size                       | AWG 22-10                   | 2,5 mm <sup>2</sup> |
| Rated impulse voltage           |                             | 4,0 kV              |
| Pollution degree                |                             | 3                   |
| Rated torque/ screw size        |                             | 0,5 Nm/M3           |
| <b>Max. rated cross section</b> | Single wire (solid)         | 2,5 mm <sup>2</sup> |
|                                 | Stranded wire (flex.)       | 2,5 mm <sup>2</sup> |
|                                 | Stranded wire with ferrules | 2,5 mm <sup>2</sup> |
| <b>Dimensions</b>               | Spacing                     | 5,08 mm             |
|                                 | Stripped length             | 7,0 mm              |
| <b>Materials</b>                | Insulating material         | PA                  |
|                                 | Flammability class          | UL 94 V-0           |
|                                 | Temperature range           | -30°C/+105°C        |
|                                 | Terminal block              | CuZn                |
|                                 | Contact spring              | CuSn                |
| <b>Colour</b>                   | RAL 6018                    | green               |

### Dimensions

