

AC ACC11 1211


Amphenol

Introduction

Amphenol Protective caps are developed for environmental protection needs of Circular connectors in Threaded & Bayonet versions. These are designed to meet the requirements of military standards.


We also offer dummy storage receptacle to secure your cable harness when not in functional use. This catalogue describes the standard and special purpose designs used in Military and Industrial Circular connectors.

	Page
MIL-C-26482 (MS3180 & MS181) Caps -----	1-2
MIL-DTL-38999 Series I (MS27501 & MS27502) Caps -----	3-4
MIL-DTL-38999 Series II (MS27510 & MS27511) Caps -----	5-6
MIL-DTL-38999 Series III (D38999/32 & D38999/33) Caps -----	7-8
MIL-DTL-5015 Reverse Bayonet Caps (97B-25042 & 97B-25043) Caps -----	9
MIL-DTL-5015 Threaded Caps (MS25042 & MS25043) Caps -----	10
MIL-C-10544 Audio Connector Caps for 10 Pin Caps-----	11
MIL-C-55116 Audio Connector Caps for 5 & 6 Pin Caps-----	12
MIL-DTL-22992 Caps -----	13
MIL-C-26482 & MIL-DTL-5015 Dummy Receptacle -----	14-16
MIL-DTL-38999 Series III Dummy Receptacle-----	16
Insertion & Removal Tool-----	17
Backshell for MIL-DTL-24308 -----	18
Square Flange Gaskets for (MIL-C-26482 & MIL-DTL-5015)-----	19



Ordering Information (MIL Part Number)

JANMS3180	10	C	W	L
Designates Plug Dust Cover				
Shell Size: 08, 10, 12, 14, 16, 18, 20, 22 & 24				
Style: C - With Chain R - With SS Rope				
Class: A - Hard Anodize black finish W - Cadmium plate finish				
Length: L - 127.0 + 12.7/-6.35 chain/rope in lieu of std. length				
Note: For non. std. long "L" Contact factory				



Ordering Information (Proprietary Part Number)


IMB3180	08	A	F	N	H
Designates Plug Dust Cover					
Shell Size: 08, 10, 12, 14, 16, 18, 20, 22 & 24					
Class: Aluminium A - Hard anodic B - Zinc nickel finish F - 48 hrs. electroless nickel W - 500 hrs. cadmium olive drab EB - Cad. free zinc cobalt -olive drab finish FB - Cad. free zinc cobalt - black finish T- PT FE nickel finish SD- Zinc Ni Black finish					
Type of attachment D - bead chain passivated F - Wire rope with teflon jacket G - Nylon cord S - Sash chain passivated X - None					
Type of end link: N - Solid ring T -Tie wrap X - None					
Length of attachment: H - Standard length For non- standard 'H', length has to be specified in mm.					

All Dimensions are in mm

Shell Size	ϕA Ref.	ϕF Max. Overall.	H +12.70/-6.35	L Max. Length	X Max. Overall	ϕF +0.00/-0.08 For Heavy Duty
08	12.01	18.26	76.20			22.10
10	14.99	21.44				24.86
12	19.05	25.40				29.24
14	22.22	28.58	88.90	14.27	19.84	32.41
16	25.40	31.75				35.58
18	28.58	34.92				38.22
20	31.75	38.10	101.60	15.88	21.44	41.94
22	34.92	41.28				45.11
24	38.10	44.45		16.71	22.22	48.18


All Dimensions for reference only

Cap without attachment



Ordering information IMB3180 -08 - A - V1

Plug Dust Cover	
Shell Size : 08,10,12,14,16,18,20,22 & 24	
Class: A - Hard Anodic W - Aluminium, 500 hrs. Cadmium Olive Drab F - Aluminium, 48 hrs. electroless nickel T- Nickel PTFE finish	
Variant	



Ordering Information (MIL Part Number)

JANMS3181 10 C W L

Designates Receptacle Dust Cover

Shell Size: 08, 10, 12, 14, 16, 18, 20, 22 & 24

Style:

C - With Chain
N - With Chain & Ring.
R - With SS Rope


Class:

A - Hard Anodize black finish
W - Cadmium plate finish

Length:

L - 127.0 + 12.7/-6.35 chain/rope in lieu of std. length
Leave blank for std.length

Note: For non. std. long "L" Contact factory



Ordering Information (Proprietary Part Number)

IMB3181 08 A F N H

Designates Receptacle Duct Cover

Shell Size: 08, 10, 12, 14, 16, 18, 20, 22 & 24

Class: Aluminium

A - Hard anodic
B - Zinc nickel finish
F - 48 hrs. electroless nickel
W - 500 hrs. cadmium olive drab
EB - Cad. free zinc cobalt -olive drab finish
FB - Cad. free zinc cobalt - black finish
T - PT FE nickel finish
SD- Zinc Ni Black finish

Type of attachment

D -Bead chain passivated
F - Wire rope with teflon jacket
G - Nylon cord
S - Sash chain passivated
X - None

Type of end link:

N - Solid ring
T -Tie wrap
X - None

Length of attachment:


H - Standard length
For non- standard 'H', length has to be specified in mm.

All Dimensions are in mm

Shell Size	H +12.70/ -6.35	ϕK MAX.	L Max.	ϕN MIN	ϕQ MIN	X Max.
08		20.62		14.68	18.64	
10	76.20	25.40		17.86	21.82	
12		30.18		22.63	25.40	
14		36.67	14.27	25.81	28.58	21.44
16	88.90	39.67		28.98	31.75	
18		42.88		32.16	34.92	
20		46.02		35.33	38.10	
22	101.60	49.23		38.51	41.28	
24		52.37	15.29	41.68	44.45	22.22

All Dimensions for reference only

Cap without attachment



Ordering information IMB3181 -08 - A - V1

Designates: Receptacle Dust Cover

Shell Size : 08,10,12,14,16,18,20,22 & 24

Class:

A - Hard Anodic
W - Aluminium, 500 hrs. Cadmium Olive Drab
F - Aluminium, 48 hrs. electroless nickel
T- Nickel PTFE finish

Variant

Technical drawing of the 1000 Series Chain End Fitting, showing top and side views with dimensions.

Top View Dimensions:

- Overall Diameter: $\varnothing B$


Side View Dimensions:

- Overall Height: 29.46 max.
- Flange Height: 22.86 max.
- Chain Link Height: 1.19 max.
- Flange Thickness: 14.73 min.
- Flange Width: 14.40-0.38
- Flange Hole Offset: +0.25
- Chain Link Offset: 4.24-0.13
- Chain Link Length: 12.7
- Chain Link Length: 6.35
- Overall Length: STD. LENGTH

Labels:

- Cover
- Gasket
- Rivet
- Chain S/A

Marking P/No. as per BOM. Location Optional



Shell Size	Ø 'A' +0.02 -0.13	Ø 'B' max	H +12.70 -6.35
09	14.53	18.29	76.20
11	17.78	21.59	
13	21.59	25.40	
15	24.77	28.70	88.90
17	27.94	31.75	
19	30.66	35.05	
21	33.83	38.10	101.60
23	37.01	41.40	
25	40.18	44.45	

Ordering Information

JANMS27501 B 11 C L

Shell Size: 09, 11, 13, 15, 17, 19, 21, 23 & 25

Class:
B-Cadmium plate olive drab finish
C-Hard Anodize black finish
F-Electroless nickel finish

Style: C-With chain
A- Without chain

Length
L- 127.0 + 12.7/-6.35 chain/Rope in lieu of std. length.
Leave blank for std. length. 'H'

Ordering Information (Proprietary)

ILJT27501 09 A D T H

Shell Size: 09, 11, 13, 15, 17, 19, 21, 23 & 25

Finish:
A-Hard anodic non-conductive
W-Cadmium plate with olive drab
E-Electroless nickel
X-Zinc cobalt olive drab
Z-Zinc cobalt olive drab

Type of attachment:
D-Bead chain passivated
G-Nylon cord
S-Sash chain
T-S.S. wire rope with teflon jacket
X- None

Type of end link:
T- Tie wrap
X- None (Small link hole dia 4.49 mm max.)

Length of attachment: H-Standard length For non-standard 'H' length has to be specified in inches.
--

Technical drawing of a shaft-hub assembly. The drawing shows a shaft with a diameter of $\varnothing A$ and a hub with a width of 22.86 max. The shaft has a step with a diameter of 14.73 min. The hub has a step with a diameter of 14.40 - 0.38. The distance between the steps is 1.19 max. The drawing includes a cross-section of the shaft and a cross-section of the hub.



Ordering Information

ILJT27501 08 A V1

Shell Size: 09, 11, 13, 15, 17, 19, 21, 23 & 25

Class: A-Hard Anodic W-Aluminium, 500 hrs. cadmium olive drab. F-Aluminium, 48 hrs. electroless nickel. T-Nickel PTFE finish.
--

Variant



All Dimensions are in mm

Shell Size	ø 'A' max.	ø'B' min	H +12.70 -6.35	J ±0.38	ø'B' max
09	19.81	17.78	76.20	2.67	21.84
11	22.99	21.34			24.89
13	26.95	25.65			29.46
15	30.12	28.96	88.90		32.51
17	33.05	32.00			35.81
19	36.12	35.31			38.61
21	39.22	38.35	101.60		41.91
23	42.34	41.66		44.96	
25	45.54	44.70		48.01	
				3.51	

All Dimensions for reference only

Ordering Information (MIL Part Number)

JANMS27502 B 11 C L

Designates Plug Dust Cover

Shell Size: 09, 11, 13, 15, 17, 19, 21, 23 & 25

Class:
B-Cadmium plate olive drab finish
C-Hard Anodize black finish
F-Electroless nickel finish

Style: C-With chain
A- Without chain

Length
L- 127.0 + 12.7/-6.35 chain/Rope in lieu of std. length.
Leave blank for std. length. 'H'

Note: For non-standard long 'L' contact factory.

Ordering Information (Proprietary Part Number)

ILJT27502 09 A D S H

Designates Plug Dust Cover

Shell Size: 09, 11, 13, 15, 17, 19, 21, 23 & 25


Finish:
A-Hard anodic non-conductive
W-Cadmium plate with olive drab
E-Electroless nickel
X-Zinc cobalt olive drab
Z-Zinc cobalt olive drab

Type of attachment:
D-Bead chain passivated
G-Nylon cord
S-Sash chain
T-S.S. wire rope with teflon jacket
X- None

Type of end link:
S- Solid ring
T- Tie wrap
X- None (Small link hole dia 4.49 mm max.)

Length of attachment:
H-Standard length
For non-standard 'H' length has to be specified in inches.

Cap without attachment




Ordering Information ILJT27502 09 A V1

Designates: Receptacle Dust Cover

Shell Size: 09, 11, 13, 15, 17, 19, 21, 23 & 25

Class:
A-Hard Anodic
W-Aluminium, 500 hrs. cadmium olive drab.
F-Aluminium, 48 hrs. electroless nickel.
T-Nickel PTFE finish.

Variant

[illegible]

Shell Size	Ø 'A' +0.02 -0.13	Ø'B' max OVERALL	H +12.70 -6.35
08	12.01	18.29	76.20
10	14.99	21.59	
12	19.05	25.40	
14	22.22	28.70	88.90
16	25.40	31.75	
18	28.58	35.05	
20	31.75	38.10	101.60
22	34.92	41.40	
24	38.10	44.45	

Ordering Information (MIL Part Number)

JANMS27510 A 08 C L

Designates Plug Dust Cover

Shell Size: 08, 10, 12, 14, 16, 18, 20, 22 & 24

Class:
B-Cadmium plate olive drab finish
C-Hard Anodize black finish
F-Electroless nickel finish

Style: C-With chain
A- Without chain

Length
L- 127.0 + 12.7/-6.35 chain/Rope in lieu of std. length.
Leave blank for std. length. 'H'

Ordering Information (Proprietary Part Number)

```

graph TD
    IJT27510[IJT27510] --> 08[08]
    IJT27510 --> A[A]
    08 --> ShellSize[Shell Size: 08, 10, 12, 14, 16, 18, 20, 22 & 24]
    A --> Finish[Finish:  
A-Hard anodic non-conductive  
W-Cadmium plate with olive drab  
E-Electroless nickel  
X-Zinc cobalt olive drab  
Z-Zinc cobalt olive drab]
    Finish --> Attachment[Type of attachment:  
D-Bead chain passivated  
G-Nylon cord  
S-Sash chain  
T-S.S. wire rope with teflon jacket  
X- None]
    Attachment --> EndLink[Type of end link:  
T- Tie wrap  
X- None (Small link hole dia 4.49 mm max.)]
    EndLink --> Length[Length of attachment:  
H-Standard length  
For non-standard 'H' length has to be specified in inches.]
  
```

IJT27510

08

A

Designates Plug Dust Cover

Shell Size: 08, 10, 12, 14, 16, 18, 20, 22 & 24

Finish:
A-Hard anodic non-conductive
W-Cadmium plate with olive drab
E-Electroless nickel
X-Zinc cobalt olive drab
Z-Zinc cobalt olive drab

Type of attachment:
D-Bead chain passivated
G-Nylon cord
S-Sash chain
T-S.S. wire rope with teflon jacket
X- None

Type of end link:
T- Tie wrap
X- None (Small link hole dia 4.49 mm max.)

Length of attachment:
H-Standard length
For non-standard 'H' length has to be specified in inches.

Technical drawing of a shaft-hub assembly. The drawing shows a shaft with a diameter of $\varnothing A$ and a hub with a bore diameter of $\varnothing A$. The shaft has a total length of 14.48 max. The hub has a total length of 7.87 min. The shaft has a step of 1.19 max. The hub has a step of 1.19 max. The shaft has a tolerance of $+0.25$ and -0.38 on the diameter. The hub has a tolerance of $+0.25$ and -0.38 on the bore diameter. The drawing includes a cross-section of the shaft and a cross-section of the hub.

Ordering Information



Designates Plug Dust Cover

Shell Size: 08, 10, 12, 14, 16, 18, 20, 22 & 24

Class:
A-Hard Anodic
W-Aluminium, 500 hrs. cadmium olive drab.
F-Aluminium, 48 hrs. electroless nickel.
T-Nickel PTFE finish.

Variant

IJT27510 08 A V1

Style C

All Dimensions are in mm

Shell Size	Ø 'A' max.	Ø 'B' min	'C' max	H max.
08	16.00	19.05	22.61	76.20
10	19.23	21.82	25.65	
12	23.77	26.19	28.96	
14	27.28	29.36	32.0	88.90
16	29.77	32.54	35.31	
18	33.12	35.71	38.35	
20	36.45	38.89	41.66	101.60
22	39.62	41.68	44.70	
24	42.88	44.86	48.0	

All Dimensions for reference only

Ordering Information (MIL Part Number)

JANMS27511 A 08 C L

Designates Plug Dust Cover

Class:
B-Cadmium plate olive drab finish
C-Hard Anodize black finish
F-Electroless nickel finish

Shell Size: 08, 10, 12, 14, 16, 18, 20, 22 & 24

Style:
C-With chain
A- Without chain
N-With chain & ring
R-S.S. Rope hole 3.28 max. (08 to 22 size)
3.68 max. (24 size)

Length
L- 127.0 + 12.7/-6.35 chain/Rope in lieu of std. length.
Leave blank for std. length. 'H'
Note: For non-standard long 'L' contact factory.

Note: For non-standard long 'L' contact factory.

Ordering Information (Proprietary Part Number)

IJT27511 08 A D S H

Designates: Receptacle Dust Cover


Shell Size: 08, 10, 12, 14, 16, 18, 20, 22 & 24

Finish:
A-Hard anodic non-conductive
W-Cadmium plate with olive drab
E-Electroless nickel
X-Zinc cobalt olive drab
Z-Zinc cobalt olive drab

Type of attachment:
D-Bead chain passivated
F-S.S. wire rope with nylon jacket
G-Nylon cord
S-Sash chain
T-S.S. wire rope with teflon jacket
X- None

Type of end link:
S- Solid ring
T- Tie wrap
X- None (Small link hole dia 4.49 mm max.)
X1-None (Small link hole dia 3.28 mm max.)
X-2 None (Small link hole dia 3.68 mm max.)

Length of attachment:
H-Standard length
For non-standard 'H' length has to be specified in inches.


Cap without attachment**Ordering information** IJT27511 - 08 - A - V1

Designates: Receptacle Dust Cover


Shell Size : 08,10,12,14,16,18,20,22 & 24

Class:
A - Hard Anodic
W - Aluminium, 500 hrs. Cadmium Olive Drab
F - Aluminium, 48 hrs. electroless nickel
T- Nickel PTFE finish

Variant



(Alternate Type For
Jam Nut Type Only)
S.S. Rope with Ring
Teflon Coating (N)



S.S. Rope
With Teflon Coating (R)

All Dimensions are in mm

Shell Size	'A' Thread -2A -0.1P -0.3L-TS	ØB Max	'C' +0.0 -0.15	ØD Max	ØE Min	'L' + 13.0 -7.0
09	0.625"	23.0	12.50	24.0	13.0	127
11	0.750"	26.0	15.75	27.0	18.0	
13	0.875"	31.0	19.53	30.0	20.0	
15	1.000"	33.0	22.71	31.0	23.0	
17	1.1875"	37.0	25.88	37.0	26.0	
19	1.250"	40.0	28.55	40.0	29.0	
21	1.375"	44.0	31.72	44.0	32.0	
23	1.500"	46.0	34.80	45.0	34.0	
25	1.625"	50.0	38.07	49.0	39.0	

All Dimensions for reference only

Ordering Information (MIL Part Number)

JAND38999/32 W 15 R

Designates Plug Dust Cover

Class:-
F - Electroless nikel finish.
W- Aluminium,500 hrs cadmium olive drab.

Shell Size : 09,11,13,15,17,19,21,23,&25

Style-
R - Rope
N - With rope & ring.

Ordering Information (Proprietary Part Number)

ITV32 09 A F N H

Designates Plug Dust Cover

Shell Size: 09, 11, 13, 15, 17, 19, 21, 23, & 25


Class
Aluminium
A - Hard seal nickel finish
B - Zinc nickel finish cadmium olive drab
F - 48 hrs. elctroless nickel
T - PTFE Nickel Plating
W - 500 Hrs. cadmium olive drab
EB - Cad. free zinc cobolt -olive drab finish
FB - Cad. free zinc cobolt - black finish
T- PT FE nickel finish
SD- Zinc Ni Black finish
Composite
J - Composite cadmium olive drab
M - Composite electroless nickel
NB - Nickel Aluminum Bronze
CD - S. Steel Passivated

Type of attachment
D - Bead chain passivated
F - Wire rope with teflon jacket
G - Nylon cord
S - Sash chain passivated
X - None

Type of end link
N - Solid ring
T - Tie wrap
X - None

Length of attachment
H - Standard length
For non-standard 'H' length has to be specified in mm.

Cap without attachment







Ordering information ITV32 - 09 - A - V1

Designates Plug Cover

Shell Size : 09,11,13,15,17,19,21,23 & 25

Class:
A - Hard Anodic
W - Aluminium, 500 hrs. Cadmium Olive Drab
J - Composite cadmium olive drab
M - Composite electroless nickel
F - Aluminium, 48 hrs. electroless nickel
EB - Zinc Cobalt Loive drab
T- Nickel PTFE finish

Variant



All Dimensions are in mm

Shell Size	'A' Thread -2A-0.1P -0.3L-TS	ØB Max	'C' Max	ØD Min	'L' +13.0 -7.0
09	0.625"	23.0	27.0	17.64	127
11	0.750"	28.0	32.0	21.97	
13	0.875"	31.0	37.0	25.15	
15	1.000"	32.0	40.0	29.92	
17	1.1875"	37.0	44.0	32.0	
19	1.250"	39.0	46.0	36.27	
21	1.375"	42.0	49.0	38.25	
23	1.500"	45.0	54.0	42.62	
25	1.625"	49.0	56.0	44.45	

All Dimensions for reference only

Ordering Information (Proprietary Part Number)

ITV33 09 A F N H

Designates Receptacle Dust Cover

Shell Size: 09, 11, 13, 15, 17, 19, 21, 23, & 25

Class
Aluminium
A - Hard seal nickel finish
B - Zinc nickel finish cadmium olive drab
F - 48 hrs. electroless nickel
T - PTFE Nickel Plating
W - 500 Hrs. cadmium olive drab
EB - Cad. free zinc cobalt -olive drab finish
FB - Cad. free zinc cobalt - black finish
T-PT FE nickel finish
SD- Zinc Ni Black finish
Composite
J - Composite cadmium olive drab
M - Composite electroless nickel
NB - Nickel Aluminum Bronze
CD - S. Steel Passivated

Type of attachment
D - Bead chain passivated
F - Wire rope with teflon jacket
G - Nylon cord
S - Sash chain passivated
X - None

Type of end link
N - Solid ring
T - Tie wrap
X - None

Length of attachment
H - Standard length
For non-standard 'H' length has to be specified in mm.

Ordering Information (MIL Part Number)

JAND38999/33 W 15 R

Designates Receptacle Dust Cover


Class:-
F - Electroless nickel finish.
W- Aluminium, 500 hrs cadmium olive drab.

Shell Size : 09,11,13,15,17,19,21,23,&25

Style-
R - Rope
N - With rope & ring.

Note: For non. std. long "L" Contact factory

Cap without attachment



Ordering information ITV33 - 09 - A - V1

Designates Receptacle Cover

Shell Size : 09,11,13,15,17,19,21,23 & 25

Class:
A - Hard Anodic
W - Aluminium, 500 hrs. Cadmium Olive Drab
J - Composite cadmium olive drab
M - Composite electroless
F - Aluminium, 48 hrs. electroless nickel
T- Nickel PTFE finish


Variant

Other Accessories

Protective cap for 97B series

97B-25042

For Plugs




All dimensions are in mm

PART NUMBER	SHELL SIZE	'A' MAX.	'B' MAX.	'D' + 0.60/-0	'E' MIN.
97 B - 25042 - 10SL	10 SL	21.0	23.50	4.30	90.0
97 B - 25042 - 14S	14 S	27.50			100.0
97 B - 25042 - 16S	16 S	30.0			115.0
97 B - 25042 - 16	16	33.50	31.50	4.70	130.0
97 B - 25042 - 18	18	37.0			
97 B - 25042 - 20	20	40.0			
97 B - 25042 - 22	22	43.0		5.50	190.0
97 B - 25042 - 24	24	49.50			
97 B - 25042 - 28	28	56.0			
97 B - 25042 - 32	32	62.50			
97 B - 25042 - 36	36	68.50			
97 B - 25042 - 40	40	68.50			

Protective Cap For 97B Series

97B-25043

For Receptacle



All dimensions are in mm

PART NUMBER	SHELL SIZE	'A' MAX.	'B' ± 0.20	'D' + 0.60/-0	'E' MIN.
97 B - 25043 - 10SL	10 SL	23.0	16.0	4.30	90.0
97 B - 25043 - 14S	14 S	30.0			100.0
97 B - 25043 - 16S	16 S	32.50			115.0
97 B - 25043 - 16	16	37.0	20.70	5.50	160.0
97 B - 25043 - 18	18	40.50			
97 B - 25043 - 20	20	43.50			
97 B - 25043 - 22	22	47.0			
97 B - 25043 - 24	24	54.0			
97 B - 25043 - 28	28	60.50			
97 B - 25043 - 32	32	67.0			
97 B - 25043 - 36	36	73.0			
97 B - 25043 - 40	40	73.0			

Note :- Please add 07 suffix for bigger end link. Applicable for Jam Nut

97B-25043-XX-624-LXX-V1

97B- Reverse Bayonet caps
MS- Threaded Caps

25042 - Caps for plug
25043 - Caps for receptacle

Shell Size 10sl To 36


Cap w/o chain & rivet hole
For non - std length specified in cm.

A23 Electroless Nickel Finish
624 : Zn CO Black
622 : Zn Co Green
610 : Hard Anodize finish
(Standard supplied Cadmium green colour)

Protective Cap For MS Series

MS-25043

For receptacles Has internal threads and is used on all receptacles. Gasket is provided in the dust cap forming a watertight seal.



All dimensions are in mm


MS Part number	Shell size	A Thread in inches	B	C	D	E
MS 25043-10	10S	5/8-24	11.11	20.7	3.6	102
MS 25043-12	12S	3/4- 20	11.11	25.4	3.6	115
MS 25043-14	14S	7/8-20	11.11	28.6	3.6	115
MS 25043-16	16-16S	1-20	11.11	30.2	3.6	115
MS 25043-18	18	1 1/8-18	11.11	34.1	3.6	115
MS 25043-20	20	1 1/4-18	11.11	37.3	4.4	127
MS 25043-22	22	1 3/8-18	11.11	40.4	4.4	127
MS 25043-24	24	1 1/2-18	11.11	43.6	4.4	140
MS 25043-28	28	1 3/4-18	12.7	50	4.4	197
MS 25043-32	32	2-18	12.7	56.3	4.8	197
MS 25043-36	36	2 1/4-18	12.7	62.7	4.8	197
MS 25043-40	40	2 1/2-16	12.7	69	4.8	197

Other Accessories

Protective cap for MS series

MS-25042



For plugs Has external threads and is used on all plugs where a coupling ring is provided.



All dimensions are in mm

MS Part number	Shell size	A Thread in inches	B	C	D	E
MS 25042-10	10S-1-SL	5/8-24	16.67	17.4	4	102
MS 25042-12	12-12S	3/4- 20	21.4	20.6	4	115
MS 25042-14	14-14S	7/8-20	21.4	23.7	4	115
MS 25042-16	16-16S	1-20	21.4	26.9	4	115
MS 25042-18	18	1 1/8-18	21.4	30	4	115
MS 25042-20	20	1 1/4-18	21.4	33	4.8	127
MS 25042-22	22	1 3/8-18	21.4	36.4	4.8	127
MS 25042-24	24	1 1/2-18	21.4	39.6	4.8	140
MS 25042-28	28	1 3/4-18	21.4	46	4.8	197
MS 25042-32	32	2-18	21.4	52	5.6	197
MS 25042-36	36	2 1/4-18	21.4	58.7	5.6	197
MS 25042-40	40	2 1/2-16	21.4	65	5.6	197

MIL C26482 Heavy Duty Cap 62IN - 1069 - XX For Receptacle



FOR OTHER DETAILS & CONN. SPEC. REF. OUR 62IN CATALOGUE

All Dimensions are in mm

Shell Size	Ø 'A' Min.	Ø 'B'	Ø 'C' Max	Ø 'D' ±0.25	Ø 'J' ±0.25	'L' LENGTH
08	12.22	17.60	22.66	13.13	14.69	76.20
10	15.29	20.35	26.84		17.86	
12	19.33	24.50	29.01		22.64	
14	22.48	27.90	32.19		25.81	
16	25.05	31.07	36.94		28.99	88.90
18	28.85	33.33	39.70		32.16	
20	32.0	36.89	42.85		35.35	
22	35.18	40.06	45.65	14.15	38.51	101.60
24	38.35	43.14	48.82		41.68	


All Dimensions for reference only

Ordering Information

62IN-1069-10-XXX

Series	Shell Size
D/Cap Type	Plating Finish


MIL-C 1054 Dust Cap for 10 Pin Audio Connector




All dimensions in mm

Table 1

Dust Cap No.	Link Type	Cap Finish
164-377	Type-2	Black Anodised
164-377-714	Type-2	Cadmium Plate with Electroless Under Coat
164-377-01	Type-1	Black Anodised
164-377-01-714	Type-1	Cadmium Plate with Electroless Under Coat



ORDERING INFORMATION FOR 164 DUST CAP



895:-Receptacle dust caps for 5 & 6 pin audio connector with chain & solid ring

896:-Plug dust caps for 5 & 6 pin audio connector with chain & solid ring

897:-Receptacle dust caps for 5 & 6 pin audio connector with nylon rope & loop

898:-Receptacle dust caps for 5 & 6 pin audio connector with nylon rope & SS lug

899:-Receptacle dust caps for 5 & 6 pin audio connector with SS rope & lug


900:-Plug dust caps for 5 & 6 pin audio connector with SS rope & loop

901:-Receptacle dust caps for 5 & 6 pin audio connector with nylon rope & solid ring

MATERIAL

Cover : Machined Alluminium Alloy
Gasket : Silicon elastomer
Chain : Stainless steel passivated
Ring : Stainless steel passivated
SS Rope : Stainless steel teflon coated
Rope : Nylon (olive green)
Fastners : Stainless steel passivated

Receptacle Dustcap (AQWLD-17349)





All dimensions are in mm

Amphenol Part No.	MS Part No.	A Thread 2B Double Start	ØD MAX.	E MIN.	L MAX.	ØG MIN.	Q
AQWLD-17349C12*	MS17349C12*	0.875-0.1P-0.2L-DS	27.80	21.10	19.43	25.80	127.00
AQWLD-17349C14*	MS17349C14*	1.000-0.1P-0.2L-DS	31.00	22.10		29.00	
AQWLD-17349C16*	MS17349C16*	1.1250-0.1P-0.2L-DS	34.10	24.60		32.20	
AQWLD-17349C18*	MS17349C18*	1.250-0.1P-0.2L-DS	37.30	25.70		35.30	
AQWLD-17349C20*	MS17349C20*	1.375"-0.1P-0.2L-DS	39.70	28.40		38.50	
AQWLD-17349C22*	MS17349C22*	1.500"-0.1P-0.2L-DS	42.90	30.20	24.90	41.70	152.40
AQWLD-17349C24*	MS17349C24*	1.750-0.1P-0.2L-DS	49.30	33.80		48.00	
AQWLD-17349C28*	MS17349C28*	2.000"-0.1P-0.2L-DS	56.40	37.60		54.40	
AQWLD-17349C32*	MS17349C32*	2.250-0.1P-0.2L-DS	62.70	41.10		60.70	
AQWLD-17349C36*	MS17349C36*	2.500-0.1P-0.2L-DS	69.10	45.00		67.10	
AQWLD-17349C40*	MS17349C40*	2.750-0.1P-0.2L-DS	75.40	48.50		73.40	

*Add attaching ring A, B, or C.

Plug Dustcap (AQWLD-17350)

All dimensions are in mm



Amphenol Part No.	MS Part No.	A Thread 2A Double Start	ØD MAX.	ØH MIN.	Q -0.0 +1 LINK
AQWLD-17350C10*	MS17350C10*	0.750-0.1P-0.2L-DS	20.60	18.30	127.00
AQWLD-17350C12*	MS17350C12*	0.875-0.1P-0.2L-DS	23.80	21.40	
AQWLD-17350C14*	MS17350C14*	1.000-0.1P-0.2L-DS	27.00	24.70	
AQWLD-17350C16*	MS17350C16*	1.1250-0.1P-0.2L-DS	30.20	27.70	
AQWLD-17350C18*	MS17350C18*	1.250-0.1P-0.2L-DS	33.30	30.90	
AQWLD-17350C20*	MS17350C20*	1.375"-0.1P-0.2L-DS	36.50	34.00	152.40
AQWLD-17350C22*	MS17350C22*	1.500"-0.1P-0.2L-DS	39.70	37.30	
AQWLD-17350C24*	MS17350C24*	1.750-0.1P-0.2L-DS	46.00	43.60	
AQWLD-17350C28*	MS17350C28*	2.000"-0.1P-0.2L-DS	52.40	50.00	
AQWLD-17350C32*	MS17350C32*	2.250-0.1P-0.2L-DS	58.70	56.30	
AQWLD-17350C36*	MS17350C36*	2.500-0.1P-0.2L-DS	65.10	62.70	
AQWLD-17350C40*	MS17350C40*	2.750-0.1P-0.2L-DS	71.40	70.60	

*Add attaching ring A, B, or C.

Series
AQWLD

Type
AQWLD 17349 - Cap for Receptacle
AQWLD 17350 - Cap for Plug

Finish
N - Black Anodized (Non-conductive)
C - Cadmium over electroless nickel (Conductive)


Size
12 14 16 18 20 22 24 28 32 36 40

Design
A - Chain & mounting ring
B - Chain without ring
C - Chain with clip


Ordering Information AQWLD 49 C 20 A

Series	_____
Type	_____
Finish	_____
Size	_____
Design	_____

MIL 26482 Dummy Receptacle




Shell Size	'B' Sq.	'C' ±0.08
08	20.62	11.96
10	23.80	14.94
12	26.59	18.97
14	28.58	22.17
16	31.34	25.32
18	33.32	28.52
20	36.50	31.70
22	39.67	34.87
24	42.85	38.05




MIL 5015 Dummy Receptacle Bayonet


Front Panel Mounting Dummy Receptacles Rear Side Closed



Part No.	'A' +0.18 -0.20	'B' ±0.13	Ø'C' +0.00 -0.13	Ø'D' +0.10 -0.00	'E' +0.30 -0.00	'F' +0.18	'G'
97B-3105-10SL-CF	25.40	18.20	18.20	3.20	14.20	2.80	M4
97B-3105-14SL-CF	30.00	23.00	23.00	3.20	14.20	3.20	M4
97B-3105-16SL-CF	32.50	24.60	24.60	3.20	14.20	3.20	M4
97B-3105-16-CF	32.50	24.60	24.60	3.20	19.00	3.20	M4
97B-3105-18-CF	35.00	27.00	30.80	3.20	19.00	4.00	M4
97B-3105-20-CF	38.00	29.40	34.20	3.20	19.00	4.00	M4
97B-3105-22-CF	41.00	31.80	37.40	3.20	19.00	4.00	M4
97B-3105-24-CF	44.50	34.90	40.90	3.70	20.60	4.00	M4
97B-3105-28-CF	50.80	39.70	46.70	3.70	20.60	4.00	M5
97B-3105-32-CF	57.10	44.50	53.40	4.30	22.20	4.00	M5
97B-3105-36-CF	63.50	49.20	59.60	4.30	22.20	4.00	M5
97B-3105-40-CF	69.90	55.50	65.50	4.30	22.20	4.00	M5




Front Panel Mounting Dummy Receptacles Rear Side Opened




Part No.	'A' +0.18 -0.20	'B' ±0.13	Ø'C' +0.00 -0.13	Ø'D' +0.10 -0.00	'E' +0.30 -0.00	'F' ±0.18	'G'
97B-3105-10SL-HF	25.40	18.20	18.20	3.20	14.20	2.80	M4
97B-3105-14SL-HF	30.00	23.00	23.00	3.20	14.20	3.20	M4
97B-3105-16SL-HF	32.50	24.60	24.60	3.20	14.20	3.20	M4
97B-3105-16-HF	32.50	24.60	24.60	3.20	19.00	3.20	M4
97B-3105-18-HF	35.00	27.00	30.80	3.20	19.00	4.00	M4
97B-3105-20-HF	38.00	29.40	34.20	3.20	19.00	4.00	M4
97B-3105-22-HF	41.00	31.80	37.40	3.20	19.00	4.00	M4
97B-3105-24-HF	44.50	34.90	40.90	3.70	20.60	4.00	M4
97B-3105-28-HF	50.80	39.70	46.70	3.70	20.60	4.00	M5
97B-3105-32-HF	57.10	44.50	53.40	4.30	22.20	4.00	M5
97B-3105-36-HF	63.50	49.20	59.60	4.30	22.20	4.00	M5
97B-3105-40-HF	69.90	55.50	65.50	4.30	22.20	4.00	M5

Back Panel Mounting Dummy Receptacles Rear Side closed




Part No.	'A' +0.18 -0.20	'B' ±0.13	Ø'C' +0.00 -0.13	Ø'D' +0.10 -0.00	'E' +0.30 -0.00	'F' ±0.18	'G'
97B-3105-10SL-CF	25.40	18.20	18.20	3.20	18.30	2.80	M4
97B-3105-14SL-CF	30.00	23.00	24.60	3.20	18.30	3.20	M4
97B-3105-16SL-CF	32.50	24.60	27.40	3.20	18.30	3.20	M4
97B-3105-16-CF	32.50	24.60	27.40	3.20	23.15	3.20	M4
97B-3105-18-CF	35.00	27.00	30.80	3.20	23.15	4.00	M4
97B-3105-20-CF	38.00	29.40	34.20	3.20	23.15	4.00	M4
97B-3105-22-CF	41.00	31.80	37.40	3.20	23.15	4.00	M4
97B-3105-24-CF	44.50	34.90	40.90	3.70	23.15	4.00	M4
97B-3105-28-CF	50.80	39.70	46.70	3.70	24.15	4.00	M5
97B-3105-32-CF	57.10	44.50	53.40	4.30	24.15	4.00	M5
97B-3105-36-CF	63.50	49.20	59.60	4.30	24.15	4.00	M5
97B-3105-40-CF	69.90	55.50	65.50	4.30	24.15	4.00	M5

Front Back Mounting Dummy Receptacles Rear Side Opened



Part No.	'A' +0.18 -0.20	'B' ±0.13	Ø'C' +0.00 -0.13	Ø'D' +0.10 -0.00	'E' +0.30 -0.00	'F' ±0.18	'G'
97B-3105-10SL-HF	25.40	18.20	18.20	3.20	18.30	2.80	M4
97B-3105-14SL-HF	30.00	23.00	24.60	3.20	18.30	3.20	M4
97B-3105-16SL-HF	32.50	24.60	27.40	3.20	18.30	3.20	M4
97B-3105-16-HF	32.50	24.60	27.40	3.20	23.15	3.20	M4
97B-3105-18-HF	35.00	27.00	30.80	3.20	23.15	4.00	M4
97B-3105-20-HF	38.00	29.40	34.20	3.20	23.15	4.00	M4
97B-3105-22-HF	41.00	31.80	37.40	3.20	23.15	4.00	M4
97B-3105-24-HF	44.50	34.90	40.90	3.70	23.15	4.00	M4
97B-3105-28-HF	50.80	39.70	46.70	3.70	24.15	4.00	M5
97B-3105-32-HF	57.10	44.50	53.40	4.30	24.15	4.00	M5
97B-3105-36-HF	63.50	49.20	59.60	4.30	24.15	4.00	M5
97B-3105-40-HF	69.90	55.50	65.50	4.30	24.15	4.00	M5

Other Accessories Dummy receptacle MS-3105





All dimensions are in mm

Part number (see note)	A	B	C	D Thread in inches	E	F max.	G
MS-3105-10S	25.4	18.26	3.05	5/8-24	14.27	3.96	8.20
MS-3105-12S	27.79	20.62	3.05	3/4-20	14.27	3.96	11.43
MS-3105-12	27.79	20.62	3.05	3/4-20	19.05	3.96	11.43
MS-3105-14S	30.17	23.01	3.05	7/8-20	14.27	3.96	13.36
MS-3105-14	30.17	23.01	3.05	7/8-20	19.05	3.96	13.36
MS-3105-16S	32.54	24.61	3.05	1-20	14.27	3.96	16.41
MS-3105-16	32.54	24.61	3.05	1-20	19.05	3.96	16.41
MS-3105-18	34.92	26.97	3.05	1 1/8-18	19.05	5.16	18.03
MS-3105-20	38.10	29.36	3.05	1 1/4-18	19.05	5.16	23.54
MS-3105-22	41.27	31.75	3.05	1 3/8-18	19.05	5.16	25.93
MS-3105-24	44.45	34.92	3.73	1 1/2-18	20.62	5.16	29.21
MS-3105-28	50.8	39.67	3.73	1 3/4-18	20.62	5.16	34.67
MS-3105-36	63.5	49.22	4.39	2 1/4-16	22.2	9.11	46.56

Note: The dash number also indicates shell size.

MIL DTL 38999 Series III Dummy Receptacle




Shell Size	Mil. Code	Ø A +0.13 -0.0	'B' R H Thread	Ø D	'G' +0.23 -0.25	'L'
09	A	11.23	5/8" 0.1P-.3LTS	31.75	23.83	18.50
11	B	14.48	3/4" 0.1P-.3LTS	34.93	26.19	
13	C	17.32	7/8" 0.1P-.3LTS	38.10	28.58	
15	D	20.50	1.0" 0.1P-.3LTS	41.28	30.96	
17	E	23.67	1 3/16" 0.1P-.3LTS	44.45	33.32	
19	F	26.34	1 1/4" 0.1P-.3LTS	47.63	36.53	19.50
21	G	29.51	1 3/8" 0.1P-.3LTS	50.80	39.67	
23	H	32.69	1 1/2" 0.1P-.3LTS	55.58	42.88	
25	J	35.86	1 5/8" 0.1P-.3LTS	60.33	46.02	

Ordering Information

ITV22 - 09 - W

Series Plating Finish

Insertion Removal Tool



Ordering Information

IRT - XXX - XX

Insertion & Removal Tool

Contact Size





Colour Code

SR. NO	MIL Part Number	Amphenol Part Number	Contact Size	Colour Installing Tip	Code Removal Tip	'A' max.	'M' min.	'L' max.	'H' max.
1	M81969/14-01	IRT - 22D -GW	22D	Green	White	114.0	15.24	7.36	2.28
2	M81969/14-11	IRT - 20 -RW	20	Red	White	114.0	19.30	7.36	3.81
3	M81969/14-10	IRT - 20 -RO	20	Red	Orange	114.0	19.30	7.36	3.81
4	M81969/14-03	IRT - 16 -BW	16	Blue	White	114.0	25.40	11.18	5.87
5	M81969/14-04	IRT - 12 -YW	12	Yellow	White	114.0	25.40	11.18	7.29

Backshell for D - SUB (M24308) Connector

BACKSHELL FOR D-SUB (M24308) CONNECTOR:

A. METALLIC STRAIGHT CABLE HOUSING WITH CABLE CLAMP :



Ordering Information

M2000/48 - 2 - X - XX

SERIES No.

DASH No.


SHELL SIZE

FINISH DESIGNATOR

FINISH : F - CADMIUM PLATE WITH YELLOW PASSIVATION
Z - ZINC PLATE WITH YELLOW PASSIVATION
TI - TIN PLATED

Sr.No.	MIL Part No.	SHELL SIZE	No. of PINS DENSITY		A	B	C	D max	L max
			STD	HIGH					
1	M2000/48-2-1Z	1	9	15	30.70	12.40	24.99	10.30	27.80
2	M2000/48-2-2Z	2	15	26	39.00	12.40	33.32	10.30	27.80
3	M2000/48-2-3Z	3	25	44	52.90	12.40	47.04	15.10	28.60
4	M2000/48-2-4Z	4	37	62	69.20	12.40	63.50	18.30	28.60
5	M2000/48-2-5Z	5	50	78	66.80	15.25	61.11	18.30	28.60

Hood for D-Sub (M24308) Connector Metal Hood (Straight Entry)



Ordering Information (Military Part Number)

M2000 / X X-XXXX

Series No.	
Shell Size	
Finish Designator	
Type-	
MH- Metal Hood (Straight Entry)	
MHA- Metal Hood (Angle Entry)	
PH- Plastic Hood (Straight Entry)	
PHA- Plastic Hood (Angle Entry)	
MPH- Metallized Plastic Hood (Straight Entry)	
MPHA- Metallized Plastic Hood (Angle Entry)	

All Dimensions are in mm

Sr. No.	Shell Size	No. of Pins Density		'A'	'B'	'C'	'D'	'L'
		Std.	High					
01	01	09	15	31.50	15.60	24.99	6.00	47.60
02	02	15	26	40.80	15.60	33.30	10.00	48.20
03	03	25	44	54.20	16.00	47.00	10.00	48.80
04	04	37	62	69.20	16.00	63.50	10.20	48.60
05	05	50	78	67.10	18.00	61.10	12.30	48.60

* For angle entry please contact factory.

Finish-


Z- Zinc Plate with yellow passivation

F- Cadmium Plate with yellow passivation


For nickel plated no suffix is required.

Flange Mounting Gasket

(Replace XX with the required shell size)



62IN-760-XX




All dimensions in mm

Shell size	D	E	F Dia	G Dia	H max
8	20.62	15.08	12.90	3.30	1.06
10	23.82	18.26	16.07	3.30	1.06
12	26.18	20.65	19.25	3.30	1.06
14	28.57	23.01	22.42	3.30	1.06
16	30.96	24.61	25.60	3.30	1.06
18	33.32	27.00	28.77	3.30	1.06
20	36.52	29.36	31.95	3.30	1.06
22	39.70	31.75	35.13	3.30	1.06
24	42.87	34.92	38.30	3.96	1.06

Other Accessories

Plain flat gasket

For MS and 97B flange mounted receptacles



All dimensions are in mm

Part number	Shell size	A max	B	C	D	T
MS-101000	10SL	18.26	15.90	25.40	4.35	1.5
MS-108686	12S & 12	20.62	19.05	27.80	4.35	1.5
MS-101001	14S & 14	23.01	22.20	30.15	4.35	1.5
MS-101002	16S & 16	24.61	25.40	32.50	4.35	1.5
MS-101003	18	27.00	28.57	34.90	5.15	1.5
MS-101004	20	29.36	31.75	38.10	5.15	1.5
MS-101005	22	31.75	34.90	41.20	5.15	1.5
MS-108687	24	34.90	38.10	44.45	5.15	1.5
MS-101006	28	39.70	44.45	50.80	5.15	1.5
MS-108688	32	44.45	50.80	57.15	5.55	1.5
MS-101007	36	49.22	55.57	63.50	5.55	1.5
MS-110831	40	55.77	61.92	69.85	5.55	1.5

*For Conductive and rear Mount Gasket contact factory.

Notice : All information, including illustrations given herein is believed to be accurate at the time of printing. In lieu of design advances, Amphenol reserves the right to change specifications without notice. This publication Dust Cap Accessory Series Connectors AC ACC11 1211 supercedes all existing Amphenol literature on Dust Cap Accessory Series Connectors.

NORTH AMERICA

Sales & Product Support

Amphenol PCD
72 Cherry Hill Drive
Beverly, MA 01915 USA
Tel: +1-978-624-3400
Fax: +1-978-927-1513
info@amphenolpcd.com
www.amphenolpcd.com
www.backshellworld.com

Amphenol Aerospace Operations
40-60, Delaware Avenue
Sidney, NY 13838-1395
Tel: +1-607-563-5011
Fax: +1-607-563-5357

Amphenol Canada
Meford Drive
Scarborough,
ON M1B 2X6
Tel: +416-291-4401
Fax: +416-292-0647

Amphenol Fiber Systems International
1300 Central Expressway North
Suite 100 Allen, Texas 75013, USA
Tel: +1-214-547-2400
Fax: +1-214-547-9344

EUROPE

France

Amphenol Socapex S.A.S.
948, Promenade de l'Arve
Bp29, Thyez Cedex
74311, France
Tel: +33-4-5089-2800
Fax: +33-4-5096-1941

United Kingdom

Amphenol Limited
Thanet Way, Whitstable
Kent CT5 3JF, England
Tel: +44-1227-773-200
Fax: 44-1227-276-571

Germany

Amphenol-Air LB GmbH
Am Kleinbahnhof 4
Saarlouis
D-66740, Germany
Tel: 49-6831-9810-00
Fax: 49-6831-9810-30

Italy

Via Barbaiana 5
20020 Lainate (Milano)
Italy
Tel: +39-02-93254.209
+39-02-93254.214
Fax: +39-02-93254-444

Center & East Europe

Amphenol
Wiener Gasse 68
2380 Perchtoldsdorf
Tel: +43-699-10396071
Fax: +43 699 40396071

Amphenol Air-LB
Immeuble Le Doublon
11, Avenue Dobonnet
Courbevoie-Cedex
92407, France
Ph: +33-1-4905-3000
Fax: +33-1-4905-3043

Spain

Amphenol Iberica
Edificio Burgosol Oficina
N 55 C/Comunidad de
Madrid 35 bis -
Las Rozas (Madrid)
Tel: +34-91-6407302
+34-91-6407306
Fax: +34-91-6407307

Austria

Amphenol Austria
Wiener Gasse 68
2380, Erchtoldsdarf,
Austria
Tel: + 43-69910396071
Fax: + 43-69940306071

Holland

Amphenol Benelux
Zadelmaker 121
NL-2401 PD Alphen
aan den Rijn Holland
Tel: +31-172-444903
Fax: +31-172 240254

Sweden

Amphenol
(Nordic & Baltic)
Ängsullsvägen 7
S-187 51 Täby.
Sweden
Tel: +46-85-1051816
+46-76-8418600
Fax: +46-70- 2634677
+46-70-2203197

ASIA

India

Amphenol Interconnect India Pvt. Ltd.
105 Bhosari Industrial Area
Pune-411026, India
Tel: +9120-3068-8305
Fax: +9120-2712-9158

Amphenol Interconnect India Pvt. Ltd.
61 Electronics City
Bangalore-560 100, India
Ph: +9180-2852-3838
Fax: +9180-2852-0418

Japan

Amphenol Japan
471-1, Deba, Ritto City
Shiga 520-3041, Japan
Tel: +81-77-553-8501
Fax: +81-77-551-2200

Korea

Amphenol Daeshin Electronics
558 SoSa, SongNae, Bucheon-City
Kyunggi-Do, Korea 420-130
Tel: +82-32-610-3800
Fax: +92-32-673-2507

Singapore

Amphenol East Asia Ltd.
72 Bendemeer Road
03-33 Luzerne
Singapore 339 941
Tel: 65-6294-2128
Fax: 65-6294-3522

China

Amphenol PCD Shenzhen
3/F Building, A4 Songbai
Industrial Park
East Road of Minghuan
Gongming Town, Baon District
Shenzhen, China
Tel: +86-755-8173-8000
Fax: +86-755-8173-8180

ROW

Australia

Amphenol Australia Pty Ltd
2 Fiveways Boulevard
Keysborough
VIC 3173
Ph: +61-3-8796-8888
Fax: +61-3-8796-8801

Africa

Amphenol South Africa
30 Impala Road
2196 Sandton-Chistlehurst
South Africa
Tel: +27-11-783-9517
Fax: +27-11-783-9519

Russia

Amphenol Russia
8-2 Yaroslavskaja Str
129164 Moscow, Russia
Tel: +7-495-937-6341
Fax: +7-495-937-6319

Argentina

Amphenol Argentina
Avenida Callao 930
2nd Floor, Office B Plaza
C1023AAP Buenos Aires
Argentina
Tel: 54-11-4815-6886
Fax: 54-11-4814-5779

Israel

Bar-Tec Ltd.
P.O. Box 279
Kfar Sava, 44102 Israel
Tel: +972-9-7644100
Fax: +972-9-7674324

Maslak

34396 Istanbul
Tel: +90-212-335-2501
Fax: +90-212-335-2500

Brazil

Amphenol do Brasil Ltda
Rua Diogo Moreira 132
CEP 05423-010
Sao Paulo-SP, Brazil
Tel: +55-11-3815-1003
Fax: +55-11-3815-1629

Amphenol

A Global Company



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

[MS3181-12CA](#) [MS3180-14RA](#) [MS318110N](#) [MS3181-10RAL](#) [MS3180-18C](#) [MS3181-12RA](#) [MS3180-10C](#)
[MS31818CA](#) [MS318112N](#) [MS3181-14RA](#) [MS3181-24CA](#) [MS318122CA](#) [MS31808CA](#) [MS3181-8RA](#) [MS318116C](#)
[MS3181-18NA](#) [MS3180-16CA](#) [MS318014CA](#) [MS3180-12C](#) [MS3180-10CA](#) [MS3180-12RAL](#) [MS318114CA](#)
[MS318120NA](#) [MS3181-12RAL](#) [MS3180-8C](#) [MS3180-14C](#) [MS3181-18C](#) [MS318020CA](#) [MS3180-24CA](#) [MS3181-14C](#)
[MS318018CA](#) [MS318118RA](#) [MS3180-8CAL](#) [MS3181-10NA](#) [MS3181-16CA](#) [MS3181-10RA](#) [MS31818C](#)
[MS318122C](#) [MS318120CA](#) [MS318112CAL](#) [MS3180-22CA](#) [MS318122NA](#) [MS318116NA](#) [MS318012CA](#)
[MS318110C](#) [MS3181-18CA](#) [MS318114NA](#) [MS318022CAL](#) [MS3180-14CA](#) [MS3181-18CL](#) [MS3180-14RW](#) [MS3181-](#)
[10NL](#) [MS3181-20NW](#) [MS3180-16CL](#) [MS3181-08CA](#) [MS3181-16RA](#) [MS3181-08RA](#) [MS3181-24CL](#) [MS3181-08RW](#)
[MS3181-10RW](#) [MS3181-08CL](#) [MS3181-08CW](#) [MS3181-24RL](#) [MS3181-14RW](#) [MS3181-14RL](#) [MS3181-18NL](#)
[MS3180-18RW](#) [MS3181-08RL](#) [MS3180-24CL](#) [MS3181-20RW](#) [MS3180-14CL](#) [MS3181-22NL](#) [MS3181-22NW](#)
[MS3180-18CW](#) [MS3180-16RA](#) [MS3181-14CL](#) [MS3180-08RW](#) [MS3180-12RW](#) [MS3181-12CL](#) [MS3180-20CL](#)
[MS3181-10NW](#) [MS3180-24RW](#) [MS3180-16CW](#) [MS3180-24RA](#) [MS3180-18RA](#) [MS3181-14NL](#) [MS3181-20NL](#)
[MS3181-16NW](#) [MS3181-12NA](#) [MS3181-12NW](#) [MS3181-16RW](#) [MS3181-12RW](#) [MS3180-08RA](#) [MS3180-10RW](#)
[MS3181-24NW](#) [MS3181-12CW](#) [MS3181-08NA](#) [MS3181-10RL](#) [MS3181-14NW](#) [MS3181-10CW](#)