



Standard Plugs & Sockets



Plessey

The Company's development engineers are constantly improving designs, thus equipment supplied may vary in detail from that illustrated in this catalogue.

Standard Plugs & Sockets

Plessey

INTRODUCTION

Plessey multi-pin plugs and sockets have long been standard fitments in nearly every British aircraft.

First produced in World War II—under the trade name “Breeze”—they replaced “point-to-point” wiring systems and opened the way for mass aircraft production. These plugs and sockets allowed the prefabrication of complete wiring systems, which were then fitted at any convenient assembly stage. All parts conform to official specifications and many carry Air Ministry reference numbers. The Plessey range of Standard plugs and sockets is now one of the most comprehensive ranges in the industry and is constantly being enlarged to meet the demands of supersonic flight.


Intensive development has been carried out to improve the temperature conditions, altitude and general electrical characteristics of these connectors with the result that the range illustrated in this publication is capable of operating between ambient temperatures of -65°C . and $+150^{\circ}\text{C}$.

Careful attention has been paid to improvements made in order that this new uprated range remains interchangeable wherever possible with earlier types. This has proved to be highly successful and production of all items other than those illustrated within this publication will cease upon the introduction of the slit comb (see page 11).

Certain items however cannot be considered to be interchangeable in certain circumstances and have therefore been classified as “obsolete” in the index and production of small quantities may be undertaken to special order but a protracted delivery and special prices may prove unavoidable.


It is important that the specification of Standard plugs and sockets on new equipment is limited only to items illustrated within this publication.

RANGE OF STANDARD PLUGS & SOCKETS




Single plug (climatic proof)

Shells available in aluminium or steel, with plug pins suitable for crimping or soldering.




Bulkhead plug (climatic proof)

Double-ended for "breaks" on both sides of bulkheads. Shells available in lightweight aluminium or steel.




Bulkhead plug (pressurised)

Double-ended for "breaks" on both sides of pressurised bulkheads. Suitable where a minimum leakage of 1 c.c. per hour is permissible at a pressure difference of 1 atmosphere. Available in aluminium only.




Normal and reverse socket (vibration and climatic proof)

Sealed against climatic conditions, with vibration-proof inserts. Supplied in aluminium or steel, with inserts suitable for crimping or soldering.




Right-angle short-reach socket

For use in confined space. Soldered connections, with shell in aluminium or steel.




Thermo-couple plug and socket

For use in circuits employing temperature compensating leads. Pin and socket inserts of constantan and brass, or chromel and alumel.



Heavy duty pressurised bulkhead connector block

For use at pressure cabin bulkheads, where heavy duty leads must be broken. Fully pressurised at 15 lb.



Plug (detachable leads)

For use on equipment where only short leads are required behind the plug. Shell in aluminium, and with soldered connections.

This page shows the types of Standard plugs and sockets available, with some indication of typical uses and applications.

INDEX

INTRODUCTION	2
Illustrated range	3
Performance and method of selection	5
Design and electrical features	6
Summary of part numbers	7
Single plug	8
Bulkhead (climatic proof) plug	9
Bulkhead (pressurised) plug	10
Socket (climatic and vibration proof) normal and reverse	11
Thermocouple plug and socket	12
Special purpose plugs and sockets	13
Panel piercing details	14
Spare parts for replacement	15
Evolution of the single plug	16
Evolution of the bulkhead (climatic proof) plug	17
Evolution of the bulkhead (pressurised) plug	18
Evolution of the contact design	19
Evolution of the socket (normal and reverse)	20-21
ACCESSORIES	22
Plug sealing cap	22
Plug screening cap	22
Coupling nuts	22
Plug shrouds	23
Ferrule plate assembly	23
Clamp rings	23
Inner and outer ferrules	24
Ferrules for plastic tubing	24
Conduit (type H) ferrules	24
Conduit (type G) ferrules	25
Elbow assemblies	25
Tee connectors	25
Cut ferrules (round base)	26
Cut ferrules (square base)	26
Index to Air Ministry reference numbers	27-28
Index to Plessey part numbers	29-39
Contact arrangements	pull-out sheet

PERFORMANCE

Plessey Standard plugs and sockets were primarily designed for d.c. systems, but their use is not restricted to low voltage circuits although their suitability for a.c. naturally depends on voltage, frequency and other characteristics.

This range of plugs and sockets is normally climatic proof, but should not be mounted under conditions of full exposure. Contact resistance does not exceed 2 milliohms on contacts up to 10 amperes, and 1 milliohm for contacts rated above this figure. By the use of special fittings, the steel range can be adapted to withstand a flame temperature of 1,200° C. for a short period without circuit failure. Details are available on request.

Laboratory tests under simulated high altitude conditions have proved that these assemblies can be safely employed for duty at 208 volts a.c. at altitudes up to and including 60,000 feet.

By virtue of the introduction of silicone gaskets and insulants moulded from alkyd, combined with other slight design changes, these plugs and sockets are suitable for use between ambient temperatures of -65° C. and +150° C.

There are 23 normal contact combinations available, which can be contained within aluminium or steel shells. Contacts are available for 7, 19, 37 and 64 ampere ratings, in 6 basic shell or body sizes.

A wide variety of fittings is available to take multi-core and single cables, both braided and unbraided. Although primarily designed to accommodate the "cel" range of cables they can as readily be used with the "pren" range. Many other different types of cable can be used and expert advice on the fittings required will always gladly be given by the Company's advisory service at Cheney Manor, Swindon.

Standard sockets are listed as "normal" and "reverse". "Reverse" sockets are identical to the "normal" sockets except that the coding of the inserts is reversed (i.e., a mirror reflection of the coding of the "normal" socket), and the moulding is marked with the letter "A". "Reverse" sockets are only used with bulkhead plugs which mate with one "normal" and one "reverse" socket, thus facilitating continuity of the coding system throughout the circuit. All socket assemblies listed in the main catalogue are specially proofed against vibration.

Pin dispositions are so arranged that it is impossible to mis-mate a plug and socket; the latter being fully floating within the housing ensuring an evenly balanced contact pressure. To disconnect a plug and socket, the coupling nut has only to be slackened to allow the socket housing, outside the mouldings, to be unscrewed from the plug shell.

Failure of electrical systems in adverse weather has often been attributed to the closeness of pins in multi-connectors. Since a creepage path occurs by deposited moisture forming a chain, widely spaced pins in a single plane will be no improvement if condensation is present. The solution, embodied in all Standard plugs, has been to increase the dielectric spacing between pins on different planes, thus breaking the continuity of condensation deposits and counteracting the formation of creepage paths. To make this possible, the moulding is so designed that the pins stand in a cavity formed by a series of ridges.

SELECTING SUITABLE PLUGS AND SOCKETS

Full details of the Standard range of Plessey plugs and sockets, and numerous accessories, will be found in the body of the catalogue. To select a suitable plug and socket, reference should first be made to the folded sheet facing page 39, wherein details of the 23 normal contact combinations are contained. Reference should then be made to the classified tables of plugs and sockets on pages 8 to 13 and against the contact combination already identified will be found the requisite part numbers of the plugs or sockets, together with Air Ministry reference numbers, as applicable, and dimensional information.

To assist in the identification of items of current manufacture, an index to the entire range of Plessey Standard plugs, sockets and accessories has been compiled on pages 29 to 39. Those part numbers in heavy print are of current manufacture and detailed information regarding them will be found in the classified tables on pages 8 to 13, whilst the remainder are either discontinued or obsolescent.

A comparator of Air Ministry reference numbers to Plessey part numbers will also be found on pages 27 to 28, and here again, heavy print denotes current manufacture.

It will assist greatly if the relevant Plessey part numbers are quoted on all orders.

design AND electrical FEATURES OF STANDARD PLUGS AND SOCKETS

APPROVAL	Approved by the Ministry of Supply and specified for use on civil and military aircraft.
HIGH ALTITUDE	Suitable for operation at altitudes up to and including 60,000 feet, at which height tests show safe rating of 208 volts a.c.
TEMPERATURE	Suitable for operation between - 65° C. to + 150° C. ambient temperatures.
PRESSURISED	The pressurised bulkhead plug only is sealed against pressures up to 15 lb. per square inch.
HUMIDITY	All types are climatic proof, suitable for operation under humid conditions, but should not be mounted under conditions of full exposure.
VIBRATION PROOF	Suitable for operation where vibration is encountered, the coupling nuts on the sockets being provided with holes for wire locking.
VOLTAGE RATING	250 volts d.c. or 350 volts a.c. at sea level.
CURRENT RATING	Contacts are available for 7, 19, 37 and 64 ampere ratings.
CONTACT RESISTANCE	Does not exceed 2 milliohms on contacts up to 10 amperes and 1 milliohm for contacts rated above 10 amperes.
FLAMEPROOF	By the use of special fittings, the steel range can be adapted to withstand a flame temperature of 1,200° C. for a short period without circuit failure. Details are available on request.
CONTACTS	Plug pins and socket inserts are of brass, silver plated for good electrical connection and may be soldered or crimped as desired.
SHELL DESIGN	Throughout the ranges, the plug is always the fixed unit and the socket the free unit. A reverse socket being used on one side of each bulkhead plug.
CABLE FITTINGS	A comprehensive range of fittings are available to suit almost any known type of cable available.
EXTENDED CREEPAGE PATH	By virtue of design of the moulding, voltage breakdown between pins is practically eliminated.

Plessey

STANDARD PLUGS & SOCKETS

Detailed particulars of Plessey Standard plugs and sockets of current manufacture will be found on pages 8 to 11. For convenience, a summary of these part numbers is given in the tables below, but the thermo-couple and special purpose plugs and sockets listed on pages 12 and 13 are not included.

PLUGS

Body Size	Code *	Contact Combination				SINGLE		BULKHEAD		
		7A	19A	37A	64A	Aluminium	Steel	Aluminium	Pressurised	Steel
						Climatic	Climatic	Climatic		Climatic
A	1	2	—	—	—	2CZ 111223	2CZ 108906	2CZ 111413	2CZ 138097	2CZ 84864
	2	4	—	—	—	111399	84870	111414	138099	84865
	3	—	1	—	—	111400	108907	111415	138096	108925
Z	4	5	—	—	—	111401	85945	111416	138104	108926
	5	—	2	—	—	111402	108908	111417	138098	108927
	6	2	2	—	—	111403	108909	111418	138100	108928
B	7	9	—	—	—	111224	84871	111419	138246	84866
	8	2	4	—	—	111404	108910	111420	138106	108929
	9	—	4	—	—	111299	108911	111421	138101	108930
	10	—	5	—	—	111405	108912	111422	138105	108931
	11	7	2	—	—	111225	108913	111423	138247	108932
C	12	1	—	3	—	111406	108914	111424	138102	108933
	13	12	—	—	—	111226	108915	111425	138111	84867
	14	12	2	—	—	111227	108916	111426	138113	84868
	15	—	6	—	—	111297	108917	111427	138107	108934
	16	—	—	4	—	111228	108918	111428	138103	108935
	17	2	2	4	—	111407	108919	111429	138109	108936
D	18	4	7	2	—	111408	108920	111430	138112	108937
	19	6	2	2	—	111409	108921	111431	138110	108938
	20	12	4	—	—	111410	108922	111432	138114	108939
	21	24	2	—	—	111229	108923	111433	138115	84869
	22	4	—	—	2	111411	108924	111434	138108	108940
E	23	20	4	3	—	111412	108905	111435	138116	108941
See page						8	8	9	10	9

* These codes represent the various contact arrangements, which are illustrated on the folded sheet facing page 39.

SOCKETS




Body Size	Code *	Contact Combination				NORMAL		REVERSE (BULKHEAD)	
		7A	19A	37A	64A	Aluminium	Steel	Aluminium	Steel
						Vib. proof and Climatic			
A	1	2	—	—	—	2CZ 111230	2CZ 108972	2CZ 111448	2CZ 84879
	2	4	—	—	—	111231	84873	111449	84880
	3	—	1	—	—	111232	108943	111232	108943
Z	4	5	—	—	—	111233	84874	111451	108959
	5	—	2	—	—	111436	108944	111452	108960
	6	2	2	—	—	111437	108945	111453	108961
B	7	9	—	—	—	111234	84875	111454	84881
	8	2	4	—	—	111438	108946	111455	108962
	9	—	4	—	—	111298	108947	111456	108963
	10	—	5	—	—	111439	108948	111457	108964
	11	7	2	—	—	111440	108949	111458	108965
C	12	1	—	3	—	111441	108950	111459	108966
	13	12	—	—	—	111235	84876	111460	84882
	14	12	2	—	—	111236	84877	111461	84883
	15	—	6	—	—	111296	108951	111462	108967
	16	—	—	4	—	111237	108952	111463	108968
D	17	2	2	4	—	111442	108953	111464	108969
	18	4	7	2	—	111443	108954	111465	108970
	19	6	2	2	—	111444	108955	111466	108971
	20	12	4	—	—	111445	108956	111467	108972
	21	24	2	—	—	111238	84878	111468	84884
	22	4	—	—	2	111446	108957	111469	108973
E	23	20	4	3	—	111447	108942	111470	108974
See page						11	11	11	11

* These codes represent the various contact arrangements, which are illustrated on the folded sheet facing page 39.

Plessey

SINGLE PLUG (Climatic Proof)

Proof against all climatic conditions, being fitted with gaskets on each side of the front moulding. Suitable for crimped or soldered connections. Shells available in aluminium, or steel.




NOTE : A brass backing plate is to be introduced for use behind the rear moulding in order to prevent any damage by undue tightening of the fixing screws.

Body Size	CONTACTS				ALUMINIUM			STEEL			A	B	C dia.	D dia.	E sq.	F crs. sq.	Fixing holes
	7 A.	19 A.	37 A.	64 A.	Part No.	A/M Ref.	Weight oz.	Part No.	A/M Ref.	Weight oz.							
A	2	—	—	—	2CZ	5X/111223	.8	2CZ	5X/108906	1.1	.941	1.384	.497	.781	.937	.720	6BA
	4	—	—	—	111399	7140	.8	8470	7030	1.2							
	—	—	—	—	111400	7141	.8	108907	7050	1.1							
Z	5	—	—	—	111401	7142	1.1	85945	7032	1.4	.941	1.509	.679	.934	1.125	.875	6BA
	2	—	—	—	111402	7143	1.1	108908	7109	1.4							
B	—	—	—	—	111403	7144	1.2	108909	7110	1.5	.941	1.509	.897	1.153	1.250	1.000	6BA
	9	—	—	—	111224	7145	1.5	84871	7033	1.9							
	2	—	—	—	111404	7146	1.6	108910	7111	2.0							
	—	—	—	—	111299	7147	1.5	108911	7112	2.0							
C	—	—	—	—	111405	7148	1.6	108912	7113	2.1	.941	1.509	.897	1.153	1.250	1.000	6BA
	7	—	—	—	111225	7149	1.6	108913	7034	2.0							
D	—	—	3	—	111406	7150	2.0	108914	7031	2.5	.941	1.509	1.047	1.341	1.437	1.187	6BA
	12	—	—	—	111226	7151	1.9	108915	7035	2.4							
	12	—	—	—	111227	7152	2.0	108916	7036	2.5							
	—	—	6	—	111297	7153	2.0	108917	7114	2.5							
E	—	—	4	—	111228	7154	2.2	108918	7115	2.7	.941	1.509	1.047	1.341	1.437	1.187	6BA
	2	—	—	—	111407	7155	3.0	108919	—	3.7							
D	4	—	2	—	111408	7156	3.1	108920	—	3.9	.941	1.509	1.416	1.715	1.750	1.469	6BA
	6	—	2	—	111409	7157	2.9	108921	—	3.6							
	12	—	4	—	111410	7158	2.8	108922	7116	3.6							
D	24	—	2	—	111229	7159	2.9	108923	7037	3.6	.941	1.509	1.416	1.715	1.750	1.469	6BA
	4	—	2	—	111411	7445	2.4	108924	7117	3.2							
E	20	4	3	—	111412	7160	4.2	108905	7118	5.1	.941	1.509	1.672	1.965	2.000	1.687	4BA


Illustrations of the various contact arrangements are shown on the folded sheet facing page 39. Suitable mating sockets for these plugs are listed on page 11. Panel piercing details are shown on page 14. All dimensions are in inches.

Plessey



BULKHEAD PLUG (Climatic Proof)

Sealed against all climatic conditions, and ideal for use where a "break" is required on both sides of the bulkhead. Shells available in aluminium—where light weight is essential—and also in steel.






Body Size	CONTACTS				ALUMINIUM			STEEL			A	B	D dia.	E sq.	F crs. sq.	Fixing holes
	7 A	19 A	37 A	64 A	Part No.	A/M Ref.	Weight oz.	Part No.	A/M Ref.	Weight oz.						
A	2 —	— —	— —	— —	2CZ 111413	5X/ 7161	1·0	2CZ 84864 108925	5X/ 7021 7022 7119	1·6 1·6 1·6	1·182	1·625	-781	-937	-720	6BA
	4 —	— —	— —	— —	111414	7162	1·0	84865	7022	1·6						
	— 1	— —	— —	— —	111415	—	1·0	108925	7119	1·6						
Z	5 —	— —	— —	— —	111416	7163	1·3	108926	7120	2·0	1·307	1·875	-934	1·125	-875	6BA
	2 —	— —	— —	— —	111417	7164	1·3	108927	7121	2·0						
	2 —	— —	— —	— —	111418	7165	1·4	108928	7122	2·1						
B	9 —	— —	— —	— —	111419	7166	1·6	84866	7025	2·6	1·307	1·875	1·153	1·250	1·000	6BA
	2 4	— —	— —	— —	111420	—	1·9	84867	7123	2·8						
	— 4	— —	— —	— —	111421	—	1·8	108930	7023	2·7						
C	— 5	— —	— —	— —	111422	—	1·9	108931	7124	2·9	1·037	1·875	1·341	1·437	1·187	6BA
	— 7	— —	— —	— —	111423	7167	1·8	108932	7026	2·8						
	— 1	— —	3 —	— —	111424	—	2·4	108933	7024	3·4						
D	— 12	— —	— —	— —	111425	7168	2·1	84867	7027	3·2	1·307	1·875	1·715	1·750	1·469	6BA
	— 12	2 —	— —	— —	111426	7169	2·3	84868	7028	3·4						
	— 6	— —	— —	— —	111427	—	2·3	108934	7028	3·4						
E	— 1	— —	4 —	— —	111428	7170	2·6	108935	7125	3·7	1·307	1·875	1·965	2·000	1·687	4BA
	— 2	2 —	4 —	— —	111429	—	3·5	108936	—	5·1						
	— 4	7	2 —	— —	111430	—	3·3	108937	—	5·0						
D	— 6	2	2 —	— —	111431	7448	3·2	108938	—	4·7	1·307	1·875	1·715	1·750	1·469	6BA
	— 12	4	— —	— —	111432	—	3·1	108939	—	4·7						
	— 24	2	— —	— —	111433	7171	3·2	84869	7029	4·8						
E	— 4	— —	2	— —	111434	7377	3·7	108940	—	5·2	1·307	1·875	1·965	2·000	1·687	4BA
	— 20	4	3 —	— —	111435	—	4·8	108941	7126	6·6						

Illustrations of the various contact arrangements are shown on the folded sheet facing page 39. Suitable mating sockets for these plugs are listed on page 11. Panel piercing details are shown on page 14. All dimensions are in inches.

BULKHEAD PLUG (Pressurised)

Specially designed for use in pressurised aircraft cabins, and double-ended for "breaks" on both sides of bulkheads. Effectively sealed against a pressure difference of 15 lb. per square inch. Suitable where a minimum leakage of 1 c.c. per hour is permissible at a pressure difference of 1 atmosphere. Shell supplied in aluminium only, to reduce weight to a minimum.



Body Size	CONTACTS				ALUMINIUM			A	B	C dia.	D dia.	E	F P.C.D.	Fixing holes	Fixing holes size
	7 A	19 A	37 A	64 A	Part No.	A/M Ref.	Weight oz.								
A	2	—	—	—	2CZ	5X/	2.1	1.201	1.763	1.572	.781	90°	1.018	4	6BA
	4	—	—	—	I38097	—	2.2								
	—	1	—	—	I38099	—	2.0								
Z	5	—	—	—	I38104	—	2.5	1.327	2.036	1.812	.934	90°	1.237	4	6BA
	2	2	—	—	I38098	—	2.5								
	2	2	—	—	I38100	—	2.7								
B	9	—	—	—	I38246	—	3.5	1.327	2.036	2.000	1.153	45°	1.414	8	6BA
	2	4	—	—	I38106	—	3.9								
	—	4	—	—	I38101	—	3.3								
	—	5	—	—	I38105	—	4.0								
C	9	—	—	—	I38247	—	3.3	1.327	2.036	2.312	1.341	45°	1.678	8	6BA
	2	4	—	—	I38102	—	4.8								
	—	4	—	—	I38111	—	4.4								
	—	5	—	—	I38113	—	4.7								
D	9	—	—	—	I38107	—	4.4	1.327	2.036	2.687	1.715	45°	2.076	8	6BA
	2	4	—	—	I38103	—	5.6								
	—	6	—	—	I38109	—	7.5								
	—	6	—	—	I38112	—	6.8								
E	9	—	—	—	I38110	—	6.5	1.327	2.036	3.062	1.965	45°	2.386	8	4BA
	2	4	—	—	I38114	—	5.9								
	—	4	—	—	I38115	—	6.0								
	—	4	—	2	I38108	—	6.2								
E	20	4	3	—	I38116	—	7.9	1.327	2.036	3.062	1.965	45°	2.386	8	4BA

Illustrations of the various contact arrangements are shown on the folded sheet facing page 39. Suitable mating sockets for these plugs are listed on page 11. Panel piercing details are shown on page 14. All dimensions are in inches.


Plessey



SOCKET (Climatic and Vibration Proof)

Sealed against all climatic conditions, and with circlip-type inserts. Available in aluminium or steel, with crimped or soldered connections. The coupling nuts on these sockets have holes provided for wire locking.

In order to facilitate wiring and servicing of Standard sockets, it is planned to introduce a slit comb at a later date.





Body Size	CONTACTS				ALUMINIUM (Climatic and vibration proof)						STEEL (Climatic and vibration proof)						A	B'	C dia.	E dia. Thread				
					Part No.		A/M Reference		Wt. oz.	Part No.		A/M Reference		Wt. oz.										
	7 A	19 A	37 A	64 A	Normal	Reverse	Normal	Reverse		Normal	Reverse	Normal	Reverse											
A	2	—	—	—	2CZ 111230	2CZ 111448	5X/ 7172	5X/ 7194	.8	2CZ 84872	2CZ 84879	5X/ 7038	5X/ 7051	1.7	-610	1.750	.885	.692 24 T.P.I.						
	4	—	—	—	111231	111449	7173	7195	.8	84873	84880	7039	7052	1.8										
Z	—	1	—	—	111232	111450	7174	7174	.8	108943		7127	7127	1.7	-735	1.750	1.050	.875 20 T.P.I.						
	5	—	—	—	111233	111451	7175	7197	1.2	84874	108959	7128	7134	2.5										
B	2	—	—	—	111436	111452	7176	7198	1.2	108944	108960	7044	7044	2.5	-735	1.812	1.250	1.062 20 T.P.I.						
	2	2	—	—	111437	111453	7177	7199	1.2	108945	108961	7042	7135	2.5										
C	9	—	—	—	111234	111454	7178	7200	1.6	84875	84881	7045	7055	3.0	-735	1.812	1.435	1.250 20 T.P.I.						
	2	4	—	—	111438	111455	7179	—	1.7	108946	108962	7129	7136	3.1										
D	—	4	—	—	111298	111456	7180	7326	1.7	108947	108963	7040	7053	3.4	-735	2.375	1.810	1.625 20 T.P.I.						
	—	5	—	—	111439	111457	7181	—	1.7	108948	108964	7043	7137	3.4										
E	—	2	—	—	111440	111458	7182	7201	1.7	108949	108965	7046	7056	3.1										
	—	2	—	—	111235	111459	7183	—	2.4	108950	108966	7041	7054	4.4										
C	1	—	3	—	111235	111460	7184	7202	2.4	84876	84882	7047	7057	4.3	-735	1.812	1.435	1.250 20 T.P.I.						
	12	2	—	—	111236	111461	7185	7203	2.4	84877	84883	7048	7058	4.4										
D	12	2	—	—	111296	111462	7186	—	2.4	108951	108967	7130	—	4.4	-735	2.375	1.810	1.625 20 T.P.I.						
	—	6	—	—	111237	111463	7187	7204	2.4	108952	108968	7131	7138	4.4										
E	2	2	4	—	111442	111464	7188	—	4.0	108953	108969	7132	—	7.0	-735	2.375	1.995	1.875 20 T.P.I.						
	4	7	2	—	111443	111465	7189	—	4.1	108954	108970	7132	—	7.1										
D	6	2	2	—	111444	111466	7190	7346	3.9	108955	108971	—	—	6.9	-735	1.810	1.625 20 T.P.I.							
	12	4	—	—	111445	111467	7191	7327	4.0	108956	108972	7446	—	7.0										
E	24	2	—	—	111238	111468	7192	7205	4.1	84878	84884	7049	7059	7.2	-735	2.375	1.995	1.875 20 T.P.I.						
	4	—	2	—	111446	111469	—	7378	3.6	108957	108973	7335	—	6.6										

Illustrations of the various contact arrangements are shown on the folded sheet facing page 39. Suitable mating plugs for these sockets are listed on page 8, and mating bulkhead plugs on pages 9 and 10. All dimensions are in inches.

THERMO-COUPLE PLUG & SOCKET

For use in circuits employing temperature compensating leads. A limited number of contact combinations within the standard range are now obtainable, with pin and socket inserts of constantan and brass, or chromel and alumel. Due consideration will be given to special requirements of contact combinations other than those listed below. In such cases the Company's advisory service at Cheney Manor, Swindon, should be consulted.



Identification of thermo-couple contacts is by a series of grooves together with a band of colour on the conductor well of the plug pin or socket insert. Identification of the mouldings is by a similar colour code against the appropriate contact position.

Details of the identification codes are as follows:—

Chromel—Red (1 groove)	Alumel—Blue (2 grooves)
Constantan—Yellow (3 grooves)	

Shell size & Contact Arrangement Code * * *	Thermo-couple Contacts						Plug Single Climatic Proof	Plug Bulkhead	Plug Bulkhead Pressurised	Socket Normal	Socket Reverse
	Contact Designation (see Pull- out Sheet)	Current Rating (Amps.)	Material	Contact Designation (see Pull- out Sheet)	Current Rating (Amps.)	Material					
A 2/0/0 I	A	7	Constantan	B	7	Brass	Alum.	2CZ 139864	—	2CZ 139865	2CZ 139866
A 2/0/0 I	A	7	Constantan	B	7	Brass	Steel	2CZ 139868	2CZ 139869	—	2CZ 139870
A 2/0/0 I	A	7	Chromel	B	7	Alumel	Steel	—	2CZ 139872	—	2CZ 139873
Z 0/2/0 5	I	19	Constantan	2	19	Brass	Steel	2CZ 139875	—	—	2CZ 139876
Z 0/2/0 5	I	19	Chromel	2	19	Alumel	Alum.	2CZ 139877	—	2CZ 139878	2CZ 139879
Z 0/2/0 5	I	19	Chromel	2	19	Alumel	Steel	2CZ 139881	2CZ 139882	—	2CZ 139883
Z 5/0/0 4	A, C, E	7	Chromel	B, D	7	Alumel	Steel	2CZ 139884	2CZ 139885	—	2CZ 139886
B 7/2/0 II	I	19	Chromel	2	19	Alumel	Steel	2CZ 139888	—	—	2CZ 139889
	A,B,C,D,E,F,G	7	Brass								—
B 0/4/0 9	I, 3	19	Constantan	2, 4	19	Brass	Steel	2CZ 139890	2CZ 139891	—	2CZ 139892
B 0/4/0 9	I, 3	19	Chromel	2, 4	19	Alumel	Steel	2CZ 139894	2CZ 139895	—	2CZ 139896
B 0/4/0 9	I, 3	19	Constantan	2, 4	19	Brass	Alum.	—	2CZ 139898	2CZ 139899	2CZ 139900
C 0/0/4 16	I, 3	37	Chromel	2, 4	37	Alumel	Steel	2CZ 139902	2CZ 139903	—	2CZ 139904
C 12/0/0 13	A,C,E,G,J,L	7	Constantan	B,D,F,H,K,M	7	Brass	Alum.	2CZ 139906	2CZ 139907	2CZ 139908	2CZ 139909
E 20/4/3 23	M,O,Q,S,U,D I, 2, 3, 4	7 19	Constantan	A,B,C,E,F,G,H, J,K,L,N,P,R,T 5, 6, 7	7 37	Brass Brass Brass	Steel	2CZ 139911	—	—	2CZ 139912

* These codes represent the various contact arrangements that are illustrated on the folded sheet facing page 39.


NOTE: It is recommended that all thermo-couple, plug pin and socket inserts are soldered notwithstanding the fact that in certain instances they are supplied to a design which permits crimping.

SPECIAL PURPOSE PLUGS & SOCKETS


These items are supplied to special order only.

RIGHT-ANGLE SHORT-REACH SOCKET ASSEMBLY

Specially designed for easy withdrawal in cramped conditions. It overcomes the difficulties of using straight-outlet sockets where space is limited. The socket shell is aluminium or steel and the elbow assembly is fabricated in brass and finished in dull nickel plate. Special soldered-type socket inserts are incorporated.



Body Size	Shell	Contact Combination	Part No.	A/M Ref.	A	B	C Dia.	D	E	Weight oz.	Suitable Mating Plug
A	Alum.	Two 7A	2CZ 138244	—	1.715	.609	.692	1.120	1.332	2CZ 111223	
A	Alum.	Four 7A	2CZ 138245	—	1.715	.609	.692	1.120	1.332	2CZ 111399	
A	Steel	Two 7A	2CZ 138243	—	1.715	.609	.692	1.120	1.332	2CZ 108906	
A	Steel	Four 7A	2CZ 111242	—	1.715	.609	.692	1.120	1.332	2CZ 84870	



PLUG (DETACHABLE LEADS)

For use on electric motors and other equipment where only short leads are required behind the plug. The pins are removable from the mouldings for easy wiring before fitting the plug, and they can be withdrawn from the moulding with the leads still attached. Supplied in one size only, with shell in aluminium or steel and with soldered connections.


Body Size	Shell	Contact Combination	Part No.	A/M Ref.	A	B	C	Weight oz.	Suitable Mating Socket
A	Alum.	Two 7A	2CZ 140052	—	1.019	.784	.937	—	2CZ 111230
A	Steel	Two 7A	2CZ 140053	—	1.019	.784	.937	—	2CZ 84872

HEAVY DUTY PRESSURISED BULKHEAD CONNECTOR BLOCK


This connector block is fully pressurised at 15 lb. for use at pressure cabin bulkheads wherever heavy duty leads must be broken. For use with crimped or soldered lugs, and available with end covers, if required.

Connections	Part No.	A/M Ref.	A	B Dia.	C	Weight oz.	Cover	
							Part No.	A/M Ref.
Three 200A	CZ 51091	5H/112	3.62	3.62	1.937	19.6	Z 51094	5H/111
Two 200A One 19A	CZ 51097	5H/110	3.62	3.62	1.937	18.2	Z 51094	5H/111

Add .125" to each end of dimension "A" if covers are used. Panel piercing details are given on page 14. All dimensions are in inches.




PANEL PIERCING DETAILS



CLIMATIC PROOF SINGLE AND BULKHEAD PLUGS

Body Size	G dia.	H sq. crs.	J dia.	Recommended minimum distance between centres of similar size plugs
A	.797	.720	.120	1.125
Z	.953	.875	.120	1.250
B	1.171	1.000	.120	1.500
C	1.359	1.187	.120	1.625
D	1.734	1.469	.120	2.000
E	1.984	1.687	.152	2.250



PRESSURISED BULKHEAD PLUGS

Body Size	Fixing holes	G dia.	H P.C.D.	J dia.	Recommended minimum distance between centres of similar size plugs
A	4	.797	1.018	.120	1.625
Z	4	.953	1.237	.120	1.875
B	8	1.171	1.414	.120	2.062
C	8	1.359	1.678	.120	2.375
D	8	1.734	2.076	.120	2.750
E	8	1.984	2.386	.152	3.125

HEAVY DUTY BULKHEAD CONNECTOR BLOCK

G dia.	H P.C.D.	J dia.	Recommended minimum distance between centres
2.380	3.062	.152	3.687

All dimensions are in inches.

SPARE PARTS FOR STANDARD PLUGS & SOCKETS

FOR AIR MINISTRY REFERENCE NUMBERS REFER TO PAGES 29 TO 39


Description	For Assemblies listed on page	Material	Part Numbers					
			A	Z	B	C	D	E
Plug Shell	8, 9 & 12	Aluminium	Z 49249	Z 49251 *Z 49252	Z 24923 *Z 24932	Z 24924 *Z 24933	Z 24925	Z 49278
		Steel	2Z 109905	2Z 111186 *2Z 109933	2Z 111189 *2Z 109906	2Z 109908 *2Z 109907	2Z 109909	2Z 111184
Plug Shell Gasket	8, 9 & 12	Silicone Rubber	2Z 84911/A	2Z 84911/Z	2Z 84911/B	2Z 84911/C	2Z 84911/D	2Z 84911/E
Plug Moulding Gasket	8, 9 & 12	Silicone Rubber	2Z 84912/A	2Z 84912/Z	2Z 84912/B	2Z 84912/C	2Z 84912/D	2Z 84912/E
Plug Seating Gasket	8, 9 & 12	Silicone Rubber	2Z 85140/A	2Z 85140/Z	2Z 85140/B	2Z 85140/C	2Z 85140/D	2Z 85140/E
Reverse Plug Seating Gasket	8, 9 & 12	Silicone Rubber	2Z 110061/A	2Z 110061/Z	2Z 110061/B	2Z 110061/C	2Z 110061/D	2Z 110061/E
Socket Shell	11 & 12	Aluminium	Z 49250	Z 49253	Z 49803	Z 49804	Z 24915	Z 49806
		Steel	2Z 109910	2Z 109911	2Z 109912	2Z 109913	2Z 109914	2Z 111188
Circlip	11 & 12	Steel	2Z 110344	2Z 110343	2Z 110345	2Z 110346	2Z 110347	2Z 111197
Insulating Ring	11 & 12	Glass Fibre (P.T.F.E. Coated)	2Z 84917	2Z 84918	2Z 84919	2Z 84920	2Z 84921	2Z 111190
Insulating Sleeve	11 & 12	Glass Fibre (P.T.F.E. Coated)	2Z 84922	2Z 84923	2Z 84924	2Z 84925	2Z 84926	2Z 111191
Socket Ferrule Gasket	11 & 12	Silicone Rubber	2Z 84914/A	2Z 84914/Z	2Z 84914/B	2Z 84914/C	2Z 84914/D	2Z 84914/E
†Socket Sealing Gasket	11 & 12	Synthetic Rubber	Z 23201/A	Z 23201/Z	Z 23201/B	Z/23201/C	Z 23201/D	Z 23201/E
Thrust Washer	11 & 12	Steel	2Z 109947/A	2Z 109947/Z	2Z 109947/B	2Z 109947/C	2Z 109947/D	2Z 109947/E
Packing Cap (Plugs)	8, 9, 10 & 12	Waxed Cardboard	Z 17830	Z 17835	Z 17831	Z 17832	Z 17833	Z 17834
Packing Cap (Sockets)	11 & 12	Waxed Cardboard	Z 17836	Z 17841	Z 17837	Z 17838	Z 17839	Z 17840

* Required on plugs containing all 7 amp. pins (codes 4, 7 and 13)

Contact	For Assemblies on page	Material	7 amp.	7 amp. (Special)	19 amp.	37 amp.	64 amp.
Plug Pin	8	Brass	Z 27323	Z 28146	Z 28147	2Z 138788	Z 53006
Bulkhead Plug Pin		Brass	Z 19269	Z 19273	Z 19270	Z 19271	Z 19272
Socket Insert	11	Brass	2CZ 109944	2CZ 109946	2CZ 109945	2CZ 138789	2CZ 111902


†The Socket Sealing Gasket will be supplied with all sockets for use should the socket be required to mate with earlier versions of the Standard plugs. When mating assemblies are both of the uprated version, the gasket should be discarded.

EVOLUTION OF THE SINGLE PLUG



STAGE 1 (Fixed Pin)

The original design of the "Breeze" single plug consisted of a base of phenolic material with the plug pins moulded in position. The plug shell was machined from bar and fixing bolt holes plain drilled. Suitable for soldered connection only.




STAGE 2 (Loose Pin)

Two identical mouldings introduced each with a stepped creepage barrier round the base of each pin to increase distance without altering contact centres. The plug pins were sandwiched between the two mouldings and retained in position by the fixing bolts fitting the tapped holes in the plug shell. Suitable for soldered connection only.

STAGE 3 (Climatic Proof)

The introduction of two rubber moulding gaskets and the plug shell gasket, designed to make the plug proof against all climatic conditions other than those of full exposure. Introduction also of the redesigned plug pin to permit a soldered or crimped connection and an extended rear moulding to shroud the connection made.



STAGE 4 (Uprated Type)


Current production version. The introduction of the uprated range to operate between ambient temperatures of -65°C . and $+150^{\circ}\text{C}$.

Design of the plug shell and plug pins remains unchanged, but front and rear mouldings now manufactured from alkyd.

Plug shell gasket and moulding gasket manufactured from silicone rubber.

A modified seating gasket in silicone rubber introduced to accept the mating rim of the socket shell.


A brass backing plate behind rear moulding to be introduced.



EVOLUTION OF THE BULKHEAD PLUG

STAGE 1 (Fixed Pin)



The original design of the "Breeze" bulkhead plug, consisting of one moulding in a phenolic material with the special plug pins moulded into position.



STAGE 2 (Loose Pin)


Two identical mouldings introduced, each with a stepped creepage barrier round the base of the plug pins to increase creepage distance without altering pin centres.

The bulkhead plug pins being sandwiched in position between the two mouldings.



STAGE 3 (Climatic Proof)


The introduction of rubber moulding gaskets and plug shell gasket, designed to make the connector proof against all climatic conditions other than those of full exposure.



STAGE 4 (Upated Type)

Current production version.
The introduction of the uprated range designed to operate between ambient temperatures of -65°C . and $+150^{\circ}\text{C}$. Design of the plug shells and plug pins remains unchanged but the mouldings now manufactured from alkyd. Plug shell gasket now manufactured from silicone rubber. Two types of modified seating gaskets in silicone rubber introduced to accept the mating rims of the connected socket shells.

EVOLUTION OF THE PRESSURISED BULKHEAD PLUG




STAGE 1 (Pressurised Type)

Specially designed for use in pressurised aircraft cabins and effectively sealed against a pressure difference of 15 lb. per square inch. A specially designed and strengthened shell containing two identical mouldings of a phenolic material with plug pins bonded into position. Four fixing bolts are provided for Sizes A and Z whilst eight are provided for the remaining sizes.

STAGE 2 (Upgraded Type)






Current production version. Similar to Stage 1, but with the two mouldings manufactured from alkyd. Design of the shells and plug pins virtually unchanged but the mounting gasket manufactured from silicone rubber. Two types of modified seating gaskets in silicone rubber introduced to accept the leading edges of the mating sockets.




CONTACT DESIGN

On several occasions during its life to date, different types of socket inserts have been introduced consistent with the general evolution of the design of the Standard connector. As certain of these contacts may still be encountered on old equipment, a brief description and illustration of each type is set out below and should prove of assistance in identification.

In order to retain the feature of interchangeability of sockets, the dimensions of the mating portions of the contacts have been maintained or improved to permit correct connection with any plug pin of equivalent rating.


Typical Illustrations of Socket Inserts	STAGE 1	STAGE 2	STAGE 3	STAGE 4	STAGE 5					
										
Pin Rating (Amps)	Part No.	A/M Reference	Part No.	A/M Reference	Part No.	A/M Reference	Part No.	A/M Reference	Part No.	A/M Reference
7	Z 1340	—	Z 27330	5X/3237	Z 56404	5X/6924	2CZ 110175	5X/7329	2CZ 109944	5X/7516
7 Special	Z 1590	—	Z 28143	5X/3239	Z 56480	5X/6949	2CZ 110176	5X/7330	2CZ 109946	5X/7517
19	Z 1341	—	Z 28144	5X/3241	Z 56405	5X/6950	2CZ 109945	5X/7331	2CZ 109945	5X/7331
37	Z 1342	—			Z 60366	5X/6951	2CZ 110292	5X/7332	2CZ 138789	5X/7514
64	Z 1462	—			CZ 56408	5X/6400	2CZ 111902	5X/7520	2CZ 111902	5X/7520
<p>The illustrations above show the main types of Inserts only. Certain modified forms of these Inserts existed, e.g., rolled inserts having parallel barrels were made up in 37 and 64 amp. ratings, but were replaced by the solid and crimp type inserts.</p>										
<p>STAGE 1 was the original design for use with the pressed comb and suitable only for a soldered connection. STAGE 2 was introduced during World War II due to the shortage of machining capacity and was redesigned to be a simple press operation. Although ideally suitable for a soldered connection, a crimped joint could be made by using a suitable thimble. STAGE 3 was the re-introduction of the original type of contact with the solid ring entry but with modification to length to permit a crimped or soldered joint without the use of thimbles. STAGES 4 and 5 are the two designs which are in current production today and are a much improved design incorporating a circlip of beryllium copper which ensures a perfect contact at all times. The illustration of Stage 5 is applicable to the 7 amp. and 7 amp. special contacts only. All are suitable for a soldered or crimped joint without the use of thimbles.</p>										

EVOLUTION OF THE STANDARD SOCKET



STAGE 1

The original design of the "Breeze" socket containing a long socket moulding in a phenolic material with a pressed comb and short, turned type socket inserts. Suitable only for a soldered connection. The circlip retaining the moulding in the shell was positioned at the front end of the assembly.




STAGE 2


A redesigned shell and coupling nut containing a shortened socket moulding and a comb moulding with rolled type socket inserts. Suitable for a soldered or crimped connection with suitable thimble. The circlip retaining the mouldings repositioned at the rear of the assembly. The socket shell lengthened for sizes D, E and F, two insulating sleeves being used.

STAGE 3

Socket shell and coupling nut modified to give a straight knurl for tightening. Introduction of the socket sealing gasket and ferrule gasket. Socket moulding and comb moulding unchanged for combinations using 7 and 19 amp. inserts only, together with rolled type socket inserts, suitable for a soldered or crimped connection with a suitable thimble. For combinations containing 37 and 64 amp. inserts, the moulding and comb were as stage 4.



EVOLUTION OF THE STANDARD SOCKET




STAGE 4

The introduction of the vibration-proof socket insert suitable for a soldered or crimped connection without the use of a thimble.
Reintroduction of the pressed comb in place of the comb moulding.
Wire locking holes provided in the coupling nut.

STAGE 5


The introduction of the improved circlip type socket insert—designed to eliminate defects discovered in contact mating.
All other items identical to Stage 4 design.

Air Ministry reference number unchanged but allocated the suffix " /B ".



STAGE 6


Current production version.
The introduction of the uprated range to operate between ambient temperatures of -65°C . and $+150^{\circ}\text{C}$.
Socket moulding and comb moulding manufactured from alkyd. Insulating sleeve and washer manufactured from glass fibre and P.T.F.E. coated.
A steel thrust washer introduced.
Ferrule gasket manufactured from silicone rubber. The socket sealing gasket no longer supplied as a fitment, but enclosed with the socket for use when mating with any obsolete type of plug.



PLUG & SOCKET ACCESSORIES

PLUG SEALING CAPS (Bakelite)


Designed to prevent the ingress of dust or moisture when the plug is not in use.



Size	Part No.	A/M Ref.	A	Weight oz.
A	Z 22164	5X/1963	.250	.11
Z	Z 22165	5X/1964	.250	.16
B	Z 22166	5X/1965	.250	.22
C	Z 22167	5X/1966	.250	.25
D	Z 22168	5X/1967	.250	.39
E	Z 23276	5X/2185	.250	.48

PLUG SCREENING CAPS (Aluminium)


Designed to prevent the ingress of dust or moisture when the plug is not in use.



Size	Part No.	A/M Ref.	A	Weight oz.
A	Z 13031	5X/1097	.250	.20
Z	Z 13106	5X/1088	.250	.29
B	Z 13032	5X/1089	.250	.37
C	Z 13033	5X/1575	.250	.46

COUPLING NUTS (Aluminium or Steel)

Designed for use with sockets, plug shrouds, elbow or tee assemblies and used for clamping all forms of cable fittings into position.




Size	ALUMINIUM			STEEL (Nickel Plated)			A	B
	Part No.	A/M Ref.	Weight oz.	Part No.	A/M Ref.	Weight oz.		
A	Z 61535	5X/ 6312	.11	2Z	109915	—	.34	.692x24 T.P.I. .585
Z	Z 61536	5X/ 6500	.18	2Z	109916	—	.53	.875x20 T.P.I. .723
B	Z 61537	5X/ 6405	.21	2Z	109917	—	.65	1.062x20 T.P.I. .877
C	Z 61538	5X/ 6424	.26	2Z	109918	—	.78	1.250x20 T.P.I. 1.022
D	Z 61539	5X/ 6425	.33	2Z	109919	—	.99	1.625x20 T.P.I. 1.440
E	Z 61540	5X/ 6820	.42	2X	111196	—	1.27	1.875x20 T.P.I. 1.567

All dimensions are in inches.

PLUG & SOCKET ACCESSORIES

PLUG SHROUDS (Aluminium or steel)


Designed for mounting at the rear of single plugs for the purpose of attaching cable fittings.



Size	ALUMINIUM			STEEL (Nickel Plated)			A
	Part No.	A/M Ref.	Wt. oz.	Part No.	A/M Ref.	Wt. oz.	
A 1499	5X/282	-2	139928	5X/-	-3	.750	
Z 1500	283	-3	139929	—	-8	.750	
B 1275	284	-3	139930	—	-9	.750	
C 1688	285	-4	139931	—	1.3	.750	
D 1690	286	-6	139932	—	1.7	.750	
E 13299	287	-8	139933	—	2.3	1.375	

FERRULE PLATE ASSEMBLY (Brass)

Designed for use with plastic tubing where cables enter a panel or junction box. The 4 fixing holes and spigot on the leading face being designed to fit panel piercings of a single plug of similar size.




Size	Part No.	A/M Ref.	Ferrule size	Tubing size	A	B	Wt. oz.	Clamp Ring	A/M Ref.
A CZ 24626 CZ 24628	6850 6631	5X/ A Z	3/8 1/2	.722 .909	1.000 1.000	.45	.27	Z 18501/A CZ 23144/Z	5X/ 1529 6440
Z CZ 24632 CZ 24634	6603 6797	Z B	1/2 5/8	.722 .909	1.187 1.187	.54	.35	CZ 23144/Z CZ 23144/B	6440 6488
B CZ 24636 CZ 24638 CZ 24640	— 6604 6605	Z B C	1/2 5/8 3/4	.909 .722 .909	1.312 1.312 1.312	.39 .42 .73	.35	CZ 23144/Z CZ 23144/B CZ 23144/C	6440 6488 6489
C CZ 24642 CZ 24644 CZ 24646	— 6177 6178	B C D	5/8 3/4 1	.909 .722 1.026	1.500 1.500 1.500	.83 .83 1.00	.46	CZ 23144/B CZ 23144/C CZ 23144/D	6488 6489 3143
D CZ 24648 CZ 24650 CZ 24652	6628 6180 —	C D E	3/4 1 1-1/4	.909 .839 1.026	1.812 1.812 1.812	.60 .35 .12	.60	CZ 23144/C CZ 23144/D CZ 23144/E	6489 3143 6490
E CZ 24654 CZ 24656 CZ 24658	— 6606 —	D E dia. 1-525	1 1-1/4 1-1/2	1.026 .839 1.151	2.06 2.06 2.06	2.0 1.6 1.75	.35	CZ 23144/D CZ 23144/E CZ 23144/F	3143 6490 —

Panel piercing details are shown on page 14. Dimension "A" Tolerance $\pm .064$.
All these assemblies are electro-tin finish except CZ 24634 and CZ 24640 which are dull nickel plate.

CLAMP RINGS

Designed for clamping plastic tubing to ferrules or ferrule plate assemblies.



Size	PLAIN TYPE (BRASS) (Cadmium Plated)			SCREW TYPE (STEEL) (Cadmium Plated)		
	Part No.	A/M Ref.	Wt. oz.	Part No.	A/M Ref.	Wt. oz.
A Z 18501/A	5X/1529	.04	—	—	—	—
Z Z 18501/Z	5X/1530	.07	CZ 23144/Z	5X/6440	.24	
B Z 18501/B	5X/1531	.07	CZ 23144/B	5X/6488	.25	
C Z 18501/C	5X/1532	.09	CZ 23144/C	5X/6489	.26	
D Z 18501/D	5X/1533	.14	CZ 23144/D	5X/3143	.30	
E Z 18501/E	5X/1534	.18	CZ 23144/E	5X/6490	.35	
Dia. 1-525 Z 18501/F	5X/1535	.23	CZ 23144/F	—	.38	

Clamp rings are used in conjunction with ferrules for plastic tubing, see page 24. Dimensions are given in inches.

PLUG & SOCKET ACCESSORIES

INNER AND OUTER FERRULES (Brass—nickel plated)

Designed to form a sound joint when using plastic tubing, loose braid or conduit.
May be used on a socket or with a plug shroud and coupling nut.

Size	INNER				OUTER					
	Part No.	A/M Ref.	A	B	Wt. oz.	Part No.	A/M Ref.	A	B	Wt. oz.
A	2Z 139934/A	5X/ —	.250	.628	.04	Z 139935/A	5X/ —	.256	.628	.04
Z	139934/Z	—	.325	.800	.07	139935/Z	—	.325	.800	.07
B	139934/B	—	.360	.990	.10	139935/B	—	.360	.990	.11
C	139934/C	—	.395	1.175	.14	139935/C	—	.395	1.175	.15
D	139934/D	—	.450	1.547	.23	139935/D	—	.450	1.547	.25
E	139934/E	—	.562	1.795	.37	139935/E	—	.562	1.795	.39

FERRULES FOR PLASTIC TUBING (Brass—electro-tinned)

Designed for use with plastic tubing and clamp ring.
May be used on a socket or with a plug shroud and coupling nut.

Size	STANDARD						OVERSIZE					
	Part No.	A/M Ref.	Tubing Size I/D	A	B	Wt. oz.	Part No.	A/M Ref.	Tubing Size I/D	A	B	Wt. oz.
A	18500/A	5X/1522	.375	.750	.628	.14	18764/A	5X/1546	.500	.937	.628	.20
Z	18500/Z	1523	.500	.750	.800	.19	18764/Z	1547	.625	.937	.800	.21
B	18500/B	1524	.625	.750	.990	.22	18764/B	1548	.750	.937	.990	.34
C	18500/C	1525	.750	.750	1.175	.30	18764/C	1549	1.000	1.062	1.175	.53
D	18500/D	1526	1.000	.875	1.547	.58	18764/D	1550	1.250	1.062	1.547	.77
E	18500/E	1527	1.250	.875	1.795	.81	18764/E	2187	1.500	1.062	1.795	.96

Clamp rings for these ferrules are shown on page 23.

CONDUIT FERRULES TYPE "H" (Aluminium or brass)

Designed for use with metal conduit and to be swaged or soldered into position.
May be used on a socket or with a plug shroud and coupling nut.


Size	Conduit Size	ALUMINUM				BRASS (Nickel Plated)				A	B	C	D
		Part A/M No.	Wt. oz.	Part No.	A/M Ref.	Wt. oz.							
A	1/4	Z 1350	5X/0.4	139936/1	—	.09	.250	.447	.437	.628			
	3/8	1694	1344	139937	—	.11	.375	.572	.437	.628			
Z	3/8	1442	1571	139936/12	—	.13	.375	.572	.437	.800			
	1/2	1441	1343	139936/11	—	.14	.500	.697	.437	.800			
B	3/8	1369	1074	139936/2	—	.21	.375	.572	.437	.990			
	5/8	1359	1327	139936/4	—	.21	.625	.828	.500	.990			
C	1/2	1361	1328	139936/9	—	.19	.500	.697	.437	.990			
	5/8	1353	1325	139936/10	—	.26	.625	.828	.500	1.175			
D	3/4	1352	909	139936/5	—	.24	.750	.982	.500	1.175			
	1	1362	1329	139936/14	—	.30	.750	.982	.500	1.574			
E	I	1365	1330	139936/15	—	.50	1.000	1.267	.625	1.800			

Coupling nuts for use with these items are listed on page 22. All dimensions are in inches.

PLUG & SOCKET ACCESSORIES

CONDUIT FERRULES TYPE "G" (Aluminium or brass)


Designed for use with metal conduit and to be swaged or soldered into position.



Conduit Size	ALUMINIUM			BRASS (Nickel Plated)			A	B	C
	Part No.	A/M Ref.	Wt. oz.	Part No.	A/M Ref.	Wt. oz.			
3/8	Z 1431	5X/ 2073	.03	2Z 139938	5X/ —	—	.375	.572	.437
1/2	1432	2074	.04	139939	—	.12	.500	.697	.437
5/8	1433	1342	.05	139940	—	.14	.625	.828	.437
3/4	1434	2075	.07	139941	—	—	.750	.982	.500
1	1435	2076	.11	139942	—	.30	1.000	1.267	.625
1-1/4	1450	2077	.11	—	—	—	1.250	1.522	.625

ELBOW ASSEMBLY (Brass—nickel plated)


Designed to allow a right-angle entry into the rear of a socket or plug with a plug shroud.



Size	Part No.	A/M Ref. 5X/	A	B	Weight oz.
A	2CZ 139944	—	.70	.81	1.20
Z	2CZ 139945	—	.72	.93	1.42
B	2CZ 139946	—	.84	1.02	1.80
C	2CZ 139947	—	.94	1.02	2.56
D	2CZ 139948	—	1.12	1.31	4.18
E	2CZ 139949	—	1.18	1.50	5.24

TEE CONNECTORS (Brass—nickel plated)

Designed for use with metal conduit where take-off leads are required at right angles to the existing run.



Size	Part No.	A	B	Weight oz.
A	2CZ 139950	2.02	.81	1.09
Z	2CZ 139951	2.24	.93	2.12
B	2CZ 139952	2.50	1.02	3.34
C	2CZ 139953	2.74	1.02	3.55
D	2CZ 139954	3.00	1.31	6.86
E	2CZ 139955	3.25	1.50	6.96

All dimensions are in inches.

Stone X
2605

523140 - 4 -

5935-99-203-
2


Plessey

Adams

PLUG & SOCKET ACCESSORIES

CUT FERRULES ROUND BASE (Brass—nickel plated)

Designed for use with single or multi-way cables where a clamp is required immediately behind the socket or plug shroud, thus preventing any cable strain being transmitted to the contacts.




Size	Part No.	A/M Ref.	Wt. oz.	A	B	C	D	E
A	2Z 139956	—	.22	.275	.375	.625	.036	.625
	139957	—	.21	.355	.500	.687	.036	.625
	139958	—	.23	.405	.468	.625	.036	.625
	139959	—	.23	.442	.500	.687	.020	.625
Z	139960 139961	—	.33	.355	.437	.750	.036	.800
B	139962	—	.42	.355	.500	1.000	.048	.990
	139963	—	.35	.405	.593	1.187	.036	.990
	139964	—	.40	.505	.650	1.187	.036	.990
	139965	—	.40	.605	.725	.687	.020	.990
	139966	—	.43	.723	.812	.687	.020	.990
	139967	—	.43	.755	.812	.687	.020	.990
C	139968	—	.54	.405	.593	1.187	.048	1.175
	139969	—	.50	.605	.781	1.187	.036	1.175
	139970	—	.56	.705	.906	1.187	.036	1.175
	139971	—	.46	.905	1.000	.875	.036	1.175
D	139972	—	.68	.805	1.000	1.125	.036	1.550
	139973	—	.78	1.005	1.281	1.125	.036	1.550
E	139974	—	.95	1.205	1.500	1.125	.036	1.800
	139975	—	.94	1.255	1.537	.875	.036	1.800

Coupling nuts for use with these items are listed on page 22.

CUT FERRULES SQUARE BASE (Brass—nickel plated)

Designed for use where single or multi-way cables are required to be clamped immediately behind a single plug or where cables are to be clamped on entering a junction box.



Size	Part No.	A/M Ref.	Wt. oz.	A	B	C	D	E
A	2Z 139976	—	.47	.320	.406	.875	.036	.937
	139977	—	.48	.405	.468	.875	.036	.937
	139978	—	.56	.405	.500	.750	.036	.937
Z	139979	—	.56	.500	.562	1.187	.036	1.125
B	139980	—	.56	.500	.593	1.187	.036	1.250
	139981	—	.56	.505	.625	1.187	.036	1.250
	139982	—	.56	.600	.687	1.187	.036	1.250
	139983	—	.58	.687	.750	1.187	.036	1.250
	139984	—	.64	.705	.906	1.187	.036	1.250
	139985	—	.68	.905	1.000	.875	.036	1.250
C	139986	—	.75	.750	.812	1.187	.036	1.437
D	139987 139988	—	.82	.805	.875	1.375	.036	1.750
		—	.84	1.000	1.062	1.500	.036	1.750

Panel piercing details are shown on page 14. All dimensions are in inches.

INDEX OF AIR MINISTRY REFERENCE NUMBERS OF STANDARD PLUGS & SOCKETS

5X/ No.	Plessey Part No. CZ	Page No.												
1	1064	30	92	12367	31	174	*1031A-/2/3	30	4035	1782/2	30	6050	*27989	33
2	1760	30	93	1077	30	175	*1111A-/2/3	30	4037	2672/2	31	6056	28101	33
3	1050	30	94	12379	32	176	*2094-/2/3	31	4038	2755/2	31	6057	28191	33
4	2754	31	95	12353	31	177	*2121A-/2/3	31	4039	2110/2	31	6058	28042	33
5	2686	31	101	*1114-2/3	30	178	*1127A-/2/3	30	4040	1055/2	30	6059	*27911	33
6	2685	31	102	*1761-/2	30	179	*1089A-/2/3	30	4041	2757/2	31	6060	*27991	33
7	2750	31	102	*1761/3	30	180	*2122A-/2/3	31	4042	2753/2	31	6061	28102	33
8	12347	31	103	*1100-/2/3	30	181	*1102A-/2/3	30	4043	2739/2	31	6062	28192	33
9	1765	30	104	*2704-/2/3	31	182	*1095A-/2	30	4044	2743/2	31	6063	28043	33
10	1060	30	105	*2698-/2/3	31	182	*1095A/3	30	4045	1054/2	30	6064	*27912	33
11	1776	30	106	*1144-/2	30	183	*10349A-/2/3	31	4046	2758/2	31	6065	*27992	33
12	1770	30	106	*1144/3	30	184	*2707A-/2/3	31	4047	12365/2	31	6066	28103	33
13	2655	31	107	*2702-/2/3	31	185	*2121A-/2/3	31	4048	1092/2	30	6067	28193	33
14	2097	31	108	*10340-/2/3	31	186	*2123A-/2/3	31	4049	2091/2	31	6068	28044	33
15	2678	31	109	*1766-/2/3	30	187	*1093A-/2/3	30	4050	1067/2	30	6069	*27913	33
16	1065	30	110	*1110-/2/3	30	188	*1135A-/2/3	30	4051	1053/2	30	6070	*27993	33
17	2687	31	111	*1777-/2/3	30	189	*1117A-/2/3	30	4052	12377/2	32	6071	28104	33
18	2664	31	112	*1771-/2	30	190	*2128A-/2	31	4055	1058/2	30	6072	28194	33
19	12348	31	112	*1771/3	30	198	17883	32	4056	1057/2	30	6073	28045	33
20	1033	30	113	*2135-/2	31	199	17884	32	4066	2670/2	31	6074	*27914	33
21	1051	30	113	*2135/3	31	1285	12391	32	4067	2660/2	31	6075	*27994	33
22	1066	30	114	*2118-/2/3	31	1286	*10348	31	4068	2109/2	31	6076	28105	33
23	1070	30	115	*2697-/2/3	31	1554	16568	32	4069	2688/2	31	6077	28195	33
24	2682	31	116	*1115-/2	30	1555	*15155-/3	32	4070	2746/2	31	6078	28046	33
25	1061	30	116	*1115/3	30	1567	18960	32	4071	11408/2	31	6079	*27915	33
26	12384	32	117	*2699-/2/3	31	1568	18961	32	4072	2668/2	31	6080	*27995	33
27	2744	31	118	*2695-/2/3	31	1582	*2129/A	31	4073	2105/2	31	6086	28107	33
28	1071	30	119	*2138	31	1583	*2129	31	4074	2676/2	31	6087	28197	33
29	2658	31	120	*10343-/2/3	31	1584	*2118/A	31	4076	2653/2	31	6088	28048	33
30	1068	30	121	*1134	30	1585	12386	32	4077	2677/2	31	6089	*27917	33
31	12370	32	122	*1101-/2/3	30	1589	17924	32	4078	2669/2	31	6090	*27997	33
32	2103	31	123	*1116-/2/3	30	1706	19250	32	4079	12390/2	32	6091	28108	33
33	1052	30	124	*1120-/2/3	30	1707	19251	32	4080	1076/2	30	6092	28198	33
34	1094	30	125	*2693-/2/3	31	1708	19252	32	4081	2102/2	31	6093	28049	33
35	1782	30	126	*1031-/2/3	30	1709	19253	32	4082	2681/2	31	6094	*27918	33
37	2672	31	127	*1111-/2/3	30	1766	2684	31	4083	2107/2	31	6095	*27998	33
38	2755	31	128	*2095-/2/3	31	1767	2114	31	4084	2104/2	31	6096	28109	33
39	2110	31	129	*2121-/2	31	1946	*22118	32	4085	2100/2	31	6097	28199	33
40	1055	30	129	*2121/3	31	1947	*22119	32	4086	2673/2	31	6098	28050	33
41	2757	31	130	*1127-/2/3	30	2043	*22344	32	4087	10710/2	31	6099	*27919	33
42	2753	31	131	*2692-/2/3	31	2128	22794	32	4088	2756/2	31	6100	*27999	33
43	2739	31	132	*1089-/2	30	2129	22796	32	4089	12378/2	32	6101	28110	33
44	2743	31	132	*1089/3	30	2130	*1103A/3	30	4090	2106/2	31	6102	28200	33
45	1054	30	133	*10354-/2/3	31	2131	*1107A/3	30	4091	2675/2	31	6103	28051	33
46	2758	31	134	*2122-/2/3	31	2181	22982	32	4092	12367/2	31	6104	*27920	33
47	12365	31	135	*1102-/2/3	30	2182	22983	32	5554	16568/2	32	6105	*28000	33
48	1092	30	136	*1095-/2	30	2183	22238	32	6001	28090	33	6106	28111	33
49	2091	30	136	*1095/3	30	2881	22580	32	6002	28180	33	6107	28201	33
50	1067	30	137	*1783-/2/3	30	2882	*22579/3	32	6003	28031	33	6108	28052	33
51	1053	30	138	*10349-/2/3	31	2883	*22579A/3	32	6004	*27900	33	6109	*27921	33
52	12377	32	139	*1119	30	2928	*27004	32	6005	*27980	33	6110	*28001	33
54	12380	32	140	*2696-/2/3	31	3157	19147	32	6006	28091	33	6111	28112	33
55	1058	30	141	*2707-/2/3	31	3158	19145	32	6007	28181	33	6112	28202	33
56	1057	30	142	*2126-/2/3	31	3159	*19148	32	6008	28032	33	6113	28053	33
57	2099	31	143	*1105-/2/3	30	3160	*19146	32	6009	*27901	33	6114	*27922	33
58	2679	31	144	*2713-/2/3	31	4001	1064/2	30	6010	27981	33	6115	28002	33
59	2680	31	145	*2712-/2	31	4002	1760/2	30	6011	28092	33	6116	28113	33
60	1072	30	145	*2712/3	31	4003	1050/2	30	6012	28182	33	6117	28203	33
61	2113	31	146	*2120-/2/3	31	4004	2754/2	31	6013	28033	33	6118	28054	33
62	2752	31	147	*2123-/2	31	4005	2686/2	31	6014	*27902	33	6119	*27923	33
63	12381	32	147	*2123/3	31	4006	2685/2	31	6016	28093	33	6120	*28003	33
64	12363	32	148	*1104-/2/3	30	4007	2750/2	31	6017	28183	33	6126	28115	33
65	12389	32	149	*2714-/2/3	31	4008	12347/2	31	6018	28034	33	6127	28205	33
66	2670	31	150	*10352-/2/3	31	4009	1765/2	30	6019	*27903	33	6128	28056	33
67	2660	31	151	*1093-/2/3	30	4010	1060/2	30	6020	*27983	33	6129	*27925	33
68	2109	31	152	*2115-/2/3	31	4011	1776/2	30	6026	28095	33	6130	*28005	33
69	2688	31	153	*1135-/2	30	4012	1770/2	30	6027	28185	33	6131	28116	33
70	2746	31	153	*1135/3	30	4013	2655/2	31	6028	28036	33	6132	28206	33
71	11408	31	154	*1103-/2/3	30	4014	2097/2	31	6029	*27905	33	6133	28057	33
72	2668	31	155	*10365-/2/3	31	4015	2678/2	31	6030	*27985	33	6134	*27926	33
73	2105	31	156	*1143	30	4016	1065/2	30	6031	28096	33	6135	*28006	33
74	2676	31	158	*1108-/2/3	30	4017	2687/2	31	6032	28037	33	6136	28117	33
75	2652	31	159	*1107-/2/3	30	4018	2664/2	31	6033	28037	33	6137	28207	33
76	2653	31	160	*1117-/2	30	4019	12348/2	31	6034	*27906	33	6138	28058	33
77	2677	31	161	*2128-/2	31	4020	1033/2	30	6035	*27986	33	6139	*27927	33
78	2669	31	162	*1114A-/2/3	30	4021	1051/2	30	6036	28097	33	6140	*28007	33
79	12390	32	163	*1761A-/2	30	4022	1066/2	30	6037	28187	33	6141	28118	33
80	1076	30	163	*1761A/3	30	4023	1070/2	30	6038	28038	33	6142	28208	33
81	2102	31	164	*1100A-/2/3	30	4024	2682/2	31						

INDEX OF AIR MINISTRY REFERENCE NUMBERS
OF STANDARD PLUGS & SOCKETS

5X/ No.	Plessey Part No. CZ	Page No.												
6155	*28138	33	6363	*50411	34	6649	71906	36	6840/B	*111687	38	7128	*84874	11
6156	*50951	35	6364	*56076	35	6651	53206	35	6841	*56114	35	7129	*108946	11
6158	51396	35	6365	*60524	35	6662	*59831	35	6841/B	*111681	38	7130	*108951	11
6159	*51395	35	6366	*60528	35	6695	*73360	36	6842	*71761	36	7131	*108952	11
6179	50355	34	6367	*60530	35	6704	64591	36	6842/B	*111663	38	7132	*108954	11
6181	50356	34	6368	*60531	35	6705	64599	36	6843	*71776	36	7134	*108959	11
6182	50357	34	6369	*60533	35	6707	*64183	36	6843/B	*111686	38	7135	*108961	11
6183	50359	34	6370	*56080	35	6717	60477	35	6844	*71772	36	7136	*108962	11
6184	50360	34	6371	*60499	35	6720	76498	36	6844/B	*111682	38	7137	*108964	11
6185	50361	34	6372	*56072	35	6744	83223	36	6845	*71766	36	7138	*108968	11
6186	50369	34	6373	*60509	35	6745	*83224	36	6845/B	*111668	38	7139	111223	8
6188	*50398	34	6374	*56085	35	6761	50378	34	6846	*71780	36	7140	111399	8
6189	*50399	34	6374/B	*111692	38	6772	*56084	35	6846/B	*111691	38	7141	111400	8
6190	*50400	34	6375	*56089	35	6772/B	*111646	38	6847	*83851	36	7142	111401	8
6191	*50401	34	6375/B	*111693	38	6773	*71748	36	6851	*71783	36	7143	111402	8
6192	*50403	34	6376	*56093	35	6773/B	*111648	38	6851/B	*111719	38	7144	111403	8
6193	*50404	34	6376/B	*111695	38	6774	*56104	35	6867	69865	36	7145	111404	8
6194	*50405	34	6377	*56097	35	6774/B	*111653	38	6871	50392	34	7146	111405	8
6195	*50408	34	6377/B	*111697	38	6775	*56096	35	6873	*60501	35	7147	111406	8
6196	*50409	34	6378	*64772	36	6775/B	*111651	38	6873/B	*111707	38	7148	111407	8
6197	*50410	34	6378/B	*111696	38	6776	*56092	35	6913	84859	36	7149	111408	8
6198	*50412	34	6379	*56101	35	6776/B	*111649	38	6917	*71788	36	7150	111409	8
6199	*50413	34	6379/B	*111698	38	6777	*56100	35	6917/B	*111730	38	7151	111410	8
6200	*50414	34	6380	*56105	35	6777/B	*111652	38	6925	50386	34	7152	111411	8
6201	*50421	34	6380/B	*111699	38	6778	*71757	36	6929	*71758	36	7153	111412	8
6207	50377	34	6381	*56109	35	6778/B	*111656	38	6929/B	*111694	38	7154	111413	8
6262	50363	34	6381/B	*111700	38	6779	*56108	35	6930	*71792	36	7155	111414	8
6263	50364	34	6382	*64770	36	6779/B	*111654	38	6930/B	*111734	38	7156	111415	8
6264	50365	34	6382/B	*111701	38	6780	*56112	35	6932	59834	35	7157	111416	8
6265	50370	34	6383	*64771	36	6780/B	*111658	38	6933	*59835	35	7158	111417	8
6274	50329	34	6383/B	*111702	38	6781	*71751	36	6934	64872	36	7159	111418	8
6284	50383	34	6384	*56113	35	6781/B	*111659	38	7021	84864	9	7160	111419	8
6285	*62086	36	6384/B	*111704	38	6782	*71753	36	7022	84865	9	7161	111420	8
6289	55325	35	6385	*64517	36	6782/B	*111665	38	7023	108930	9	7162	111421	8
6290	*50407	34	6385/B	*111705	38	6783	*71754	36	7024	108933	9	7163	111422	8
6291	50390	34	6386	*64773	36	6783/B	*111666	38	7025	84866	9	7164	111423	9
6292	*50434	34	6386/B	*111711	38	6788	*56195	36	7026	108932	9	7165	111424	9
6297	50373	34	6387	*56087	35	6798	*71760	36	7027	84867	9	7166	111425	9
6298	*50417	34	6387/B	*111715	38	6798/B	*111661	38	7028	84868	9	7167	111426	9
6299	*56067	35	6388	*56091	35	6799	*56088	35	7029	84869	9	7168	111427	9
6300	56068	35	6388/B	*111716	38	6799/B	*111647	38	7030	84870	8	7169	111428	9
6302	50372	34	6389	*56095	35	6800	*71778	36	7031	108914	8	7170	111429	9
6304	50381	34	6389/B	*111718	38	6800/B	*111688	38	7032	85945	8	7171	111430	9
6305	50382	34	6390	*56099	35	6801	*56094	35	7033	84871	8	7172	111431	9
6306	*50426	34	6390/B	*111720	38	6801/B	*111672	38	7034	108913	8	7173	111432	9
6307	*50427	34	6391	*56103	35	6802	*71781	36	7035	108915	8	7174	111433	9
6308	*56071	35	6391/B	*111721	38	6802/B	*111689	38	7036	108916	8	7175	111434	9
6309	*56065	35	6392	*56107	35	6811	*71768	36	7037	108923	8	7176	111435	9
6310	57216	35	6392/B	*111722	38	6811/B	*111673	38	7038	*84872	11	7177	111436	9
6313	56077	35	6393	*56111	35	6813	*71765	36	7039	*84873	11	7178	111437	9
6318	60492	35	6393/B	*111723	38	6813/B	*111662	38	7040	*108947	11	7179	111438	9
6319	*60522	35	6394	*56115	35	6821	*56086	35	7041	108950	11	7180	111439	9
6321	*56078	35	6394/B	*111727	38	6821/B	*111669	38	7042	*108945	11	7181	111440	9
6326	50354	34	6420	50391	34	6822	*71749	36	7043	*108948	11	7182	*111230	11
6327	50374	34	6421	*50416	34	6822/B	*111650	38	7044	*108944	11	7183	*111231	11
6328	50375	34	6422	57212	35	6823	*56090	35	7045	*84875	11	7184	*111232	11
6329	50358	34	6470	70185	36	6823/B	*111670	38	7046	*108949	11	7185	*111233	11
6330	56073	35	6471	*70186	36	6824	*56098	35	7047	*84876	11	7186	*111234	11
6331	60491	35	6479	58511	35	6824/B	*111674	38	7048	*84877	11	7187	*111235	11
6332	60493	35	6575	*67679	36	6825	*56110	35	7049	*84878	11	7188	*111236	11
6333	60494	35	6576	61468	35	6825/B	*111677	38	7050	108907	8	7189	*111296	11
6334	60496	35	6577	61467	35	6826	*71759	36	7051	*84879	11	7190	*111237	11
6335	60495	35	6598	56000	35	6826/B	*111657	38	7052	*84880	11	7191	*111442	11
6336	60497	35	6608	*73359	36	6827	*71771	36	7053	*108963	11	7192	*111443	11
6337	60478	35	6608/B	*111703	38	6827/B	*111680	38	7054	*108966	11	7193	*111444	11
6338	60481	35	6609	*71785	36	6828	*71774	36	7055	*84881	11	7194	*111445	11
6339	60483	35	6609/B	*111726	38	6828/B	*111684	38	7056	*108965	11	7195	*111446	11
6340	50387	34	6610	*66955	36	6829	*71750	36	7057	*84882	11	7196	*111447	11
6341	50366	34	6610/B	*111724	38	6829/B	*111655	38	7058	*84883	11	7197	*111448	11
6342	50388	34	6611	*71764	36	6830	*71769	36	7059	*84884	11	7198	*111449	11
6343	50367	34	6611/B	*111713	38	6830/B	*111678	38	7108	108906	8	7199	*111450	11
6344	50368	34	6612	*71794	36	6831	*56106	35	7109	108908	8	7200	*111451	11
6345	56075	35	6612/B	*111736	38	6831/B	*111676	38	7110	108909	8	7201	*111452	11
6346	56069	35	6613	*71784	36	6832	*71752	36	7111	108910	8	7202	*111453	11
6347	50371	34	6613/B	*111725	38	6832/B	*111660	38	7112	108911	8	7203	*111454	11
6348	56079	35	6614	*71786	36	6833	*71773	36	7113	108912	8	7204	*111455	11
6349	56070	35	6614/B	*111728	38	6833/B	*111683	38	7114	108917	8	7205	*111456	11
6350	*50418	34</												

INDEX

to part numbers of standard plugs and sockets

The following pages contain an index of Plessey part numbers cross-referenced with Air Ministry reference numbers and the page on which full details may be found.

In view of the development of Standard plugs and sockets over the years of their use, certain items have been redesigned, improved, or production may have been discontinued for a variety of reasons. These items have been included in the index for ease of reference and have been classified as follows:—

“DISCONTINUED”—items classified as such are no longer in production and an alternative should be selected from items of current manufacture.

“REPLACED BY”—items classified as such have been superseded by the assembly quoted and are considered to be completely interchangeable.

“OBSOLESCENT”—items classified as such have in many cases been shown with an alternative item from current manufacture. If it is not possible to use these alternatives, obsolescent items will be supplied but special prices and more protracted delivery may be unavoidable.

INDEX TO PART NUMBERS OF STANDARD PLUGS AND SOCKETS

Plessey Part No.	5X/No.		Page No.	Plessey Part No.	5X/No.		Page No.
Z 239	1521	Replaced by 2Z 139937	24	CZ 1135A-/2/3	188	Discontinued	—
CZ 1031-/2/3	126	Discontinued	—	CZ 1143	156	“	—
CZ 1031A-/2/3	174	“	—	CZ 1144-/2	106	Replaced by CZ 1144/3	—
CZ 1033	20	“	—	CZ 1144/3	106	Obsolete/No direct alternative	—
CZ 1033/2	4020	“	—	Z 1275	284	“	23
CZ 1050	3	Obsolete/Alternative 2CZ 111399	8	Z 1280	1504	Replaced by 2Z 84922	15
CZ 1050/2	4003	Replaced by 2CZ 111399	8	Z 1281	1506	“	15
CZ 1051	21	Obsolete/Alternative 2CZ 111225	8	Z 1282	1507	“	15
CZ 1051/2	4021	Replaced by 2CZ 111225	8	Z 1283	1508	“	15
CZ 1052	33	Obsolete/Alternative 2CZ 111227	8	Z 1285	1505	“	15
CZ 1052/2	4033	Replaced by 2CZ 111227	8	Z 1300	1497	“	15
CZ 1053	51	Obsolete/Alternative 2CZ 111229	8	Z 1301	1499	“	15
CZ 1053/2	4051	Replaced by 2CZ 111229	8	Z 1302	1500	“	15
CZ 1054	45	Discontinued	—	Z 1303	1501	“	15
CZ 1054/2	4045	“	—	Z 1306	1498	“	15
CZ 1055	40	Replaced by 2CZ 111408	8	Z 1307	1502	“	15
CZ 1055/2	4040	“	2CZ 111408	Z 1350	1570	“	24
CZ 1057	56	Obsolete/Alternative 2CZ 111412	8	Z 1352	909	“	24
CZ 1057/2	4056	Replaced by 2CZ 111412	8	Z 1353	1325	“	24
CZ 1058	55	Discontinued	—	Z 1359	1327	“	24
CZ 1058/2	4055	“	—	Z 1361	1328	“	24
CZ 1060	10	“	—	Z 1362	1329	“	24
CZ 1060/2	4010	“	—	Z 1363	912	“	24
CZ 1061	25	“	—	Z 1365	1330	“	24
CZ 1061/2	4025	“	—	Z 1369	1074	“	24
CZ 1064	1	Obsolete/Alternative 2CZ 111223	8	Z 1379/2	1331	Replaced by 2Z 139968	26
CZ 1064/2	4001	Replaced by 2CZ 111223	8	Z 1381/2	1333	“	26
CZ 1065	16	Obsolete/No direct alternative	—	Z 1382/2	921	“	26
CZ 1065/2	4016	Replaced by CZ 1065	—	Z 1383/2	330	“	26
CZ 1066	22	Discontinued	—	Z 1384/2	319	“	26
CZ 1066/2	4022	“	—	Z 1386/2	320	“	26
CZ 1067	50	“	—	Z 1388/2	1335	“	26
CZ 1067/2	4050	“	—	Z 1431	2073	“	25
CZ 1070	23	Obsolete/Alternative 2CZ 111299	8	Z 1431/B	—	Replaced by 2Z 139938	25
CZ 1070/2	4023	Replaced by 2CZ 111299	8	Z 1432	2074	“	25
CZ 1071	28	Discontinued	—	Z 1432/B	2230	Replaced by 2Z 139939	25
CZ 1071/2	4028	“	—	Z 1433	1342	“	25
CZ 1072	60	“	—	Z 1433/B	—	Replaced by 2Z 139940	25
CZ 1076	80	Replaced by 2CZ 111424	9	Z 1434	2075	“	25
CZ 1076/2	4080	“	2CZ 111424	Z 1434/B	—	Replaced by 2Z 139941	25
CZ 1077	93	Discontinued	—	Z 1435	2076	“	25
CZ 1088	30	“	—	Z 1435/B	—	Replaced by 2Z 139942	25
CZ 1088/2	4030	“	—	Z 1439/1	2082	“	24
CZ 1089-/2	132	Replaced by CZ 1089/3	—	Z 1439/2	1070	“	24
CZ 1089/3	132	Obsolete/No direct alternative	—	Z 1439/4	2086	“	24
CZ 1089A-/2/3	179	Discontinued	—	Z 1439/5	1072	“	24
CZ 1092	48	Obsolete/Alternative 2CZ 111410	8	Z 1439/6	2088	“	24
CZ 1092/2	4048	Replaced by 2CZ 111410	8	Z 1439/9	1071	“	24
CZ 1093-/2/3	151	“	2CZ 111445	Z 1439/10	1944	“	24
CZ 1093A-/2/3	187	“	2CZ 111467	Z 1439/11	2084	“	24
CZ 1094	34	Discontinued	—	Z 1439/12	2083	“	24
CZ 1094/2	4034	“	—	Z 1439/14	2087	“	24
CZ 1095-/2	136	Replaced by CZ 1095/3	—	Z 1439/15	2089	“	24
CZ 1095/3	136	Obsolete/No direct alternative	—	Z 1441	1343	“	24
CZ 1095A-/2	182	Replaced by CZ 1095A/3	—	Z 1442	1571	“	24
CZ 1095A/3	182	Obsolete/No direct alternative	—	Z 1450	2077	“	25
CZ 1100-/2/3	103	Replaced by 2CZ 111231	11	Z 1499	282	“	23
CZ 1100A-/2/3	164	“	2CZ 111449	Z 1500	283	“	23
CZ 1101-/2/3	122	“	2CZ 111440	Z 1650	1513	Replaced by 2Z 84917	15
CZ 1101A-/2/3	172	“	2CZ 111458	Z 1651	1515	“	15
CZ 1102-/2/3	135	“	2CZ 111236	Z 1652	1516	“	15
CZ 1102A-/2/3	181	“	2CZ 111461	Z 1653	1517	“	15
CZ 1103-/2/3	154	“	2CZ 111238	Z 1654	1518	“	15
CZ 1103A/3	2130	“	2CZ 111468	Z 1657	1514	“	15
CZ 1104-/2/3	148	Discontinued	—	Z 1688	285	“	23
CZ 1105-/2/3	143	Replaced by 2CZ 111443	11	Z 1690	286	“	23
CZ 1107-/2/3	159	“	2CZ 111447	Z 1694	1344	“	24
CZ 1107A/3	2131	“	2CZ 111470	Z 1760	2	Obsolete/No direct alternative	—
CZ 1108-/2/3	158	Discontinued	—	CZ 1760/2	4002	Replaced by CZ 1760	—
CZ 1110-/2/3	110	“	—	CZ 1761-/2	102	“	—
CZ 1110A-/2/3	168	“	—	CZ 1761/3	102	Obsolete/No direct alternative	—
CZ 1111-/2/3	127	“	—	CZ 1761A-/2	163	Replaced by CZ 1761A/3	—
CZ 1111A-/2/3	175	“	—	CZ 1761A/3	163	Obsolete/No direct alternative	—
CZ 1114-/2/3	101	Replaced by 2CZ 111230	11	CZ 1765	9	Discontinued	—
CZ 1114A-/2/3	162	“	2CZ 111448	Z 1765/2	4009	“	—
CZ 1115-/2	116	“	CZ 1115/3	Z 1766-/2/3	109	“	—
CZ 1115/3	116	Obsolete/No direct alternative	—	CZ 1770	12	“	—
CZ 1115A-/2/3	170	Discontinued	—	CZ 1770/2	4012	“	—
CZ 1116-/2/3	123	“	—	CZ 1771-/2	112	Replaced by CZ 1771/3	—
CZ 1117-/2	160	“	—	CZ 1771/3	112	Obsolete/No direct alternative	—
CZ 1117A-/2/3	189	“	—	CZ 1771A-/2	169	Replaced by CZ 1771A/3	—
CZ 1119	139	“	—	CZ 1771A/3	169	Obsolete/No direct alternative	—
CZ 1120-/2/3	124	Replaced by 2CZ 111298	11	CZ 1776	11	“	—
CZ 1120A-/2/3	173	“	2CZ 111456	Z 1776/2	4011	“	8
CZ 1127-/2/3	130	Discontinued	—	CZ 1777-/2/3	111	Replaced by 2CZ 111224	8
CZ 1127A-/2/3	178	“	—	CZ 1782	35	“	8
CZ 1134	121	“	—	CZ 1782/2	4035	Obsolete/Alternative 2CZ 111297	8
CZ 1135-/2	153	Replaced by CZ 1135/3	—	CZ 1783-/2/3	137	Replaced by 2CZ 111297	8
CZ 1135/3	153	Obsolete/No direct alternative	—	CZ 2091	49	“	11
						Discontinued	—

INDEX TO PART NUMBERS OF STANDARD PLUGS AND SOCKETS

Plessey Part No.	5X/ No.		Page No.	Plessey Part No.	5X/ No.		Page No.
CZ 2091/2	4049	Discontinued	—	CZ 2676	74	Discontinued	—
CZ 2094-/2/3	176	Replaced by 2CZ 111459	11	CZ 2676/2	4074	”	—
CZ 2095-/2/3	128	” 2CZ 111441	11	CZ 2677	77	Replaced by 2CZ 111421	9
CZ 2097	14	Discontinued	—	CZ 2677/2	4077	” 2CZ 111421	9
CZ 2097/2	4014	”	—	CZ 2678	15	Discontinued	—
CZ 2099	57	”	—	CZ 2678/2	4015	”	—
CZ 2100	85	Obsolete/Alternative 2CZ 111426	9	CZ 2679	58	”	—
CZ 2100/2	4085	Replaced by 2CZ 111426	9	CZ 2680	59	”	—
CZ 2102	81	Discontinued	—	CZ 2681	82	”	—
CZ 2102/2	4081	”	—	CZ 2681/2	4082	”	—
CZ 2103	32	Obsolete/Alternative 2CZ 111226	8	CZ 2682	24	Obsolete/Alternative 2CZ 111405	8
CZ 2103/2	4032	Replaced by 2CZ 111226	8	CZ 2682/2	4024	Replaced by 2CZ 111405	8
CZ 2104	84	Obsolete/Alternative 2CZ 111425	9	CZ 2684	1766	Discontinued	—
CZ 2104/2	4084	Replaced by 2CZ 111425	9	CZ 2685	6	Obsolete/No direct alternative	—
CZ 2105	73	Obsolete/No direct alternative	—	CZ 2685/2	4006	Replaced by CZ 2685	—
CZ 2105/2	4073	Replaced by CZ 2105	—	CZ 2686	5	Obsolete/Alternative 2CZ 111401	8
CZ 2106	90	Discontinued	—	CZ 2686/2	4005	Replaced by 2CZ 111401	8
CZ 2106/2	4090	”	—	CZ 2687	17	Obsolete/Alternative 2CZ 111404	8
CZ 2107	83	”	—	CZ 2687/2	4017	Replaced by 2CZ 111404	8
CZ 2107/2	4083	”	—	CZ 2688	69	” 2CZ 111416	9
CZ 2109	68	Obsolete/Alternative 2CZ 111414	9	CZ 2688/2	4069	” 2CZ 111416	9
CZ 2109/2	4068	Replaced by 2CZ 111414	9	CZ 2692-/2/3	131	Discontinued	—
CZ 2110	39	Discontinued	—	CZ 2693-/2/3	125	Replaced by 2CZ 111439	11
CZ 2110/2	4039	”	—	CZ 2695-/2/3	118	Discontinued	—
CZ 2113	61	”	—	CZ 2696-/2/3	140	Replaced by 2CZ 111442	—
CZ 2114	1767	”	—	CZ 2697-/2/3	115	Discontinued	—
CZ 2115-/2/3	152	”	—	CZ 2698-/2/3	105	Replaced by 2CZ 111233	—
CZ 2118-/2/3	114	”	—	CZ 2698A-/2/3	165	” 2CZ 111451	—
CZ 2118A	1584	”	—	CZ 2699-/2/3	117	” 2CZ 111438	—
CZ 2120-/2/3	146	”	—	CZ 2702-/2/3	107	” 2CZ 111436	—
CZ 2121-/2	129	Replaced by CZ 2121/3	—	CZ 2702A-/2/3	166	” 2CZ 111452	—
CZ 2121/3	129	Obsolete/No direct alternative	—	CZ 2704-/2/3	104	” 2CZ 111232	—
CZ 2121A-/2/3	177	Discontinued	—	CZ 2707-/2/3	141	” 2CZ 111446	—
CZ 2122-/2/3	134	Replaced by 2CZ 111235	11	CZ 2707A-/2/3	184	” 2CZ 111469	—
CZ 2122A-/2/3	180	” 2CZ 111460	11	CZ 2712-/2	145	Replaced by CZ 2712/3	—
CZ 2123-/2	147	” CZ 2123/2	—	CZ 2712/3	145	Obsolete/No direct alternative	—
CZ 2123/3	147	Obsolete/No direct alternative	—	CZ 2712A-/2/3	185	Discontinued	—
CZ 2123A-/2/3	186	Discontinued	—	CZ 2713-/2/3	144	Replaced by 2CZ 111444	—
CZ 2126-/2/3	142	”	—	CZ 2714-/2/3	149	Discontinued	—
CZ 2128-/2	161	”	—	CZ 2739	43	”	—
CZ 2128A/2	190	”	—	CZ 2739/2	4043	”	—
CZ 2129	1583	”	—	CZ 2743	44	”	—
CZ 2129/A	1582	”	—	CZ 2743/2	4044	”	—
CZ 2135-/2	113	Replaced by CZ 2135/3	—	CZ 2744	27	”	—
CZ 2135/3	113	Obsolete/No direct alternative	—	CZ 2744/2	4027	”	—
CZ 2138	119	Discontinued	—	CZ 2746	70	”	—
CZ 2138/A	171	”	—	CZ 2746/2	4070	”	—
Z 2260/2	335	Replaced by Z 139964	—	CZ 2750	7	”	—
Z 2263/2	1348	” Z 139974	26	CZ 2750/2	4007	”	—
Z 2264/2	1351	” Z 139976	26	CZ 2752	62	”	—
Z 2265/2	1353	” Z 139980	26	CZ 2753	42	”	—
Z 2266/2	2189	” Z 139982	26	CZ 2753/2	4042	”	—
Z 2267/2	345	” Z 139981	26	CZ 2754	4	”	—
Z 2268/2	243	” Z 139973	26	CZ 2754/2	4004	”	—
Z 2269/2	244	” Z 139975	26	CZ 2755	38	”	—
Z 2271/2	239	” Z 139959	26	CZ 2755/2	4038	”	—
Z 2272/2	1356	” Z 139957	26	CZ 2756	88	”	—
Z 2273/2	1357	” Z 139967	26	CZ 2756/2	4088	”	—
Z 2274/2	242	” Z 139971	26	CZ 2757	41	”	—
Z 2277/2	240	” Z 139960	26	CZ 2757/2	4041	”	—
Z 2280/2	2190	” Z 139986	26	CZ 2758	46	”	—
Z 2281/2	2191	” Z 139987	26	CZ 2758/2	4046	”	—
Z 2575/2	1893	” Z 139984	26	CZ 10340-/2/3	108	”	—
Z 2588/2	2188	” Z 139958	26	CZ 10340A-/2/3	167	”	—
Z 2593/2	333	” Z 139961	26	CZ 10343-/2/3	120	”	—
Z 2594/2	2193	” Z 139979	26	CZ 10348	1286	”	—
CZ 2652	75	Discontinued	—	CZ 10349-/2/3	138	”	—
CZ 2653	76	Replaced by 2CZ 111423	9	CZ 10349A-/2/3	183	”	—
CZ 2653/2	4076	” 2CZ 111423	9	CZ 10352-/2/3	150	”	—
CZ 2655	13	Discontinued	—	CZ 10354-/2/3	133	”	—
CZ 2655/2	4013	”	—	CZ 10365-/2/3	155	”	—
CZ 2658	29	”	—	CZ 10710	87	”	—
CZ 2658/2	4029	”	—	CZ 10710/2	4087	”	—
CZ 2660	67	Obsolete/No direct alternative	—	Z 1394/2	1373	”	—
CZ 2660/2	4067	Replaced by CZ 2660	—	Z 1397/2	1375	”	—
CZ 2664	18	Discontinued	—	CZ 11408	71	”	—
CZ 2664/2	4018	”	—	CZ 11408/2	4071	”	—
CZ 2668	72	”	—	Z 11601/2	1379	”	—
CZ 2668/2	4072	”	—	Z 11602	2195	”	—
CZ 2669	78	”	—	CZ 12347	8	”	—
CZ 2669/2	4078	”	—	CZ 12347/2	4008	”	—
CZ 2670	66	Replaced by 2CZ 111413	9	CZ 12348	19	”	—
CZ 2670/2	4066	” 2CZ 111413	9	CZ 12348/2	4019	”	—
CZ 2672	37	” 2CZ 111407	8	CZ 12353	95	”	—
CZ 2672/2	4037	” 2CZ 111407	8	CZ 12363	64	”	—
CZ 2673	86	Obsolete/No direct alternative	—	CZ 12365	47	”	—
CZ 2673/2	4086	Replaced by CZ 2673	—	CZ 12365/2	4047	”	—
CZ 2675	91	” 2CZ 111432	9	CZ 12367	92	”	—
CZ 2675/2	4091	” 2CZ 111432	9	CZ 12367/2	4092	”	—

INDEX TO PART NUMBERS OF STANDARD PLUGS AND SOCKETS

Plessey Part No.	5X/ No.		Page No.	Plessey Part No.	5X/ No.		Page No.
CZ 12370	31	Discontinued	—	Z 22675/A	2110	Replaced by 2Z 139935/A	24
CZ 12370/2	4031	"	—	Z 22675/Z	2111	" 2Z 139935/Z	24
CZ 12377	52	"	—	Z 22675/B	2112	" 2Z 139935/B	24
CZ 12377/2	4052	"	—	Z 22675/C	2113	" 2Z 139935/C	24
CZ 12378	89	"	—	Z 22675/D	2114	" 2Z 139935/D	24
CZ 12378/2	4089	"	—	Z 22675/E	2115	" 2Z 139935/E	24
CZ 12379	94	"	—	Z 22676/A	2117	" 2Z 139934/A	24
CZ 12380	54	"	—	Z 22676/Z	2118	" 2Z 139934/Z	24
CZ 12381	63	"	—	Z 22676/B	2119	" 2Z 139934/B	24
CZ 12384	26	Obsolete/Alternative 2CZ 111406	8	Z 22676/C	2120	" 2Z 139934/C	24
CZ 12384/2	4026	Replaced by 2CZ 111406	8	Z 22676/D	2121	" 2Z 139934/D	24
CZ 12386	1585	Discontinued	—	Z 22676/E	2122	" 2Z 139934/E	24
CZ 12389	65	"	—	CZ 22794	2128	" 2CZ 111433	9
CZ 12390	79	"	—	CZ 22796	2129	" 2CZ 111435	9
CZ 12390/2	4079	"	—	CZ 22982	2181	" 2CZ 111433	9
CZ 12391	1285	"	—	CZ 22983	2182	" 2CZ 111435	9
Z 12550/2	2197	Replaced by 2Z 139983	26	CZ 23144/Z	6440	...	23
Z 13031	1097	...	22	CZ 23144/B	6488	...	23
Z 13032	1089	...	22	CZ 23144/C	6489	...	23
Z 13033	1575	...	22	CZ 23144/D	3143	...	23
Z 13106	1088	...	22	CZ 23144/E	6490	...	23
Z 13299	287	...	23	CZ 23144/F	—	...	23
Z 14040	1512	Replaced by 2Z 111191	15	Z 23195	6167	Replaced by 2Z 84912/A	15
Z 14485/2	7320	" 2Z 139956	26	Z 23196	6206	" 2Z 84912/B	15
Z 15003/2	1588	" 2Z 139985	26	Z 23197	6168	" 2Z 84912/C	15
CZ 15155/-3	1555	Discontinued	—	Z 23198	6169	" 2Z 84912/D	15
CZ 16568	1554	"	—	Z 23201/A	3094	...	15
CZ 16568/2	5554	"	—	Z 23201/Z	3095	...	15
Z 17830	—	...	15	Z 23201/B	3096	...	15
Z 17831	—	...	15	Z 23201/C	3097	...	15
Z 17832	—	...	15	Z 23201/D	3098	...	15
Z 17833	—	...	15	Z 23201/E	3099	...	15
Z 17834	—	...	15	Z 23276	2185	...	22
Z 17835	—	...	15	Z 23414	6402	Replaced by 2Z 84912/Z	15
Z 17836	—	...	15	CZ 24626	6850	...	23
Z 17837	—	...	15	CZ 24628	6631	...	23
Z 17838	—	...	15	CZ 24632	6603	...	23
Z 17839	—	...	15	CZ 24634	6797	...	23
Z 17840	—	...	15	CZ 24636	—	...	23
Z 17841	—	...	15	CZ 24638	6604	...	23
CZ 17883	198	Discontinued	—	CZ 24640	6605	...	23
CZ 17884	199	"	—	CZ 24642	—	...	23
CZ 17924	1589	"	—	CZ 24644	6177	...	23
Z 18500/A	1522	...	24	CZ 24646	6178	...	23
Z 18500/Z	1523	...	24	CZ 24648	6628	...	23
Z 18500/B	1524	...	24	CZ 24650	6180	...	23
Z 18500/C	1525	...	24	CZ 24652	—	...	23
Z 18500/D	1526	...	24	CZ 24654	—	...	23
Z 18500/E	1527	...	24	CZ 24656	6606	...	23
Z 18501/A	1529	...	23	CZ 24658	—	...	23
Z 18501/Z	1530	...	23	Z 24915	—	...	15
Z 18501/B	1531	...	23	Z 24923	—	...	15
Z 18501/C	1532	...	23	Z 24924	6492	...	15
Z 18501/D	1533	...	23	Z 24925	6914	...	15
Z 18501/E	1534	...	23	Z 24932	—	...	15
Z 18501/F	1535	...	23	Z 24933	6493	...	15
Z 18764/A	1546	...	24	Z 24995	—	Replaced by 2Z 109914	15
Z 18764/Z	1547	...	24	Z 25003	6396	" 2Z 111189	15
Z 18764/B	1548	...	24	Z 25004	—	" 2Z 109908	15
Z 18764/C	1549	...	24	Z 25005	—	" 2Z 109909	15
Z 18764/D	1550	...	24	Z 25012	—	" 2Z 109906	15
Z 18764/E	2187	...	24	Z 25013	—	" 2Z 109907	15
CZ 18960	1567	Discontinued	—	CZ 26519	—	Discontinued	—
CZ 18961	1568	"	—	CZ 26521	—	...	—
CZ 19145	3158	Obsolete/No direct alternative	—	CZ 27004	2928	Replaced by 2CZ 138244	13
CZ 19146	3160	" "	—	Z 27323	3238	...	15
CZ 19147	3157	" "	—	Z 27441	3151	Replaced by 2Z 139928	23
CZ 19148	3159	" "	—	Z 27442	3152	" 2Z 139929	23
CZ 19250	1706	Discontinued	—	Z 27443	3090	" 2Z 139930	23
CZ 19251	1707	"	—	Z 27444	3154	" 2Z 139931	23
CZ 19252	1708	"	—	Z 27445	3155	" 2Z 139932	23
CZ 19253	1709	"	—	Z 27446	3156	" 2Z 139933	23
Z 19269	2049	...	15	CZ 27501	—	Replaced by 2CZ 84872	11
Z 19270	2050	...	15	CZ 27502	—	Discontinued	—
Z 19271	2051	...	15	CZ 27511	—	Replaced by 2CZ 84875	11
Z 19272	2052	...	15	CZ 27522	—	" 2CZ 108949	11
Z 19273	2053	...	15	CZ 27530	—	Discontinued	—
CZ 22118	1946	Discontinued	—	CZ 27531	—	...	—
CZ 22119	1947	"	—	CZ 27536	—	...	—
Z 22164	1963	...	22	CZ 27561	—	Replaced by 2CZ 108906	8
Z 22165	1964	...	22	CZ 27562	—	Discontinued	—
Z 22166	1965	...	22	CZ 27563	—	Replaced by 2CZ 84870	8
Z 22167	1966	...	22	CZ 27564	—	" 2CZ 108907	8
Z 22168	1967	...	22	CZ 27565	—	" 2CZ 85945	8
CZ 22238	2183	Replaced by 2CZ 140052	13	CZ 27567	—	" 2CZ 108908	8
CZ 22344	2043	Discontinued	—	CZ 27568	—	" 2CZ 108909	8
CZ 22579/3	2882	Replaced by 2CZ 139900	12	CZ 27571	—	" 2CZ 84871	8
CZ 22579A/3	2883	" 2CZ 139901	12	CZ 27577	—	" 2CZ 108910	8
CZ 22580	2881	" 2CZ 139898	12	CZ 27582	—	" 2CZ 108911	8

INDEX TO PART NUMBERS OF STANDARD PLUGS AND SOCKETS

Plessey Part No.	5X/ No.		Page No.	Plessey Part No.	5X/ No.		Page No.									
CZ 27583	—	Replaced by 2CZ 108912	8	CZ 28040	6048	Discontinued	10
CZ 27585	—	" 2CZ 108914	8	CZ 28042	6058	Replaced by	2CZ 138101	10
CZ 27588	—	Discontinued	8	CZ 28043	6063	"	2CZ 138105	10
CZ 27591	—	Replaced by 2CZ 108915	8	CZ 28044	6068	Discontinued	10
CZ 27592	—	" 2CZ 108916	8	CZ 28045	6073	Replaced by	2CZ 138102	10
CZ 27593	—	Discontinued	—	CZ 28046	6078	"	2CZ 138102	10
CZ 27594	—	Replaced by 2CZ 108917	8	CZ 28048	6088	"	2CZ 138111	10
CZ 27595	—	" 2CZ 108919	8	CZ 28049	6093	"	2CZ 138113	10
CZ 27598	—	" 2CZ 108920	8	CZ 28050	6098	"	2CZ 138107	10
CZ 27599	—	" 2CZ 108921	—	CZ 28051	6103	"	2CZ 138103	10
CZ 27602	—	Discontinued	—	CZ 28052	6108	"	2CZ 138109	10
CZ 27606	—	Replaced by 2CZ 108922	8	CZ 28053	6113	"	2CZ 138112	10
CZ 27609	—	" 2CZ 108923	8	CZ 28054	6118	"	2CZ 138110	10
CZ 27622	—	" 2CZ 108905	8	CZ 28056	6128	"	2CZ 138114	10
CZ 27810/2	6147	Discontinued	—	CZ 28057	6133	"	2CZ 138115	10
CZ 27811/3	6149	"	—	CZ 28058	6138	Discontinued	10
CZ 27811/A/3	6150	"	—	CZ 28059	6143	Replaced by	2CZ 138116	10
Z 27880	6208	Replaced by 2Z 109905	15	CZ 28090	6001	"	2CZ 108906	8
Z 27881	—	" Z 111186	15	CZ 28091	6006	"	2CZ 84870	8
Z 27885	—	" Z 111184	15	CZ 28093	6016	"	2CZ 111400	8
Z 27888	—	" Z 109933	15	CZ 28095	6026	"	2CZ 111402	8
Z 27892	—	" Z 109910	15	CZ 28096	6031	"	2CZ 108909	8
Z 27893	—	" Z 109911	15	CZ 28097	6036	"	2CZ 84871	8
Z 27894	—	" Z 109912	15	CZ 28098	6041	"	2CZ 108910	8
Z 27895	—	" Z 109913	15	CZ 28099	6046	Discontinued	—
Z 27897	—	" Z 111188	15	CZ 28101	6056	Replaced by	2CZ 108911	8
CZ 27900	6004	" 2CZ 84872	—	CZ 28102	6061	"	2CZ 108912	8
CZ 27901	6009	" 2CZ 84873	—	CZ 28103	6066	Discontinued	—	—
CZ 27902	6014	" 2CZ 111123	—	CZ 28104	6071	Replaced by	2CZ 111406	8
CZ 27903	6019	" 2CZ 84874	—	CZ 28105	6076	"	2CZ 108914	8
CZ 27905	6029	" 2CZ 111436	—	CZ 28107	6086	"	2CZ 111227	8
CZ 27906	6034	" 2CZ 108945	—	CZ 28108	6091	"	2CZ 111229	8
CZ 27907	6039	" 2CZ 84875	—	CZ 28109	6096	"	2CZ 111228	8
CZ 27908	6044	" 2CZ 108946	—	CZ 28110	6101	"	2CZ 111407	8
CZ 27909	6049	Discontinued	—	CZ 28111	6106	"	2CZ 111408	8
CZ 27911	6059	Replaced by 2CZ 108947	—	CZ 28112	6111	"	2CZ 111409	8
CZ 27912	6064	" 2CZ 108948	—	CZ 28113	6116	"	2CZ 111410	8
CZ 27913	6069	Discontinued	—	CZ 28115	6126	"	2CZ 108923	8
CZ 27914	6074	Replaced by 2CZ 111441	—	CZ 28116	6131	Discontinued	—	—
CZ 27915	6079	" 2CZ 108950	—	CZ 28117	6136	Replaced by	2CZ 108905	8
CZ 27917	6089	" 2CZ 84876	—	CZ 28118	6141	Discontinued	—	—
CZ 27918	6094	" 2CZ 111236	—	CZ 28137	6154	Replaced by	2CZ 111442	8
CZ 27919	6099	" 2CZ 111296	—	CZ 28138	6155	"	2CZ 108915	8
CZ 27920	6104	" 2CZ 111237	—	CZ 28139	6151	"	2CZ 111227	8
CZ 27921	6109	" 2CZ 111442	—	CZ 28140	6152	"	2CZ 111228	8
CZ 27922	6114	" 2CZ 111443	—	CZ 28141	6153	"	2CZ 111407	8
CZ 27923	6119	" 2CZ 111444	—	Z 28146	3240	"	2CZ 111408	8
CZ 27925	6129	" 2CZ 111445	—	Z 28147	3242	"	2CZ 111409	8
CZ 27926	6134	" 2CZ 84878	—	Z 28156/A	3168	Replaced by	2Z 84914/A	8
CZ 27927	6139	Discontinued	—	Z 28156/Z	3169	"	2Z 84914/Z	8
CZ 27928	6144	Replaced by 2CZ 108942	—	Z 28156/B	3170	"	2Z 84914/B	8
CZ 27980	6005	" 2CZ 84879	—	Z 28156/C	3171	"	2Z 84914/C	8
CZ 27981	6010	" 2CZ 84880	—	Z 28156/D	3172	"	2Z 84914/D	8
CZ 27983	6020	" 2CZ 108959	—	Z 28156/E	3173	"	2Z 84914/E	9
CZ 27985	6030	" 2CZ 108961	—	CZ 28180	6002	"	2CZ 84864	9
CZ 27986	6035	" 2CZ 84881	—	CZ 28181	6007	"	2CZ 84865	9
CZ 27987	6040	" 2CZ 108962	—	CZ 28182	6012	"	2CZ 111415	9
CZ 27988	6045	Discontinued	—	CZ 28183	6017	"	2CZ 108926	9
CZ 27989	6050	Replaced by 2CZ 108963	—	CZ 28183	6027	"	2CZ 111417	9
CZ 27991	6060	" 2CZ 108964	—	CZ 28185	6032	"	2CZ 108927	9
CZ 27992	6065	"	—	CZ 28186	6037	"	2CZ 84866	9
CZ 27993	6070	Discontinued	—	CZ 28187	6042	"	2CZ 108929	9
CZ 27994	6075	Replaced by 2CZ 111459	—	CZ 28188	6047	Discontinued	—	—
CZ 27995	6080	" 2CZ 108966	—	CZ 28189	6057	Replaced by	2CZ 108930	9
CZ 27997	6090	" 2CZ 84882	—	CZ 28191	6062	"	2CZ 108931	9
CZ 27998	6095	" 2CZ 111461	—	CZ 28192	6067	Discontinued	—	—
CZ 27999	6100	" 2CZ 111462	—	CZ 28193	6072	Replaced by	2CZ 111424	9
CZ 28000	6105	" 2CZ 111463	—	CZ 28194	6077	"	2CZ 108933	9
CZ 28001	6110	" 2CZ 111464	—	CZ 28195	6087	"	2CZ 84867	9
CZ 28002	6115	" 2CZ 111465	—	CZ 28197	6092	"	2CZ 111426	9
CZ 28003	6120	" 2CZ 111466	—	CZ 28198	6097	"	2CZ 111427	9
CZ 28005	6130	" 2CZ 111467	—	CZ 28199	6102	"	2CZ 111428	9
CZ 28006	6135	" 2CZ 84884	—	CZ 28200	6107	"	2CZ 111429	9
CZ 28007	6140	Discontinued	—	CZ 28201	6107	"	2CZ 111430	9
CZ 28008	6145	Replaced by 2CZ 108974	—	CZ 28202	6112	"	2CZ 111431	9
Z 28021/A	3174	" 2Z 84911/A	15	CZ 28203	6117	"	2CZ 111432	9
Z 28021/Z	3175	" 2Z 84911/Z	15	CZ 28205	6127	"	2CZ 111433	9
Z 28021/B	3176	" 2Z 84911/B	15	CZ 28206	6132	"	2CZ 84869	9
Z 28021/C	3177	" 2Z 84911/C	15	CZ 28207	6137	Discontinued	—	—
Z 28021/D	3178	" 2Z 84911/D	15	CZ 28208	6142	Replaced by	2CZ 108941	9
Z 28021/E	3179	" 2Z 84911/E	15	CZ 28342	—	"	2CZ 108906	9
CZ 28031	6003	" 2CZ 138097	10	CZ 28343	—	Discontinued	—	—
CZ 28032	6008	" 2CZ 138099	10	CZ 28344	—	Replaced by	2CZ 108915	8
CZ 28033	6013	" 2CZ 138096	10	CZ 28348	—	"	2CZ 108915	8
CZ 28034	6018	" 2CZ 138104	10	CZ 28349	—	"	2CZ 108915	8
CZ 28035	6028	" 2CZ 138098	10	CZ 28350	—	"	2CZ 108915	8
CZ 28036	6033	" 2CZ 138100	10	CZ 28353	—	"	2CZ 108915	8
CZ 28037	6038	" 2CZ 138246	10	CZ 28354	—	"	2CZ 108915	8
CZ 28038	6043	" 2CZ 138106	10	CZ 28356	—	Replaced by	2CZ 108915	8

INDEX TO PART NUMBERS OF STANDARD PLUGS AND SOCKETS

Plessey Part No.	5X/ No.	Page No.	Plessey Part No.	5X/ No.	Page No.
CZ 28357	—	Discontinued	CZ 50388	6342	Replaced by 2CZ 111420
CZ 28422	—	Replaced by 2CZ 84871	CZ 50390	6291	2CZ 84868
Z 28786	6403	" 2Z 84912/E	CZ 50391	6420	2CZ 108934
CZ 28978	—	Discontinued	CZ 50392	6871	2CZ 108935
CZ 49095	—	"	CZ 50393	—	2CZ 108936
CZ 49164	6148	"	CZ 50394	—	2CZ 108937
Z 49249	6311	"	CZ 50395	—	2CZ 108938
Z 49250	6303	"	CZ 50396	6626	2CZ 108939
Z 49251	6494	"	CZ 50398	6188	2CZ 111230
Z 49252	6495	"	CZ 50399	6189	2CZ 111231
Z 49253	—	"	CZ 50400	6190	2CZ 111233
Z 49278	—	"	CZ 50401	6191	2CZ 111234
Z 49803	—	"	CZ 50402	6352	2CZ 111298
Z 49804	—	"	CZ 50403	6192	2CZ 111439
Z 49806	—	"	CZ 50404	6193	2CZ 111235
CZ 50310	—	Replaced by 2CZ 108906	CZ 50405	6194	2CZ 111238
CZ 50311	—	2CZ 84870	CZ 50406	—	2CZ 111447
CZ 50312	—	2CZ 108907	CZ 50407	6290	2CZ 111448
CZ 50313	—	2CZ 85945	CZ 50408	6195	2CZ 111449
CZ 50314	—	2CZ 108908	CZ 50409	6196	2CZ 111451
CZ 50315	—	2CZ 108909	CZ 50410	6197	2CZ 111454
CZ 50316	—	2CZ 84871	CZ 50411	6363	2CZ 111456
CZ 50317	—	2CZ 108910	CZ 50412	6198	2CZ 111457
CZ 50318	—	2CZ 108911	CZ 50413	6199	2CZ 111460
CZ 50319	—	2CZ 108912	CZ 50414	6200	2CZ 111468
CZ 50320	—	2CZ 108914	CZ 50415	—	2CZ 111470
CZ 50321	—	2CZ 108915	CZ 50416	6421	2CZ 108943
CZ 50322	—	2CZ 108916	CZ 50417	6298	2CZ 108944
CZ 50323	—	2CZ 108917	CZ 50418	6350	2CZ 111437
CZ 50324	—	2CZ 108918	CZ 50419	6351	2CZ 111438
CZ 50325	—	2CZ 108919	CZ 50421	6201	2CZ 84877
CZ 50326	—	2CZ 108920	CZ 50422	—	2CZ 108951
CZ 50327	—	2CZ 108921	CZ 50423	—	2CZ 108952
CZ 50328	—	2CZ 108922	CZ 50424	—	2CZ 108953
CZ 50329	6274	2CZ 108923	CZ 50425	—	2CZ 108954
CZ 50331	—	2CZ 108905	CZ 50426	6306	2CZ 108955
CZ 50332	—	2CZ 84864	CZ 50427	6307	2CZ 108956
CZ 50333	—	2CZ 84865	CZ 50430	—	2CZ 108960
CZ 50334	—	2CZ 108925	CZ 50431	6361	2CZ 111453
CZ 50335	—	2CZ 108926	CZ 50432	6362	2CZ 111455
CZ 50336	—	2CZ 108927	CZ 50434	6292	2CZ 84883
CZ 50337	—	2CZ 108928	CZ 50435	—	2CZ 108967
CZ 50338	—	2CZ 84866	CZ 50436	—	2CZ 108968
CZ 50339	—	2CZ 108929	CZ 50437	—	2CZ 108969
CZ 50340	—	2CZ 108930	CZ 50438	—	2CZ 108970
CZ 50341	—	2CZ 108931	CZ 50439	—	2CZ 108971
CZ 50342	—	2CZ 108933	CZ 50440	6625	2CZ 108972
CZ 50343	—	2CZ 84867	CZ 50442	—	2CZ 84872
CZ 50344	—	2CZ 84868	CZ 50443	—	2CZ 84873
CZ 50345	—	2CZ 108934	CZ 50444	—	2CZ 108943
CZ 50346	—	2CZ 108935	CZ 50445	—	2CZ 84874
CZ 50347	—	2CZ 108936	CZ 50446	—	2CZ 108944
CZ 50348	—	2CZ 108937	CZ 50447	—	2CZ 108945
CZ 50349	—	2CZ 108938	CZ 50448	—	2CZ 84875
CZ 50350	—	2CZ 108939	CZ 50449	—	2CZ 108946
CZ 50351	—	2CZ 84869	CZ 50450	—	2CZ 108947
CZ 50353	—	2CZ 108941	CZ 50451	—	2CZ 108948
CZ 50354	6326	2CZ 111223	CZ 50452	—	2CZ 108950
CZ 50355	6179	2CZ 111399	CZ 50453	—	2CZ 84876
CZ 50356	6181	2CZ 111401	CZ 50454	—	2CZ 84877
CZ 50357	6182	2CZ 111224	CZ 50455	—	2CZ 108951
CZ 50358	6329	2CZ 111229	CZ 50456	—	2CZ 108952
CZ 50359	6183	2CZ 111405	CZ 50457	—	2CZ 108953
CZ 50360	6184	2CZ 111226	CZ 50458	—	2CZ 108954
CZ 50361	6185	2CZ 111229	CZ 50459	—	2CZ 108955
CZ 50362	—	2CZ 111412	CZ 50460	—	2CZ 108956
CZ 50363	6262	2CZ 111413	CZ 50461	—	2CZ 84878
CZ 50364	6263	2CZ 111414	CZ 50463	—	2CZ 108942
CZ 50365	6264	2CZ 111416	CZ 50464	—	2CZ 84879
CZ 50366	6341	2CZ 111419	CZ 50465	—	2CZ 84880
CZ 50367	6343	2CZ 111421	CZ 50466	—	2CZ 108959
CZ 50368	6344	2CZ 111422	CZ 50467	—	2CZ 108960
CZ 50369	6186	2CZ 111425	CZ 50468	—	2CZ 108961
CZ 50370	6265	2CZ 111433	CZ 50469	—	2CZ 84881
CZ 50371	6347	2CZ 111435	CZ 50470	—	2CZ 108962
CZ 50372	6302	2CZ 108907	CZ 50471	—	2CZ 108963
CZ 50373	6297	2CZ 108908	CZ 50472	—	2CZ 108964
CZ 50374	6327	2CZ 111403	CZ 50473	—	2CZ 108966
CZ 50375	6328	2CZ 111404	CZ 50474	—	2CZ 84882
CZ 50377	6207	2CZ 108916	CZ 50475	—	2CZ 84883
CZ 50378	6761	2CZ 108917	CZ 50476	—	2CZ 108967
CZ 50379	—	2CZ 108918	CZ 50477	—	2CZ 108968
CZ 50380	—	2CZ 108919	CZ 50478	—	2CZ 108970
CZ 50381	6304	2CZ 108920	CZ 50480	—	2CZ 108971
CZ 50382	6305	2CZ 108921	CZ 50481	—	2CZ 108972
CZ 50383	6284	2CZ 108922	CZ 50482	—	2CZ 84884
CZ 50385	—	2CZ 108925	CZ 50484	—	2CZ 108974
CZ 50386	6925	2CZ 108927	CZ 50622	—	2CZ 85945
CZ 50387	6340	2CZ 111418	CZ 50663	—	2CZ 111228

INDEX TO PART NUMBERS OF STANDARD PLUGS AND SOCKETS

Plessey Part No.	5X/ No.	Page No.	Plessey Part No.	5X/ No.	Page No.
CZ 50675	—	Replaced by 2CZ 108918	8	CZ 59067	—
CZ 50951	6156	" 2CZ 138245	13	CZ 59068	—
CZ 51091	5H/112	13	CZ 59586	—
Z 51094	5H/111	13	CZ 59675	—
CZ 51097	5H/110	13	CZ 59808	—
CZ 51395	5X/6159	Replaced by 2CZ 83851	—	CZ 59809	—
CZ 51396	6158	" CZ 70185	—	CZ 59810	—
Z 53003	—	" 2Z 138788	15	CZ 59831	6662
Z 53006	6805	15	CZ 59834	6932
CZ 53206	6651	Discontinued	—	CZ 59853	6933
CZ 53252	—	Replaced by 2CZ 108913	8	Z 60366	—
CZ 53321	—	Discontinued	—	CZ 60477	6717
CZ 53343	—	"	—	CZ 60478	6377
CZ 54982	—	"	—	CZ 60479	—
CZ 55149	—	"	—	CZ 60480	—
CZ 55325	6289	"	—	CZ 60481	6338
CZ 55897	6632	"	—	CZ 60482	—
CZ 56000	6598	Replaced by 2CZ 139899	12	CZ 60483	6339
CZ 56065	6309	" 2CZ 111446	11	CZ 60484	—
CZ 56066	—	" 2CZ 111411	8	CZ 60485	—
CZ 56067	6299	" 2CZ 108957	11	CZ 60486	—
CZ 56068	6300	" 2CZ 108924	8	CZ 60487	—
CZ 56069	6346	" 2CZ 111434	9	CZ 60488	—
CZ 56070	6349	" 2CZ 108940	9	CZ 60489	—
CZ 56071	6308	" 2CZ 111469	11	CZ 60490	—
CZ 56072	6372	" 2CZ 108973	11	CZ 60491	6331
CZ 56073	6330	" 2CZ 111225	8	CZ 60492	6318
CZ 56074	6353	" 2CZ 111440	11	CZ 60493	6332
CZ 56075	6345	" 2CZ 111423	9	CZ 60494	6333
CZ 56076	6364	" 2CZ 111458	11	CZ 60495	6335
CZ 56077	6313	" 2CZ 108913	8	CZ 60496	6334
CZ 56078	6321	" 2CZ 108949	11	CZ 60497	6336
CZ 56079	6348	" 2CZ 108932	9	CZ 60498	6359
CZ 56080	6370	" 2CZ 108965	11	CZ 60499	6371
CZ 56084	6772	" 2CZ 111230	11	CZ 60500	—
CZ 56085	6374	" 2CZ 84872	11	CZ 60501	6873
CZ 56086	6821	" 2CZ 111448	11	CZ 60502	—
CZ 56087	6387	" 2CZ 84879	11	CZ 60503	—
CZ 56088	6799	" 2CZ 111231	11	CZ 60504	—
CZ 56089	6375	" 2CZ 84873	11	CZ 60505	—
CZ 56090	6823	" 2CZ 111449	11	CZ 60506	—
CZ 56091	6388	" 2CZ 84880	11	CZ 60507	—
CZ 56092	6776	" 2CZ 111233	11	CZ 60508	6360
CZ 56093	6376	" 2CZ 84874	11	CZ 60509	6373
CZ 56094	6801	" 2CZ 111451	11	CZ 60510	—
CZ 56095	6389	" 2CZ 108959	11	CZ 60511	—
CZ 56096	6775	" 2CZ 111437	11	CZ 60512	—
CZ 56097	6377	" 2CZ 108945	11	CZ 60513	—
CZ 56098	6824	" 2CZ 111453	11	CZ 60514	—
CZ 56099	6390	" 2CZ 108961	11	CZ 60515	—
CZ 56100	6777	" 2CZ 111234	11	CZ 60516	—
CZ 56101	6379	" 2CZ 84875	11	CZ 60517	—
CZ 56102	6837	" 2CZ 111454	11	CZ 60518	—
CZ 56103	6391	" 2CZ 84881	11	CZ 60519	—
CZ 56104	6774	" 2CZ 111438	11	CZ 60520	—
CZ 56105	6380	" 2CZ 108946	11	CZ 60521	6319
CZ 56106	6831	" 2CZ 111455	11	CZ 60522	—
CZ 56107	6392	" 2CZ 108962	11	CZ 60523	—
CZ 56108	6779	" 2CZ 111298	11	CZ 60524	6365
CZ 56109	6381	" 2CZ 108947	11	CZ 60525	6354
CZ 56110	6825	" 2CZ 111456	11	CZ 60526	6357
CZ 56111	6393	" 2CZ 108963	11	CZ 60527	6355
CZ 56112	6780	" 2CZ 111235	11	CZ 60528	6366
CZ 56113	6384	" 2CZ 84876	11	CZ 60529	6356
CZ 56114	6841	" 2CZ 111460	11	CZ 60530	6367
CZ 56115	6394	" 2CZ 84882	11	CZ 60531	6368
Z 56404	—	" 2CZ 109944	15	CZ 60532	6358
Z 56405	—	" 2CZ 109945	15	CZ 60533	6369
Z 56408	6400	" 2CZ 111902	15	CZ 61467	6577
Z 56480	—	" 2CZ 109946	15	CZ 61468	6576
CZ 57115	6633	Discontinued	—	Z 61535	6312
CZ 57205	—	Replaced by 2CZ 108949	11	Z 61536	6500
CZ 57206	—	" 2CZ 108965	11	Z 61537	6405
CZ 57207	—	" 2CZ 108957	11	Z 61538	6424
CZ 57208	—	" 2CZ 108973	11	Z 61539	6425
CZ 57209	—	" 2CZ 108913	8	Z 61540	6820
CZ 57210	—	" 2CZ 108913	8	Z 61541	6301
CZ 57211	—	" 2CZ 108932	9	Z 61542	6293
CZ 57212	6422	" 2CZ 138247	10	Z 61543	6294
CZ 57213	—	" 2CZ 108924	8	Z 61544	6295
CZ 57214	—	" 2CZ 108924	8	Z 61545	6296
CZ 57215	—	" 2CZ 108940	9	Z 61546	6325
CZ 57216	6310	" 2CZ 138108	10	CZ 61565	6594
CZ 57545	—	Discontinued	—	CZ 61566	6770
CZ 57546	—	"	—	CZ 61568	6624
CZ 57709	—	Replaced by 2CZ 139881	12	CZ 61569	6478
CZ 57711	—	" 2CZ 139883	12	CZ 61570	6455
CZ 58511	6479	" 2CZ 139890	12	CZ 61571	6456
CZ 59066	—	" CZ 63842	—	CZ 61574	6682

INDEX TO PART NUMBERS OF STANDARD PLUGS AND SOCKETS

Plessey Part No.	5X/No.	Page No.	Plessey Part No.	5X/No.	Page No.							
CZ 61576	—	Replaced by 2CZ 139952	25	CZ 71784	6613	Replaced by 2CZ 108965	11
CZ 61577	—	" 2CZ 139951	25	CZ 71785	6609	" 2CZ 108966	11
CZ 61579	—	" 2CZ 139953	25	CZ 71786	6614	" 2CZ 84883	11
CZ 61580	—	" 2CZ 139954	25	CZ 71787	—	" 2CZ 108967	11
CZ 61581	—	" 2CZ 139955	25	CZ 71788	6917	" 2CZ 108968	11
CZ 62086	6285	Discontinued	—	CZ 71789	—	" 2CZ 108969	11
CZ 62422	—	Replaced by 2CZ 84873	11	CZ 71790	—	" 2CZ 108970	11
CZ 63842	—	Obsolescent/No direct alternative	—	CZ 71791	—	" 2CZ 108971	11
CZ 63843	—	Replaced by 2CZ 138240	—	CZ 71792	6930	" 2CZ 108972	11
CZ 63844	—	" 2CZ 138241	—	CZ 71793	6616	" 2CZ 84884	11
CZ 64183	6707	Obsolescent/No direct alternative	—	CZ 71794	6612	" 2CZ 108973	11
CZ 64213	—	Discontinued	—	CZ 71795	6618	" 2CZ 108974	11
CZ 64214	—	"	—	CZ 71906	6649	Obsolescent/No direct alternative	—
CZ 64370	—	Replaced by 2CZ 139882	12	CZ 73359	6608	Replaced by 2CZ 108950	11
CZ 64372	—	" 2CZ 139883	12	CZ 73360	6695	" 2CZ 108952	11
CZ 64373	—	Discontinued	—	CZ 73361	—	" 2CZ 108953	11
CZ 64517	6385	Replaced by 2CZ 84877	11	CZ 73362	—	" 2CZ 108954	11
CZ 64591	6704	Discontinued	—	CZ 73363	—	" 2CZ 108955	11
CZ 64595	6788	"	—	CZ 73647	—	" 2CZ 139906	12
CZ 64599	6705	"	—	CZ 76498	6720	" 2CZ 140052	13
CZ 64634	—	"	—	CZ 77866	—	Obsolescent/No direct alternative	—
CZ 64635	—	"	—	2CZ 83003	—	Replaced by 2CZ 139885	12
CZ 64670	—	Replaced by 2CZ 139875	12	2CZ 83004	—	" 2CZ 139880	12
CZ 64671	—	" 2CZ 139876	12	2CZ 83005	—	" 2CZ 139878	12
CZ 64770	6382	" 2CZ 108948	11	2CZ 83007	—	" 2CZ 139884	12
CZ 64771	6383	" 2CZ 108949	11	2CZ 83046	—	" 2CZ 139871	12
CZ 64772	6378	" 2CZ 108944	11	2CZ 83047	—	" 2CZ 138230	12
CZ 64773	6386	" 2CZ 108956	11	2CZ 83048	—	" 2CZ 138231	—
CZ 64855	—	Obsolescent/No direct alternative	—	2CZ 83051	—	" 2CZ 139869	12
CZ 64872	6934	Discontinued	—	2CZ 83052	—	Obsolescent/No direct alternative	—
CZ 64879	—	Obsolescent/No direct alternative	—	2CZ 83054	—	Replaced by 2CZ 139885	12
CZ 66955	6610	Replaced by 2CZ 108964	11	2CZ 83055	—	" 2CZ 139887	12
CZ 66956	—	" 2CZ 108951	11	2CZ 83056	—	" 2CZ 139886	12
CZ 67679	6575	" 2CZ 139896	12	2CZ 83223	6744	" 2CZ 139888	12
CZ 69757	—	" 2CZ 139865	12	2CZ 83224	6745	" 2CZ 139889	12
CZ 69758	—	" 2CZ 139866	12	2CZ 83340	—	" 2CZ 138231	—
CZ 69759	—	" 2CZ 139867	12	2CZ 83341	—	" *2CZ 83052	—
CZ 69760	—	" 2CZ 139875	12	2CZ 83456	—	" 2CZ 139882	12
CZ 69761	—	" 2CZ 139870	12	2CZ 83603	—	" 2CZ 139881	12
CZ 69865	6867	Obsolescent/No direct alternative	—	2CZ 83607	—	" 2CZ 139907	12
CZ 69888	—	Replaced by 2CZ 108907	8	2CZ 83662	—	" 2CZ 139877	12
CZ 70185	6470	Obsolescent/No direct alternative	—	2CZ 83851	6847	Obsolescent/No direct alternative	—
CZ 70186	6471	Replaced by 2CZ 83851	—	2CZ 84005	—	" 2CZ 138218	—
CZ 70368	—	" 2CZ 139502	39	2CZ 84006	—	" 2CZ 138219	—
CZ 70369	—	" 2CZ 139841	39	2CZ 84007	—	" 2CZ 138230	—
CZ 70839	—	" 2CZ 139908	12	2CZ 84175	—	" 2CZ 138210	—
CZ 70840	—	" 2CZ 139909	12	2CZ 84253	—	" 2CZ 138211	—
CZ 70841	—	" 2CZ 139910	12	2CZ 84254	—	" 2CZ 139874	12
CZ 70866	—	Obsolescent/No direct alternative	—	2CZ 84255	—	" 2CZ 139872	12
CZ 70868	—	"	—	2CZ 84259	—	Obsolescent/No direct alternative	—
CZ 70869	—	Replaced by 2CZ 138236	—	2CZ 84260	—	Replaced by 2CZ 138237	—
CZ 70870	—	" 2CZ 138237	—	2CZ 84261	—	" 2CZ 139873	12
CZ 70871	—	" 2CZ 138232	—	2CZ 84262	—	Replaced by 2CZ 139873	12
CZ 70872	—	" 2CZ 138233	—	2CZ 84263	—	Obsolescent/No direct alternative	—
CZ 71733	6634	...	—	2CZ 84264	—	"	"	"	—
CZ 71748	6773	Obsolescent/No direct alternative	—	2CZ 84267	—	"	"	"	—
CZ 71749	6822	Replaced by 2CZ 111436	—	2CZ 84268	—	Replaced by 2CZ 138221	—
CZ 71750	6829	" 2CZ 111439	—	2CZ 84337	—	" 2CZ 139911	12
CZ 71751	6781	" 2CZ 111236	—	2CZ 84338	—	" 2CZ 139912	12
CZ 71752	6832	" 2CZ 111296	—	2CZ 84721	—	" 2CZ 139864	12
CZ 71753	6782	" 2CZ 111445	—	2CZ 84742	—	Obsolescent/No direct alternative	—
CZ 71754	6783	" 2CZ 111238	—	2CZ 84743	—	"	"	"	—
CZ 71755	6834	" 2CZ 111446	—	2CZ 84859	6913	"	"	"	—
CZ 71756	6617	" 2CZ 108942	—	2CZ 84860	—	Replaced by 2CZ 138229	—
CZ 71757	6778	" 2CZ 111440	—	2CZ 84864	7021	9
CZ 71758	6929	" 2CZ 108943	—	2CZ 84865	7022	9
CZ 71759	6826	" 2CZ 111441	—	2CZ 84866	7025	9
CZ 71760	6798	" 2CZ 111237	—	2CZ 84867	7027	9
CZ 71761	6842	" 2CZ 111443	—	2CZ 84868	7028	9
CZ 71762	6839	" 2CZ 111444	—	2CZ 84869	7029	9
CZ 71763	6615	" 2CZ 84878	—	2CZ 84870	7030	8
CZ 71764	6611	" 2CZ 108957	—	2CZ 84871	7033	8
CZ 71765	6813	" 2CZ 111442	—	2CZ 84872	7038	11
CZ 71766	6845	" 2CZ 111447	—	2CZ 84873	7039	11
CZ 71768	6811	" 2CZ 111452	—	2CZ 84874	7128	11
CZ 71769	6830	" 2CZ 111457	—	2CZ 84875	7045	11
CZ 71770	6838	" 2CZ 111458	—	2CZ 84876	7047	11
CZ 71771	6827	" 2CZ 111459	—	2CZ 84877	7048	11
CZ 71772	6844	" 2CZ 111461	—	2CZ 84878	7049	11
CZ 71773	6833	" 2CZ 111462	—	2CZ 84879	7051	11
CZ 71774	6828	" 2CZ 111463	—	2CZ 84880	7052	11
CZ 71775	6836	" 2CZ 111464	—	2CZ 84881	7055	11
CZ 71776	6843	" 2CZ 111465	—	2CZ 84882	7057	11
CZ 71777	6840	" 2CZ 111466	—	2CZ 84883	7058	11
CZ 71778	6800	" 2CZ 111467	—	2CZ 84884	7059	11
CZ 71779	6835	" 2CZ 111469	—	2Z 84911/A	—	15
CZ 71780	6846	" 2CZ 111470	—	2Z 84911/Z	—	15
CZ 71781	6802	" 2CZ 111468	—	2Z 84911/B	—	15
CZ 71783	6851	" 2CZ 108960	—	2Z 84911/C	—	15

Only assemblies in heavy type are of current manufacture

INDEX TO PART NUMBERS OF STANDARD PLUGS AND SOCKETS

Plessey Part No.	5X/ No.	Page No.	Plessey Part No.	5X/ No.	Page No.
2Z 84911/D	—	15	2CZ 108953	—	11
2Z 84911/E	—	15	2CZ 108954	7132	11
2Z 84912/A	—	15	2CZ 108955	—	11
2Z 84912/Z	—	15	2CZ 108956	7446	11
2Z 84912/B	—	15	2CZ 108957	7335	11
2Z 84912/C	—	15	2CZ 108959	7134	11
2Z 84912/D	—	15	2CZ 108960	—	11
2Z 84912/E	—	15	2CZ 108961	7135	11
2Z 84914/A	—	15	2CZ 108962	7136	11
2Z 84914/Z	—	15	2CZ 108963	7053	11
2Z 84914/B	—	15	2CZ 108964	7137	11
2Z 84914/C	—	15	2CZ 108965	7056	11
2Z 84914/D	—	15	2CZ 108966	7054	11
2Z 84914/E	—	15	2CZ 108967	—	11
2Z 84917	—	15	2CZ 108968	7138	11
2Z 84918	—	15	2CZ 108969	—	11
2Z 84919	—	15	2CZ 108970	—	11
2Z 84920	—	15	2CZ 108971	—	11
2Z 84921	—	15	2CZ 108972	—	11
2Z 84922	—	15	2CZ 108973	—	11
2Z 84923	—	15	2CZ 108974	7449	11
2Z 84924	—	15	2Z 109905	—	15
2Z 84925	—	15	2Z 109906	—	15
2Z 84926	—	15	2Z 109907	—	15
2Z 85140/A	—	15	2Z 109908	—	15
2Z 85140/Z	—	15	2Z 109909	—	15
2Z 85140/B	—	15	2Z 109910	—	15
2Z 85140/C	—	15	2Z 109911	—	15
2Z 85140/D	—	15	2Z 109912	—	15
2Z 85140/E	—	15	2Z 109913	—	15
2CZ 85190	—	—	2Z 109914	—	15
2CZ 85191	—	—	2Z 109915	—	22
2CZ 85313	—	—	2Z 109916	—	22
2CZ 85348	—	—	2Z 109917	—	22
2CZ 85349	—	—	2Z 109918	—	22
2CZ 85350	—	—	2Z 109919	—	22
2CZ 85351	—	—	2Z 109933	—	15
2CZ 85352	—	—	2CZ 109944	—	15
2CZ 85353	—	—	2CZ 109945	—	15
2CZ 85354	—	—	2CZ 109946	—	15
2CZ 85945	7032	8	2Z 109947/A	—	15
2CZ 108905	7118	8	2Z 109947/Z	—	15
2CZ 108906	7108	8	2Z 109947/B	—	15
2CZ 108907	7050	8	2Z 109947/C	—	15
2CZ 108908	7109	8	2Z 109947/D	—	15
2CZ 108909	7110	8	2Z 109947/E	—	15
2CZ 108910	7111	8	2Z 110061/A	—	15
2CZ 108911	7112	8	2Z 110061/Z	—	15
2CZ 108912	7113	8	2Z 110061/B	—	15
2CZ 108913	7034	8	2Z 110061/C	—	15
2CZ 108914	7031	8	2Z 110061/D	—	15
2CZ 108915	7035	8	2Z 110061/E	—	15
2CZ 108916	7036	8	2CZ 110175	—	Replaced by 2CZ 109944
2CZ 108917	7114	8	2CZ 110176	—	15
2CZ 108918	7115	8	2CZ 110292	—	15
2CZ 108919	—	—	2Z 110343	—	15
2CZ 108920	—	—	2Z 110344	—	15
2CZ 108921	—	—	2Z 110345	—	15
2CZ 108922	7116	8	2Z 110346	—	15
2CZ 108923	7037	8	2Z 110347	—	15
2CZ 108924	7117	8	2Z 111184	—	15
2CZ 108925	7119	9	2Z 111186	—	15
2CZ 108926	7120	9	2Z 111188	—	15
2CZ 108927	7121	9	2Z 111189	—	15
2CZ 108928	7122	9	2Z 111190	—	15
2CZ 108929	7123	9	2Z 111191	—	15
2CZ 108930	7023	9	2Z 111196	—	22
2CZ 108931	7124	9	2Z 111197	—	15
2CZ 108932	7026	9	2CZ 111223	7139	8
2CZ 108933	7024	9	2CZ 111224	7145	8
2CZ 108934	—	—	2CZ 111225	7149	8
2CZ 108935	7125	9	2CZ 111226	7151	8
2CZ 108936	—	—	2CZ 111227	7152	8
2CZ 108937	—	—	2CZ 111228	7154	8
2CZ 108938	—	—	2CZ 111229	7159	8
2CZ 108939	—	—	2CZ 111230	7172	11
2CZ 108940	—	—	2CZ 111231	7173	11
2CZ 108941	7126	9	2CZ 111232	7174	11
2CZ 108942	—	—	2CZ 111233	7175	11
2CZ 108943	7127	11	2CZ 111234	7178	11
2CZ 108944	7044	11	2CZ 111235	7184	11
2CZ 108945	7042	11	2CZ 111236	7185	11
2CZ 108946	7129	11	2CZ 111237	7187	11
2CZ 108947	7040	11	2CZ 111238	7192	11
2CZ 108948	7043	11	2CZ 111242	—	13
2CZ 108949	7046	11	2CZ 111296	7186	11
2CZ 108950	7041	11	2CZ 111297	7153	8
2CZ 108951	7130	11	2CZ 111298	7180	11
2CZ 108952	7131	11	2CZ 111299	7147	8

Only assemblies in heavy type are of current manufacture

INDEX TO PART NUMBERS OF STANDARD PLUGS AND SOCKETS


Plessey Part No.	5X/ No.	Page No.	Plessey Part No.	5X/ No.	Page No.
2CZ 111399	7140	8	2CZ 111664	6839/B	Replaced by 2CZ 111444
2CZ 111400	7141	8	2CZ 111665	6782/B	2CZ 111445
2CZ 111401	7142	8	2CZ 111666	6783/B	2CZ 111238
2CZ 111402	7143	8	2CZ 111667	6834/B	2CZ 111446
2CZ 111403	7144	8	2CZ 111668	6845/B	2CZ 111447
2CZ 111404	7146	8	2CZ 111669	6821/B	2CZ 111448
2CZ 111405	7148	8	2CZ 111670	6823/B	2CZ 111449
2CZ 111406	7150	8	2CZ 111672	6801/B	2CZ 111451
2CZ 111407	7155	8	2CZ 111673	6811/B	2CZ 111452
2CZ 111408	7156	8	2CZ 111674	6824/B	2CZ 111453
2CZ 111409	7157	8	2CZ 111675	6837/B	2CZ 111454
2CZ 111410	7158	8	2CZ 111676	6831/B	2CZ 111455
2CZ 111411	7445	8	2CZ 111677	6825/B	2CZ 111456
2CZ 111412	7160	8	2CZ 111678	6830/B	2CZ 111457
2CZ 111413	7161	9	2CZ 111679	6838/B	2CZ 111458
2CZ 111414	7162	9	2CZ 111680	6827/B	2CZ 111459
2CZ 111415	—	9	2CZ 111681	6841/B	2CZ 111460
2CZ 111416	7163	9	2CZ 111682	6844/B	2CZ 111461
2CZ 111417	7164	9	2CZ 111683	6833/B	2CZ 111462
2CZ 111418	7165	9	2CZ 111684	6828/B	2CZ 111463
2CZ 111419	7166	9	2CZ 111685	6836/B	2CZ 111464
2CZ 111420	—	9	2CZ 111686	6843/B	2CZ 111465
2CZ 111421	—	9	2CZ 111687	6840/B	2CZ 111466
2CZ 111422	—	9	2CZ 111688	6800/B	2CZ 111467
2CZ 111423	7167	9	2CZ 111689	6802/B	2CZ 111468
2CZ 111424	—	9	2CZ 111690	6835/B	2CZ 111469
2CZ 111425	7168	9	2CZ 111691	6846/B	2CZ 111470
2CZ 111426	7169	9	2CZ 111692	6374/B	2CZ 84872
2CZ 111427	—	9	2CZ 111693	6375/B	2CZ 84873
2CZ 111428	7170	9	2CZ 111694	6929/B	2CZ 108943
2CZ 111429	—	9	2CZ 111695	6376/B	2CZ 84874
2CZ 111430	—	9	2CZ 111696	6378/B	2CZ 108944
2CZ 111431	7448	9	2CZ 111697	6377/B	2CZ 108945
2CZ 111432	—	9	2CZ 111698	6379/B	2CZ 84875
2CZ 111433	7171	9	2CZ 111699	6380/B	2CZ 108946
2CZ 111434	7377	9	2CZ 111700	6381/B	2CZ 108947
2CZ 111435	—	9	2CZ 111701	—	2CZ 108948
2CZ 111436	7176	II	2CZ 111702	—	2CZ 108949
2CZ 111437	7177	II	2CZ 111703	6608/B	2CZ 108950
2CZ 111438	7179	II	2CZ 111704	6384/B	2CZ 84876
2CZ 111439	7181	II	2CZ 111705	6385/B	2CZ 84877
2CZ 111440	7182	II	2CZ 111706	—	2CZ 108951
2CZ 111441	7183	II	2CZ 111707	6873/B	2CZ 108952
2CZ 111442	7188	II	2CZ 111708	—	2CZ 108953
2CZ 111443	7189	II	2CZ 111709	—	2CZ 108954
2CZ 111444	7190	II	2CZ 111710	—	2CZ 108955
2CZ 111445	7191	II	2CZ 111711	6386/B	2CZ 108956
2CZ 111446	—	II	2CZ 111712	6615/B	2CZ 84878
2CZ 111447	7193	II	2CZ 111713	6611/B	2CZ 108957
2CZ 111448	7194	II	2CZ 111714	6617/B	2CZ 108942
2CZ 111449	7195	II	2CZ 111715	6387/B	2CZ 84879
2CZ 111451	7197	II	2CZ 111716	6388/B	2CZ 84880
2CZ 111452	7198	II	2CZ 111718	6389/B	2CZ 108959
2CZ 111453	7199	II	2CZ 111719	6851/B	2CZ 108960
2CZ 111454	7200	II	2CZ 111720	6390/B	2CZ 108961
2CZ 111455	—	II	2CZ 111721	6391/B	2CZ 84881
2CZ 111456	7326	II	2CZ 111722	6392/B	2CZ 108962
2CZ 111457	—	II	2CZ 111723	6393/B	2CZ 108963
2CZ 111458	7201	II	2CZ 111724	6616/B	2CZ 108964
2CZ 111459	—	II	2CZ 111725	6613/B	2CZ 108965
2CZ 111460	7202	II	2CZ 111726	6609/B	2CZ 108966
2CZ 111461	7203	II	2CZ 111727	6394/B	2CZ 84882
2CZ 111462	—	II	2CZ 111728	6614/B	2CZ 84883
2CZ 111463	7204	II	2CZ 111729	—	2CZ 108967
2CZ 111464	—	II	2CZ 111730	6917/B	2CZ 108968
2CZ 111465	—	II	2CZ 111731	—	2CZ 108969
2CZ 111466	7346	II	2CZ 111732	—	2CZ 108970
2CZ 111467	7327	II	2CZ 111733	—	2CZ 108971
2CZ 111468	7205	II	2CZ 111734	6930/B	2CZ 108972
2CZ 111469	7378	II	2CZ 111735	6616/B	2CZ 84884
2CZ 111470	7450	II	2CZ 111736	6612/B	2CZ 108973
2CZ 111646	6772/B	II	2CZ 111737	6618/B	2CZ 108974
2CZ 111647	6799/B	II	2CZ 111902	—	15
2CZ 111648	6773/B	II	2CZ 138096	—	10
2CZ 111649	6776/B	II	2CZ 138097	—	10
2CZ 111650	6822/B	II	2CZ 138098	—	10
2CZ 111651	6775/B	II	2CZ 138099	—	10
2CZ 111652	6777/B	II	2CZ 138100	—	10
2CZ 111653	6774/B	II	2CZ 138101	—	10
2CZ 111654	6779/B	II	2CZ 138102	—	10
2CZ 111655	6829/B	II	2CZ 138103	—	10
2CZ 111656	6778/B	II	2CZ 138104	—	10
2CZ 111657	6826/B	II	2CZ 138105	—	10
2CZ 111658	6780/B	II	2CZ 138106	—	10
2CZ 111659	6781/B	II	2CZ 138107	—	10
2CZ 111660	6832/B	II	2CZ 138108	—	10
2CZ 111661	6798/B	II	2CZ 138109	—	10
2CZ 111662	6813/B	II	2CZ 138110	—	10
2CZ 111663	6842/B	II	2CZ 138111	—	10

Only assemblies in heavy type are of current manufacture

INDEX TO PART NUMBERS OF STANDARD PLUGS AND SOCKETS


Plessey Part No.	5X/ No.	Page No.	Plessey Part No.	5X/ No.	Page No.
2CZ 138112	—	10	2CZ 139902	—	12
2CZ 138113	—	10	2CZ 139903	—	12
2CZ 138114	—	10	2CZ 139904	—	12
2CZ 138115	—	10	2CZ 139905	—	12
2CZ 138116	—	10	2CZ 139906	—	12
2CZ 138204	—	12	2CZ 139907	—	12
2CZ 138205	—	12	2CZ 139908	—	12
2CZ 138206	—	12	2CZ 139909	—	12
2CZ 138207	—	12	2CZ 139910	—	12
2CZ 138208	—	12	2CZ 139911	—	12
2CZ 138209	—	12	2CZ 139912	—	12
2CZ 138210	—	12	2CZ 139913	—	12
2CZ 138211	—	—	2Z 139928	—	23
2CZ 138212	—	—	2Z 139929	—	23
2CZ 138213	—	—	2Z 139930	—	23
2CZ 138214	—	—	2Z 139931	—	23
2CZ 138215	—	—	2Z 139932	—	23
2CZ 138216	—	—	2Z 139933	—	23
2CZ 138217	—	—	2Z 139934/A	—	23
2CZ 138218	—	—	2Z 139934/Z	—	24
2CZ 138219	—	—	2Z 139934/B	—	24
2CZ 138220	—	—	2Z 139934/C	—	24
2CZ 138221	—	—	2Z 139934/D	—	24
2CZ 138222	—	—	2Z 139934/E	—	24
2CZ 138223	—	—	2Z 139935/A	—	24
2CZ 138224	—	—	2Z 139935/Z	—	24
2CZ 138225	5X/7232	—	2Z 139935/B	—	24
2CZ 138226	5X/7233	—	2Z 139935/C	—	24
2CZ 138227	—	—	2Z 139935/D	—	24
2CZ 138228	—	—	2Z 139935/E	—	24
2CZ 138229	—	—	2Z 139936/I	—	24
2CZ 138230	—	—	2Z 139936/2	—	24
2CZ 138231	—	—	2Z 139936/4	—	24
2CZ 138232	—	—	2Z 139936/5	—	24
2CZ 138233	—	—	2Z 139936/6	—	24
2CZ 138234	—	—	2Z 139936/9	—	24
2CZ 138235	—	—	2Z 139936/10	—	24
2CZ 138236	—	—	2Z 139936/11	—	24
2CZ 138237	—	—	2Z 139936/12	—	24
2CZ 138238	—	—	2Z 139936/14	—	24
2CZ 138239	—	—	2Z 139936/15	—	24
2CZ 138240	—	—	2Z 139937	—	24
2CZ 138241	—	—	2Z 139938	—	25
2CZ 138242	—	—	2Z 139939	—	25
2CZ 138243	—	—	2Z 139940	—	25
2CZ 138244	—	—	2Z 139941	—	25
2CZ 138245	—	—	2Z 139942	—	25
2CZ 138246	—	—	2CZ 139944	—	25
2CZ 138247	—	—	2CZ 139945	—	25
2Z 138788	—	—	2CZ 139946	—	25
2CZ 138789	—	—	2CZ 139947	—	25
2CZ 139502	—	—	2CZ 139948	—	25
2CZ 139841	—	—	2CZ 139949	—	25
2CZ 139864	—	—	2CZ 139950	—	25
2CZ 139865	—	—	2CZ 139951	—	25
2CZ 139866	—	—	2CZ 139952	—	25
2CZ 139867	—	—	2CZ 139953	—	25
2CZ 139868	—	—	2CZ 139954	—	25
2CZ 139869	—	—	2CZ 139955	—	25
2CZ 139870	—	—	2Z 139956	—	26
2CZ 139871	—	—	2Z 139957	—	26
2CZ 139872	—	—	2Z 139958	—	26
2CZ 139873	—	—	2Z 139959	—	26
2CZ 139874	—	—	2Z 139960	—	26
2CZ 139875	—	—	2Z 139961	—	26
2CZ 139876	—	—	2Z 139962	—	26
2CZ 139877	—	—	2Z 139963	—	26
2CZ 139878	—	—	2Z 139964	—	26
2CZ 139879	—	—	2Z 139965	—	26
2CZ 139880	—	—	2Z 139966	—	26
2CZ 139881	—	—	2Z 139967	—	26
2CZ 139882	—	—	2Z 139968	—	26
2CZ 139883	—	—	2Z 139969	—	26
2CZ 139884	—	—	2Z 139970	—	26
2CZ 139885	—	—	2Z 139971	—	26
2CZ 139886	—	—	2Z 139972	—	26
2CZ 139887	—	—	2Z 139973	—	26
2CZ 139888	—	—	2Z 139974	—	26
2CZ 139889	—	—	2Z 139975	—	26
2CZ 139890	—	—	2Z 139976	—	26
2CZ 139891	—	—	2Z 139977	—	26
2CZ 139892	—	—	2Z 139978	—	26
2CZ 139893	—	—	2Z 139979	—	26
2CZ 139894	—	—	2Z 139980	—	26
2CZ 139895	—	—	2Z 139981	—	26
2CZ 139896	—	—	2Z 139982	—	26
2CZ 139897	—	—	2Z 139983	—	26
2CZ 139898	—	—	2Z 139984	—	26
2CZ 139899	—	—	2Z 139985	—	26
2CZ 139900	—	—	2Z 139986	—	26
2CZ 139901	—	—	2Z 139987	—	26
	—	—	2Z 139988	—	26
	—	—	2Z 140052	—	26
	—	—	2Z 140053	—	13

Only assemblies in heavy type are of current manufacture




7

Nine 7A




8

Two 7A
Four 19A


9

Four 19A




10


Five 19A



11


Seven 7A
Two 19A

12


One 7A
Three 37A

13

Twelve 7A




14

Twelve 7A
Two 19A

15

Six 19A



16

Four 37A



CONTACT COMBINATIONS

6 SIZES AND 23 CONTACT COMBINATIONS

The diagrams on this page represent the twenty-three different contact combinations available with Standard plugs and sockets. Each combination is coded so that by reference to this page in conjunction with the appropriate tables on pages 8 to 12, full details of all assemblies may be noted. The current-carrying capacity, varying from 7 amp. to 64 amp., is indicated on each diagram. Each contact is identified by a letter or number which is clearly marked on the mouldings of plugs and sockets. Reverse sockets, one of which is necessary when using bulkhead plugs, in addition to the normal socket, are marked in reverse to ensure continuity of the coding system throughout the circuit. A reverse socket may be identified by the letter "A" on the moulding.

It will be seen from the diagrams that plug and socket shells are made in six sizes, to accommodate the various contact arrangements. These sizes must be noted when ordering accessories for plugs and sockets, such as sealing caps or ferrules, which vary with the body size but not necessarily with the contact combinations.


All plugs and sockets with contact combinations listed on this page are standard items, and are particularly recommended for use wherever possible as delivery conditions and price for special types are less favourable.

KEEP THIS PAGE OPEN FOR EASY REFERENCE

DIAGRAMS ARE ACTUAL SIZE

VIEWED FROM MATING END OF NORMAL SOCKET


STANDARD PLUGS AND SOCKETS



Z


17

Two 7A
Two 19A
Four 37A




18

Four 7A
Seven 19A
Two 37A




19

Six 7A
Two 19A
Two 37A




20

Twelve 7A
Four 19A




21

Twenty-four 7A
Two 19A



22


Four 7A
Two 64A




E

23

Twenty 7A
Four 19A
Three 37A





Products of the

Plessey

Group of Companies

The Plessey activity is divided into five main Groups, four of these being concerned with manufacturing equipment such as that listed below, the fifth, Plessey International Ltd., being concerned solely with overseas sales. The four manufacturing Groups are divided into autonomous Divisions or Associated Companies each being equipped with its own Development and Production facilities.

Aircraft and Atomic Energy Group

Actuators
Aircraft Fuel Pumps
Air Motor Rams
Atomic Detection Gear
Constant Speed Drives
Control Panels
Converters and Inverters
DC and AC Generating Systems
DC and AC Motors
FHP Motors
Health Physics Instruments
Helicopter Winches
High Temperature Screw Jacks
Instrumentation
Missile Power Packs
Nucleonic Instrumentation
Ram Air Turbines
Relays and Flashers
Resolvers
Servo Motors and Systems
Turbine Controls

Components Group

Accelerometers
Aerial Matching Units
Air and Compression Trimmers
Auto Selector Units, 12 Channel
C Core Transformers
Centring Units
Ceramic Capacitors
Ceramic Piece Parts
Cermets (High Temp. Materials)
Coils and Chokes
Contactor Coils, Solenoids
Deflector Coils
Delay Lines
Drive & Tuning Mechanisms & Knobs
Dummy Loads for Wave Guides
EHT and Scan Output Transformers
Encapsulated Windings
Ferrite Coated Inductors and
Transformers
Ferrites
Filters
Flake-iron Cores
IF Transformers
Infra-red Detectors
Insulating Materials
Interference Suppressors
Ion Traps
Iron dust cores
Lampholders
Loudspeakers
Magnetic Reactors
Memory Cores and Matrices

Output Transformers
Pick-up Cartridges
Piezoelectric Transducers
Post Office Transformers
Pulse Transformers
Radar Absorbing Materials
Relays, Standard and Miniature
Services Approved Transformers
Silicon Rectifiers
Strain Gauges
Switches and Switch Boxes
Tantalum Electrolytic Capacitors
Thermistors
Transformers
Tuners, Turret, F.M., etc.
Turret Lugs
UHF Components
Valveholders
Variable Capacitors
Vibrators
Voltage Regulating Relays
Wavewound and Toroid Coils

Electronic and Equipment Group

Aerial Exchanges
Amplifiers
Anglicisation of Electronic Equipment
Business Machines
Car Radio Receivers
Coin Collecting Boxes
Computing Equipment and
Accessories
Contents Gauges
Counting Machines
Data Transmission
Dimensional Gauges, Capacity Type
Direction Finding Equipment
Diversity Receiving Systems
Domestic Appliances
Domestic Mains and Battery Receivers
Electronic Industrial Control
Equipment
Electronic Measuring Equipment
Electronic Muting Units
Electro-optical Equipment
Frequency Synthesis Equipment
FSK Radio Equipment
Guided Weapons Electronic
Equipment
Heat Detection Devices
HF Transmitters and Receivers
High Speed Oscilloscopes
Infra-red Equipment
Line Transmission Equipment
Machine Tool Control Systems
Military Mobile Communications
Equipment

Moisture Meters
Printed Circuits
Radio-activity Survey Meters
Radiograms
Radio Teleprinter Equipment
Remote Control Equipment
Telemetry Equipment
Telephone and Telegraph Power and
Test Equipment
Telephones
Television Receivers
Terminating and Power Feeding
Equipment for Submerged Re-
peater Routes
Test Equipment
Transistorised Equipment
Transistorised Power Packs
UHF Communications Equipment
(Airborne, Ground and Shipborne)
Vehicle Communications Installations
VHF and HF Airport Ground
Equipment
VHF Communications Equipment
(Airborne and Ground)
Voltage Regulators
Wattmeters

Swindon Group

Cast Permanent Magnets
Cold Moulded Insulating Materials
Electrical Connectors and Fuse and
Terminal Blocks
Electrolytic Capacitors
Flexible Seamless Metal Hoses
Gauges, Drill Jigs and Fixtures
High Speed Tools
Hydraulic Control Valves
Hydraulic Pumps and Rams
Investment Castings
Jigs and Press Tool Sets
Loudspeaker Cones
Machined Parts and Assemblies
Metal Braiding and Flexible Conduit
Miniature Ceramic Capacitors
Moulded Fibre Products
Paper Capacitors
Potentiometers & Variable
Resistors
Powder Metallurgy Components
Precision resistive elements
Preformed Wiring
Record Changers
Refrigeration Components
Resistors
Sheet Metalwork and Presswork
SHF Connectors
Switchgear
Transistors

The design and productive capacity of the Company's main plant at Ilford, and its associate factories in other centres, are such that the organisation can offer a unique service to manufacturers in the electronic, electrical, and precision mechanical engineering fields. Literature is available on the majority of the equipment listed above, and will gladly be sent on request.

8194-4-5588

Plessey

THE PLESSEY COMPANY LIMITED

WIRING & CONNECTORS DIVISION

SWINDON GROUP

CHENEY MANOR • SWINDON • WILTSHIRE

Telephone : SWINDON 6251

Telex 44-355

Telegrams : PLESSEY TELEX SWINDON

OVERSEAS SALES ORGANISATION

PLESSEY INTERNATIONAL LIMITED

Overseas Telegrams : PLESSINTER TELEX ILFORD

Head Office : ILFORD • ESSEX • ENGLAND

Telephone : ILFORD 3040 Telex : 23166 Plessey Ilford

Telegrams : PLESSEY TELEX ILFORD