


3 contact 19 A 2 kV A.C. (peak)

aluminium

	Chloroprene	Fluorinated Silicone
Free Socket	508/1/07005/220	508/1/07005/320
Free Plug	508/1/07025/220	508/1/07025/320
Fixed Plug	508/1/07065/220	508/1/07065/320
Free Coupler Plug	508/1/07105/220	508/1/07105/320
Fixed Socket	508/1/07045/220	508/1/07045/320
Free Coupler Socket	508/1/07085/220	508/1/07085/320
Ambient temperature	-55° to +100°C	-55° to +150°C

Shell size 2



Datum keyway

brass


	Chloroprene	Fluorinated Silicone
Free Socket	508/1/07205/220	508/1/07205/320
Free Plug	508/1/07225/220	508/1/07225/320
Fixed Plug (Round Flange)	508/1/07345/220	508/1/07345/320
Fixed Plug (Square Flange)	508/1/07265/220	508/1/07265/320
Free Coupler Plug	508/1/07305/220	508/1/07305/320
Fixed Socket (Round Flange)	508/1/07325/220	508/1/07325/320
Fixed Socket (Square Flange)	508/1/07245/220	508/1/07245/320
Free Coupler Socket	508/1/07285/220	508/1/07285/320
Ambient temperature	-55° to +100°C	-55° to +150°C

4 contact 5 A 250 V A.C.

aluminium

	Patt. 104 A4	Patt. 104 A6
Free Socket	508/1/07002/220	508/1/07002/320
Free Plug	508/1/07022/220	508/1/07022/320
Fixed Plug	508/1/07062/220	508/1/07062/320
Free Coupler Plug	508/1/07102/220	508/1/07102/320
Fixed Socket	508/1/07042/220	508/1/07042/320
Free Coupler Socket	508/1/07082/220	508/1/07082/320
Ambient temperature	-55° to +100°C	-55° to +150°C

Shell size 1



Datum keyway

brass


	Patt. 104 B4	Fluorinated Silicone
Free Socket	508/1/07202/220	508/1/07202/320
Free Plug	508/1/07222/220	508/1/07222/320
Fixed Plug (Round Flange)	508/1/07342/220	508/1/07342/320
Fixed Plug (Square Flange)	508/1/07262/220	508/1/07262/320
Free Coupler Plug	508/1/07302/220	508/1/07302/320
Fixed Socket (Round Flange)	508/1/07322/220	508/1/07322/320
Fixed Socket (Square Flange)	508/1/07242/220	508/1/07242/320
Free Coupler Socket	508/1/07282/220	508/1/07282/320
Ambient temperature	-55° to +100°C	-55° to +150°C

4 contact 5 A 250 V A.C.

aluminium

	Patt. 104 A4	Patt. 104 A6
Free Socket	508/1/07006/220	508/1/07006/320
Free Plug	508/1/07026/220	508/1/07026/320
Fixed Plug	508/1/07066/220	508/1/07066/320
Free Coupler Plug	508/1/07106/220	508/1/07106/320
Fixed Socket	508/1/07046/220	508/1/07046/320
Free Coupler Socket	508/1/07086/220	508/1/07086/320
Ambient temperature	-55° to +100°C	-55° to +150°C

Shell size 2



Datum keyway

brass

	Patt. 104 B4	Fluorinated Silicone
Free Socket	508/1/07206/220	508/1/07206/320
Free Plug	508/1/07226/220	508/1/07226/320
Fixed Plug (Round Flange)	508/1/07346/220	508/1/07346/320
Fixed Plug (Square Flange)	508/1/07266/220	508/1/07266/320
Free Coupler Plug	508/1/07306/220	508/1/07306/320
Fixed Socket (Round Flange)	508/1/07326/220	508/1/07326/320
Fixed Socket (Square Flange)	508/1/07246/220	508/1/07246/320
Free Coupler Socket	508/1/07286/220	508/1/07286/320
Ambient temperature	-55° to +100°C	-55° to +150°C

To specify orientated version: replace last digit of part number with relevant position number, e.g. 508/1/07005/225 = orientation position 5.