




6 contact 5 A 500 V A.C. (peak)

aluminium

	Chloroprene	Fluorinated Silicone
Free Socket	508/1/07007/220	508/1/07007/320
Free Plug	508/1/07027/220	508/1/07027/320
Fixed Plug	508/1/07067/220	508/1/07067/320
Free Coupler Plug	508/1/07107/220	508/1/07107/320
Fixed Socket	508/1/07047/220	508/1/07047/320
Free Coupler Socket	508/1/07087/220	508/1/07087/320
Ambient temperature	-55° to +100°C	-55° to +150°C

Shell size 2



Datum keyway

brass


	Chloroprene	Fluorinated Silicone
Free Socket	508/1/07207/220	508/1/07207/320
Free Plug	508/1/07227/220	508/1/07227/320
Fixed Plug (Round Flange)	508/1/07347/220	508/1/07347/320
Fixed Plug (Square Flange)	508/1/07267/220	508/1/07267/320
Free Coupler Plug	508/1/07307/220	508/1/07307/320
Fixed Socket (Round Flange)	508/1/07327/220	508/1/07327/320
Fixed Socket (Square Flange)	508/1/07247/220	508/1/07247/320
Free Coupler Socket	508/1/07287/220	508/1/07287/320
Ambient temperature	-55° to +100°C	-55° to +150°C

6 contact 5 A 2 kV A.C. (peak)

aluminium

	Patt. 104 A4	Patt. 104 A6
Free Socket	508/1/07008/220	508/1/07008/320
Free Plug	508/1/07028/220	508/1/07028/320
Fixed Plug	508/1/07068/220	508/1/07068/320
Free Coupler Plug	508/1/07108/220	508/1/07108/320
Fixed Socket	508/1/07048/220	508/1/07048/320
Free Coupler Socket	508/1/07088/220	508/1/07088/320
Ambient temperature	-55° to +100°C	-55° to +150°C

Shell size 2



Datum keyway

brass


	Patt. 104 B4	Fluorinated Silicone
Free Socket	508/1/07208/220	508/1/07208/320
Free Plug	508/1/07228/220	508/1/07228/320
Fixed Plug (Round Flange)	508/1/07348/220	508/1/07348/320
Fixed Plug (Square Flange)	508/1/07268/220	508/1/07268/320
Free Coupler Plug	508/1/07308/220	508/1/07308/320
Fixed Socket (Round Flange)	508/1/07328/220	508/1/07328/320
Fixed Socket (Square Flange)	508/1/07248/220	508/1/07248/320
Free Coupler Socket	508/1/07288/220	508/1/07288/320
Ambient temperature	-55° to +100°C	-55° to +150°C

6 contact 19 A 2.5 kV A.C. (peak)

aluminium

	Chloroprene	Fluorinated Silicone
Free Socket	508/1/07012/220	508/1/07012/320
Free Plug	508/1/07032/220	508/1/07032/320
Fixed Plug	508/1/07072/220	508/1/07072/320
Free Coupler Plug	508/1/07112/220	508/1/07112/320
Fixed Socket	508/1/07052/220	508/1/07052/320
Free Coupler Socket	508/1/07092/220	508/1/07092/320
Ambient temperature	-55° to +100°C	-55° to +150°C

Shell size 3



Datum keyway

brass

	Patt. 104 B4	Fluorinated Silicone
Free Socket	508/1/07212/220	508/1/07212/320
Free Plug	508/1/07232/220	508/1/07232/320
Fixed Plug (Round Flange)	508/1/07352/220	508/1/07352/320
Fixed Plug (Square Flange)	508/1/07272/220	508/1/07272/320
Free Coupler Plug	508/1/07312/220	508/1/07312/320
Fixed Socket (Round Flange)	508/1/07332/220	508/1/07332/320
Fixed Socket (Square Flange)	508/1/07252/220	508/1/07252/320
Free Coupler Socket	508/1/07292/220	508/1/07292/320
Ambient temperature	-55° to +100°C	-55° to +150°C

To specify orientated version: replace last digit of part number with relevant position number, e.g. 508/1/07006/225 = orientation position 5.