




Cable entry ancillary fittings—Mk 4, Mk 7

All ancillaries for a given outlet must be selected from the same code letter as the outlet.
Individual fittings should only be ordered if no suitable outlet accessory set is available from those listed.


**Outlet gasket
(rubber)**



Code	Part No.	A dia.	B	C dia.
a b	508/2/07705/*00	·666	·375	·515
c d e f	508/2/07706/*00	·882	·375	·693
g hi	508/2/07707/*00	1·259	·375	1·073


**Sealing ring
(rubber)**

Note:
Cable passing through the bore of the sealing ring should, if necessary, be packed with adequate sleeving in order to effect a watertight seal.




Code	Part Number	A dia.	B dia.	C dia.	D	E°
a	508/2/07708/*00	·200	·320	·485	·156	156 RAD
b	508/2/07709/*00 508/2/07710/*00	·362 ·335 x ·195	·484 ·445	·558 ·520	·205 ·205	15° 15°
c	508/2/07708/*00	·200	·320	·485	·156	156 RAD
d	508/2/07709/*00 508/2/07709/*00	·362 ·362	·484 ·484	·558 ·558	·205 ·205	15° 15°
e	For cable O/D ·345—·465 508/2/07711/*00 For cable O/D ·455—·480	·400 ·400 ·455	·491 ·491	·533 ·533	·280 ·280	15° 15°
f	508/2/07712/*00 For cable O/D ·460—·550 508/2/07713/*00 For cable O/D ·515—·575	·440 ·440 ·500	·640 ·640 ·640	·715 ·715 ·715	·205 ·205 ·205	15° 15° 15°
g	508/2/07712/*00 For cable O/D ·460—·550 508/2/07713/*00 For cable O/D ·515—·575	·440 ·440 ·500	·640 ·640 ·640	·715 ·715 ·715	·205 ·205 ·205	15° 15° 15°
hi	508/2/07714/*00	·665	·805	·890	·205	15°

**Cable sleeve
(Silicone sponge rubber)**



Code	Part Number	A dia.	B dia.
a b	508/2/07715/100	·156	·503
c	508/2/07715/100	·156	·503
d e	508/2/07716/100	·312	·562
f	508/2/07717/100	·406	·687
g	508/2/07717/100	·406	·687
hi	508/2/07718/100	·562	·812

**Union gasket
(rubber)**



Code	Part Number	A dia.	B dia.	C dia.	D
a	508/2/07719/*00	·218	·345	·535	1/2"
b	508/2/07720/*00 508/2/07721/*00	·275 ·340 x ·200	·430 ·400 x ·260	·625 ·580	1/2"
c	508/2/07719/*00	·218	·345	·535	1/2"
d	508/2/07720/*00	·275	·430	·625	1/2"
e	508/2/07722/*00	·315	·477	·672	1/2"
f	508/2/07723/*00 For cable O/D ·470—·530 or ·455—·490 (Vin type cable only) 508/2/07724/*00 For cable O/D ·525—·575 or ·490—·510 (Vin type cable only)	·440 ·440 ·500	·505 ·505	·780 ·780	1/2"
g	508/2/07723/*00 For cable O/D ·470—·530 or ·470—·540 (Vin type cable only) 508/2/07724/*00 For cable O/D ·525—·575 or ·525—·560 (Vin type cable only)	·440 ·440 ·500	·505 ·505	·780 ·780	1/2"
hi	508/2/07725/*00	·670	·735	·984	1/2"

Mk 4 Connectors in all cases use—/200, viz. 508/2/07705/200.

* Note. For Mk 7 suffix digit to be inserted to indicate temperature range required.

T4= /2=Chloroprene rubber items. T6= /3=Fluorinated silicone rubber items.