

Eaton 225MMT

Catalog Number: 225MMT

Eaton Bussmann series high speed British standard fuse, Double barrel, 225A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed British standard fuse	225MMT
	UPC
	051712832571
EAN	Product Length/Depth
5027590037518	98 mm
Product Height	Product Width
40 mm	97 mm
Product Weight	Warranty
464 g	Not Applicable
Compliances	Certifications
CE Marked RoHS Compliant	IEC Rated UL Recognized Designed and tested to BS88 part 4 IEC 60269-4 UL recognized



Electrical data

Amperage Rating

225 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

350 V

Interrupt rating

200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC)

Class

Class aR

Pre arc (I2T)

3700

Clearing (I2T)

26000

Watt losses

42 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatible Trip indicator/Microswitch

Suitable for

MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Catalogs

[IEC high speed fuse links](#)

[Bussmann series complete full line catalog no. 1007](#)

Certification reports

[DA-DC-00004685](#)

[DA-DC-00004682](#)

Compliance information

[UKCA Low voltage fuse-links *AET,*AEET,*AFEE etc](#)

Specifications and datasheets

[Eaton Specification Sheet - 225MMT](#)

Technical data sheets

[720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)