


Miniature Low Voltage SECTION 11



Order Code	GE Lamp	Case Qty. BP/*Unit	Primary Application	Volts	Amps or Watts	MSCP	Bulb	Base	Filament Design	LCL	MOL	Life (hrs)	Footnotes	Figure Number
S-8 Bulbs – S.C. Bayonet														
25811	93	50	Auto	12.8	1.04A	15	S-8	S.C. Bayonet	C-6	1.12	2	700		184
37985	199	50	Truck Signal	12.8	2.25A	32	S-8	S.C. Bayonet	C-6	1.25	2	1200	117	184
26838	1073	50	Auto Signal	12.8	1.80A	32	S-8	S.C. Bayonet	C-6	1.25	2	200		184
26872	1129	10	Special Service	6.4	2.63A	21	S-8	S.C. Bayonet	C-6	1.25	2	200		184
26903	1141	50	Auto	12.8	1.44A	21	S-8	S.C. Bayonet	C-6	1.25	2	1000		184
26960	1156	50	Auto Stop	12.8	2.10A	32	S-8	S.C. Bayonet	C-6	1.25	2	1200		184
20248	1156NA	50	Auto Stop. Amber	12.8	2.10A	24	S-8	S.C. Bayonet	C-6	1.25	2	1200		184
22523	1295NA	10	Auto Signal	12.5	3.00A	37	S-8	S.C. Bayonet	C-2R	1.25	2	200		184
27472	1619	10	Instrument	6.7	1.90A	15	S-8	S.C. Bayonet	C-6	1.12	2	500		184
18047	2396	10	Auto Stop	12.8	2.23A	40	S-8	S.C. Bayonet	C-6	1.25	2	400		184
40778	P21W 24V	10	Bus Stop-European (ECE)	28	1.00A	36.6	S-8	S.C. Bayonet	C-6	1.25	2	150		184
S-8 Bulbs – S.C. Prefocused (B)														
27431	1561	10	Instrument, Colorimeter	6.3	4.00A	24	S-11	S.C. Pf. (B)	C-8Z	0.88	2.38	1500		231
T-1 ¾ Bulbs – Bi-Pin M-23														
28926	7387	50	Indicator	28	.04A	0.3	T-1 ¾	Bi-Pin M-23	C-2F	0.5	0.61	7000	113	232
T-1 ¾ Bulbs – Midget Grooved														
28662	386	50	Indicator	14	.08A	0.3	T-1 ¾	Midget Grooved	C-2F	0.38	0.63	40000	113	189
28672	388	50	Indicator	28	.04A	0.3	T-1 ¾	Midget Grooved	C-2F	0.38	0.63	7000	113	189
T-1 ¾ Bulbs – S.C. Midget Flanged														
28653	381	50	Indicator	6.3	.20A	0.4	T-1 ¾	S.C. Midget Flanged	C-2F	0.38	0.63	20000	113	188
28657	382	50	Indicator	14	.08A	0.3	T-1 ¾	S.C. Midget Flanged	C-2F	0.38	0.63	40000	113	188
28660	385	50	Indicator	28	.04A	0.15	T-1 ¾	S.C. Midget Flanged	C-2F	0.44	0.81	10000	112, 113	188
28664	387	50	Indicator	28	.04A	0.3	T-1 ¾	S.C. Midget Flanged	C-2F	0.38	0.63	7000	113	188
T-1 ¾ Bulbs – Wedge														
39220	37	50	Auto	14	.09A	0.5	T-1 ¾	Wedge	C-2F	0.4	0.8	2500		233
43606	70	50	Auto	14	.15A	1.5	T-1 ¾	Wedge	C-2F	0.4	0.8	100	103	233
39218	73	50	Indicator	14	.08A	0.3	T-1 ¾	Wedge	C-2F	0.4	0.8	15000	113	233
38457	74	50	Auto	14	.10A	0.7	T-1 ¾	Wedge	C-2F	0.4	0.8	1000		233
40969	85	50	Indicator	28	.04A	0.3	T-1 ¾	Wedge	C-2F	0.4	0.8	7000	113	233
40967	86	50	Indicator	6.3	.20A	0.4	T-1 ¾	Wedge	C-2F	0.4	0.8	20000	113, 123	233
T-2 Bulbs – Telephone Slide #3														
29001	TEL/24E2	50	Telephone	24	.035A	600	T-2	Tel. Slide #3	C-2F		1.69	7000	114	234
29041	TEL/48C2	50	Telephone	48	.035A	750	T-2	Tel. Slide #3	C-2F		1.69	5000	114	234
T-2 Bulbs – Telephone Slide #5														
12756	TEL/6PSB	50	Indicator	6	.14A	550	T-2	Tel. Slide #5	C-2V		1.11	20000	114	235
12760	TEL/12PSB	50	Indicator	12	.17A	2000	T-2	Tel. Slide #5	C-2F		1.11	12000	114	235
12071	TEL/24PSB	50	Indicator	24	.073A	3000	T-2	Tel. Slide #5	C-2F		1.11	10000	114	235
12072	TEL/28PSB	50	Indicator	28	.04A	1600	T-2	Tel. Slide #5	C-2F		1.11	5000	114	235
12075	TEL/48PSB	50	Indicator	48	.05A	1800	T-2	Tel. Slide #5	C-7A		1.11	10000	114	235
12077	TEL/60PSB	50	Indicator	60	.05A	1800	T-2	Tel. Slide #5	C-7A		1.11	7,500	114	235
12080	TEL/120PSB	50	Indicator	120	.025A	1000	T-2	Tel. Slide #5	CC-7A		1.11	7,500	114	235
T-2 ¼ Bulbs – G-4 Two Pin														
12723	774	10	Emergency Lighting	12	.67A	13	T-2 ¼	G-4 Two Pin	C-6	0.77	1	50	76, 120	170
47618	777	500	Flashlight, Halogen	4	1.20A	5.5	T-2 ¼	G-4 Two Pin	C-6	0.77	1	275	76, 120	170
44500	783	10	Emergency Lighting	12	1.00A	22	T-2 ¼	G-4 Two Pin	C-6	0.77	1	50	76, 120	170
43760	784	10	Emergency Lighting	6	1.00A	9	T-2 ¼	G-4 Two Pin	C-6	0.77	1	50	76, 120	170
43762	785	10	Emergency Lighting	6	1.33A	13	T-2 ¼	G-4 Two Pin	C-6	0.77	1	50	76, 120	170
43764	786	10	Emergency Lighting	6	2.00A	19	T-2 ¼	G-4 Two Pin	C-6	0.77	1	50	76, 120	170
43115	787	10	Instrument	6	1.67A	16	T-2 ¼	G-4 Two Pin	C-6	0.77	1	100	76, 120	170
43117	788	10	Instrument	6	3.33A	32	T-2 ¼	G-4 Two Pin	C-6	0.77	1	100	76, 120	170
18167	882X	10	Auto Inst.	12.8	.35A	3.8	T-2 ¼	G-4 Two Pin	C-6	0.77	1	2000	76, 120	170
15246	891	10	Auto High Mounted Stop	12.8	.63A	11	T-2 ¼	G-4 Two Pin	C-6	0.77	1	500	76, 120	170


Miniature Low Voltage Indicators and Illuminators

FEATURES

- Low voltage lighting offers increased strength in shock and vibration
- Compact lamps in both Incandescent and Halogen
- Safer low voltage illumination
- Sorted by bulb shape, base

APPLICATIONS

- Battery/Transformer Devices (Except Aircraft and Auto)
- Flashlights and Lanterns
- Medical, Microscopes, Other Instruments
- Emergency Lighting
- Telephone and Other Indicator Lights
- European "H" Halogen Lamps
- Coin Machines, Strip Lighting, Pinball, Toys
- Garden Lighting



Order Code	GE Lamp	Case Qty. BP/* Unit	Primary Application	Volts	Amps or Watts	MSCP	Bulb	Base	Filament Design	LCL	MOL	Life (hrs)	Footnotes	Figure Number
B-3 1/2 Bulbs – S.C. Miniature Flanged														
22961	KPR102	48*	Flashlight – 2D Krypton	2.4	.70A	1.3	B-3 1/2	S.C. Miniature Flanged	C-2R	0.25	1.25	15 118		217
23151	KPR104	48*	Flashlight – 2D Krypton	2.2	.47A	0.47	B-3 1/2	S.C. Miniature Flanged	C-2R	0.25	1.25	15 118		217
23153	KPR113	48*	Flashlight – 4D Krypton	4.8	.75A	4.1	B-3 1/2	S.C. Miniature Flanged	C-2R	0.25	1.25	20 118		217
23154	KPR118	48*	Flashlight – 6D Krypton	7.2	.55A	5.2	B-3 1/2	S.C. Miniature Flanged	C-2R	0.25	1.25	15 118		217
25181	PR2	50	Flashlight – 2D Cells	2.38	.50A	0.8	B-3 1/2	S.C. Miniature Flanged	C-2R	0.25	1.25	15 118		217
25193	PR3	50	Flashlight – 3D Cells	3.57	.50A	1.5	B-3 1/2	S.C. Miniature Flanged	C-2R	0.25	1.25	15 118		217
12677	PR4	48*	Flashlight – 2C Cells	2.33	.27A	0.4	B-3 1/2	S.C. Miniature Flanged	C-2R	0.25	1.25	10 118		217
25222	PR6	50	Flashlight – 2D Cells	2.47	.30A	0.45	B-3 1/2	S.C. Miniature Flanged	C-2R	0.25	1.25	30 118		217
25235	PR7	50	Flashlight – 3D Cells	3.7	.30A	0.9	B-3 1/2	S.C. Miniature Flanged	C-2R	0.25	1.25	30 118		217
25252	PR12	50	Flashlight – 5D Cells	5.95	.50A	3.1	B-3 1/2	S.C. Miniature Flanged	C-2R	0.25	1.25	15 118		217
25262	PR13	50	Lantern – 4F Cells	4.75	.50A	2.2	B-3 1/2	S.C. Miniature Flanged	C-2R	0.25	1.25	15 118		217
25289	PR18	50	Flashlight – 6D Cells	7.2	.55A	5.5	B-3 1/2	S.C. Miniature Flanged	C-2R	0.25	1.25	3 103, 118		217
B-6 Bulbs – D.C. Bayonet														
25988	210	50	Instrument	6.5	1.78A	15	B-6	D.C. Bayonet	C-6	1.06	1.75	100		218
26726	1004	50	Auto Interior and Marine	12.8	.94A	15	B-6	D.C. Bayonet	C-6	1.06	1.75	200		218
B-6 Bulbs – S.C. Bayonet														
36147	105	50	Auto Interior – Heavy Duty	12.8	1.00A	12	B-6	S.C. Bayonet	C-6	1.06	1.75	500		193
26709	1003	50	Auto Interior	12.8	.94A	15	B-6	S.C. Bayonet	C-6	1.06	1.75	200		193
G-3 1/2 Bulbs – Miniature Bayonet														
25529	51	50	Indicator	7.5	.22A	1	G-3 1/2	Miniature Bayonet	C-2R	0.5	0.94	1000		190
25550	53	50	Auto and Indicator	14.4	.12A	1	G-3 1/2	Miniature Bayonet	C-2V	0.5	0.94	1000		190
44719	265	50	Indicator	28	.08A	0.75	G-3 1/2	Miniature Bayonet	C-2F	0.5	0.94	5000		190
27207	1445	50	Auto / Toy Train Ratings	14.4	.135A	0.7	G-3 1/2	Miniature Bayonet	C-2V	0.5	0.94	2000 102		190
27263	1450	50	Indicator	24	.035A	0.23	G-3 1/2	Miniature Bayonet	C-2F	0.5	0.94	3000		190
G-3 1/2 Bulbs – Miniature Screw														
25331	13	50	Flashlight – 3D Cells	3.7	.30A	0.98	G-3 1/2	Miniature Screw	C-2R	0.72	0.94	15 118		219
25354	14	50	Flashlight – 2D Cells	2.47	.30A	0.5	G-3 1/2	Miniature Screw	C-2R	0.72	0.94	15 118		219
27252	1449	50	Toy Train	14	.20A	2	G-3 1/2	Miniature Screw	C-2V	0.72	0.94	250 102		219
G-3 1/2 Bulbs – Miniature Two Pin														
25312	10	50	Indicator	2.5	.50A	0.5	G-3 1/2	Miniature Two Pin	C-6	0.62	0.94	3000 110		220
25319	12	50	Radio	6.3	.15A	0.35	G-3 1/2	Miniature Two Pin	C-6	0.62	0.94	5000 108, 110		220
25377	19	50	Toy Train	14.4	.10A	0.9	G-3 1/2	Miniature Two Pin	C-6	0.62	0.94	1000 110		220
G-4 1/2 Bulbs – Miniature Bayonet														
25576	55	50	Instrument	7	.41A	2	G-4 1/2	Miniature Bayonet	C-2R	0.56	1.07	500		221
25591	57	50	Auto and Instrument	14	.24A	2	G-4 1/2	Miniature Bayonet	C-2V	0.56	1.07	500		221
32688	293	50	Auto and Radio	14	.33A	2	G-4 1/2	Miniature Bayonet	C-2F	0.56	1.07	7500		221
26441	456	50	Instrument	28	.17A	2	G-4 1/2	Miniature Bayonet	C-2F	0.56	1.07	5000		221
27945	1895	50	Auto, Truck Marker	14	.27A	2	G-4 1/2	Miniature Bayonet	C-2F	0.56	1.07	2000		221