



Main

Range of product	DF6
Device short name	DF6 AB
Fuse size	8.5 x 31.5 mm 10 x 38 mm
Product or component type	Fuse holder
Poles description	1P
Network type	AC DC
[I _{th}] conventional free air thermal current	25 A at ≤ 40 °C with aM cartridge fuses 30 A at ≤ 40 °C with gG cartridge fuses 32 A at ≤ 40 °C with tubular links
Quantity per set	Set of 12

Complementary

Network frequency	50/60 Hz
Mounting support	Rail
[U _i] rated insulation voltage	690 V
[I _{pk}] rated peak withstand current	8 kA with tubular links conforming to IEC 60269-1
Connections - terminals	Control circuit: screw terminals 1 cable 10 mm ² - cable stiffness: flexible - without cable end Control circuit: screw terminals 2 cable 6 mm ² - cable stiffness: flexible - without cable end Control circuit: screw terminals 1 cable 10 mm ² - cable stiffness: solid - without cable end Control circuit: screw terminals 2 cable 6 mm ² - cable stiffness: solid - without cable end
Tightening torque	Control circuit: 1.2 N.m - on screw terminals
Operating position	+/- 23°
Height	81 mm
Width	17.5 mm
Depth	68 mm
Product weight	0.07 kg

Environment

Standards	IEC 60947-3 NF C 61-201
Protective treatment	TC
Ambient air temperature for operation	-50...70 °C