Fuses and Fuseholders

PTF/45

Vertical mount fuseholder with bayonet cap to suit 5 x 20mm fuse. Rated 6.3 A at 250 V AC. Made from UL94 VO thermoplastic material. SEMKO and FEMKO approved.



33.1 Pin spacing 5 28.1 5 10

PTF/50

Horizontal mount fuseholder with bayonet cap to suit 5 x 20mm fuse. Rated 6.3 A at 250 V AC. Made from UL94 VO thermoplastic material. SEMKO and FEMKO approved.



PTF/30

Panel mount fuseholder with screw cap to suit 5 x 20mm fuse. Made from UL94 VO thermoplastic material. Rated 6.3 A at 250 V AC. VDE approved.



CQ-206HU

Panel mount fuseholder to suit 5 x 20mm fuse. Rated 10 A at 250 V AC. UL /CSA approved.





PTF/40

Snap-in panel mount fuseholder with screw cap to suit 5 x 20mm fuse. Rated 6.3 A at 250 V AC. Made from UL94 VO thermoplastic material. SEMKO approved.





FH-1 Non UL/CSA approved, spring in base FH-1U UL/CSA approved, spring in cap only Panel mount fuseholder with screw cap to suit $\frac{1}{4} \times 1^{\frac{1}{4}}$ fuse. Rated 10 A at 250 V AC.



T Shock-safe and waterproof versions also available - please ask.



340-267 RF Shielded/Watertight (Littelfuse)

Radio frequency shielded fuseholders eliminate possible transmission or reception of RF signals through the hole in the chassis in which the fuseholder is mounted. These fuseholders comply with the watertight construction requirement of MIL-F-19207 and the

V E COMPONENTS Auckland 0-9-443 9500 Christchurch 0-3-355 4545





Mounting Holes





