

SOLID STATE RELAY CROSS PRODUCTS

Guaranteed-for-life Opto 22 solid state relays (SSRs) can in many cases be substituted for other manufacturers' SSRs. This technical note lists part number matches and notes differences with other manufacturers' products.

If you have any questions on the list or on Opto 22 SSRs, please contact Opto 22.

Phone: 800-321-6786 (toll-free in the U.S. and Canada) or 951-695-3000

Email: systemseng@opto22.com

NOTE: Although this information is accurate to the best of our knowledge as of the document date, Opto 22 accepts no liability for the completeness or accuracy of the information nor for the consequences of any actions taken on the basis of the information provided. Please let us know if you find inaccuracies.

Cross-Reference Product List

For details on Opto 22 SSRs, see the [SSR Data Sheet, form 0859](#).

Opto 22	Crydom	Crouzet (Crydom)	Notes
120A10	A1210	--	
120A25	A1225	--	
240A10	A2410	84134001	
240A25	A2425	84134011	
240A45	A2450	84134021	Opto 22 is rated at 45 A.
120D3	--	--	No cross.
120D10	D1210	--	
120D25	D1225	--	
120D45	D1240	--	Opto 22 is rated at 45 A.
240D3	--	--	No cross.
240D10	D2410	84134000	
240Di10	D2410	84134000	Opto 22 part has LED indicator.
240D25	D2425	84134010	
240Di25	D2425	84134010	Opto 22 part has LED indicator.
240D30-HS	D2425		Opto 22 part has integrated heat sink and is rated at 30 A.
240D45	D2450	84134020	Opto 22 is rated at 45 A.
240Di45	D2450	84134020	Opto 22 part has LED indicator and is rated at 45 A.
380D25	--	--	No cross.*
380D45	--	--	No cross.*
480D10-12	HD4812	--	
480D15-12	--	--	
480D25-12	HD4825	--	
480D25-HS	HD4825	--	Opto 22 has an integrated heatsink.
480D45-12	HD4850	--	Opto 22 part is rated at 45 A.
575D15-12	--	84134100	Opto 22 operating voltage is 100-600 VAC, rated at 15 A.
575D45-12	HD6025	84134120	Opto 22 operating voltage is 100-600 VAC, rated at 45 A.

Opto 22	Crydom	Crouzet (Crydom)	Notes
575D30-HS	HD6025	84134110	Opto 22 part has integrated heatsink, operating voltage 100-600 VAC, rated at 30 A.
575Di45-12	HD6050	--	Opto 22 has LED indicator, operating voltage 100-600 VAC, rated at 45 A.
MP120D2	--	--	No cross.
MP120D4	MP120D3	GA8-6B02	
MP240D2	--	GA8-6B02	
MP240D4	MP240D3	GA8-6B02	
MP380D4	MCX380D5	--	Opto 22 is rated at 4 A.
P120D2	--	GA1-6B02	
P120D4	--	GA1-6B02	
P240D2	--	GA1-6B02	
P240D4	--	GA1-6B02	
Z120D10	EZ240D12	--	Opto 22 is rated at 10 A.
Z240D10	EZ240D12	--	Opto 22 is rated at 10 A.
DC60P	--	--	No cross.
DC60MP	MPDCD3, MODC5	--	
DC200P	--	--	No cross.
DC200MP	MODC5A	--	
DC60S3	DC60S3	--	Opto 22 is rated at 3 A.
DC60S5	DC60S5	84134750	Opto 22 is rated at 5 A.
* If your distributor is temporarily out of stock on Opto 22 380D25 or 380D45, you can substitute Opto 22 480D25-12 or 480D45-12.			