Assembly Instructions Type 122 1.2 Meter Class I Antenna System with Precision Az/El Cap Mount





RavenSkyware 1315 Industrial Park Drive Smithfield, NC 27577 Telephone: +1-919-934-9711

Internet: www.raven.co.uk

Printed in China 07/09 8001025-01 Rev C

MANUAL REVISION HISTORY

DATE	DESCRIPTION	REVISION
4/09	5080545	Rev A
6/09		Rev B
7/09	574	Rev C

WARNINGS

LAW: Installation and installer must meet local codes and ordinances regarding safety! Installation of this product should be performed only by a professional installer and is not recommended for consumer Do-It-Yourself installations.

DANGER: WATCH FOR WIRES! Installation of this product near power lines is extremely dangerous and must never be attempted. Installation of this product near power lines can result in death or serious injury! For your own safety, you must follow these important safety rules. Failure to follow these rules could result in death or serious injury

- 1. Perform as many functions as possible on the ground
- 2. Watch out for overhead power lines. Check the distance to the power lines before starting installation. Stay at least 6 meters (20 feet) away from all power lines.
- 3. Do not install antenna or mast assembly on a windy day.
- 4. If you start to drop antenna or mast assembly, move away from it and let it fall.
- 5. If any part of the antenna or mast assembly comes in contact with a power line, call your local power company. DO NOT TRY TO REMOVE IT YOURSELF! They will remove it safely.
- 6. Make sure that the mast assembly is properly grounded.

WARNING: Assembling dish antennas on windy days is extremely dangerous and must never be attempted. Due to the surface area of the reflector, even slight winds create strong forces. For example, this antenna facing a wind of 32 km/h (20 mph) can undergo forces of 269 N (60 lb). BE PREPARED TO SAFELY HANDLE THESE FORCES AT UNEXPECTED MOMENTS. ATTEMPTING TO ASSEMBLE, MOVE OR MOUNT A DISH ON WINDY DAYS COULD RESULT IN DEATH OR SERIOUS INJURY. Raven is not responsible or liable for damage or injury resulting from antenna installations.

WARNING: Antennas improperly installed or installed to an inadequate structure are very susceptible to wind damage. This damage can be very serious or even life threatening. The owner and installer assumes full responsibility that the installation is structurally sound to support all loads (weight, wind and ice) and properly sealed against leaks. Raven will not accept liability for any damage caused by a satellite system due to the many unknown variable applications.

PRE INSTALLATION CONSIDERATIONS

TOOLS REQUIRED:

Compass13 mm Deep Socket (3/8" Drive)Clinometer#1 or #2 Phillips Screwdriver3/8" Drive Ratchet Wrench13 mm Combination Wrench

10 mm Nut Driver 10 mm Socket (3/8" Drive) 10 mm Combination Wrench Torque Wrench 9″ Magnetic Level

ADDITIONAL INSTALLATION MATERIALS (Not Included with Antenna System)

Installation Mount (Ground Pole, King Post, Wall Mount or Roof Mount) Grounding Rod, Clamp & Grounding Block - As required by National Electric Code or local codes. Ground Wire - #10 solid copper or #8 aluminum as required by National Electric Code or local codes (length as required). RG-6 Coaxial Cables from antenna to indoor units. Concrete: See "Ground Pole" section for quantity M10 or #3 Rebar: See "Ground Pole" section for quantity. Deformed steel per ASTM A615, Grade 40 or 60.



DO NOT DISCARD CONTENTS

The product in this packaging was placed in the market after August 13, 2005. Its components must not be discarded with normal municipal or household waste.

Contact your local waste disposal agency for recovery, recycling, or disposal instructions.

SITE SELECTION

The first and most important consideration when choosing a prospective antenna site is whether or not the area can provide an acceptable "look angle" at the satellites. A site with a clear, unobstructed view is preferred. Also consider any obstruction that may occur in the future such as the growth of trees. Your antenna site must be selected in advance so that you will be able to receive the strongest signal available. To avoid obstructions, etc., conduct an on-site survey with a portable antenna. The satellite antenna can be installed on a ground pole, wall/ roof mount, or non-penetrating roof mount with 2-7/8" or 3" outside diameter mast. The chosen mount type should be assembled and in place before installing the antenna. Refer to instructions packed with mount for its proper installation. The mast pipe must be vertical and plumb to insure ease of alignment.

As with any other type of construction, a local building permit may be required before installing an antenna. It is the property owner's responsibility to obtain any and all permits.

Before any digging is done, information regarding the possibility of underground telephone lines, power lines, storm drains, etc., in the excavation area should be obtained from the appropriate agency.

Because soils vary widely in composition and load capacity, consult a local professional engineer to determine the appropriate foundation design and installation procedure. A suggested foundation design with conditions noted is included in this manual for reference purposes only.

GROUND POLE INSTALLATION



		Pier Foundations			De					
		EXPOSURE B		EXPOSURE C		EXPO	EXPOSURE B		EXPOSURE C	
	WIND VEL km/h (mph)	DIME D cm (in)	CONC VOL m ³ (ft ³)	DIM D cm (in)	CONC VOL m ³ (ft ³)	DIM D cm (in)	CONC VOL m ³ (ft ³)	DIM D cm (in)	${ m CONC} \ { m VOL} \ { m m}^3 \ ({ m ft}^3)$	GROUND POLE
1.2 m Antenna	161 (100)	30 (12)	0.08 (2.9)	46 (18)	0.18 (6.5)	20 (8)	0.05 (1.6)	33 (13)	0.12 (4.2)	A ,B or C
	201 (125)	43 (17)	0.17 (5.9)	61 (24)	0.33 (11.5)	30 (12)	0.10 (3.6)	48 (19)	0.25 (9.0)	С

POLE SPECIFICATIONS:

 Ground Pole "A"
 2

 Ground Pole "B"
 3.0

 Ground Pole "C"
 2

2-1/2 Schedule 40 Steel ASTM A53 Pipe (73 mm x 5 mm Wall/2.88" OD x .203" Wall) 3.0" OD x 9 Gauge (.148" Wall) Steel ASTM A501 Pipe (76 mm OD x 3.8 mm Wall) 2-1/2 Schedule 80 Steel ASTM A53 Pipe (73 mm x 7 mm Wall/2.88" OD x .276" Wall)

NOTE:

- 1. Poles are not supplied (purchase locally to above specifications) and must be field drilled 5/8" diameter for M10 #3 rebar, drilled 5.55 mm
 - (.218") for 1/4-20 self tapping grounding screw and galvanized or painted for protection.
- 2. Pole and foundation design based on the following criteria:
 - a. Uniform building code Exposure B or C wind loading.
 - b. Vertical soil pressure of 13790 kPa (2000 pounds per square foot).
 - c. Lateral soil pressure of 2758 kPa (400 pounds per square foot).
 - d. Concrete compressive strength of 17.2 MPa (2500 pounds per square inch) in 28 days.
- 3. See page 6 for grounding recommendations.

CAUTION: The foundation design shown does not represent an appropriate design for any specific locality. Soil conditions vary and may not meet design criteria given in Note 2. Consult a local professional engineer to determine your soil conditions and appropriate foundation.

ASSEMBLY AND INSTALLATION

Installing Az/El Cap Mount Onto Pole

The az/el cap is factory pre assembled. No assembly is required. Before installing az/el cap onto pole, installation mount should be in place. Loosen (3) az/el locking nuts on pipe clamp. Install az/el cap onto pole. If using 2 7/8" ground pole, ensure that the inner sleeve is inserted and that the open side is aligned with the open side of the pipe clamp (see Bottom View). If using 3.00" ground pole, remove inner sleeve on pipe clamp and discard it. Position the az/el cap in approximate azimuth setting and equally tighten (3) clamp nuts so that cap is held stationary on pole, but can be swiveled with slight pressure. Tighten to approximately 2.7 N-m (2 ft-lb).



Back View

Bottom View

ANTENNA ALIGNMENT PROCEDURE

Satellite Alignment

Alignment with the satellite is obtained by setting polarization, elevation, and azimuth. Charts are provided in this manual to determine the values for your earth station antenna site. "\(\DL'') is the difference between the earth station antenna site longitude and the satellite longitude. Use "\DL" and your earth station latitude to obtain polarization, elevation or azimuth setting.

Polarization of Feed

Refer to instructions packed with feed assembly.



Elevation - Initial Setting

Use Chart 2 and determine your elevation setting. Loosen elevation locking bolts, located in curved slots, on both sides. Turn elevation adjustment bolt clockwise to decrease elevation or counterclockwise to increase elevation. Position the elevation alignment arrow with the appropriate mark on the housing at the desired elevation reading. Scale is in 1 degree increments. This will be an approximate setting. Snug tighten elevation locking bolts. (Finger tighten only).

Azimuth - Initial Setting

Refer to the azimuth value determined on chart 3. Values in chart must be adjusted for magnetic deviation for your location for correct compass reading. Rotate the reflector and az/el mount, on the pipe, pointing it to the compass reading for your location and satellite. Sweep in azimuth for signal. If desired signal is not located, increase or decrease elevation setting and repeat the azimuth sweep. Tighten progressively (1/8 turn each) all three pipe clamp nuts. Repeat until 24 N-m (18 ft-lb) torque is reached.



(Azimuth ± Magnetic Deviation)



Elevation and Azimuth Fine Tuning

Loosen (3) azimuth locking nuts. Note that the square nuts are factory preset, and should not be loosened or

tightened. Turn the azimuth fine tune bolt clockwise or counterclockwise for azimuth fine tuning.

Use a signal strength measuring device to obtain the most accurate alignment and maximum antenna performance. Alternate between elevation and azimuth fine tuning to reach maximum signal strength, until no improvement can be detected. Tighten and torque all hardware, alternating sequence, until all bolts are equally torqued to 24 N-m (18 ft-lb).

GROUNDING PROCEDURE



SURVIVAL WIND LOAD CHARTS



1.2 m Antenna Survival Wind Loads at 125 mph Velocity

Elevation Degrees		Force N (Pounds)				Moments N-m (Foot-Pounds)				
Mech.	Beam	F _H		F,	FV		MT		Mo	
0	17	5,716	(1,285)	-156	(-35)	678	(500)		5401	(3,991)
10	27	5,413	(1,217)	-1,143	(-257)	662	(488)		5115	(3,780)
20	37	5,258	(1,182)	-2,211	(-497)	629	(464)		4969	(3,672)
30	47	4,764	(1,071)	-3,163	(-711)	571	(421)		4501	(3,326)
40	57	4,195	(943)	-3,812	(-857)	484	(357)		3964	(2,929)
50	67	3,656	(822)	-4,195	(-943)	405	(299)		3455	(2,553)
60	77	3,051	(686)	-4,381	(-985)	315	(232)		2883	(2,130)
70	87	2,291	(515)	-3,390	(-762)	241	(178)		2585	(1,910)

Mo based on 945 mm (37.2 in) from mounting surface of center line of antenna. Values shown represent maximum forces for any wind direction and include 1.5 **Fs**. Height and exposure factors from uniform building code are NOT included. Center line based on 36" max. height of mounting post.

POLARIZATION CHART





AZIMUTH CHART



EARTH STATION ANTENNA AZIMUTH IN DEGREES

" \bigtriangleup " is the difference between the earth station antenna site longitude and the satellite longitude