



Type 122: 1.2m Rx/Tx Class I Antenna System



- ISO 9001:2008 Certificate of Registration
- All materials comply with EU Directive No. 2002/95/EC (RoHS).
- One-piece precision offset thermoset-molded reflector.
- Available with Ku-band co-pol or cross-pol feeds.
- Galvanized 19 mm (.75 in) O.D. feed support legs for lightweight outdoor units (ODU's).
- Plated hardware for maximum corrosion resistance.
- Az/El mount includes both elevation and azimuth fine adjustments.
- Class I system designed for typical lightweight Ku-band RF Electronics.*
- Marineised version option is finished in a 2-part Epoxy paint on all 316 stainless steel hardware and galvanised steel fabricated components.

* 2.0 kg or 4.5 lb max. weight (For BUC and LNB) 2.2 kg or 4.8 lb max. weight (For Transceiver)



The **Skyware Global 1.2m Rx/Tx Class I Antenna** is a rugged commercial grade product suitable for the most demanding applications.

- The reflector is thermoset-molded for strength and surface accuracy. Molded into the rear of the reflector is a network of support ribs which not only strengthens the antenna, but also helps to sustain the critical parabolic shape necessary for transmit performance.
- The precision Az/El mount is constructed from heavy-gauge steel to provide a rigid support to the reflector.
- The Az/El mount secures the antenna to any 73-76 mm (2.88"-3.00") mast and prevents slippage in high winds.
- A specially formulated powder paint process offers excellent protection from weather-related corrosion.
- The antenna features a unique feed which provides cross-pol performance that exceeds industry standards.

Satcom solutions for the long haul

REV 03/15-03
Page 1 of 2

1315 Outlet Center Drive, Smithfield, NC 27577 T + 1 919 934 9711 F + 1 919 989 2274 Sales @ Skyware Global.com

All designs, specification and availabilities of products and services presented in this bulletin are subject to change without notice. ©2015 Skyware Global

•PRODUCT SPECIFICATIONS

Type Approval Information

Antenna Model62-1225401/02

(See Our Website for a Complete List of Type Approvals)

RF Performance

Effective Aperture1.2m (48 in)

Operating Frequency

TX 13.75-14.50GHz

RX 10.70-12.75GHz

Polarization Linear, Orthogonal
(Co-Pol Optional)

Gain (± 0.3 dB)

TX 43.3 dBi @ 14.3GHz

RX 41.8 dBi @ 12.0GHz

3 dB Beamwidth

TX 1.2° @ 14.3GHz

RX 1.5° @ 12.0GHz

Sidelobe Envelope (Tx, Co-Pol dBi)

Mainbeam $< \theta < 20^\circ$ $29-25 \log \theta$ dBi

$20^\circ < \theta < 26.3^\circ$ -3.5 dBi

$26.3^\circ < \theta < 48^\circ$ $32-25 \log \theta$ dBi

$48^\circ < \theta < 180^\circ$ -10

Antenna Cross-Polarization. 30 db in 1 dB
Contour

Antenna Noise Temperature

10° EL 48°K

20° EL 35°K

30° EL 29°K

VSWR

TX 1.3:1

RX 1.5:1

Isolation (Port to Port)

TX 90db

RX 40db

Feed Interface

TX WR75 Flat Flange

RX WR75 Flat Flange

(All specifications typical)

1.2 m Rx/Tx Class I Antenna

Mechanical Performance

Reflector Material. Glass Fiber Reinforced Polyester

Antenna Optics One-Piece Offset Feed Prime Focus

Mount Type Elevation over Azimuth

Elevation Adjustment Range 8° - 90° Continuous
Fine Adjustment

Azimuth Adjustment Range 360° Continuous
 $\pm 5^\circ$ Fine Adjustment

Mast Pipe Interface. 73-76mm (2.88in-3.00in)
Diameter

Enviromental Performance

Wind Loading

Operational. 45mph (72km/h)

Functional Survival. 80mph (128km/h)

Ultimate Survival 125mph (200km/h)

Operational Temperature. -40°C to $+60^\circ\text{C}$

Survival Temperature. -50°C to $+80^\circ\text{C}$

Humidity. 0 to 100% (Condensing)


Atmosphere. Standard Hardware 500 Hrs

SST Requirements (ASTM B-117)

..... Marineised Option has AISI
316 Stainless Steel Hardware

Solar Radiation 360 BTU/h/ft²

Shock and Vibration. As Encountered during
Shipping and handling



REV 03/15-03

Page 2 of 2

Satcom solutions for the long haul

1315 Outlet Center Drive, Smithfield, NC 27577 T + 1 919 934 9711 F + 1 919 989 2274 Sales @ Skyware Global.com

All designs, specification and availabilities of products and services presented in this bulletin are subject to change without notice. ©2015 Skyware Global