PRODUCT AESTHETICS

- 1.2m flex and plug
- Single colours available in 3000K or 4000K
- 60° beam angle with 30° adjustable head

Key Sellers

| Wattage | 7W | 10W |
|---------|-----------------|------------------|
| Model | LDVDLGIM7W840G2 | LDVDLGIM10W840G2 |
| Lumens | 630 | 920 |
| Lm/W | 90 | 90 |
| ССТ | 4000K | 4000K |



AVAILABLE SIZES



7W Cut out 70mm, H 64.5mm, D 85mm




10W Cut out 92mm, H 71.5mm, D 105mm

TECHNICAL INFORMATION

Photometrics

(Example of LDVDLGIM10W840G2)



Single colour

Available in 3000K and 4000K

Applications

Residential or commercial use (indoor only)

High performance

Up to 80lm/W with 5-years warranty

Adjustable

Gimble frame for directional lighting

Lifetime

50,000hr lifetime (L70/25°)









| Wattage | 7W | 10W |
|-----------------------|-----------------|------------------|
| Key Model | LDVDLGIM7W840G2 | LDVDLGIM10W840G2 |
| Lumens | 630 | 920 |
| Lm/W | 90 | 90 |
| CCT | 4000K | 4000K |
| IP . | 40 | 40 |
| CRI | 80 | 80 |
| Lifetime (ta at 25°) | 30000 | 30000 |
| Operating temperature | -20+45 °C | -20+45 °C |
| Beam angle | 60 | 60 |
| Diameter | 85 | 105 |
| Cutout | 70 | 92 |
| Height | 64.5 | 71.5 |
| Weight | 220 | 280 |
| Finish | White | White |
| PF | 0.9 | 0.9 |
| Housing Material | PC | PC |
| Warranty | 5 years | 5 years |

