



CHEROKEE INTERNATIONAL

"The Powerful Choice"

QT24 Series

*150 Watt Switching Regulated
Single & Multiple Output Power Supplies*

Features

- ◆ UL Recognized to UL 1950
- ◆ CSA Certified to C22.2 No. 234-950
- ◆ Fully compliant with FCC and VDD (Level B) Standards for EMI
- ◆ Meets IEEE 578 for input transients
- ◆ Auto range 85-264VAC
- ◆ Input surge current limit
- ◆ Brown out protected
- ◆ Overload Protection
- ◆ Overvoltage protected
- ◆ Low output noise
- ◆ Isolated output



150 Watts

Specifications

AC INPUT: 115/230VAC, Single phase jumper selectable. Optional Auto Range 90-264VAC, 47-63Hz.

DC OUTPUT: V1 $\pm 5\%$, all other outputs tack V1

REGULATION: Combination of line, load, and cross. V1, V3, & V4 = $\pm 5\%$, V2 = $\pm 10\%$, V1 = $\pm 2\%$ on Single Output Model.

RIPPLE/NOISE: Less than 1% Pk-Pk (BW 20 MHz)

TRANSIENT RESPONSE: Deviation on all output is $\pm 2\%$ with a 25% load step at 5A/msec slew rate.

TEMPERATURE COEFFICIENT: $\pm 2\%$ / $^{\circ}\text{C}$ for all outputs

TEMPERATURE RANGE: Operation 0°C at rated output power of 150 Watts with 25CFM air provided. (100 Watts Convection) Storage: -55 to $+85^{\circ}\text{C}$.

EFFICIENCY: 75% typical @ full rated load, nominal line.

INRUSH CURRENT: 35 Amps maximum

OVERLOAD PROTECTION: Total primary power limit set at 200 Watts.

OVERVOLTAGE: Set at 120% ($\pm 5\%$) V1 only.

HOLD-UP TIME: 16 ms after loss of nominal AC input

FUSING (F-1): 4A, 250VAC 5MF type.

EMI: FCC and VDE Level "B".

POWER FAIL (Good): Power applied: Output "LOW" until all outputs are in regulation. Power lost: After 1 cycle ridethrough (16 ms min.) output goes "LOW" 2.0 ms min. before loss of regulation.

HIPOT: Input to Output & Input to Chassis rated for 2600VDC for one (1) second.

MINIMUM CURRENT: A 20% minimum load is required on multi-output models. Single output models do not require a minimum load.




MECHANICAL OUTLINE: L: 6.8" (172.72mm); W: 3.8" (96.52mm); H: 1.5" (38.1mm).

SHOCK/VIBRATION: Per MIL-STD-810C; Vibration: Method 514.2 Proc. X.X1; Shock: Method 512.2, Proc. L, III; Shock (Transit): Method 516.2 Proc. LI.

Weight: 1.3 lbs. (0.61 Kg.)

Note: All specifications subject to change without notice.

Outline/Mounting/Interface



J1	PCB CONNECTOR	MATING CONNECTOR
AMP	640445-5	640426-5
PANDUIT	HLSS-156-5	CE 156F20-5
J2		
AMP	1-640445-5	1-640426-5
MOLEX	09-74-1151	09-50-3151
PANDUIT	HLSS-156-15	CE 156F20-15
J3		
AMP	640456-2	640440-2
PANDUIT	HLSS-100-2	CE 100F22-2-D

Output Specifications

QT24 Voltage/Current Combinations								
MODEL NUMBER	OUTPUT 1		OUTPUT 2		OUTPUT 3		OUTPUT 4	
	Volts	Amps	Volts	Amps	Volts	Amps	Volts	Amps
QT24A1	+5	15	-5	1	-12	1	+12	5
QT24B1	+5	15	-5	1	-24	1	+24	3
QT24C1	+5	15	-5	1	-15	1	+15	4
QT24D1	+5	15	-	-	12	1	+12	6 (8)
QT24E1	+5	15	-	-	-	-	+12	6 (8)
QT21E2V	+5	24					+12	2
QT24F1	+5	30	-	-	-	-		
QT24G1	+12	12	-	-	-	-		
QT24H1	+15	10	-	-	-	-		
QT24I1	+24	7	-	-	-	-		

070199 REV.A