

Océ|3045 specifications



Versatile office copier

Top of its class for awards and performance





Printing for Professionals

For Océ
information
and services,
visit us at
www.oce.com

Océ enables people to share information by offering products and services for the reproduction, presentation, distribution and management of documents.

With headquarters in the Netherlands, the Océ Group is active in approximately 80 countries, with subsidiaries in some 30 countries.

Océ employs 20,000 people worldwide. Annual revenue in 1999 exceeded US \$3 billion.

Océ 3045 Technical Specifications

Basic features

<i>Copy speed</i>	45 copies per minute: A4 27 copies per minute: A3
<i>Warm-up time</i>	10 minutes
<i>First copy time</i>	9.5 seconds
<i>Selection</i>	1 - 999
<i>Original handling</i>	
<i>RDF</i>	A4: 60 - 120 g/m ² Capacity: up to 70 sheets (80 g/m ²)
<i>SADF</i>	Minimum: A5 Maximum: A3 Weight: 50 - 200 g/m ²
<i>Glass platen</i>	Maximum: A3 Maximum weight: 10 kg
<i>Copy materials</i>	
<i>Copy size</i>	Minimum: A5 Maximum: A3
<i>Copy material weight</i>	Paper: 65 to 120 g/m ² Covers, inserts and dividers: 65 to 170 g/m ² Bypass: 50 to 200 g/m ²
<i>Paper capacity</i>	Trays 1, 2 & 3: 500 sheets (80 g/m ²) Tray 4: 1,600 sheets (80 g/m ²)
<i>Double-sided copying</i>	Fully automatic, one-pass duplex system with unlimited copying: ■ single-sided to double-sided ■ double-sided to double-sided ■ double-sided to single-sided
<i>Zoom</i>	Variable reduction/enlargement from 64% to 141% in 1% increments. Automatic reduction/enlargement selection when using the SADF
<i>Finishing</i>	On-line automatic stapling with one staple in the top left-hand corner Maximum: 35 sheets (80 g/m ²) Off-line stapling facility

Standard features

Recirculating Document Feeder with flat feed and air separation
Semi-automatic Document Feeder with automatic paper size selection/zoom
Automatic paper tray switching
Automatic exposure control
Covers, sheet insertion, appendix
Image shift
Priority copy (interrupt)
Photo mode
Split page/book copying
Full job and error recovery
Energy save mode
Auto power off
Unlimited sorting with continuous unloading
Internal Copy Control System (200 accounts)
PIN-code access for authorised users


Optional features

ICCS printer interface
Copy control device/coin box interface
Department counter
Locks for paper and toner compartments
On/off key switch

Specifications

<i>Dimensions</i>	1,750 mm (W) × 870 mm (D) × 1,280 mm(H)
<i>Weight</i>	380 kg
<i>Electrical requirements</i>	230V, 50 Hz, 10 or 14A 240V, 50 Hz, 13A 120/240V, 60 Hz, 20A
<i>Power consumption</i>	500 W (standby) 1900 W (in operation)
<i>Noise level</i>	50 dB(A) (standby) 69 dB(A) (in operation)
<i>Ozone concentration</i>	0.0005 mg/m ³ (Threshold Limit: 0.2 mg/m ³)

Energy Star compliant



Océ-Technologies B.V.

Designed for Recycling



Venlo, the Netherlands