

# HD-CVI-TVI Coaxial camera

|                               |                                                                                                                 |      |      |                   |      |      |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------|------|------|-------------------|------|------|
| Image Sensor                  | 1/3" Mega Pixel CMOS SONY                                                                                       |      |      |                   |      |      |
| Effective pixels              | 1280(H) X 720(V)                                                                                                |      |      | 1920(H) X 1080(V) |      |      |
| Lens focal length             | 2.8~16MM optional                                                                                               |      |      |                   |      |      |
| Pixel                         | 100W                                                                                                            | 130W | 200W | 300W              | 400W | 500W |
| Minimum Illumination          | 0.1Lux/F1.2 (color) 0Lux (black and white)(IR ON)                                                               |      |      |                   |      |      |
| Video standard                | Follow the HDCVI and CVBS standards                                                                             |      |      |                   |      |      |
| Day and night conversion mode | ICR Double filter automatic switching                                                                           |      |      |                   |      |      |
| Video frame rate              | 1920X 1080@25fps; 1920X 1080@30fps;<br>1280X 720@25 fps; 1280X 720@30fps;<br>1280X 720@50 fps; 1280X 720@60fps; |      |      |                   |      |      |
| Maximum transmission distance | Using twisted pair or 75-3 above video transmission, distance can reach 500 meters                              |      |      |                   |      |      |
| S/N Ratio                     | Greater than 52dB                                                                                               |      |      |                   |      |      |
| Back light compensation       | ON/OFF                                                                                                          |      |      |                   |      |      |
| Synchronization               | Internal synchronization                                                                                        |      |      |                   |      |      |
| White balance                 | Automatic                                                                                                       |      |      |                   |      |      |
| Video Output                  | 1 way HDCVI HD BNC output                                                                                       |      |      |                   |      |      |
| Power input                   | DC 12V                                                                                                          |      |      |                   |      |      |
| Power consumption             | Less than 2W                                                                                                    |      |      |                   |      |      |
| Operating temperature         | -10℃~50℃ (14 ℉~122 ℉)                                                                                           |      |      |                   |      |      |
| Operating Humidity            | Less than 85%                                                                                                   |      |      |                   |      |      |