

ICP-CP508W LED Codepad

www.boschsecurity.com



BOSCH

Invented for life



- ▶ Single button arming of alarm system
- ▶ Fire, medical and panic alarms
- ▶ Stylish and modern design with a protective door
- ▶ Easy to use
- ▶ Backlit buttons for illuminated operation during day or night

The ICP-CP500AW is an eight-zone LED codepad that is compatible with certain Solution Series control panels. LEDs make system conditions easy to read. Zone status is indicated numerically across the top of the screen.

The codepad notifies you when a zone is unsealed, when there has been an alarm and in which zone the alarm has occurred.

Also included are a number of single button functions that allow a user to perform various system operations by simply holding down a button for 2 sec. For example, holding the [#AWAY] key arms the system, holding the [1] key tests the sirens, and holding the [3] key tests the strobe lights.

Functions

Arming Methods

You can arm the system by entering your User code and pressing the [#AWAY] key, or quick arm the system by holding down the [#AWAY] key for 2 sec.

Fire, Medical and Panic Alarms

If programmed to do so, simultaneously pressing the outside buttons of a row on any codepad triggers an audible alarm, and an alarm report is sent to the control panel. Press [4] and [6] simultaneously for a

fire alarm; press [7] and [9] simultaneously for a medical alarm; and press [1] and [3] or [*STAY] and [#AWAY] simultaneously for a panic alarm.

Certifications and approvals

The ICP-CP508W has been tested to the following standards:

Region	Standards	
Australia	A-tick	
New Zealand	Tele-permit	PTC-200
Europe	CE	EMC: EN 55022, EN 55024 Safety: EN 60950 Telecom: TBR21 Environment: EN 50130-4, EN 61000-3-2, EN 61000-3-3

Region	Certification	
Europe	CE	2004/108/EC EMC Directive (EMC); 2006/95/EC Low-voltage Directive (LVD) [ICP-CP500PW][ICP-CP508W] [ICP-CP508LW][ICP-CP516LW][ICP-CP516W][ICP-CP500AW]ICP-CP500ALW]

Installation/configuration notes

Compatibility Information Control Panels

ICP-CC404P, ICP-CC408-CHI, ICP-CC408-APR, ICP-CC408P,
ICP-CC408P-ES, ICP-CC488-CHI, ICP-CC488-APR, ICP-CC488P,
ICP-CC488P-ES, CC408, CC488, CC880, Solution 4 + 4, Solution 6,
Solution 6 + 6, Solution 8, Solution 862, and Solution Ultima 862

Mounting Considerations

The ICP-CP508W can be surface mounted indoors
using two to four screws.

Parts included

Quant.	Component
1	Codepad

Technical specifications

Enclosure Design

Dimensions:	7.2 cm x 12.7 cm x 2.3 cm (2.8 in. x 5 in. x 1 in.)
-------------	--

Environmental Considerations

Storage Temperature:	+0°C to +50°C (+32°F to 122°F)
Relative Humidity:	20% to 90% (non-condensing)

Power Requirements

Operating Voltage:	11 VDC to 14VDC
Current Draw:	50 mA (maximum)
Radio Frequency Interference (RFI) Immunity:	Complies with AS/NZS3548

Ordering information

ICP-CP508W LED Codepad

Eight-zone LED codepad with easy-to-read system
condition text and numerically- indicated zone status
Order number **ICP-CP508W**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com