



Light Capacity Tweezer-Style Resistance Soldering System

Model: 10502



Description

American Beauty offers the most advanced and complete line of resistance soldering systems available anywhere in the world. Here are just a few of the advantages that you will find with resistance soldering systems:

- Smash Operational Bottlenecks - Concentrated heat reduces solder time many times over.
- Improve Solder Joint Quality - Poor solder joints are often the result of insufficient heat throughout the joint, creating weak spots.
- Eliminate Thermal Damage - Traditional soldering methods introduce too much heat into surrounding areas damaging critical components or desoldering of previously soldered joints.
- Reduce Liability - Light-weight handpieces cool within seconds greatly reducing likelihood of repetitive strain injury and virtually eliminating the burn risk for the user.
- Solder in Tight Spots - Versatile systems allow easy access to restricted areas.
- Cut down on Energy Consumption - Instant heat means you're not paying to heat a soldering station all day long.
- Save on Maintenance and Consumables - Electrodes last twice as long as soldering tips and don't require constant rewetting.

Stop trying to perform your difficult soldering operation the same old way with the same old tools. Try an American Beauty Resistance Soldering System today.

Features and Benefits

250 Watts (2.8 VAC) of Infinitely Variable Power provides the ideal combination of intensity and control.

Light-weight, palm-sized hand piece with comfort grip padding minimizes operator fatigue.

Copper-coated, stainless steel electrodes can be easily bent, allowing the user to customize the handpiece to their specific application.

Footswitch permits hands-free activation of power, vastly improving control of your applications and virtually eliminating the sparking that is common with other brands of resistance based systems.

Technical Specifications

User Manual	Download
Is a high voltage version (220-240VAC) available?	Yes
Wattage	250 watts
Opening between Electrodes	.25 in / 0.64 cm
Electrode Size/Diameter	.078 in / 0.20 cm
Connection Type	Tapered Pins
RoHS Compliant	Yes
Country of Origin	US
Package Length	10.25 in / 26.04 cm
Package Width	8.25 in / 20.96 cm
Package Height	6.50 in / 16.51 cm
Shipping Weight	8.50 lbs / 3.86 kg
Warranty Policy	Details

Applications

Users of this product have stated that they use it for several jobs which include but are not limited to:

1. Soldering wire terminations 18 AWG and finer
2. Soldering fiber optic cable into gold plated termination
3. Soldering lead wires to multi-pin tap switch & military connectors
4. Soldering component leads for through hole PCB assembly

5. Repairing fine jewelry
6. Repairing cable assemblies in submarines
7. Soldering delicate photo etch brass & stainless
8. Soldering microwave cable assemblies
9. Soldering in process of jewelry making
10. Removing an oxidized screw by heating
11. Soldering RF Connector PINs
12. Soldering surface mounted componet repairs
13. Repairing electrical and metal soldering joints
14. Repairing surface mount componets
15. Soldering parts/components onto **aircraft**
16. Soldering connectors on Remote Control Helicopters

Replacement Parts

The following products can be used as replacements for Model 10502 featured on this page:

Model	Product Name	Price
10519	Standard Footswitch	\$54.00
10541	Light Tweezer Style Handpiece	\$148.00
10542	5/64" Steel Electrodes for Resistance Soldering	\$19.80
105A12	250 Watt Infinitely-Variable Resistance Soldering Power Unit	\$404.00

Accessories

The following products can be used as Accessories for Model 10502 featured on this page:

Model	Product Name	Price
105PTM	Resistance Soldering Precision Timer Module	\$825.00
105V12	Grounding Vise for Holding Parts Hands-Free	\$155.00

Similar Products

The following products are related (similar model but different specifications, etc.) to Model 10502 featured on this page:

Model	Product Name	Price
10504	Standard Capacity Tweezer-Style Resistance Soldering System	\$682.00