SPECIFICATIONS

Video Head Configuration:

3 Heads

Recording:

Rotary Two-Head Helical Scan Azimuth Recording

Tape Speed:

23.39 mm/sec. (03 mode)

Tape Width:

12.7 mm 5°C to 40°C

Operation Temperature:

PAL colour (system I) & CCIR monochrome signals (625 lines)

Video: Recording Time:

448 hours (when E180 cassette is used and the tape speed set to 480

mode)

Video Input: Video Output: 1 Vp-p 75 ohm Unbalanced 1 Vp-p 75 ohm Unbalanced

S/N Ratio (Video): S/N Ratio (Audio): 43 dB (03 mode) 40 dB (03 mode)

Horizontal Resolution:

Colour: 240 lines (03 mode) B&W: 300 lines (03 mode)

Audio Input: Audio Output: -7.8 dBm 100 Kohm -7.8 dBm 600 ohm

Audio Frequency Range:

200 Hz to 8 kHz (03 mode)

Power:

(TLC1600X) AC 220V, 50 Hz (TLC1600UK) AC 240V, 50 Hz

Power Consumption:

33W (including timer)

Cabinet Size:

435 mm(W) x 95 mm(H) x 324 mm(D)

Weight:

7 kg

^{*} Design and specifications are subject to change without notice.