


2011 METALWORKING CUTTING TOOLS



 **TaeguTec**
Member IMC Group

Concise Catalogue Guide

TaeguTec now proudly presents its brand new 2011 Concise Catalogue that introduces a complete range of standard cutting tool products. Within this catalogue, customers will find the 'perfect fit' solution for a wide variety of machining applications. Thorough reading of the catalogue before purchasing of new tools will enable the customer to efficiently access and identify the most specific product and information for their exact needs.



- ▶ The contents of this catalogue are based on the metric system.
- ▶ This catalogue is mainly composed of TaeguTec standard cutting tool products. Tailor made cutting tools do not appear in this catalogue.
- ▶ The below instructions will guide you to the required product fast and efficiently.

STEP1: Select an application line from the main Table of Contents. (Each line is distinguishable with alphabetical initials and colors.)
STEP2: Choose the required machining solutions and tools from each Application Section contents or Application Program Section.
STEP3: Required information on the tooling products can be acquired from the Product Pages.
STEP4: Additional information on products such as holders, inserts and other components are available from the Reference Pages that are indicated in each designation table.



- ▶ In cases where the product designation is already at hand, it is easier to look at the Index at the end of the catalogue.

▶ A User Guide for each product line contains recommended working conditions as well as technical information.
Information regarding the TaeguTec grades and work materials are highlighted in the Grades and Materials Information.



- ▶ Economical cutting tools can be recommended by TaeguTec technical engineers, if customers provide information such as workpiece materials, drawings, cutting conditions and any additional information.
- ▶ All products introduced in this catalogue can also be found and downloaded from the e-Catalogue on the TaeguTec website. The e-catalogue is updated on a weekly-basis where the latest TaeguTec product information is readily available.



Should you require more information and data from TaeguTec, please contact the nearest TaeguTec Global Service Center or visit our website. www.taegutec.com

CONTENTS

Taegu  Turn



A

Taegu  Thread



B

Taegu  Clamp



C

Taegu  Holemaking



D

Taegu  Mill



E

Taegu  Solid Mill



F

Taegu  Tooling



G

Grades and Materials
Information




I

Index



J

It Just Gets Better



 **TaeguTec**
Member IMC Group

A

Taegu  Turn



 TaeguTec
Member IMC Group

New Products

TURN•RUSH HB chipbreaker

For semi heavy turning


- Low cutting forces and an optimized chip-breaker suitable for semi heavy machining
- Hook lever clamping system gives unique contact surface with large convex
- 3 dimensional geometry that is exchangeable with the ISO standard holder



TOPDUTY 40mm helix cutting edge

For large part machining in the wind power, shipbuilding and power plant industries

- High helix cutting edge with 40mm cutting edge
- Unique geometry gives low cutting force
- Suitable for low-powered machines



TOPDUTY 50mm cutting edge

For large part machining in the wind power, shipbuilding and power plant industries

- 50mm cutting edge enables cutting up to 45mm depth of cut
- Rectilinear shaped cutting edge ideal for heavy roughing on a high-powered machine



TOPDUTY Double sided H series chipbreaker

New Double-Sided Chipbreaker Insert for Rough and Finish Machining

- Utilizes both sides to improve economy & cost reduction
- Offers a variety of sizes and chip breakers to meet customers specific heavy rough machining requirements
- Economy is further improved by using one tool holder for rough to finish machining



New Products

TOPDUTY Double sided insert with 32mm cutting edge

Brand New Double-Sided Insert

- The upper-side has a negative chip breaker type that is suitable for heavy machining
- The under-side is designed to minimize the cutting load and break chips effectively when machining depths of cut less than 5mm
- Strong clamping force due to hook lever system



T-TURN EM chipbreaker

For stainless steels machining

- Cooling effectiveness & stability:
Broad boss face and heat dissipating design improves surface contact ratio and heat transfer
- Low cutting force:
 - Sharp land design reduces cutting forces and prevents built-up edges
 - Broad chip groove is suitable for smooth chip evacuation for medium machining applications



T-TURN Positive insert with PC chipbreaker

New single sided 'PC' chipbreaker is suited to semi-finish and medium machining

- Low cutting forces credit to its positive rake angle
- Wide application range
- Suitable for a wide variety of materials
- For semi-finish to medium application



T-TURN RA chipbreaker with positive insert

For rough machining of medium and large sized components.

- Better chip control range at low feed rates and D.O.C
- Suitable for heavy & interrupted machining
- Broad chip control range



T-TURN RX chipbreaker for semi rough machining of Large Parts

For semi rough machining and large sized components

- Negative and positive cutting edge: improves stability and machinability
- Helical cutting edge: increases tool life by minimizing cutting resistance
- Extensive application: applicable to a broad range of workpieces



New Products

TOPRAIL For rail wheel machining

Best solution for rail wheel profiling

- The tangential type inserts are suitable for radius and rough machining of wheel profiles
- Economical and productive insert options are based on individual cutting conditions (roughing, semi-finishing and finishing)



TOPFEED HF chipbreaker

For high feed machining

- Maximum edge life for turning: Double sided and 6 cutting edges
- Ultra high feed machining condition: Max feed rate=3.0mm/r, Max D.O.C=2.5mm
- Quick change and rigid clamping force: Due to hook lever clamping design



TOPMINI SA chipbreaker

Ground positive ISO inserts for high precision turning

- High precision is guaranteed with the peripherally ground geometry
- Low cutting forces due to the dynamic inclined sharp cutting edge with a wide groove geometry
- Suitable for Swiss sliding head turning centers with its soft cutting and excellent surface finish Small corner radius size: R0.1, 0.2 and 0.4mm



TOPMINI Back Clamping Holder

Quick change holder for Swiss type lathes

- Quick insert changeover with simple lever clamp design
- Both front and side clamping is available
- Rigid and stable clamping force guaranteed with unique backward and downward two-directional clamping force
- No limitations – can be used with all Swiss-type turning machines



New Products

TOPMINI Boring bar and insert for small component machining

New range of inserts and boring bars suitable for the turning of small workpieces

Insert Features

- Produced in two insert types - ground & pressed-to-size
- Micro size Insert (IC=3.97, 4.76mm)
- Excellent surface finish prevents micro chipping and prolongs tool life
- Available in both right-hand and left-hand operation types



Boring bar Features

- Improves chip evacuation
- Stable machining with reduced chatter
- Bore machining as small as 6mm diameter possible
- Shanks available in steel and carbide

C-ADAPTER

Quick change holders for ISO turning

- Wide range of quick change heads for ISO turning tool.
- Possible for high precision during machining due to stable clamping force.



MODULARBAR

Head exchangeable modular boring bar

- Auto-centring and excellent durability due to detachable triangular anti-rotator
- Strong adjoining force and high precision even after repeated head exchange
- Internal coolant
- Shank Diameter range from 25mm up to 32mm



COMBICLAMP Multi clamp for T-Holder

Multi functional clamp system

- Compatibility: Applicable to the existing T-Holders when clamp is changed
- Versatility: 3 different types of insert for one T-Holder
- Durability: The new carbide clamp shows better wear resistance compared to existing cast iron machining applications
- Stability: Due to the gap adjusting structure in the insert's contact area, it proves much stronger with a stable joint force



New Products

T-TURN Ceramic grade

TC430 Whisker reinforced ceramic grade
for machining high strength and high temperature
alloy material



- SiC whisker reinforced ceramics grade.
- High hardness and high fracture toughness.
- Suitable for general turning and milling applications.
- Possible to machine at high speed cutting for Ni-base superalloy (Inconel, Waspaloy, Rene, etc.), hardened steels and hard castings

T-TURN CBN grades

TB610, TB670, TB730

Excellent cutting performance for hardened steel and cast iron

TB610


- Excellent oxidation resistance and chemical stability.
- From continuous to light interrupted turning.
- For machining hard steel, alloy steel, tool steel and case hardened steel.

TB670

- High hardness and impact resistance.
- From continuous to severe interrupted turning.
- For alloy steel, tool steel, case hardened steel and chilled cast iron.

TB730


- High hardness and high fracture toughness.
- General turning and milling.
- For gray cast iron, nodular cast iron and carbide rolls.



T-TURN PCD chipbreaker insert

CB - New geometricized PCD insert

- Serrated cutting edge ensures maximum chip control and low cutting resistance that performs remarkably well even in low depth of cut and low feed
- Unique cutting edge geometry guarantees excellent chipping resistance



A CONTENTS




	Page
Grades	A8 - A13
Chipbreakers	A14 - A20
TaeguTurn Inserts	
Designation System	A22 - A23
Negative Inserts	A24 - A38
Negative HNMG Type Inserts	A30
Negative KNUX Type Inserts	A30
Positive Inserts	A39 - A48
Inserts for Pipe Skiving	A48
Inserts for Aluminum	A49 - A50
Ceramic Inserts	A53 - A61
CBN Inserts	A62 - A68
PCD Inserts	A69 - A72
TaeguTurn External Toolholders & Boring Bars	
Designation System for External Toolholders	A74 - A75
Toolholder Clamping System	A76
COMBICLAMP User Guide	A77
B-Holder	A78 - A79
External Toolholders for KNUX Type	A79 - A80
Top Clamp/External Turning Toolholders	A80 - A81
Multi Lock/External Turning Toolholders	A81 - A84
Lever Lock/External Turning Toolholders	A84 - A90
Screw Clamp/External Turning Toolholders	A91 - A98
T-Holders - External Turning	A98 - A102
Wedge Clamp/External Turning Toolholders	A102 - A103
Top Clamp/External Toolholders for CBN & Ceramic Inserts	A103 - A108
T-Holders - External Turning for Ceramic Dimple Inserts	A109 - A111
TURN+RUSH	A113 - A114
TOPFEED	A115
TOPDUTY	A116 - A122
TOPRAIL	A123 - A124
C-ADAPTER	A126 - A132
Designation System for Boring Bars	A133
Top Clamp/Boring Bars	A134 - A135
Multi Lock/Boring Bars	A135
Lever Lock/Boring Bars	A136 - A137
Screw Clamp/Boring Bars	A138 - A148
Wedge Clamp/Boring Bars	A148
T-Holders - Internal Turning	A149 - A150
T-Holders - Internal Turning for Ceramic Dimple Inserts	A150
Boring Sleeve	A151
MODULARBAR	A152 - A155
TaeguTurn Cartridges	A156 - A165
User Guide	
Components for Holder and Boring Bar	A166 - A177
Trouble Shooting	A178 - A179
Insert Selection for Cast Iron Materials	A180 - A181
Insert Geometry for Workpiece Shape	A182
Insert Selection & Recommended Cutting Parameters	A183 - A190
Comparison of Chipbreaker	A191

Insert Materials



Insert Grades



- PV3010: PVD Coated cermet, CT3000: Uncoated cermet
- TT1300, TT7310, TT8115, TT8125, TT8135, TT5100, TT7100, TT9215, TT9225, TT9235: CVD coated carbide
- TT5080, TT8020, TT9080, TT9020: PVD coated carbide

Coated Carbide, Cermet and Carbide Grades

Grades	ISO	Characteristics & Applications
TT1300 CVD Coated	K05 – K15	<ul style="list-style-type: none"> For high speed turning of cast iron Thick aluminum oxide coating on a high wear resistant substrate First choice for machining cast iron (Rough and Finish)
TT7310 CVD Coated	K10 – K20	<ul style="list-style-type: none"> For machining of ductile cast iron & gray cast iron Excellent wear and chipping resistance
 TT8115 CVD Coated	P05 – P25	<ul style="list-style-type: none"> For high speed turning continuous cutting on steels Excellent wear resistance and heat-resistance
 TT9215 CVD Coated	S10 – S25 M10 – M25	<ul style="list-style-type: none"> Excellent insert wear resistance For high cutting speed & continuous cutting on stainless steels
 TT8125 CVD Coated	P15 – P35	<ul style="list-style-type: none"> For a wide range of turning on steels Very good combination of wear resistance and toughness For general use on steels
 TT5080 PVD Coated	S05 – S15 M05 – M15	<ul style="list-style-type: none"> For a wide range of turning of high-temp alloys Very hard submicron substrate with good fracture toughness
 TT5100 CVD Coated	P20 – P40	<ul style="list-style-type: none"> For a wide range of turning of mild steel, low carbon steel and low carbon alloy steel Excellent chipping resistance and sticking resistance
 TT9225 CVD Coated	S20 – S35 M20 – M35	<ul style="list-style-type: none"> Excellent combination of insert wear resistance & fracture resistance For general use on stainless steel For continuous and interrupted cutting on stainless steel
 TT8135 CVD Coated	P25 – P40	<ul style="list-style-type: none"> Tough carbide substrate For a wide range of medium to roughing applications at low cutting speed on steels For heavy turning
 TT7100 CVD Coated	P30 – P45	<ul style="list-style-type: none"> Very tough carbide substrate base - with a CVD coating This combination provides both excellent toughness and chipping resistance For heavy turning
 TT9235 CVD Coated	S30 – S45 M30 – M45	<ul style="list-style-type: none"> Excellent combination of insert wear resistance & toughness For low cutting speed & interrupted cutting
 TT9080 PVD Coated	M10 – M30 S15 – S25	<ul style="list-style-type: none"> Very hard submicron substrate For turning small components
TT9020 PVD Coated	P30 – P40 M15 – M35	<ul style="list-style-type: none"> Submicron substrate with PVD coating For stainless steel
TT8020 PVD Coated	P30 – P45 M30 – M40 S20 – S30	<ul style="list-style-type: none"> For medium to low speed turning of stainless steel, exotic alloys and low carbon steel Toughest grade in turning grade For interrupted cut on stainless steel and exotic alloys
PV3010 PVD Coated Cermet	P01 – P20 M01 – M20 K01 – K15	<ul style="list-style-type: none"> For high surface finish turning of steel, stainless steel and cast iron Excellent wear resistance and low coefficient of friction Long tool life
CT3000 Uncoated Cermet	P05 – P25 M05 – M25 K05 – K15	<ul style="list-style-type: none"> Excellent surface finish turning on steel, stainless steel and cast iron Excellent wear resistance and low coefficient of friction
K10 Carbide	K05 – K20 N10 – N20	<ul style="list-style-type: none"> General turning of cast iron, exotic alloy and non-ferrous materials including aluminum and copper alloy Excellent wear resistant grade

Recommended Cutting Speeds: V=m/min							
Materials							
Low Carbon Steel	Low Carbon Alloy Steel	Carbon Steel	Alloy Steel	Stainless Steel	High Temp. Alloy	Cast Iron	Aluminum Alloy
						150 - 450	
						150 - 420	
440-800	330-660	170-440	110-380				
				170-250	40-80		
250-600	150-500	100-350	80-300				
				150-250	30-100		
150-500	70-350	70-250	70-220				
				130-220	30-70		
100-400	70-320	70-250	70-220				
60-350	60-300	70-200	70-180				
				110-170	30-60		
				50-160	20-40		
				50-150			
70-300	70-250	70-150	70-130	50-150	20-30		
300-800	150-600	150-400	100-350	200-300		100-300	
250-700	150-550	150-350	100-320	200-270		100-350	
					20-50	80-180	60-1500


CBN, PCD and Ceramic Grades

Grades	Composition	Characteristics & Applications
KP300 PCD	PCD + Binder	<ul style="list-style-type: none"> For general use on aluminum alloy Excellent combination of wear resistance and toughness
TB610 CBN	CBN + Binder	<p><i>New</i></p> <ul style="list-style-type: none"> Excellent wear resistant grade with low CBN content Continuous cutting at high cutting speeds on hardened steels
TB650 CBN	CBN + Binder	<ul style="list-style-type: none"> High wear resistant grade with moderate fracture toughness Can be applied to light interrupted cutting applications
TB670 CBN	CBN + Binder	<p><i>New</i></p> <ul style="list-style-type: none"> Excellent combination of wear resistance and toughness For general use on hardened steel For continuous and interrupted cutting
TB730 CBN	CBN + Binder	<p><i>New</i></p> <ul style="list-style-type: none"> Excellent toughness with high CBN content For high speed machining of cast iron Can be applied to interrupted cutting on hardened steel and other materials
KB90A CBN	CBN + Binder	<ul style="list-style-type: none"> Solid CBN with excellent impact resistance For high speed machining of cast iron Can be applied to rough to medium machining of hardened steel
AW20 CERAMIC	Al ₂ O ₃ + ZrO ₂	<ul style="list-style-type: none"> Excellent wear resistant grade with chemical stability and temperature resistance For high speed continuous turning of cast iron For finishing applications on hard materials
AB2010 COATED CERAMIC	(Al ₂ O ₃ +TiCN) +TiN PVD Coating	<ul style="list-style-type: none"> Excellent wear resistance and tool life Very good combination with improved wear and fracture resistance Finishing operations on hardened steels and hardened cast irons
AB20 CERAMIC	Al ₂ O ₃ +TiCN	<ul style="list-style-type: none"> High wear resistant grade with excellent cutting edge stability For high speed continuous turning of hardened steel and other hard materials For finishing applications on cast iron.
AB30 CERAMIC	Al ₂ O ₃ +TiC	<ul style="list-style-type: none"> Mixed ceramic with good toughness and wear resistance For general use on hardened steel, cast iron and hard materials Can be applied to interrupted cutting conditions
TC430 CERAMIC	Whisker	<p><i>New</i></p> <ul style="list-style-type: none"> SiC whisker reinforced ceramic grade General turning and milling For Ni-base superalloy, inconel, waspaloy and rene
AS500 CERAMIC	SiAlON	<p><i>New</i></p> <ul style="list-style-type: none"> For roughing to finishing cast iron applications For higher cutting speeds compared to AS10 Wet and dry cutting
SC10 COATED CERAMIC	AS10 + CVD	<ul style="list-style-type: none"> Wear resistant grade with excellent toughness and thermal shock resistance For high speed turning of cast iron Wet and dry cutting
AS10 CERAMIC	Si ₃ N ₄	<ul style="list-style-type: none"> High wear resistant grade with excellent toughness and thermal shock resistance For general use on cast iron Wet and dry cutting
AS20 CERAMIC	Si ₃ N ₄	<ul style="list-style-type: none"> Very tough Si₃N₄ ceramic grade with high cutting edge stability For roughing to finishing applications with high temperature nickel based alloys Wet and dry cutting


Recommended Cutting Conditions: V=m/min, f=mm/rev							
Materials							
Grey cast iron (180-220HB)	Ductile cast iron (200-240HB)	Chilled cast iron (400-700HB)	H.S.S. Roll	Sintered metal	Hardened steel (46-65HRC)	Aluminum Alloy	Ni-Based super alloy
						600-3000 0.05-0.3	
					100-250 0.05-0.2		
		80-150 0.1-0.2	50-100 0.2-0.6	100-300 0.05-0.2	80-200 0.05-0.2		
		80-150 0.1-0.25	30-80 0.2-0.6	100-300 0.1-0.3	80-180 0.1-0.3		
500-1000 0.1-0.3	300-800 0.1-0.3	80-150 0.1-0.3		80-250 0.1-0.25	60-150 0.1-0.3		
500-1000 0.1-0.3	300-700 0.1-0.3	80-150 0.1-0.3					
400-1000 0.1-0.5	300-600 0.1-0.2						
		50-200 0.05-0.2			80-300 0.05-0.2		
300-800 0.1-0.3		50-200 0.05-0.2	50-100 0.2-0.5		50-250 0.05-0.2		
300-800 0.1-0.5	250-500 0.1-0.3	50-150 0.05-0.2	50-80 0.2-0.5		50-200 0.1-0.25		
			50-100 0.2-0.7				150-400 0.1-0.3
400-1000 0.2-0.6	200-600 0.1-0.5		20-60 0.2-0.7				
300-1000 0.2-0.8	250-600 0.2-0.6						
400-800 0.2-0.8	200-500 0.2-0.6						
							100-300 0.1-0.3

Negative Inserts


For Finishing Applications




For Medium Applications




For Roughing Applications




For Heavy Machining



KNUX Type




HNMG Type




Positive Inserts

For Finish to Medium Applications




For Medium Applications



Positive Inserts


Ground Insert for Finishing Applications

Depth of Cut (mm)



Round Insert for Roughing Applications


Depth of Cut (mm)



'WS' and 'WT' Wiper Inserts for High Feed Turning


Negative Inserts


Depth of Cut (mm)



Positive Inserts

Depth of Cut (mm)























Negative Inserts

Chipbreaker Name and Geometry			Applications and Features	
FA		CNMG 1204 	A B 	<ul style="list-style-type: none"> For super finish applications Steel, stainless steel and heat resistant alloy machining Excellent chip control
EA		CNMG 1204 	A B 	<ul style="list-style-type: none"> For finishing applications Exotic materials Excellent chip control at low feeds and depths of cut
FG		WNMG 0604 	A B 	<ul style="list-style-type: none"> For finish and semi finish applications Steel, stainless steel and cast iron machining Low cutting forces
SF		CNMG 1204 	A B 	<ul style="list-style-type: none"> For finishing applications Stainless steel and heat resistant alloy machining Low cutting forces
New FC		CNMG 1204 	A B 	<ul style="list-style-type: none"> Ideal for finishing applications Low carbon steel & low carbon alloy steel Effective chip breaking in both turning and facing operations
MC		CNMG 1204 	A B 	<ul style="list-style-type: none"> For medium applications Steel and cast iron machining Strong rake geometry Excellent chip control on medium turning applications
New PC		CNMG 1204 	A B 	<ul style="list-style-type: none"> For medium to semi-finishing applications Steel & Automotive component Positive geometry Excellent chip control on medium applications
VF		DNMG 1504 	A B 	<ul style="list-style-type: none"> For slender workpiece applications Vibration free Steel and stainless steel machining High positive rake geometry to minimize cutting forces
ML		CNMG 1204 	A B 	<ul style="list-style-type: none"> For medium light applications Stainless steel, steel and aluminum Very high positive rake geometry to minimize built-up-edge and cutting forces
MP		CNMG 1204 	A B 	<ul style="list-style-type: none"> For medium machining applications Steel and stainless steel High positive rake geometry to optimize machining and provide stable machining conditions
New EM		CNMG 1204 	A B 	<ul style="list-style-type: none"> For medium applications Stainless steel machining Sharp land design for low cutting force
MT		WNMG 0804 	A B 	<ul style="list-style-type: none"> For medium rough applications Steel, cast iron and stainless steel Tough rake angle for general use

T-TURN Chipbreakers

Chipbreaker Name and Geometry			Applications and Features	
MG-		CNMG 1204  	A B	<ul style="list-style-type: none"> For medium rough applications Steel and cast iron machining Strong rake geometry Suitable for manual lathes
ET		CNMG 1204  	A B	<ul style="list-style-type: none"> For roughing applications on exotic materials Low cutting force Wide chip control range when roughing
RT		CNMG 1906  	A B	<ul style="list-style-type: none"> For roughing applications Steel and cast iron machining Very strong rake geometry
New HB		CNMX 1607  	A B	<ul style="list-style-type: none"> For semi heavy roughing applications Steel and alloy steel machining Double sided semi-heavy turn insert Stable contact surface with seat
RH(N)		CNMM 1906  	A B	<ul style="list-style-type: none"> For high feed roughing applications Steel, cast iron and stainless steel machining Very strong rake geometry
New RX		CNMM 1906  	A B	<ul style="list-style-type: none"> For semi heavy roughing applications Steel, stainless steel and cast iron machining Strong cutting edge with flat land Low cutting force
RH		CNMM 1906  	A B	<ul style="list-style-type: none"> For roughing applications Steel, stainless steel and cast iron machining Very strong rake geometry
HT		SNMM 1906  	A	<ul style="list-style-type: none"> For heavy roughing applications Low cutting force for low horse power machines Excellent chip control due to changeable land and a flexible chip breaker
New HD		CNMD 2509  	A B	<ul style="list-style-type: none"> For heavy roughing applications For all kinds of shafts, connecting-rods and ship building components Flexible chip breaker offers excellent chip evacuation
New HY		CNMM 2509  	A B	<ul style="list-style-type: none"> For heavy roughing applications For large depth of cut and high feed Strong cutting edge credit to a wide land and large land angle
New HZ		CNMM 2509  	A B	<ul style="list-style-type: none"> For heavy roughing applications For large depth of cut and high feed Extremely strong cutting edge credit to a wide land and large land angle Suitable for high cutting conditions
Wiper WS		CNMG 1204  	A B	<ul style="list-style-type: none"> For super finish applications Steel, cast iron and stainless steel machining Excellent chip control and low cutting forces
Wiper WT		CNMG 1204  	A B	<ul style="list-style-type: none"> For medium to rough machining applications Steel, cast iron and stainless steel machining Stable cutting and low cutting forces at high feed rates

T-TURN Chipbreakers




HNMG Type Inserts

Chipbreaker Name and Geometry			Applications and Features	
GU		HNMG 	A	<ul style="list-style-type: none"> For medium applications For general turning of steels and cast irons Strong rake geometry
SU		HNMG 	A	<ul style="list-style-type: none"> For exotic materials Stainless steels, super alloys, low carbon steels, low carbon alloy steel machining Sharp geometry to minimize built-up edge






Positive Inserts

Chipbreaker Name and Geometry			Applications and Features	
FA		DCMT 11T3 	A	<ul style="list-style-type: none"> For super finish applications Very tight chipbreaker Excellent chip control
FG		CCMT 09T3 	A	<ul style="list-style-type: none"> For finish to medium light applications Steel and stainless steel machining Low cutting forces Excellent chip control
New PC		CCMT 09T3 	A	<ul style="list-style-type: none"> For medium applications Suitable for a wide variety of materials Low cutting force
MT		CCMT 09T3 	A	<ul style="list-style-type: none"> For medium to medium rough applications Steel, stainless steel and cast iron machining Negative rake geometry for general use
PMR-		TPMR 1103 	A	<ul style="list-style-type: none"> For medium to medium rough applications Steel, stainless steel and cast iron Positive rake geometry
New RA		RCMX 3209 	A	<ul style="list-style-type: none"> For heavy and interrupted machining applications Steel, stainless steel and cast iron machining Optimized chip groove geometry
CMX-		RCMX 1204 	A	<ul style="list-style-type: none"> For high feed roughing applications Steel, stainless steel and cast iron machining Strong rake geometry
FL		CCGT 1204 	A	<ul style="list-style-type: none"> For finish to medium applications Aluminum machining Very high positive rake geometry to minimize built-up-edge
New SA		CCGT 09T3 	A	<ul style="list-style-type: none"> For finish to medium applications Steel & aluminum machining Low cutting force

Chipbreaker Name and Geometry			Applications and Features
WT Wiper		CCMT 09T3 	<p>A</p> <ul style="list-style-type: none"> For medium to rough machining applications Steel, cast iron and stainless steel machining Stable cutting and low cutting forces at high feed rates <p>B</p>

KNUX Type Inserts



Chipbreaker Name and Geometry			Applications and Features
11		KNUX 1604 	<p>A</p> <ul style="list-style-type: none"> For medium light to medium applications Steel and stainless steel machining Positive rake geometry to minimize cutting forces Excellent chip control
12		KNUX 1604 	<p>A</p> <ul style="list-style-type: none"> For medium to medium rough applications Steel and stainless steel Strong rake geometry Wide chip control range






1 Shape			2 Clearance Angle		4 Type		
C	D	E	N	B	A	G	M
H	K	R	C	P			
S	T	V					
							Special Z,X
W							
			C	N	M	G	
			1	2	3	4	

3 Tolerance							
Diameter of IC	Tolerance						
	On m		On d				
	Class M	Class U	Class M	Class U			
6.35	±0.08	±0.13	±0.05	±0.08			
9.52	±0.08	±0.13	±0.05	±0.08			
12.70	±0.13	±0.20	±0.08	±0.13			
15.88	±0.15	±0.27	±0.10	±0.18			
19.05	±0.15	±0.27	±0.10	±0.18			
25.40	±0.18	±0.38	±0.13	±0.25			
31.75	±0.18	±0.38	±0.13	±0.25			

Diagrams illustrating geometric tolerances:

- Top left: A triangle with a vertical dimension 'm' and a horizontal dimension 'd'.
- Top middle: A circle with a diameter 'd' and a vertical dimension 'm' indicating concentricity.
- Top right: A rectangle with a height 't' and a width 'd'.

Class	m	t	d
A	±0.005	±0.025	±0.025
F	±0.005	±0.025	±0.013
C	±0.013	±0.025	±0.025
H	±0.013	±0.025	±0.013
E	±0.025	±0.025	±0.025
G	±0.025	±0.13	±0.025
M	±0.08 - ±0.18	±0.13	±0.05 - ±0.13
U	±0.13 - ±0.38	±0.13	±0.08 - ±0.25


6	Thickness	7	Corner Radius	8	Hand of Insert	9	Chipbreaker
					R: Right hand		
T1 = 1.59mm		01 = 0.1mm			L: Left hand		
T2 = 1.98mm		02 = 0.2mm					
T3 = 2.38mm		04 = 0.4mm					
T4 = 2.78mm		05 = 0.5mm					
T5 = 3.18mm		08 = 0.8mm					
T6 = 3.97mm		12 = 1.2mm					
T7 = 4.76mm		16 = 1.6mm					
T8 = 5.56mm		20 = 2.0mm					
T9 = 6.35mm		24 = 2.4mm					
T10 = 7.94mm		32 = 3.2mm					
T11 = 9.52mm							

12 04 08 (R) MP

5 6 7 8 9

5 Cutting Edge Length											
I.C(mm)	C	D	E	R	S	T	V	W	K	H	
3.97	03	04			03	06		02			
4.76	04	05			04	08	08				
5.56	05	06			05	09	09	03			
6.35	06	07			06	11	11	04			
7.94	08	09			07	13	13	05			
8.0				08							
9.52	09	11		09	09	16	16	06	16		
10.0				10							
12.0				12							
12.7	12	15	13		12	22	22	08		05	
15.88	16	19		15	15	27	27	10			
16.0				16							
19.05	19	23		19	19	33	33	13		10	
20.0				20							
25.0				25							
25.4	25	31		25	25	44	44	17			
31.75	32	38			31	54	54	21			
32.0				32							

Negative 80° Rhombic Inserts




Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)																			
		feed (mm/rev)	ap (mm)	Cermet			CVD Coated					PVD Coated			Uncoated								
				PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20	
For Roughing	CNMA 120404 120408 120412 120416 160612 160616 190604 190608 190612 190616	0.15 - 0.50	1.0 - 5.0			●	●													●	●		
		0.15 - 0.60	1.0 - 6.0			●	●																
		0.15 - 0.70	1.5 - 6.0			●	●																
		0.20 - 0.80	2.0 - 6.0																				
		0.15 - 0.70	2.0 - 8.0			●	330	250													150		
		0.20 - 0.80	2.0 - 8.0																				
		0.15 - 0.50	2.0 - 10.0																				
		0.15 - 0.70	2.0 - 10.0					●	●														
		0.15 - 0.70	2.0 - 10.0																				
		0.15 - 1.00	3.0 - 10.0			●	●														●		
Wiper For Roughing	CNMA 120408 WT	0.15 - 0.8	0.7 - 5.0			330	250																
For Medium	CNGG 120401 ML 120402 ML 120404 ML 120408 ML	0.03 - 0.10	0.1 - 1.0														●						
		0.05 - 0.15	0.2 - 1.2														●	60					
		0.10 - 0.30	0.8 - 3.5														●	260					
		0.12 - 0.35	1.0 - 3.5														●						
For Medium	CNMG 090308 120404 120408 120408 120412 120416 160408 160604 160608 160612 160616 190604 190608 190612 190616 190624	0.20 - 0.50	1.0 - 3.5					●	●							●							
		0.17 - 0.45	1.0 - 5.0	●	●	●	●	●	●	●						●			●		●		
		0.23 - 0.60	1.5 - 5.0	●	●	●	●	●	●	●						●	●	●	●	●	●		
		0.25 - 0.60	2.0 - 5.0	●	●	●	●	●	●	●						●							
		0.27 - 0.60	2.5 - 5.0													●							
		0.25 - 0.60	2.0 - 6.5													●							
		0.20 - 0.45	2.0 - 6.5													●							
		0.25 - 0.60	2.0 - 6.5	290	250	330	250	●	290	265	195					●	205	170	150	190	150	120	
		0.27 - 0.60	2.0 - 6.5	250												●							
		0.29 - 0.60	2.0 - 6.5													●							
		0.20 - 0.45	3.0 - 8.0					●	●							●							
		0.25 - 0.60	3.0 - 8.0	●	●	●	●	●	●	●						●							
		0.30 - 0.60	3.0 - 8.0	●	●	●	●	●	●	●						●							
		0.35 - 0.70	3.0 - 8.0	●	●	●	●	●	●	●						●							
		0.35 - 0.80	3.0 - 8.0	●	●	●	●	●	●	●						●							
For Finishing	CNMG 120404 EA 120408 EA	0.05 - 0.30	0.15 - 1.5		340			●				●	70	50	40	240	60	150	●	40			
		0.07 - 0.40	0.15 - 1.5	●	270		340	310	●			●	200	170	140	240	260	130	●	130			
New For Medium	CNMG 120408 EM 120412 EM 120416 EM 160608 EM 160612 EM 160616 EM 190608 EM 190612 EM 190616 EM	0.13 - 0.50	0.5 - 5.0									●	●	●		●							
		0.15 - 0.55	0.5 - 5.0									●	●	●		●							
		0.17 - 0.60	0.5 - 5.0									●	●	●		●							
		0.13 - 0.50	0.5 - 6.5									●	70	50	40		●	60		30			
		0.15 - 0.55	0.5 - 6.5									●	180	150	120		●	250		110			
		0.17 - 0.60	0.5 - 6.5									●	●	●		●		●					
		0.13 - 0.50	0.5 - 8.0									●	●	●		●		●					
		0.15 - 0.55	0.5 - 8.0									●	●	●		●		●					
		0.17 - 0.60	0.5 - 8.0									●	●	●		●		●					

• For toolholders, see page A84, A85, A98, A99, A128, A136, A149, A154, A162
 • For dimensions, see page A23

● Marked: Standard Items

Negative 80° Rhombic Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)																	
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated					PVD Coated			Uncoated							
		PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	F20	K10	K20	
For Roughing	CNMG 120408 ET	0.17 - 0.55	1.2 - 5.5						●					●							
	120412 ET	0.20 - 0.60	1.2 - 5.5						●					●							
	160612 ET	0.25 - 0.60	2.5 - 7.0					280	●				●	70	●	50	●	40			
	190612 ET	0.25 - 0.60	3.0 - 9.0					●					●	160	●	130	●	100	215		
	190616 ET	0.30 - 0.65	3.0 - 9.0						●				●				●	60	●	30	
For Finishing	CNMG 120404 FA	0.05 - 0.20	0.2 - 2.0	360	●	340			●	●											
	120408 FA	0.05 - 0.25	0.3 - 2.0	300	●	270			●	●				340	●	310		240			
New For Finishing	CNMG 090304 FC	0.07 - 0.20	0.5 - 2.0		●				●	●				●							
	090308 FC	0.10 - 0.25	0.7 - 2.0	360	●	340			●	●				●	70	●	50	●	40		
	120404 FC	0.05 - 0.30	0.2 - 2.5	300	●	270			●	340	●	310		●	200	●	170	●	140	240	
	120408 FC	0.08 - 0.35	0.3 - 2.5						●	●				●							
	120412 FC	0.10 - 0.40	0.3 - 2.5						●	●				●							
For Finishing	CNMG 090304 FG	0.07 - 0.20	0.5 - 2.0		●					●											
	090308 FG	0.10 - 0.25	0.7 - 2.0	360	●	340				●											
	120404 FG	0.05 - 0.30	0.2 - 2.5	300	●	270				●	340	●	310					240			
	120408 FG	0.08 - 0.35	0.3 - 2.5		●	●				●	●										
For Medium	CNMG 120404 MC	0.10 - 0.30	0.5 - 3.5		●				●	●											
	120408 MC	0.12 - 0.35	0.7 - 3.5		310				●	265	●	310	●	280	●	220		●	215	●	170
	120412 MC	0.15 - 0.40	0.7 - 3.5		●	265				●	●						●	●	●	150	
For Medium	CNMG 120404 ML	0.10 - 0.30	0.8 - 3.5		●				●	●				●	●			●	●		
	120408 ML	0.12 - 0.35	1.0 - 3.5		340				●	340	●	310		70	●	50		●	60	●	190
	120412 ML	0.15 - 0.35	1.3 - 3.5						●	●				●	200	●	170	●	260	●	130
OLD For Medium	CNMG 090304 MP✓	0.10 - 0.30	0.8 - 3.0						●												
	090308 MP✓	0.12 - 0.35	1.0 - 3.0						●												
	120404 MP	0.10 - 0.30	0.8 - 4.0						●	330	●	300	●	210	●	70	●	50	●	40	
	120408 MP	0.12 - 0.40	1.0 - 4.0						●	330	●	300	●	180	●	150	●	120	●	225	
	120412 MP	0.15 - 0.50	1.5 - 4.0						●	●				●	190	●	180	●	250	●	120
	160612 MP✓	0.15 - 0.50	2.5 - 6.0						●	●				●	●	●	●	●	●	●	
OLD For Medium	CNMG 090304 MT	0.12 - 0.40	0.8 - 3.5						●	●											
	090308 MT	0.17 - 0.45	1.0 - 3.5						●	●											
	120404 MT	0.15 - 0.40	1.0 - 5.0		●	●	●	●	●	●								●	●		
	120408 MT	0.17 - 0.55	1.2 - 5.0		●	●	●	●	●	●								●	●		
	120412 MT	0.20 - 0.55	1.5 - 5.0		330	●	310	●	265	●	310	●	250	●	195	●	70	●	50	●	
	160608 MT✓	0.20 - 0.55	2.0 - 6.5		285	●	265							180	●	150	●	120	●	215	
	160612 MT✓	0.25 - 0.55	2.0 - 6.5						●	●				●	●	●	●	●	●	235	
	160616 MT✓	0.30 - 0.55	2.0 - 6.5						●	●				●	●	●	●	●	●	110	
	190608 MT	0.23 - 0.55	3.0 - 8.0						●	●				●	●	●	●	●	●		
	190612 MT	0.25 - 0.55	3.0 - 8.0						●	●				●	●	●	●	●	●		
	190616 MT✓	0.30 - 0.55	3.0 - 8.0						●	●				●	●	●	●	●	●		


• For toolholders, see page A84, A85, A98, A99, A128, A136, A149, A154, A162

• For dimensions, see page A23

✓ Marked: Old type chipbreaker

● Marked: Standard Items

Negative 80° Rhombic Inserts




- P Carbon Steel C: 0.45%
- M Austenitic Stainless Steel
- K High Tensile Cast Iron
- N Aluminum
- S Inconel
- H Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated			
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						PVD Coated			Uncoated								
				PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	F20	K10	K20
<i>New</i> 	For Medium	CNMG 090308 PC	0.10 - 0.25	0.6 - 2.0				●	●													
		120404 PC	0.10 - 0.40	0.4 - 5.0				●	●													
		120408 PC	0.15 - 0.50	0.5 - 5.0				●	●													
		120412 PC	0.17 - 0.55	0.6 - 5.0				●	●													
		120416 PC	0.20 - 0.60	0.8 - 5.0				●	●													
		160608 PC	0.20 - 0.55	2.0 - 6.5				●	310	250	195	70	50	40	215					30		
		160612 PC	0.25 - 0.55	2.0 - 6.5				●	●			180	150	120						140		
		160616 PC	0.30 - 0.55	2.0 - 6.5				●														
		190608 PC	0.23 - 0.55	3.0 - 8.0				●	●													
		190612 PC	0.25 - 0.55	3.0 - 8.0				●	●													
		190616 PC	0.30 - 0.55	3.0 - 8.0				●	●													
	For Roughing	CNMG 120408 RT	0.25 - 0.70	2.5 - 6.0				●	●	●	●	●	●	●	●	●	●	●	●			
		120412 RT	0.25 - 0.70	2.5 - 6.0				●	●	●	●	●	●	●	●	●	●	●	●			
		120416 RT	0.30 - 0.70	2.5 - 6.0				●	●													
		160612 RT	0.25 - 0.70	3.0 - 7.0				●	●	●	●	●	●	●	●	●	●	●	●			
		160616 RT	0.30 - 0.85	3.0 - 7.0				●	330	250	290	265	195	70	50	40	205	170	140			
		190608 RT	0.25 - 0.70	3.0 - 9.0				●	●	●	●	●	●	●	●	●	●	●	●			
		190612 RT	0.25 - 0.70	3.0 - 9.0				●	●	●	●	●	●	●	●	●	●	●	●			
		190616 RT	0.30 - 0.85	3.0 - 9.0				●	●	●	●	●	●	●	●	●	●	●	●			
		250924 RT	0.45 - 1.00	5.0 - 12.0				●	●	●	●											
	For Finishing	CNMG 120404 SF	0.08 - 0.25	0.5 - 1.5				340								240		60	30			
		120408 SF	0.10 - 0.30	0.7 - 1.5		●			340	310						●		260	130			
	For Finishing	CNMG 120404 WS	0.05 - 0.35	0.5 - 2.0				325	270			325	280									
		120408 WT	0.15 - 0.60	1.0 - 5.0				●	280	●						70	160	195				
	For Medium	120412 WT	0.20 - 0.80	1.0 - 5.0				●	240	345	240	280	250			●						

- For toolholders, see page A84, A85, A98, A99, A128, A136, A149, A154, A162
- For dimensions, see page A23
- Marked: Standard Items

Negative 80° Rhombic Inserts



Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated			
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated			F20	K10	K20		
				PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080			
For Heavy	CNMM 190612 HT	0.35 - 0.9	4.0 - 9.0					●	●	●				●								
	190616 HT	0.45 - 1.0	4.0 - 9.0					●	●	●												
	190624 HT	0.55 - 1.2	4.0 - 9.0					●	270	245	170			50		190	150					
	250724 HT	0.55 - 1.3	5.0 - 12.0					●	●	●			●	120								
	250924 HT	0.55 - 1.3	5.0 - 12.0					●	●	●					●							
	250932 HT	0.65 - 1.3	5.0 - 13.0					●														
New For Heavy	CNMM 190624 HY	0.50 - 1.10	4.0 - 12.0					●	●													
	250924 HY	0.55 - 1.50	4.0 - 15.0						260	235												
New For Heavy	CNMM 250924 HZ	0.55 - 1.50	4.0 - 15.0					●	260	235												
RH(N) RH For Roughing	CNMM 120408 RH	0.30 - 0.70	2.5 - 6.0					●	●					●								
	120408 RH(N)	0.25 - 0.60	2.0 - 5.0						●	●				●								
	120412 RH	0.30 - 0.80	2.5 - 6.0					●	●				●									
	160608 RH	0.30 - 0.70	3.0 - 8.0						●	●												
	160612 RH	0.30 - 0.80	3.0 - 8.0					●	●													
	160616 RH	0.45 - 1.00	4.0 - 8.0						●	●												
	190608 RH *	0.30 - 0.70	3.0 - 9.0						●	●												
	190612 RH	0.35 - 0.80	4.0 - 9.0					●	270	245	170			50	40	190	150					
	190612 RH(N)	0.30 - 0.70	3.0 - 8.0											120	100							
	190616 RH	0.45 - 1.00	4.0 - 9.0					●	●	●			●	●	●							
	190616 RH(N)	0.45 - 0.90	3.0 - 8.0																			
	190624 RH	0.55 - 1.20	4.0 - 9.0					●	●	●			●	●	●							
	250724 RH *	0.55 - 1.20	5.0 - 12.0						●													
	250924 RH *	0.55 - 1.20	5.0 - 12.0										●									
New For Roughing	CNMM 120408 RX	0.20 - 0.55	0.7 - 7.0					●	●	●												
	120412 RX	0.25 - 0.70	1.0 - 7.0					●	●	●												
	160612 RX	0.25 - 0.70	1.0 - 9.0					●	●	●												
	160616 RX	0.30 - 0.90	1.5 - 9.0					●	●	●												
	160624 RX	0.35 - 1.20	2.0 - 9.0					●	●	●												
	190608 RX	0.20 - 0.55	0.7 - 10.0					●	270	245	170											
	190612 RX	0.25 - 0.70	1.0 - 10.0					●	●	●												
	190616 RX	0.30 - 0.90	1.5 - 10.0					●	●	●												
	190624 RX	0.35 - 1.10	2.0 - 10.0					●	●	●												
	250724 RX	0.35 - 1.20	2.0 - 12.0					●	●	●												
	250924 RX	0.35 - 1.20	2.0 - 12.0					●	●	●												


• For toolholders, see page A84, A85, A98, A99, A128, A136, A149, A154, A162

● Marked: Standard Items

• For dimensions, see page A23

* Marked: Chipbreaker shape is not the same as shown in the catalogue.

Negative 55° Rhombic Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)																	
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						PVD Coated			Uncoated							
		PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20	
For Medium	DNGG 150401 ML	0.03 - 0.10	1.0 - 1.0																●	●	
	150402 ML	0.05 - 0.15	0.2 - 1.2																● 70	● 250	
	150404 ML	0.10 - 0.30	0.8 - 3.5																●		
	150408 ML	0.12 - 0.35	1.0 - 3.5																		
For Roughing	DNMA 110408 *	0.15 - 0.50	0.8 - 3.0																		
	110412 *	0.15 - 0.50	0.8 - 3.0																		
	150404	0.15 - 0.50	0.4 - 4.0																		
	150604	0.15 - 0.50	0.4 - 4.0																		
	150408	0.15 - 0.65	0.8 - 4.0																		
	150608	0.15 - 0.65	0.8 - 4.0																		
	150412	0.15 - 0.65	1.2 - 4.0																		
	150612	0.15 - 0.65	1.2 - 4.0																		
For Medium	DNMG 150404	0.17 - 0.45	1.0 - 4.0																		
	150604	0.17 - 0.45	1.0 - 4.0																		
	150408	0.17 - 0.55	1.5 - 4.0																		
	150608	0.17 - 0.55	1.5 - 4.0																		
	150412	0.25 - 0.55	1.5 - 4.0																		
	150612	0.25 - 0.55	1.5 - 4.0																		
	150416	0.25 - 0.65	2.5 - 4.0																		
	150616	0.25 - 0.65	2.5 - 4.0																		
For Finishing	DNMG 150404 EA	0.05 - 0.2	0.1 - 1.5																●	●	
	150408 EA	0.10 - 0.4	0.1 - 1.5																● 60	● 30	
	150604 EA	0.05 - 0.2	0.1 - 1.5																● 260	● 140	
	150608 EA	0.10 - 0.4	0.1 - 1.5																●	●	
For Medium	DNMG 110408 EM *	0.13 - 0.50	0.5 - 4.0																		
	150408 EM	0.13 - 0.50	0.5 - 5.0																		
	150608 EM	0.13 - 0.50	0.5 - 5.0																		
	150412 EM	0.15 - 0.55	0.5 - 5.0																		
	150612 EM	0.15 - 0.55	0.5 - 5.0																		
For Finishing	DNMG 150408 FA	0.05 - 0.20	0.2 - 2.0																		
	150608 FA	0.05 - 0.20	0.2 - 2.0																		
For Finishing	DNMG 110404 FC	0.07 - 0.20	0.5 - 2.0	●	●																
	110408 FC	0.10 - 0.25	0.7 - 2.0	●	●																
	150404 FC	0.05 - 0.30	0.2 - 2.5	●	●																
	150604 FC	0.05 - 0.30	0.2 - 2.5	● 360	● 340																
	150408 FC	0.08 - 0.35	0.3 - 2.5	● 300	● 270																
	150608 FC	0.08 - 0.35	0.3 - 2.5	●	●																
	150412 FC	0.08 - 0.35	0.5 - 2.5	●	●																
	150612 FC	0.08 - 0.35	0.5 - 2.5	●	●																
For Finishing	DNMG 110404 FG *	0.07 - 0.20	0.5 - 2.0	●	●													●	●		
	110408 FG *	0.10 - 0.25	0.7 - 2.0	●	●													●	●		
	150404 FG	0.07 - 0.20	0.5 - 2.0	● 360	● 340																
	150604 FG	0.07 - 0.20	0.5 - 2.0	● 300	● 270																
	150408 FG ✓	0.10 - 0.25	0.7 - 2.0	●	●																
	150412 FG	0.12 - 0.25	1.0 - 2.0	●	●																
For Finishing	150608 FG ✓	0.10 - 0.25	0.7 - 2.0	●	●																

• For toolholders, see page A81, A82, A85, A86, A92, A93, A99, A128, A136, A140, A141, A142, A149, A154


● Marked: Standard Items

• For dimensions, see page A23

* Marked: Insert with screw hole

✓ Marked: Old type chipbreaker

Negative 55° Rhombic Inserts



Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)										P20	K10	K20				
		feed (mm/rev)	ap (mm)	PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	
For Medium	DNMG 150604 MC	0.10 - 0.30	0.5 - 3.5					●	●					●						
	150408 MC	0.12 - 0.35	0.7 - 3.5					●	●					●						
	150412 MC	0.15 - 0.35	1.0 - 3.5					310	280	195				215	170		150			
	150608 MC	0.12 - 0.35	0.7 - 3.5					●	●	●				●	●		●			
	150612 MC	0.15 - 0.35	1.0 - 3.5					●						●						
For Medium	DNMG 150404 ML	0.10 - 0.30	0.8 - 3.5					●	●	●	●			●	●					
	150604 ML	0.10 - 0.30	0.8 - 3.5					●	340	310				●	●	●	●	●	●	
	150408 ML	0.12 - 0.35	1.0 - 3.5					●	●	●	●	●	●	●	●	●	●	●	●	
	150608 ML	0.12 - 0.35	1.0 - 3.5					●	●	●	●	●	●	●	●	●	●	●	●	
For Medium	DNMG 150404 MP	0.10 - 0.30	0.8 - 4.0					●			●			●						
	150604 MP	0.10 - 0.30	0.8 - 4.0					●			●			●						
	150408 MP	0.12 - 0.40	1.0 - 4.0					●	330	300	70	50	40	●	●	●	●	●	●	
	150608 MP	0.12 - 0.40	1.0 - 4.0					●	●	●	●	●	●	●	●	●	●	●	●	
	150612 MP ✓	0.15 - 0.40	1.0 - 4.0					●			●	●	●	●	●	●	●	●	●	
For Medium	DNMG 110408 MT *	0.17 - 0.40	1.0 - 3.0					●	●	●	●			●						
	110412 MT *	0.20 - 0.45	1.0 - 3.0					●			●			●						
	150404 MT	0.15 - 0.40	0.8 - 4.0					●			●			●						
	150604 MT	0.15 - 0.40	0.8 - 4.0					●	310	380	265	310	280	195	70	50	40	●	●	
	150408 MT	0.17 - 0.50	1.0 - 4.0					●	265	265	265	310	280	195	180	150	120	215	180	235
	150608 MT	0.17 - 0.50	1.0 - 4.0					●	●	●	●	●	●	●	●	●	●	●	●	
	150412 MT	0.20 - 0.50	1.3 - 4.0					●			●			●						
	150612 MT	0.20 - 0.50	1.3 - 4.0					●			●			●						
New For Medium	DNMG 110408 PC *	0.17 - 0.40	0.5 - 3.0					●	●	●	●			●						
	150404 PC	0.10 - 0.40	0.4 - 4.0					●			●			●						
	150604 PC	0.10 - 0.40	0.4 - 4.0					●			●			●						
	150408 PC	0.15 - 0.50	0.5 - 4.0					●	330	300	70	50	40	●	●	●	●	●	●	
	150608 PC	0.15 - 0.50	0.5 - 4.0					●			●			●						
	150412 PC	0.17 - 0.55	0.6 - 4.0					●			●			●						
	150612 PC	0.17 - 0.55	0.6 - 4.0					●			●			●						
For Roughing	DNMG 150408 RT	0.25 - 0.65	2.0 - 4.0					●			●			●						
	150608 RT	0.25 - 0.65	2.0 - 4.0					●	●	●	●			●						
	150412 RT	0.25 - 0.65	2.5 - 4.0					330	250	290	265	195					205			
	150612 RT	0.25 - 0.65	2.5 - 4.0					●	●	●	●	●	●	●	●	●	●	●		
	150616 RT	0.25 - 0.70	2.5 - 5.5					●		●	●			●			●			
Right Hand Shown For Medium	DNMG 150404 L-VF	0.10 - 0.35	0.7 - 4.5					●			●			●						
	150404 R-VF	0.10 - 0.35	0.7 - 4.5					●			●			●			●			
	150604 L-VF	0.10 - 0.35	0.7 - 4.5					●			●			●			●			
	150604 R-VF	0.10 - 0.35	0.7 - 4.5					●	340	340	310			●			●			
	150408 L-VF	0.12 - 0.45	1.0 - 4.5					●	340	310	310			●		240	170			
	150408 R-VF	0.12 - 0.45	1.0 - 4.5					●			●			●						
	150608 L-VF	0.12 - 0.45	1.0 - 4.5					●			●			●						
	150608 R-VF	0.12 - 0.45	1.0 - 4.5					●			●			●						
Wiper For Finishing	DNMG 150408 WS	0.10 - 0.30	0.8 - 4.0					●	310		●			●	50					
	150608 WS	0.10 - 0.30	0.8 - 4.0					●	265		●	310	280	●	150					
								●			●			●						
Wiper For Medium	DNMG 150412 WT	0.15 - 0.60	1.0 - 5.0					240		280	250			195						
	150612 WT	0.15 - 0.60	1.0 - 5.0					280		280	250			195						

• For toolholders, see page A81, A82, A85, A86, A92, A93, A99, A128, A136, A140, A141, A142, A149, A154


● Marked: Standard Items

• For dimensions, see page A23

* Marked: Insert with screw hole

✓ Marked: Old type chipbreaker

Negative 120° Hexagonal Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel


Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												Uncoated				
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated					
		PV3010	CT3000	TT1300	TT730	TT815	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
For Medium	HNMG 050408 GU	0.15 - 0.60	0.5 - 3.5			●	●													
	100612 GU	0.25 - 0.70	1.0 - 5.0			275	245	280									215			
For Medium	HNMG 050408 SU	0.15 - 0.50	0.5 - 3.5														●	60		
	100612 SU	0.25 - 0.70	1.0 - 5.0														215	160		

• For toolholders, see page A100, A149

• For dimensions, see page A23

● Marked: Standard Items

Negative 55° Rhombic Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel


Insert	Designation	Recommended Machining Conditions		Grades & Vc (m/min)												Uncoated				
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated					
		PV3010	CT3000	TT1300	TT730	TT815	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
Right Hand Shown For Medium	KNUX 160405 L11	0.15 - 0.35	1.5 - 5.0			●	●	●				●	●							
	160405 R11	0.15 - 0.35	1.5 - 5.0		●	270	●	320				●	●	●	●	●	●	●	●	●
	160410 L11	0.21 - 0.45	2.0 - 5.0		230		●	●	●	●		●	●	●	●	●	●	●	●	●
	160410 R11	0.21 - 0.45	2.0 - 5.0				●	●	●			●	●	●	●	●	●	●	●	●
Right Hand Shown For Roughing	KNUX 160405 L12	0.24 - 0.50	2.0 - 5.0									●								
	160405 R12	0.24 - 0.50	2.0 - 5.0					320				●	●	●	●	●	●	●	●	●
	160410 L12	0.30 - 0.60	2.5 - 6.0						●	●	●	●	●	●	●	●	●	●	●	●
	160410 R12	0.30 - 0.60	2.5 - 6.0						●	●	●	●	●	●	●	●	●	●	●	●

• For toolholders, see page A79, A80, A134

• For dimensions, see page A23

● Marked: Standard Items

Negative Round Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel


Insert	Designation	Recommended Machining Conditions		Grades & Vc (m/min)												Uncoated				
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated					
		PV3010	CT3000	TT1300	TT730	TT815	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
For Roughing	RNMG 120400	0.30 - 0.60	2.0 - 5.0									●								
	150600	0.35 - 0.70	3.5 - 7.0					330				●	●							
	190600	0.45 - 0.80	4.5 - 9.0						290	265	195									
	250900	0.55 - 1.20	4.0 - 12.0												205					
	310900	0.65 - 1.20	5.5 - 14.0																	

• For toolholders, see page A87

• For dimensions, see page A23

● Marked: Standard Items

Negative Square Inserts




P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated			
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated			F20	K10	K20		
				PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080			
Right Hand Shown For Medium	SNGG 090304 L 090308 L 090308 R 120404 L 120404 R 120408 L 120408 R	0.12 - 0.35	1.0 - 3.0	●																		
		0.15 - 0.40	1.0 - 3.0																			
		0.15 - 0.35	1.0 - 3.0		270																	
		0.15 - 0.35	1.0 - 4.0		200															150		
		0.12 - 0.35	1.0 - 4.0	●																		
		0.15 - 0.40	1.0 - 4.0																			
		0.15 - 0.35	1.0 - 4.0	●																●		
For Roughing	SNMA 120408 120412 120416 150612 150616 190612 190616 250716 250724	0.15 - 0.70	1.0 - 6.0		●	●														●		
		0.20 - 0.80	1.5 - 6.0		●	●																
		0.30 - 1.00	2.0 - 6.0			●																
		0.20 - 0.80	2.0 - 8.0		●																	
		0.30 - 1.00	2.0 - 8.0		330	250	280													150		
		0.20 - 0.80	2.0 - 10.0		●	●																
		0.30 - 1.00	2.0 - 10.0			●																
		0.30 - 1.00	3.0 - 13.0																			
		0.40 - 1.20	3.0 - 13.0		●	●																
For Medium	SNMG 090304 090308 120404 120408 120412 120416 150608 150612 150616 190604 190608 190612 190616 190616 250716 250724 250924	0.17 - 0.45	0.8 - 3.5	●					●						●							
		0.20 - 0.50	1.0 - 3.5	●				●	●						●							
		0.17 - 0.45	1.0 - 5.0	●			●	●	●	●	●				●							
		0.23 - 0.60	1.5 - 5.0	●	●	●	●	●	●	●					●							
		0.25 - 0.60	2.0 - 5.0	●	●	●		●							●							
		0.35 - 0.70	2.0 - 5.0					●							●							
		0.25 - 0.60	1.5 - 6.0												●							
		0.25 - 0.60	2.0 - 6.0	290	330	250	290	●	265	195					205	170	140		190	150	120	
		0.35 - 0.70	2.0 - 6.0	250				●														
		0.17 - 0.45	3.0 - 8.0																			
		0.25 - 0.60	3.0 - 8.0		●	●	●	●	●	●					●							
		0.30 - 0.60	3.0 - 8.0		●	●	●	●	●	●					●							
		0.35 - 0.70	3.0 - 8.0					●	●						●							
		0.35 - 0.70	4.0 - 12.0					●	●	●					●							
		0.50 - 1.00	5.0 - 12.0					●	●	●					●							
		0.50 - 1.00	5.0 - 12.0					●	●	●					●							
New For Finishing	SNMG 120404 EA 120408 EA	0.05 - 0.2	0.1 - 1.5									●	70	50	40	●	60	●	30			
		0.1 - 0.4	0.1 - 1.5									●	200	170	140	●	260	●	140			
New For Medium	SNMG 120408 EM 120412 EM 150612 EM 150616 EM 190612 EM 190616 EM	0.13 - 0.50	0.8 - 5.0									●	●	●		●		●				
		0.15 - 0.55	0.8 - 5.0									●	●	●		●		●				
		0.15 - 0.55	0.8 - 6.5									70	50	40		50		30				
		0.17 - 0.60	0.8 - 6.5									180	150	120		250		140				
		0.15 - 0.55	0.8 - 8.0																			
		0.17 - 0.60	0.8 - 8.0																			
New For Finishing	SNMG 090304 FC 090308 FC 120404 FC 120408 FC 120412 FC	0.07 - 0.20	0.5 - 2.0	●					●	●					●							
		0.10 - 0.25	0.7 - 2.0	350	340				●	●					●							
		0.05 - 0.30	0.2 - 2.5	300	270				●	310					●	50	220					
		0.08 - 0.35	0.2 - 2.5					●		●					●	170						
		0.10 - 0.40	0.3 - 2.5					●		●					●							

- For toolholders, see page A88, A89, A100, A101, A128, A129, A150, A162
- For dimensions, see page A23

● Marked: Standard Items

Negative Square Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)																
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						PVD Coated			Uncoated						
		PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
For Finishing	SNMG 090304 FG	0.07 - 0.20	0.5 - 2.0																	
	090308 FG	0.10 - 0.25	0.7 - 2.0		340												60			
	120404 FG ✓	0.07 - 0.20	0.5 - 3.0	● 270			340	310	●						240		260			
	120408 FG ✓	0.10 - 0.25	0.7 - 3.0	●	●			●	●											
For Medium	SNMG 120408 MC	0.12 - 0.35	0.7 - 3.5			●	●								215		150			
	120412 MC	0.15 - 0.40	0.7 - 3.5				310	280												
For Medium	SNMG 120408 ML	0.12 - 0.35	1.0 - 3.5			●	●	340	310					●	240	240	190		600	
	120412 ML	0.15 - 0.35	1.0 - 3.5				●										130			
For Medium	SNMG 120404 MP ✓	0.10 - 0.30	0.8 - 4.0					●												
	120408 MP	0.12 - 0.40	1.0 - 4.0					●	●											
	120412 MP	0.15 - 0.40	1.3 - 4.0				330	300							70	50	40	225		
	150608 MP	0.25 - 0.60	1.5 - 6.0				●								60	180	250	120		
For Medium	SNMG 090308 MT	0.15 - 0.45	1.0 - 3.5					●	●											
	120404 MT ✓	0.12 - 0.40	1.0 - 5.0	●				●	●											
	120408 MT	0.17 - 0.55	1.2 - 5.0	● 310	●	●	●	●												
	120412 MT ✓	0.20 - 0.55	1.5 - 5.0	● 265	385	265	● 310	280	195	●					50	40	215	60	150	
	150612 MT ✓	0.30 - 0.65	2.0 - 7.0												150	120		235	110	
	190608 MT	0.17 - 0.55	3.0 - 8.0																	
	190612 MT	0.20 - 0.55	3.0 - 8.0																	
For Medium	SNMG 090308 PC	0.10 - 0.25	0.6 - 2.0						●											
	120404 PC	0.12 - 0.40	0.4 - 5.0						●	●						50		220		
	120408 PC	0.15 - 0.50	0.5 - 5.0				340	310							150					
	120412 PC	0.15 - 0.50	0.6 - 5.0				●	●												
For Roughing	SNMG 120408 RT	0.25 - 0.70	2.5 - 6.0					●	●											
	120412 RT	0.30 - 0.70	2.5 - 6.0			●	●	●	●											
	120416 RT	0.40 - 0.70	2.5 - 6.0			●	●	●	●											
	150612 RT	0.30 - 0.70	3.0 - 7.0		330	250	290	265	195						50	40	205			
	190612 RT	0.30 - 0.75	3.0 - 9.0		● 120	● 100	● 265	● 195							120	100	205	140		
	190616 RT	0.40 - 0.90	3.0 - 9.0		●	●	●	●							●	●	●	●		
	250724 RT	0.40 - 1.00	5.0 - 12.0																	
	250924 RT	0.40 - 1.00	5.0 - 12.0																	
For Heavy	SNMM 190612 HT	0.35 - 0.9	4.0 - 9.0					●	●	●										
	190616 HT	0.45 - 1.0	4.0 - 9.0					●	●	●										
	190624 HT	0.55 - 1.2	4.0 - 9.0				● 270	● 245	● 170						50		190	150		
	250724 HT	0.55 - 1.3	5.0 - 12.0				●	●	●						120		● 190	● 150		
	250924 HT	0.55 - 1.3	5.0 - 12.0				●	●	●											
	250932 HT	0.65 - 1.3	5.0 - 13.0																	

• For toolholders, see page A88, A89, A100, A101, A128, A129, A150, A162

• For dimensions, see page A23

✓ Marked: Old type chipbreaker

● Marked: Standard Items

Negative Square Inserts

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)																							
		feed (mm/rev)	ap (mm)	PV3010 Cermet	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20					
For Heavy	SNMM 190624 HY	0.50 - 1.10	4.0 - 12.0					●	●																		
		0.55 - 1.50	4.0 - 15.0					●	●	280	235																
For Heavy	SNMM 250924 HZ	0.55 - 1.50	4.0 - 15.0					●	●	280	235																
RH For Roughing	SNMM 120408 RH 120408 RH(N) 120412 RH 120412 RH(N) 150612 RH 190608 RH *190612 RH 190612 RH(N) 190616 RH 190616 RH(N) 190624 RH 250716 RH *250724 RH *250924 RH *	0.30 - 0.70	2.5 - 6.0							●																	
		0.25 - 0.60	2.5 - 5.0																								
		0.30 - 0.80	2.5 - 6.0							●																	
		0.30 - 0.70	3.0 - 5.0																								
		0.30 - 0.80	3.0 - 7.0																								
		0.30 - 0.70	3.0 - 9.0																								
		0.30 - 0.80	4.0 - 9.0							270	245	170					40	30									
		0.30 - 0.70	3.0 - 8.0								120	100					190	150									
		0.45 - 1.00	4.0 - 9.0																								
		0.40 - 0.90	3.0 - 8.0																								
For Roughing	SNMM 190612 RX 120412 RX 150612 RX 190612 RX 190616 RX 190624 RX 250724 RX 250924 RX	0.20 - 0.55	0.7 - 7.0							●	●	●															
		0.25 - 0.70	1.0 - 7.0							●	●	●															
		0.25 - 0.70	1.0 - 9.0							●	●	●															
		0.25 - 0.70	1.0 - 10.0							270	245	170															
		0.30 - 0.90	1.5 - 10.0							●	●	●															
		0.35 - 1.10	2.0 - 10.0							●	●	●															
		0.35 - 1.20	2.0 - 12.0							●	●	●															
		0.35 - 1.20	2.0 - 12.0							●	●	●															

• For toolholders, see page A88, A89, A100, A101, A128, A129, A150, A162

• For dimensions, see page A23

* Marked: Chipbreaker shape is not the same as shown in the catalogue.

P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Negative Triangular Inserts


Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)																						
		feed (mm/rev)	ap (mm)	PV3010 Cermet	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P10	P20	K10				
Left Hand Shown For Medium	TNGG 160404 L 160404 R 160408 L 160408 R 220404 L 220404 R 220408 L 220408 R	0.12 - 0.30	1.0 - 3.5	●					●													●				
		0.12 - 0.30	1.0 - 3.5	●					●													●				
		0.15 - 0.35	1.3 - 3.5	●					●																	
		0.15 - 0.35	1.3 - 3.5	●	290				●																	
		0.12 - 0.30	1.0 - 5.0	●	290				●																	
		0.12 - 0.30	1.0 - 5.0	●					●																	
		0.15 - 0.35	1.3 - 5.0	●					●																	
		0.15 - 0.35	1.3 - 5.0	●					●																	

• For toolholders, see page A82, A90, A101, A102, A103, A129, A137, A148, A155, A163

• For dimensions, see page A23

• Marked: Standard Items

Negative Triangular Inserts




Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)																		
		feed (mm/rev)	ap (mm)	PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
For Roughing	TNMA 110304	0.15 - 0.30	0.5 - 2.0																			
	160404	0.15 - 0.30	1.0 - 4.0			●	●													●	●	
	160408	0.15 - 0.40	1.0 - 4.0			●	●															
	160412	0.20 - 0.50	1.5 - 4.5				●															
	160416	0.20 - 0.50	1.0 - 4.5		250	330	250													150		
	220404	0.15 - 0.30	1.5 - 5.0																			
	220408	0.15 - 0.40	1.5 - 5.0			●	●	●														
	220412	0.20 - 0.50	1.5 - 5.0			●														●		
	220416	0.20 - 0.61	2.0 - 5.0																			
For Medium	TNMG 110304	0.15 - 0.40	1.2 - 3.0							●												
	110308	0.17 - 0.40	1.5 - 3.0																			
	160404	0.17 - 0.45	1.5 - 3.5	●	●	●	●	●	●										●	●		
	160408	0.17 - 0.55	2.0 - 3.5	●	●	●	●	●	●													
	160412	0.25 - 0.55	2.0 - 3.5			●																
	220404	0.17 - 0.45	1.5 - 5.0				●	●	●													
	220408	0.17 - 0.55	2.0 - 5.0		290	●	330	250	265	235	195											
	220412	0.25 - 0.55	2.0 - 5.0		250	●	330	250	265	235	195											
	220416	0.30 - 0.60	2.0 - 5.0			●	●	●	●	●												
	270608	0.17 - 0.55	2.0 - 5.0				●	●	●	●	●											
	270612	0.25 - 0.55	3.0 - 7.0					●	●	●	●											
	270616	0.30 - 0.60	3.0 - 7.0						●	●	●											
	330716	0.35 - 0.70	3.0 - 9.0						●	●	●											
	330924	0.40 - 0.80	3.0 - 9.0																			
For Finishing	TNMG 160404 EA	0.05 - 0.2	0.1 - 1.5									●	60	●	40	●	30					
	160408 EA	0.10 - 0.4	0.1 - 1.5									●	200	●	170	●	140		●	260	●	130
For Medium	TNMG 160408 EM	0.13 - 0.50	0.8 - 4.5									●	70	●	50	●	40					
	160412 EM	0.15 - 0.55	0.8 - 4.5									●	180	●	150	●	120		●	60	●	30
	220408 EM	0.13 - 0.50	0.8 - 6.0									●							250		130	
	220412 EM	0.15 - 0.55	0.8 - 6.0									●										
For Finishing	TNMG 160404 FC	0.05 - 0.30	0.2 - 2.5	●				●	●				●									
	160408 FC	0.08 - 0.35	0.2 - 2.5		340		270			●	310	●	310	●		●	170	●	140		●	30
	160412 FC	0.10 - 0.40	0.3 - 2.5			●		●	●	●	●	●	●	●	●	●	●				●	130
For Finishing	TNMG 110304 FG	0.07 - 0.20	0.5 - 1.5	●														●				
	160404 FG	0.07 - 0.20	0.5 - 2.0	●	360	●	340			●	●							●				
	160408 FG	0.10 - 0.25	0.7 - 2.0	●	300	●	270			●	340	●	310					●	240			
	160412 FG	0.13 - 0.30	0.7 - 2.0							●	●											
	220408 FG	0.10 - 0.25	0.7 - 2.0							●	●											
Right hand shown For Medium	TNMG 160404 L-FS	0.15 - 0.30	0.8 - 3.0	●				●									●					
	160404 R-FS	0.15 - 0.30	0.8 - 3.0	●	340			●									●	240		●	190	
	160408 L-FS	0.20 - 0.40	1.0 - 3.5					●	310									●	240		130	
	160408 R-FS	0.20 - 0.40	1.0 - 3.5					●	310	●	280						●	215		●	150	
For Medium	TNMG 160408 MC	0.17 - 0.40	0.7 - 3.5					●	310	●	280						●	215		●	150	

• For toolholders, see page A82, A90, A101, A102, A103, A129, A137, A148, A155, A163

• For dimensions, see page A23

• Marked: Standard Items

Negative Triangular Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel


Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)																
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated					PVD Coated			Uncoated							
		PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	F20	K10	K20
For Medium	TNMG 160404 ML	0.10 - 0.30	0.8 - 3.5																	
	160408 ML	0.12 - 0.35	1.0 - 3.5																	
	160412 ML	0.15 - 0.35	1.5 - 3.5				●	●												
	220404 ML	0.10 - 0.30	1.0 - 4.0			●	340	310	220											
	220408 ML	0.12 - 0.35	1.0 - 4.0			●														
For Medium	TNMG 160404 MP	0.10 - 0.30	0.8 - 3.5																	
	160408 MP	0.12 - 0.40	1.0 - 3.5																	
	160412 MP	0.15 - 0.40	1.5 - 3.5				●	●												
	220404 MP	0.12 - 0.35	1.0 - 3.5			●	330	300												
	220408 MP	0.12 - 0.40	1.0 - 4.0			●														
	220412 MP	0.15 - 0.40	1.0 - 4.0			●														
For Medium	TNMG 110308 MT	0.17 - 0.40	1.0 - 3.0						●											
	160404 MT	0.17 - 0.40	1.0 - 3.5	●	●	●	●	●												
	160408 MT	0.17 - 0.50	1.2 - 3.5	●	●	●	●	●												
	160412 MT	0.20 - 0.50	1.5 - 3.5	330	310	310	●	●												
	220404 MT ✓	0.15 - 0.40	1.2 - 5.0	285	265	385	265	280	215	195	●	50	40	●	215	60	150			
	220408 MT ✓	0.17 - 0.50	1.2 - 5.0			●	●	●			●	150	120	●		235	●	110		
	220412 MT	0.20 - 0.50	1.5 - 5.0			●	●	●			●									
For Medium	TNMG 160404 PC	0.15 - 0.40	1.0 - 3.5						●	●								●		
	160408 PC	0.15 - 0.50	0.5 - 4.5						●	●							●	●	30	
	160412 PC	0.17 - 0.55	0.6 - 4.5						●	340	310	195	●	50	40	●	215		●	
	220408 PC	0.17 - 0.50	1.2 - 5.0						●	●	●		●	150	120	●	215		140	
	220412 PC	0.20 - 0.50	1.5 - 5.0						●	●	●		●							
For Roughing	TNMG 160408 RT	0.25 - 0.65	2.0 - 5.0				●													
	160412 RT	0.25 - 0.65	2.0 - 5.0			●														
	220408 RT	0.25 - 0.65	2.0 - 7.0	330	250		●	265								205				
	220412 RT	0.25 - 0.65	2.5 - 7.0			●	●													
	330924 RT	0.35 - 0.70	3.0 - 9.0			●	●													
For Finishing	TNMG 160408 SF	0.10 - 0.30	0.7 - 1.5	●	340				340	310				●	240	●	60	260		
Right hand shown For Medium	TNMG 160404 L-VF	0.10 - 0.30	0.7 - 3.5	●					●	●					●					
	160404 R-VF	0.10 - 0.30	0.7 - 3.5	●	●	340			●	340	310				●	240				
	160408 L-VF	0.12 - 0.35	1.0 - 3.5						●	●	●				●					
	160408 R-VF	0.12 - 0.35	1.0 - 3.5						●	●	●				●					
For Roughing	TNMM 160408 RH	0.30 - 0.70	2.0 - 7.0						●	●										
	220408 RH	0.30 - 0.70	2.0 - 7.0						●	●										
	220412 RH	0.30 - 0.70	2.5 - 7.0						●	270	245					190				
	220416 RH	0.40 - 0.85	3.0 - 7.0						●	●	●									
	270612 RH	0.30 - 0.80	3.0 - 8.0						●	●	●									
For Roughing	TNMM 160408 RX	0.20 - 0.55	0.7 - 6.0						●	●	●									
	160412 RX	0.25 - 0.70	1.0 - 7.0						●	●	●									
	220408 RX	0.20 - 0.55	0.7 - 7.5						●	270	245	170								
	220412 RX	0.25 - 0.70	1.0 - 7.5						●	●	●									
	220416 RX	0.30 - 0.90	1.5 - 7.5						●	●	●									

- For toolholders, see page A82, A90, A101, A102, A103, A129, A137, A148, A155, A163
- For dimensions, see page A23

● Marked: Standard Items

✓ Marked: Old type chipbreaker

Negative 35° Rhombic Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												Uncoated		
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						PVD Coated			Uncoated		P20	K10	K20
For Medium	VNGG 160401 ML	0.03 - 0.10	0.1 - 1.0															
	160402 ML	0.05 - 0.15	0.2 - 1.2															
	160404 ML	0.10 - 0.27	0.8 - 3.0															
	160408 ML	0.10 - 0.30	0.8 - 3.5															
For Medium	VNMG 160404	0.17 - 0.40	1.0 - 3.0		●	●	●	●	●	●								
	160408	0.17 - 0.50	1.5 - 3.0		● 290	● 330	● 250	● 290	● 265									
	160412	0.20 - 0.50	1.5 - 3.0		● 250													
For Finishing	VNMG 160404 EA	0.05 - 0.2	0.1 - 1.5															
	160408 EA	0.08 - 0.3	0.2 - 2.5															
New For Medium	VNMG 160408 EM	0.13 - 0.50	0.8 - 3.5															
For Finishing	VNMG 160408 FA	0.05 - 0.25	0.3 - 2.0		● 360	● 340												
					● 300	● 270												
For Finishing	VNMG 130404 FC	0.08 - 0.20	0.5 - 1.5		●													
	130408 FC	0.10 - 0.23	0.5 - 2.0		● 360	● 340												
	160404 FC	0.05 - 0.30	0.3 - 2.5		● 300	● 270												
	160408 FC	0.08 - 0.35	0.3 - 2.5		●	●												
For Finishing	VNMG 130404 FG *	0.08 - 0.20	0.5 - 1.5		●													
	130408 FG *	0.10 - 0.23	0.5 - 2.0		● 360	● 340												
	160404 FG	0.08 - 0.20	0.5 - 2.0		● 300	● 270												
	160408 FG	0.10 - 0.23	0.5 - 2.0		●	●												
For Medium	VNMM 160404 ML	0.10 - 0.27	0.8 - 3.0															
	160408 ML	0.12 - 0.32	1.0 - 3.0															
For Medium	VNMG 130404 MT *	0.15 - 0.36	0.8 - 2.5															
	130408 MT *	0.17 - 0.36	1.0 - 2.5			● 310		● 385										
	160404 MT ✓	0.15 - 0.36	0.8 - 3.0			● 265		● 310	● 280									
	160408 MT	0.17 - 0.36	1.0 - 2.5		●	●	●	●	●									
New For Medium	VNMG 160404 PC	0.15 - 0.36	0.4 - 3.0			●												
	160408 PC	0.17 - 0.36	0.5 - 3.0															

• For toolholders, see page A83, A97, A102, A129, A145


• For dimensions, see page A23

* Marked: Insert with screw hole

✓ Marked: Old type chipbreaker

● Marked: Standard Items

Negative 80° Trigon Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated		
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated						
		PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9335	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	F20	K10	K20	
For Roughing	WNMA 060408	0.15 - 0.70	1.0 - 4.0																		
	060412	0.20 - 0.80	1.5 - 4.0																		
	080408	0.15 - 0.70	1.0 - 5.0		● 330	● 250															
	080412	0.20 - 0.80	1.5 - 5.0		●																
	080416	0.20 - 0.80	1.5 - 5.0		●																
New For Finishing	WNMG 080404 EA	0.05 - 0.2	0.1 - 1.5												● 70	● 50	● 40	● 60	● 30		
	080408 EA	0.1 - 0.4	0.1 - 1.5												● 200	● 170	● 140	● 260	● 140		
New For Medium	WNMG 060408 EM	0.13 - 0.50	0.8 - 3.0												● 70	● 50	● 40	● 60	● 30		
	060412 EM	0.15 - 0.55	0.8 - 3.0												● 180	● 150	● 120	● 250	● 140		
	080404 EM	0.10 - 0.45	0.8 - 4.0												● 70	● 50	● 40	● 60	● 30		
	080408 EM	0.12 - 0.45	0.8 - 4.0												● 180	● 150	● 120	● 250	● 140		
	080412 EM	0.12 - 0.45	0.8 - 4.0												● 70	● 50	● 40	● 60	● 30		
For Roughing	WNMG 080408 ET	0.15 - 0.55	0.8 - 4.5												● 70	● 50	● 40	● 60	● 235		
New For Finishing	WNMG 060404 FC	0.07 - 0.20	0.5 - 2.0	●											● 70	● 50	● 40	● 60	● 30		
	060408 FC	0.10 - 0.25	0.5 - 2.0	360	340										● 70	● 50	● 40	● 60	● 30		
	080404 FC	0.07 - 0.20	0.5 - 2.0	300	270	● 340	● 280								● 160	● 130	● 100	● 240	● 200		
	080408 FC	0.07 - 0.20	0.5 - 2.0	●											● 70	● 50	● 40	● 60	● 30		
	080412 FC	0.10 - 0.25	0.5 - 2.0												● 160	● 130	● 100	● 240	● 200		
For Finishing	WNMG 060404 FG	0.07 - 0.20	0.5 - 2.0	●											● 70	● 50	● 40	● 60	● 30		
	060408 FG	0.10 - 0.25	0.7 - 2.0	● 360	● 340										● 340	● 310	● 280	● 240	● 200		
	080404 FG	0.07 - 0.20	0.5 - 2.0	● 300	● 270	●									● 70	● 50	● 40	● 60	● 30		
	080408 FG	0.10 - 0.25	0.7 - 2.0	●											● 160	● 130	● 100	● 240	● 200		
For Medium	WNMG 060404 MC	0.10 - 0.30	0.5 - 2.5																		
	060408 MC	0.12 - 0.35	0.7 - 3.0																		
	080408 MC	0.12 - 0.35	0.7 - 3.5																		
	080412 MC	0.15 - 0.40	0.7 - 3.5																		
For Medium	WNMG 080408 ML	0.12 - 0.35	1.0 - 3.5												● 70	● 50	● 40	● 60	● 180		
	080412 ML	0.15 - 0.35	1.3 - 3.5												● 340	● 310	● 280	● 220	● 180	● 600	
OLD For Medium	WNMG 060408 MP	0.12 - 0.35	1.0 - 3.0												● 70	● 50	● 40	● 60	● 180		
	060412 MP	0.15 - 0.40	1.3 - 3.0																		
	080404 MP ✓	0.10 - 0.35	1.0 - 4.0												● 330	● 300	● 280	● 225	● 180		
	080408 MP	0.12 - 0.40	1.0 - 4.0												● 180	● 150	● 120	● 250	● 120		
	080412 MP	0.15 - 0.40	1.3 - 4.0												● 70	● 50	● 40	● 60	● 180		


• For toolholders, see page A84, A101, A130, A135, A150

• For dimensions, see page A23

✓ Marked: Old type chipbreaker

● Marked: Standard Items

Negative 80° Trigon Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												
		feed (mm/rev)	ap (mm)	Cermet			CVD Coated						PVD Coated			
OLD For Medium	WNMG 060404 MT	0.12 - 0.40	1.0 - 3.0			●		●	●			●				
	060408 MT	0.15 - 0.45	1.2 - 3.0		●			●	●			●				
	060412 MT	0.23 - 0.50	1.5 - 3.0	310		385	265	310	280	195	70	50	40			
	080404 MT ✓	0.12 - 0.40	1.0 - 4.0	● 265		●	●	●	●	180	● 150	120	● 215	180	● 235	● 110
	080408 MT	0.17 - 0.55	1.2 - 4.0	●	●	●	●	●	●	●	●	●	●	●	●	
	080412 MT	0.25 - 0.55	1.5 - 4.0	●	●	●	●	●	●	●	●	●	●	●	●	
New For Medium	WNMG 060408 PC	0.15 - 0.50	0.5 - 4.0				●	●	●							
	060412 PC	0.17 - 0.50	0.6 - 4.0				●	●	●							
	080408 PC	0.15 - 0.50	0.5 - 4.0			270	340	310	195	70	50	40				● 30
	080412 PC	0.17 - 0.50	0.6 - 4.0			●	●	●	●	●	●	●	●	●	●	● 140
	080416 PC	0.20 - 0.50	0.8 - 4.0			●	●	●	●	●	●	●	●	●	●	
For Roughing	WNMG 080408 RT	0.25 - 0.70	2.5 - 4.0		●	●	●	●	●	●	●	●	●	●	●	
	080412 RT	0.25 - 0.70	2.5 - 4.0		● 330	● 250	● 290	● 265	195	70	50	40	● 205	● 170	● 40	
	080416 RT	0.30 - 0.75	2.5 - 4.0			●	●			● 180	● 150	● 120				
Wiper For Finishing	WNMG 080408 WS	0.07 - 0.35	0.5 - 2.0					280	250							
Wiper For Medium	WNMG 060408 WT	0.15 - 0.60	0.7 - 3.5				●	●					●			
	060412 WT	0.20 - 0.80	0.7 - 3.5	310		345	● 240	● 250		175			● 195			
	080408 WT	0.15 - 0.60	1.0 - 4.0	● 265		●	●	●					●			
	080412 WT	0.20 - 0.80	1.0 - 4.0	●	●	●	●	●					●			


• For toolholders, see page A84, A101, A130, A135, A150

● Marked: Standard Items

• For dimensions, see page A23

✓ Marked: Old type chipbreaker

Positive 7° Clearance 80° Rhombic Inserts




P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated		
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	F20	K10	K20		
				PV3010 CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9335	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	F20	K10	K20
Right hand shown For Finishing	CCET 060201 L-GF 060201 R-GF 060202 L-GF 060202 R-GF 060204 L-GF 060204 R-GF 09T301 L-GF 09T301 R-GF 09T302 L-GF 09T302 R-GF 09T304 L-GF 09T304 R-GF	0.02 - 0.15	0.2 - 1.5																		
		0.02 - 0.15	0.2 - 1.5																		
		0.03 - 0.17	0.3 - 1.5																		
		0.03 - 0.17	0.3 - 1.5																		
		0.05 - 0.20	0.3 - 1.5																		
		0.05 - 0.20	0.3 - 1.5																		
		0.02 - 0.15	0.2 - 2.5																		
		0.02 - 0.15	0.2 - 2.5																		
		0.03 - 0.17	0.3 - 2.5																		
		0.03 - 0.17	0.3 - 2.5																		
		0.05 - 0.20	0.3 - 2.5																		
		0.05 - 0.20	0.3 - 2.5																		
Wiper 	CCET 060203 L-GW 060203 R-GW 09T3003 L-GW 09T3003 R-GW	0.02 - 0.15	0.1 - 1.5																		
		0.02 - 0.15	0.1 - 1.5																		
		0.02 - 0.15	0.1 - 2.5																		
		0.02 - 0.15	0.1 - 2.5																		
New 	CCGT 030103 R-FF 030103 L-FF 030101 R-FF 030101 L-FF 030102 R-FF 030102 L-FF 030104 R-FF 030104 L-FF 0401003 R-FF 0401003 L-FF 040101 R-FF 040101 L-FF 040102 R-FF 040102 L-FF 040104 R-FF 040104 L-FF	0.03 - 0.10	0.05 - 0.3	●																	
		0.03 - 0.10	0.05 - 0.3	●																	
		0.03 - 0.12	0.08 - 0.4	●																	
		0.03 - 0.12	0.08 - 0.4	●																	
		0.03 - 0.15	0.1 - 0.4	●																	
		0.03 - 0.15	0.1 - 0.4	●																	
		0.05 - 0.20	0.1 - 0.4	●																	
		0.05 - 0.20	0.1 - 0.4	●																	
		0.03 - 0.10	0.05 - 0.4	150																	
		0.03 - 0.10	0.05 - 0.4	150																	
		0.03 - 0.12	0.1 - 0.5	●																	
		0.03 - 0.12	0.1 - 0.5	●																	
		0.03 - 0.15	0.1 - 0.5	●																	
		0.03 - 0.15	0.1 - 0.5	●																	
		0.05 - 0.20	0.1 - 0.5	●																	
		0.05 - 0.20	0.1 - 0.5	●																	
New 	CCGT 060201 SA 060202 SA 060204 SA 09T301 SA 09T302 SA 09T304 SA	0.02 - 0.15	0.1 - 1.5													●	●				
		0.02 - 0.15	0.1 - 1.5													●	●				
		0.03 - 0.20	0.1 - 2.4													●	120	●	100		
		0.02 - 0.15	0.1 - 2.5													●	100	●	90		
		0.02 - 0.15	0.1 - 2.5													●	●	●			
		0.03 - 0.20	0.1 - 2.5													●	●	●			

- For toolholders, see page A78, A91, A130, A138, A139, A153
- For dimensions, see page A23

● Marked: Standard Items

Positive 7° Clearance 80° Rhombic Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)																	
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						PVD Coated			Uncoated							
		PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	F20	K10	K20	
For Finishing	CCMT 060202 FA	0.05 - 0.15	0.1 - 1.5																		
	060204 FA	0.05 - 0.15	0.1 - 1.5	●																	
	09T302 FA	0.05 - 0.15	0.1 - 2.0	●	360	●	270											●			
	09T304 FA	0.05 - 0.20	0.1 - 2.0	●	300	●											●	60	190		
	09T308 FA	0.10 - 0.25	0.2 - 2.0		●												●	260	130		
OLD For Finishing	CCMT 060204 FG	0.05 - 0.15	0.3 - 1.5	●	●												●	●			
	09T304 FG	0.07 - 0.20	0.4 - 2.0	●	360	●	340										●	60	190		
	09T308 FG	0.10 - 0.25	0.6 - 2.0	●	290	●	270										●	260	130		
	120408 FG ✓	0.10 - 0.25	0.6 - 2.0														●				
For Medium	CCMT 060204 MT	0.07 - 0.20	0.5 - 2.0	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	060208 MT	0.13 - 0.30	0.7 - 2.0		●	●	●	●	●	●	●	●	●	●	●	●					
	09T304 MT	0.10 - 0.25	0.7 - 3.5	●	340	●	310	●	●	●	●	●	●	●	●	●	●	●			
	09T308 MT	0.13 - 0.30	1.0 - 3.5	●	340	●	310	●	385	●	250	●	310	●	280	●	195	●	50	40	
	120404 MT	0.10 - 0.25	1.0 - 5.0	●	280	●	250	●	●	●	●	●	●	●	●	●	●	160	120	215	
	120408 MT	0.13 - 0.30	1.3 - 5.0		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	120412 MT	0.17 - 0.35	1.5 - 5.0															●	235	110	150
New For Semi Finishing	CCMT 060204 PC	0.06 - 0.18	0.3 - 2.0																●		
	060208 PC	0.08 - 0.25	0.4 - 2.0		●														●		
	09T304 PC	0.08 - 0.25	0.35 - 3.0		●	340													●	30	
	09T308 PC	0.10 - 0.28	0.5 - 3.0		●	270												●	170	250	
	120404 PC	0.08 - 0.25	0.4 - 4.0		●														●	140	
	120408 PC	0.10 - 0.30	0.7 - 4.0		●														●		
	120412 PC	0.12 - 0.35	1.0 - 4.0		●														●		
Wiper For Medium	CCMT 09T308 WT	0.10 - 0.40	0.7 - 3.0		280	●	345	240	●	280	●	250					●	195			


• For toolholders, see page A78, A91, A130, A138, A139, A153

● Marked: Standard Items

• For dimensions, see page A23

✓ Marked: Old type chipbreaker

Positive 11° Clearance 80° Rhombic Inserts




P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated			
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated			P20	K10	K20		
				PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
For Finishing	CPGT 080204 C	0.05 - 0.20	0.4 - 1.5			● 270																
	090304 C	0.05 - 0.20	0.4 - 2.0			● 240																
For Finishing	CPMT 080204 FG	0.07 - 0.20	0.4 - 1.5			●				●					●							
	080208 FG	0.10 - 0.25	0.6 - 1.5			● 340				● 310					● 240							
	090304 FG	0.07 - 0.20	0.4 - 2.0			● 270			●	●					●							
	090308 FG	0.10 - 0.25	0.6 - 2.0												●							
For Semi Finishing	CPMT 060204 PC	0.06 - 0.18	0.3 - 2.0			●									●	●	●					
	060208 PC	0.08 - 0.25	0.4 - 2.0			●									●	●	●					
	090304 PC	0.08 - 0.25	0.45 - 3.0			● 340				● 340					● 50	● 240	● 60					
	090308 PC	0.10 - 0.30	0.6 - 3.0			● 270				● 160					● 240	● 245						
	09T304 PC	0.08 - 0.25	0.45 - 3.0			●				●					●	●	●					
	09T308 PC	0.10 - 0.30	0.6 - 3.0			●				●					●	●	●					

- For toolholders, see page A140
- For dimensions, see page A23

• Marked: Standard Items

Positive 7° Clearance 55° Rhombic Inserts




P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated			
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated			P20	K10	K20		
				PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
Right hand shown For Finishing	DCET 070201 L-GF	0.02 - 0.15	0.2 - 1.5																			
	070201 R-GF	0.02 - 0.15	0.2 - 1.5																			
	070202 L-GF	0.03 - 0.17	0.3 - 1.5																			
	070202 R-GF	0.03 - 0.17	0.3 - 1.5																			
	070204 L-GF	0.05 - 0.20	0.3 - 1.5																			
	070204 R-GF	0.05 - 0.20	0.3 - 1.5																			
	11T301 L-GF	0.02 - 0.15	0.2 - 2.5																			
	11T301 R-GF	0.02 - 0.15	0.2 - 2.5																			
	11T302 L-GF	0.03 - 0.17	0.3 - 2.5																			
	11T302 R-GF	0.03 - 0.17	0.3 - 2.5																			
	11T304 L-GF	0.05 - 0.20	0.3 - 2.5																			
	11T304 R-GF	0.05 - 0.20	0.3 - 2.5																			
Wiper Right hand shown For Finishing Can be applied only to toolholders with 93° approach angle	DCET 070203 L-GW	0.02 - 0.15	0.1 - 1.5																			
	070203 R-GW	0.02 - 0.15	0.1 - 1.5																			
	11T303 L-GW	0.02 - 0.15	0.1 - 2.5																			
	11T303 R-GW	0.02 - 0.15	0.1 - 1.5																			
New For Finishing	DCGT 070201 SA	0.02 - 0.15	0.1 - 1.5												●	●						
	070202 SA	0.02 - 0.15	0.1 - 1.5												●	●						
	070204 SA	0.03 - 0.20	0.1 - 1.5												● 120	● 100						
	11T301 SA	0.01 - 0.05	0.1 - 2.5												● 100	● 90						
	11T302 SA	0.02 - 0.15	0.1 - 2.5												●	●						
	11T304 SA	0.03 - 0.20	0.1 - 2.5												●	●						

- For toolholders, see page A78, A92, A93, A130, A141, A142, A153
- For dimensions, see page A23

• Marked: Standard Items

Positive 7° Clearance 55° Rhombic Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel


Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												Uncoated				
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated					
		PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
For Finishing	DCMT 070202 FA	0.05 - 0.15	0.1 - 1.5	● 360	● 340							● 60			● 60	● 190				
	11T302 FA	0.05 - 0.15	0.1 - 1.5	● 290	● 270							● 180		● 240		● 260	● 130			
For Finishing	DCMT 070204 FG	0.07 - 0.20	0.4 - 1.5	● 360	● 340							● 60	● 50	● 40	● 240		● 60	● 190		
	070208 FG	0.07 - 0.20	0.4 - 2.0	● 360	● 340							● 180	● 170	● 150	● 240		● 260	● 130		
	11T304 FG	0.10 - 0.25	0.6 - 1.5	● 290	● 270							● 180	● 170	● 150	● 240					
	11T308 FG	0.10 - 0.25	0.6 - 2.0	● 290	● 270							● 180	● 170	● 150	● 240					
For Medium	DCMT 11T304 MT	0.10 - 0.25	0.7 - 3.0		● 300	● 280	● 260	● 240	● 220	● 200	● 180	● 170	● 150	● 215		● 60	● 150			
	11T308 MT	0.13 - 0.30	1.0 - 3.0		● 270	● 385	● 250	● 310	● 280	● 195		● 170	● 150	● 215		● 235	● 110			● 120
	11T312 MT	0.17 - 0.35	1.5 - 3.0		● 270							● 170	● 150	● 215						
New For Semi Finishing	DCMT 070204 PC	0.06 - 0.18	0.3 - 2.0		● 300							● 50	● 40	● 215						
	070208 PC	0.08 - 0.25	0.4 - 2.0		● 340							● 50	● 40	● 215						
	11T304 PC	0.08 - 0.25	0.35 - 3.0		● 340							● 170								
	11T308 PC	0.10 - 0.28	0.5 - 3.0		● 270							● 170								
	11T312 PC	0.12 - 0.32	0.5 - 3.0		● 270							● 170								

• For toolholders, see page A78, A92, A93, A130, A141, A142, A153

• For dimensions, see page A23

● Marked: Standard Items

Positive 7° Clearance Round Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												Uncoated				
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated					
		PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
For Medium	RCMT 10T300 MT	0.20 - 0.50	1.0 - 4.0		● 300		● 300	● 280				● 215								
	120400 MT	0.30 - 0.60	2.0 - 5.0		● 385	● 250	● 310	● 280												
	160600 MT	0.40 - 0.80	3.0 - 7.0																	
For Semi Finishing	RCMT 120400 PC	0.2 - 0.6	1.3 - 4.5						● 280	● 250			● 200							
									● 280	● 250			● 200							
For Roughing	RCMX 100300	0.25 - 0.50	1.5 - 4.0		● 300	● 280	● 260	● 240				● 215								
	120400	0.30 - 0.60	2.5 - 5.0		● 300	● 280	● 260	● 240				● 215								
	160600	0.40 - 0.75	3.0 - 7.0		● 345	● 225	● 280	● 250				● 215								
	200600	0.48 - 0.90	3.5 - 9.0		● 300	● 280	● 260	● 240				● 215								
	250700	0.55 - 1.20	4.0 - 12.0		● 300	● 280	● 260	● 240				● 215								
	320900	0.65 - 1.50	5.0 - 15.0		● 300	● 280	● 260	● 240				● 215								
For Roughing	RCMX 100300 RA	0.20 - 0.50	1.0 - 4.0						● 300	● 280	● 260	● 240								
	120400 RA	0.25 - 0.60	2.0 - 5.0						● 300	● 280	● 260	● 240								
	160600 RA	0.35 - 0.75	2.5 - 7.0						● 280	● 250	● 195									
	200600 RA	0.40 - 0.90	3.0 - 9.0						● 280	● 250	● 195									
	250700 RA	0.50 - 1.20	3.5 - 12.0						● 300	● 280	● 260	● 240								
	320900 RA	0.60 - 1.50	4.0 - 15.0						● 300	● 280	● 260	● 240								

• For toolholders, see page A86, A87, A94, A131

• For dimensions, see page A23

● Marked: Standard Items

Positive 7° Clearance Square Inserts

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated			
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated			P20	K10	K20		
				PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
For Finishing	SCMT 09T304 FG	0.08 - 0.25	0.60 - 2.0													●						
	09T308 FG	0.10 - 0.25	0.60 - 2.0					340	310	●					●	240	60	190	200	130		
For Medium	SCMT 09T304 MT	0.10 - 0.25	0.70 - 3.5	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
	09T308 MT	0.13 - 0.30	1.00 - 3.5	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				
	120404 MT	0.10 - 0.25	1.00 - 5.0	●	●	310	350	250	310	280	195					●	50	40	●			
	120408 MT	0.13 - 0.30	1.00 - 5.0	●	●	250	●	●	●	●		●	●	●	●	●	150	140	215	180		
	120412 MT	0.15 - 0.35	1.00 - 5.0					●		●						●	235	110				
For Semi Finishing	SCMT 09T304 PC	0.08 - 0.25	0.35 - 3.0	●				●	●										●			
	09T308 PC	0.10 - 0.28	0.50 - 3.0	●				●	●										●	30		
	120404 PC	0.08 - 0.25	0.40 - 4.0	●	●	310		●	●	●						●	50					
	120408 PC	0.10 - 0.30	0.70 - 4.0	●	●			●	●	●						●	160					
	120412 PC	0.12 - 0.35	1.00 - 4.0	●	●			●	●	●						●				●		

- For toolholders, see page A94, A95, A142, A163
- For dimensions, see page A23

- P Carbon Steel C: 0.45%
- M Austenitic Stainless Steel
- K High Tensile Cast Iron
- N Aluminum
- S Inconel
- H Hardened Steel


Positive 11° Clearance Square Inserts

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated		
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated			P20	P30	K10	K20
				PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020			
For Finishing	SPGN 090304	0.08 - 0.20	0.7 - 3.5																●		
	090308	0.10 - 0.25	0.7 - 3.5																●		
	120304	0.08 - 0.20	1.0 - 5.0																●		
	120308	0.10 - 0.25	1.0 - 5.0																●		
	120312	0.15 - 0.30	1.0 - 5.0																●		
	120404	0.08 - 0.20	1.0 - 5.0																●		
	120408	0.10 - 0.25	1.0 - 5.0																●		
	120412	0.15 - 0.30	1.0 - 5.0			330		250	220									170	140	150	
	120416	0.18 - 0.33	1.0 - 5.0																●		
	150404	0.08 - 0.20	1.5 - 7.0					●										●			
	150408	0.10 - 0.25	1.5 - 7.0															●			
	150412	0.15 - 0.30	1.5 - 7.0																		
	190404	0.08 - 0.20	1.5 - 9.0																		
	190408	0.10 - 0.25	1.5 - 9.0																●		
For Medium	SPMR 090304	0.10 - 0.25	0.7 - 3.5																		
	090308	0.13 - 0.30	1.0 - 3.5			340	230	●	280	●	250										
	120304	0.10 - 0.25	1.0 - 5.0														●	190			
	120308	0.13 - 0.30	1.0 - 5.0																		
For Medium	SPUN 090304	0.10 - 0.30	1.0 - 3.5																		
	090308	0.15 - 0.40	1.0 - 3.5																		
	120304	0.10 - 0.30	1.0 - 5.0			250		330	200	●	250	●	220								
	120308	0.15 - 0.40	1.0 - 5.0			200		330	200	●	250	●	220								
	120312	0.20 - 0.50	1.0 - 5.0															●	170	140	
	150404	0.10 - 0.30	1.5 - 7.0															●	150	120	
	190412	0.20 - 0.50	1.5 - 9.0																		

- For toolholders, see page A80, A134, A161
- For dimensions, see page A23

- P Carbon Steel C: 0.45%
- M Austenitic Stainless Steel
- K High Tensile Cast Iron
- N Aluminum
- S Inconel
- H Hardened Steel

Positive 5° Clearance Triangular Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel


Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						PVD Coated			Uncoated		
For Finishing	TBGT 0601003 R-FF	0.03 - 0.1	0.05 - 0.3													
	0601003 L-FF	0.03 - 0.1	0.05 - 0.3													
	060101 R-FF	0.03 - 0.12	0.08 - 0.4	●												
	060101 L-FF	0.03 - 0.12	0.08 - 0.4	●	150											
	060102 R-FF	0.03 - 0.15	0.1 - 0.4	●												
	060102 L-FF	0.03 - 0.15	0.1 - 0.4	●												
	060104 R-FF	0.05 - 0.20	0.1 - 0.4	●												
	060104 L-FF	0.05 - 0.20	0.1 - 0.4	●												

• For toolholders, see page A144, A145

● Marked: Standard Items

• For dimensions, see page A23

Positive 7° Clearance Triangular Inserts



P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel


Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						PVD Coated			Uncoated		
For Finishing	TCET 110301 L-GF	0.02 - 0.15	0.2 - 1.5													
	110301 R-GF	0.02 - 0.15	0.2 - 1.5													
	110302 L-GF	0.03 - 0.17	0.3 - 1.5													
	110302 R-GF	0.03 - 0.17	0.3 - 1.5													
	110304 R-GF	0.05 - 0.20	0.5 - 1.5													
	TCGT 110201 SA	0.01 - 0.05	0.1 - 2.5													
	110202 SA	0.02 - 0.15	0.2 - 2.5													
	110204 SA	0.03 - 0.20	0.2 - 2.5													
For Finishing	TCMT 110202 FA	0.03 - 0.15	0.1 - 1.5	●	350											
	110204 FA	0.05 - 0.15	0.1 - 1.5	●	270											
For Finishing	TCMT 090208 FG	0.10 - 0.25	0.6 - 1.5	●	●											
	110204 FG	0.07 - 0.20	0.4 - 1.5	●	360	340										
	110208 FG	0.10 - 0.25	0.6 - 1.5	●	290	270										
	16T304 FG	0.07 - 0.20	0.4 - 2.0	●	340	310										
	16T308 FG	0.10 - 0.25	0.6 - 2.0	●	310	280	195									
	TCMT 090204 MT	0.10 - 0.25	0.6 - 2.0	●	●	●	●	●	●	●	●	●	●	●		
For Medium	090208 MT	0.13 - 0.30	0.8 - 2.0	●	●	●	●	●	●	●	●	●	●			
	110204 MT	0.10 - 0.25	0.6 - 3.0	340	310	●	●	●	●	●	●	●	●			
	110208 MT	0.13 - 0.30	0.8 - 3.0	280	250	385	250	310	310	280	195	●	●	●	●	
	16T304 MT	0.10 - 0.25	0.8 - 5.0	●	●	●	●	●	●	●	●	●	●	●	●	
	16T308 MT	0.10 - 0.30	1.0 - 5.0	●	●	●	●	●	●	●	●	●	●	●	●	
	16T312 MT	0.10 - 0.30	1.5 - 5.0	●	●	●	●	●	●	●	●	●	●	●	●	
	TCMT 090204 PC	0.06 - 0.18	0.3 - 2.0	●	●	●	●	●	●	●	●	●	●	●	●	
For Semi Finishing	090208 PC	0.08 - 0.25	0.4 - 2.0	●	●	●	●	●	●	●	●	●	●	●	●	
	110204 PC	0.06 - 0.2	0.3 - 2.5	●	320											
	110208 PC	0.09 - 0.26	0.42 - 2.5	●	250											
	16T304 PC	0.08 - 0.25	0.35 - 3.0	●	340	310										
	16T308 PC	0.10 - 0.28	0.5 - 3.0	●	310											
	16T312 PC	0.12 - 0.36	0.6 - 3.0	●	●	●	●	●	●	●	●	●	●	●	●	

• For toolholders, see page A95, A96, A131, A138, A143, A164

● Marked: Standard Items

• For dimensions, see page A23

Positive 11° Clearance Triangular Inserts




P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)													
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						PVD Coated			Uncoated			
		PV3010 CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080 TT8020	TT9020	F20 F30	K10	K20
For Finishing	TPGN 110304	0.07 - 0.20	0.7 - 3.0					●	●						●	●	●
	110308	0.10 - 0.25	1.0 - 3.0					●								●	
	160302	0.05 - 0.18	1.0 - 5.0														
	160304	0.07 - 0.20	1.0 - 5.0					●	●								
	160308	0.10 - 0.25	1.0 - 5.0					●	●								
	160312	0.15 - 0.30	1.0 - 5.0														
	220404	0.07 - 0.20	1.5 - 7.0		250	300	250	220							●	●	●
	220408	0.10 - 0.25	1.5 - 7.0		200			●							●	●	●
	220412	0.15 - 0.30	1.5 - 7.0														
	220416	0.20 - 0.35	1.5 - 7.0														
	220425	0.25 - 0.40	1.5 - 7.0														
	220430	0.30 - 0.45	1.5 - 7.0													●	
	270608	0.15 - 0.25	3.0 - 8.0					●									
Right hand shown For Finishing	TPGT 090204 L-C	0.05 - 0.20	0.3 - 1.5	●													
	110304 L-C	0.05 - 0.20	0.5 - 2.0	●	270												
	110304 R-C	0.05 - 0.20	0.5 - 2.0	●	200												
	110308 L-C	0.07 - 0.25	0.5 - 2.0	●	240												
	160404 L-C	0.05 - 0.20	0.7 - 3.0	●													
	160404 R-C	0.05 - 0.20	0.7 - 3.0	●													
Left hand shown For Finishing	TPGX 090202 L	0.05 - 0.15	0.4 - 1.5	●													
	090204 L	0.08 - 0.20	0.6 - 1.5	●	270												
	110302 L	0.08 - 0.20	0.5 - 1.5	●	200												
	110302 R	0.08 - 0.20	0.5 - 1.5	●	240												
	110304 L	0.08 - 0.20	0.6 - 2.0	●													
	110304 R	0.08 - 0.20	0.6 - 2.0	●													
For Medium	TPMR 090204	0.10 - 0.25	0.5 - 2.0					●	●								
	090208	0.13 - 0.30	0.7 - 2.0	●				●	●	●	●						
	110304	0.10 - 0.25	0.7 - 3.0	●				●	●	●	●						
	110308	0.13 - 0.30	1.0 - 3.0	●				●	●	●	●						
	160304	0.10 - 0.25	1.0 - 5.0	310	280	340	230	280	310	260		●	●	●	●	●	140
	160308	0.13 - 0.30	1.0 - 5.0	250	230	340	230	280	310	260	●	280	170	●	●	●	
	160312	0.15 - 0.35	1.0 - 5.0														
	220404	0.10 - 0.25	1.0 - 7.0														
	220408	0.13 - 0.30	1.5 - 7.0		●			●	●	●	●						
	220412	0.15 - 0.35	1.5 - 7.0					●	●	●	●						
For Finishing	TPMT 110304 FG	0.07 - 0.20	0.4 - 1.5		●	340	270		340	310		●	240		●	190	
															●	130	
New For Semi Finishing	TPMT 090204 PC	0.06 - 0.18	0.3 - 2.0	●													
	110204 PC	0.06 - 0.2	0.4 - 2.5	●													
	110208 PC	0.1 - 0.26	0.5 - 2.5	●	340												
	110304 PC	0.06 - 0.2	0.4 - 2.5	●	270		310										
	110308 PC	0.1 - 0.26	0.5 - 2.5	●				●	●	50	●	●	●	●	●	●	
	16T304 PC	0.08 - 0.25	0.45 - 3.0	●				●	●	170	●	●	●	●	●	●	
	16T308 PC	0.1 - 0.3	0.5 - 3.0	●				●	●	●	●	●	●	●	●	●	

- For toolholders, see page A80, A81, A135, A138, A143, A144, A161
- For dimensions, see page A23

● Marked: Standard Items

Positive 11° Clearance Triangular Inserts




P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						PVD Coated			Uncoated		
For Medium	TPUN 110304	0.10 - 0.30	1.0 - 3.0						●							
	110308	0.15 - 0.40	1.0 - 3.0						●						●	
	160304	0.10 - 0.30	1.0 - 5.0						●						●	●
	160308	0.15 - 0.40	1.0 - 5.0		250	330			●						●	
	160312	0.20 - 0.50	1.5 - 5.0	200				250	220					120		150
	160316	0.25 - 0.55	1.5 - 5.0										120		170	140
	220404	0.10 - 0.30	1.5 - 7.0						●						●	
	220408	0.15 - 0.40	1.5 - 7.0												●	
	220412	0.20 - 0.50	1.5 - 7.0												●	
	220416	0.25 - 0.55	1.5 - 7.0													

- For toolholders, see page A80, A81, A135, A138, A143, A144, A161
- For dimensions, see page A23

● Marked: Standard Items

Positive 5° Clearance 35° Rhombic Inserts




P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						PVD Coated			Uncoated		
Right hand shown For Finishing	VBET 110301 L-GF	0.02 - 0.15	0.2 - 1.5											●		
	110301 R-GF	0.02 - 0.15	0.2 - 1.5											●		
	110302 L-GF	0.03 - 0.17	0.3 - 1.5											150		
	110302 R-GF	0.03 - 0.17	0.3 - 1.5											● 150		
	110304 L-GF	0.05 - 0.20	0.3 - 1.5													
	110304 R-GF	0.05 - 0.20	0.3 - 1.5											●		
Wiper Right hand shown For Finishing Can be applied only to toolholders with 95° approach angle	VBET 1103003 L-GW	0.02 - 0.15	0.1 - 1.5											150		
	1103003 R-GW	0.02 - 0.15	0.1 - 1.5											150		
New For Finishing	VBGT 110301 SA	0.01 - 0.20	0.1 - 1.5										● 140			
	110302 SA	0.02 - 0.20	0.2 - 1.5										● 130			
	110304 SA	0.05 - 0.20	0.2 - 1.5										● 60			
For Finishing	VBMT 160408 FA	0.05 - 0.25	0.3 - 2.0	360 290	340 270				340 310				240	60 260	190 130	
For Finishing	VBMT 160404 FG	0.07 - 0.20	0.5 - 1.5	360 290	340 270				340 310				240	60 260	190 130	
For Finishing	160408 FG	0.10 - 0.25	0.7 - 2.0													

- For toolholders, see page A79, A96, A97, A98, A131, A132, A146, A154
- For dimensions, see page A23

● Marked: Standard Items

Positive 5° Clearance 35° Rhombic Inserts




P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated			
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated			P20	K10	K20		
				PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
For Medium	VBMT 160404 MT	0.10 - 0.25	0.6 - 3.0	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
	160408 MT	0.13 - 0.30	0.9 - 3.0	●	340	310	385	250	310	280	195	●	●	●	●	●	●	●	●	●	●	120
	160412 MT	0.15 - 0.30	1.2 - 3.0	●	280	250	330	310	310	280	195	●	●	●	●	●	●	●	●	●	●	
New For Semi Finishing	VBMT 160404 PC	0.07 - 0.22	0.5 - 2.8	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	160408 PC	0.10 - 0.27	0.5 - 2.8	360	340	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	160412 PC	0.10 - 0.28	0.5 - 2.8	290	270	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

- For toolholders, see page A79, A96, A97, A98, A131, A132, A146, A154
- For dimensions, see page A23

● Marked: Standard Items

Positive 7° Clearance 35° Rhombic Inserts




P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated			
		feed (mm/rev)	ap (mm)	Cermet		CVD Coated						PVD Coated			Uncoated			P20	K10	K20		
				PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
New For Finishing	VCGT 110301 SA	0.01 - 0.20	0.1 - 1.5	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
	110302 SA	0.02 - 0.20	0.2 - 1.5	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
	110304 SA	0.05 - 0.20	0.2 - 1.5	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
New For Semi Finishing	VCMT 080202 PC	0.02 - 0.15	0.2 - 1.5	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			
	080204 PC	0.05 - 0.20	0.2 - 1.5	●	340	310	●	●	●	●	●	●	●	●	●	●	●	●	●			
	110304 PC	0.05 - 0.20	0.1 - 1.7	●	280	250	●	●	●	●	●	●	●	●	●	●	●	●	●			
	160408 PC	0.05 - 0.20	0.3 - 2.0	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●			

- For toolholders, see page A79, A97, A98, A146, A147
- For dimensions, see page A23

● Marked: Standard Items

Positive 5° Clearance 80° Trigon Inserts




P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)														Uncoated			
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated							PVD Coated			Uncoated			F20	K10	K20	
				PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080		
For Finishing	WBMT 060102 R-C	0.03 - 0.15	0.1 - 0.4		●																
	060102 L-C	0.03 - 0.15	0.1 - 0.4		●	150															
	WBGT 0601003 R-FF	0.03 - 0.1	0.05 - 0.3																		
	0601003 L-FF	0.03 - 0.1	0.05 - 0.3																		
	060101 R-FF	0.03 - 0.12	0.08 - 0.4		●																
	060101 L-FF	0.03 - 0.12	0.08 - 0.4		●	150															
	060102 R-FF	0.03 - 0.15	0.1 - 0.4		●																
	060102 L-FF	0.03 - 0.15	0.1 - 0.4		●																
	060104 R-FF	0.05 - 0.20	0.1 - 0.4		●																
	060104 L-FF	0.05 - 0.20	0.1 - 0.4		●																

- For toolholders, see page A148
- For dimensions, see page A23

● Marked: Standard Items

Negative Square Insert for Pipe Skiving




P	Carbon Steel C: 0.45%
M	Austenitic Stainless Steel
K	High Tensile Cast Iron
N	Aluminum
S	Inconel
H	Hardened Steel

Insert	Designation	Dimension(mm)				Grade Coated
		I	d	t	r	
For Pipe Skiving	SNG 452 10R	2	12.70	7.94	10	●
	16R	2	12.70	7.94	16	●
	20R	2	12.70	7.94	20	●
	25R	2	12.70	7.94	25	●
	30R	2	12.70	7.94	30	●
	40R	2	12.70	7.94	40	●
	50R	2	12.70	7.94	50	●
	60R	2	12.70	7.94	60	●
	70R	2	12.70	7.94	70	●

- Toolholders will be produced upon request.

● Marked: Standard Items



Features

- Wide range of applications for aluminum and other non-ferrous materials
- Very high positive rake geometry to minimize cutting forces and built-up edges

Machining Conditions with K10 Grade

Materials	Hardness Brinell (HB)	Kc (N/mm ²)	Vc (m/min)	f (mm/rev)
Aluminum Alloys (Forged)	Unhardened	50 - 70	500 - 600	2500 - 1000
	Hardened	90 - 110	700 - 900	1000 - 300
Aluminum Alloys (Cast)	Unhardened	70 - 80	700 - 800	1000 - 300
	Hardened	80 - 100	800 - 950	600 - 200
Copper Alloys	90 - 110	700	600 - 250	0.1 - 0.5
Bronze	100	1700	300 - 150	0.1 - 0.6

Positive 7° Clearance Inserts for Aluminum Machining

Insert	Designation	Dimension(mm)				Grade K10
		d	t	r	ØD1	
	CCGT 060202 FL	6.35	2.38	0.2	2.8	●
	060204 FL	6.35	2.38	0.4	2.8	●
	09T302 FL	9.525	3.97	0.2	4.4	●
	09T304 FL	9.525	3.97	0.4	4.4	●
	09T308 FL	9.525	3.97	0.8	4.4	●
	120402 FL	12.70	4.76	0.2	5.5	●
	120404 FL	12.70	4.76	0.4	5.5	●
	120408 FL	12.70	4.76	0.8	5.5	●
	DCGT 070202 FL	6.35	2.38	0.2	2.8	●
	070204 FL	6.35	2.38	0.4	2.8	●
	11T302 FL	9.525	3.97	0.2	4.4	●
	11T304 FL	9.525	3.97	0.4	4.4	●
	11T308 FL	9.525	3.97	0.8	4.4	●
	RCGT 0803MO FL	8.0	3.18	-	3.4	●
	1003MO FL	10.0	3.18	-	4.4	●
	10T3MO FL	10.0	3.97	-	4.4	●
	SCGT 09T308 FL	9.525	3.97	0.8	4.4	●
	120402 FL	12.70	4.76	0.2	5.5	●
	120404 FL	12.70	4.76	0.4	5.5	●
	120408 FL	12.70	4.76	0.8	5.5	●
	TCGT 090204 FL	5.56	2.38	0.4	2.5	●
	110204 FL	6.35	2.38	0.4	2.8	●
	16T304 FL	9.525	3.97	0.4	4.4	●
	16T308 FL	9.525	3.97	0.8	4.4	●
	VCGT 110302 FL	6.35	3.18	0.2	2.8	●
	110304 FL	6.35	3.18	0.4	2.8	●
	160402 FL	9.525	4.76	0.2	4.4	●
	160404 FL	9.525	4.76	0.4	4.4	●
	160408 FL	9.525	4.76	0.8	4.4	●
	160412 FL	9.525	4.76	1.2	5.5	●
	220530 FL	12.70	5.56	3.0	5.5	●

● Marked: Standard Items



- Special inserts will be produced upon request



CERAMIC INSERTS



CBN INSERTS




PCD INSERTS

Physical Properties

Grade	AW20	AB2010	AB20	AB30	TC430	AS500	SC10	AS10	AS20
Composition	Al ₂ O ₃	Al ₂ O ₃ -ZrO ₂	Al ₂ O ₃ -Ti(C,N)	Al ₂ O ₃ -TiC	SiC Whisker	SiAlON	CVD-Si ₃ N ₄	Si ₃ N ₄	Si ₃ N ₄ -TiN
Density (g/cm ³)	4.05	4.30	4.30	4.25	3.74	3.21	3.22	3.22	3.50
Hardness	HRA	94.0	94.5	94.5	94.5	94.3	93.6	93.6	93.0
	Vickers	1,800	2,050	2,050	2,050	2,100	1,800	1,700	1,500
Bending Strength (MPa)	600	650	650	700	700	850	900	900	1,000

Application Map of Ceramic Grades



T-TURN Ceramic Inserts

AW20 (Al₂O₃+ZrO₂)



- Excellent wear resistant grade with high chemical stability and temperature resistance
- Toughened by ZrO₂
- For high speed continuous turning of cast iron
- For finishing applications on hardened steels and other hard materials

AB2010 (AB20+TiN)



- Excellent wear resistance with extended tool life when compared to uncoated ceramic grades being applied on high speed applications
- TiN coating makes it easy to identify used corners
- Successful application of ceramic inserts on hard materials can provide significant cost advantage compared to CBN
- The combination of this ceramic grade with TiN PVD coating provides improved wear resistance and fracture toughness
- Application area is in the finish machining of hardened steels and cast iron

AB20 (Al₂O₃+TiCN)



- High wear resistant grade with excellent cutting edge stability
- For high speed continuous turning of hardened steels and other hard materials
- For cast iron finishing applications

AB30 (Al₂O₃+TiC)



- Mixed ceramic with good toughness and wear resistance
- For hard steels, hard materials and cast iron finishing and roughing applications
- Can be applied for interrupted cutting

T-TURN Ceramic Inserts

New


TC430 (Whisker)



- SiC whisker reinforced ceramic grade
- High hardness with excellent fracture toughness
- General turning and milling
- High cutting speed for Ni-base superalloy. Inconel, Waspaloy and Rene

New

AS500 (SiAlON)



- High hardness and high fracture toughness
- For Gray cast iron, Nodular cast iron and Compacted graphite iron (CGI)
- Suitable for High Speed Dry Machining of Brake Discs

SC10 (AS10+CVD)




- Excellent wear resistant grade with very good toughness and thermal shock resistance
- For roughing to finishing of cast iron
- Wet and dry cutting

AS10 (Si₃N₄)



- High wear resistant grade with very good toughness and thermal shock resistance
- For roughing to finishing cast iron
- Wet and dry cutting

AS20 (Si₃N₄)



- Very tough Si₃N₄ ceramic grade with high cutting edge stability
- For roughing to finishing applications on nickel based high temperature alloys
- Wet and dry cutting

Cutting Examples

Work Material & Description	Insert		Cutting Conditions	Tool Life (pcs/edge)
	Designation	Grade		
Inconel 718, Body (350HB)	RNGN 120700	AS20	V=200m/min	1pc
			f=0.12mm/rev	
			ap=3.0mm	
			Wet, Continuous cut	
GG25, Cylinder Liner (200 - 250HB)	CNGA 120408	AW20	V=350m/min	100pcs
			f=0.25mm/rev	
			ap=0.5mm	
			Dry, Continuous cut	
100CrMo6, Ring (58 - 60HRC)	TPGN 110304	AB20	V=80m/min	2000pcs
			f=0.05mm/rev	
			ap=0.2mm	
			Dry, Continuous cut	
Case Hardened Steel, Bush(58 - 62HRC)	CNMG 120408 CE	AB30	V=100m/min	50pcs
			f=0.1mm/rev	
			ap=0.2mm	
			Dry, Continuous cut	
GG25, Pump Body (180 - 230HB)	CNMG 120404 CE	AB30	V=600m/min	100pcs
			f=0.1mm/rev	
			ap=0.5mm	
			Wet, Continuous cut	
GG25, Cylinder Jam (180 - 230HB)	TNGN 160408	AB30	V=800m/min	90pcs
			f=0.35mm/rev	
			ap=0.5mm	
			Dry, Continuous cut	
GG25, Brake Disc (180 - 230HB)	SNGN 120712	SC10	V=800m/min	290pcs
			f=0.4mm/rev	
			ap=1.5mm	
			Wet, Continuous cut	
GG25, Brake Disc (180 - 230HB)	SNGN 120412	AS10	V=400m/min	120pcs
			f=0.25 - 0.3mm/rev	
			ap=2.0mm	
			Wet, Continuous cut	
GG25, Brake Disc (180 - 230HB)	CNGA 120412	AS10	V=500m/min	30pcs
			f=0.3mm/rev	
			ap=2.0 - 3.0mm	
			Wet, Continuous cut	
GG25, Brake Disc (180 - 230HB)	SNGX 120716 CH	AS10	V=900m/min	190pcs
			f=0.6mm/rev	
			ap=2.5 - 3.0mm	
			Wet, Continuous cut	
GG25, Brake Disc (180 - 230HB)	CNGX 120716 CH	AS10	V=900m/min	130pcs
			f=0.73mm/rev	
			ap=2.5mm	
			Wet, Continuous cut	
GG20, Brake Disc (170 - 190HB)	SNGX 120716 T7-CH	AS500	V=800m/min	100pcs
			f=0.55mm/rev	
			ap=2.5mm	
			Dry, Continuous cut	
Chilled Cast, Roll (52 - 55HRC)	RCGX 120700 U2	TC430	V=42m/min	2000mm
			f=0.2mm/rev	
			ap=2mm	
			Dry, Continuous cut	
Inconell 718, Shaft (280 - 330HB)	SNGN 120408 T6	TC430	V=150m/min	4min 30sec
			f=0.2mm/rev	
			ap=0.5mm	
			Wet, Continuous cut	

Recommended Cutting Conditions

Materials	Grade V.f	AW20	AB2010	AB20	AB30	TC430	AS500	SC10	AS10	AS20
		Cutting speed: V (m/min), Feed: f (mm/rev)								
Gray cast iron (HB 180-230)	V f	400-1,000 0.1-0.5	-	-	300-800 0.1-0.5	-	400-1,000 0.2-0.6	400-1,000 0.2-0.6	400-800 0.2-0.8	-
Ductile Cast Iron (HB 200-240)	V f	300-600 0.1-0.2	-	-	250-500 0.1-0.3	-	200-600 0.1-0.5	200-600 0.1-0.5	200-500 0.2-0.6	-
Chilled Cast Iron (> HB 400)	V f	-	50-200 0.05-0.2	50-200 0.05-0.2	50-150 0.05-0.2	-	-	-	-	-
Hardened Steel (HRc 40-50)	V f	-	100-400 0.1-0.2	100-400 0.1-0.2	100-300 0.1-0.2	-	-	-	-	-
Hardened Steel (> HRc 50)	V f	-	50-250 0.05-0.2	50-250 0.05-0.2	-	-	-	-	-	-
ADI or HSS Roll	V f	-	-	50-100 0.2-0.5	50-80 0.2-0.5	50-100 0.2-0.7	20-60 0.2-0.7	-	-	-
Super Alloy (Ni-base)	V f	-	-	-	-	150-400 0.1-0.3	-	-	-	100-300 0.1-0.3

Edge Preparation for Ceramic Inserts

1. Common style (no designation)







Grade	Land specification	
	Width (mm)	Angle (°)
AB2010, AB20, AB30, TC430, AS500, SC10, AS10, AS20	0.2	25
AW20	0.2	20

2. Others (single T-land)











Designation	Land specification	
	Width (mm)	Angle (°)
T2	0.10	30
T3	0.15	30
T4	0.20	30
T5	0.30	30
T6	0.10	20
T7	0.20	20

3. Edge preparation "E" is only horing without T-land.





4. Various special edge preparations such as "Double Land" or "S" can be made upon request.

Insert	Designation	Dimension(mm)				Grade									
		d	t	r	ØD1	AW20	AB2010	AB20	AB30	TC430	AS500	New	SC10	AS10	AS20
 	CNGA 120404	12.70	4.76	0.4	5.16		●	●	●						
	120408			0.8			●	●	●				●	●	●
	120408 E														●
	120408 T7														
	120412	15.88	6.35	1.2	6.35		●	●	●				●	●	
	120412 E			1.6			●	●	●				●	●	
	120412 T7														
	120416														
	160608	19.05	7.92	0.8	7.92		●								
	160612			1.2			●	●	●						●
	160616			1.6			●	●	●						
	160624			2.4											
	190608	19.05	7.92	0.8	7.92		●	●	●						
	190612			1.2			●	●	●						
	190616			1.6											
	190624			2.4											●
 	CNGN 120404	12.70	4.76	0.4	-										
	120408			0.8			●	●	●						●
	120408 T6														
	120408 E														●
	120412	12.70	7.94	1.2	-		●	●	●				●	●	●
	120412 E			1.6			●	●	●						
	120412 T6														
	120416														
	120708	12.70	7.94	0.8	-		●	●	●						●
	120708 E														
	120708 T6														
	120712			1.2			●	●	●						●
	120712 E	12.70	7.94	1.6	-		●	●	●						●
	120712 T6														
	120716														
	120716 E														●
 	CNGX 120712 CH	12.70	7.94	1.2	-										●
	120712 T7-CH			1.6											●
	120716 CH	12.70	7.94		-									●	●
	120716 T7-CH														●
 	CNMG 120404 CE	12.70	4.76	0.4	5.16										
	120408 CE			0.8											
 	DNGA 150404	12.70	4.76	0.4	5.16										
	150408			0.8											
	150412			1.2											
	150416			1.6											
	150604	12.70	6.35	0.4	5.16										
	150606			0.6											
	150608			0.8											
	150612			1.2											●
	150616			1.6											

● Marked: Standard Items


Insert	Designation	Dimension(mm)				Grade								
		d	t	r	ØD1	AW20	AB2010	AB20	AB30	TC430 New	AS500 New	SC10	AS10	AS20
 	DNGN 150408 150704 150708 150712 150716	12.70	4.76 0.4 0.8 1.2 1.6	-										
 	DNGX 150712 CH 150712 T7-CH 150716 CH	12.70	7.94	1.2 1.6										
 	DNMG 150608 CE	12.70	6.35	0.8	5.16									
 	ENGN 130708 130712 130716	12.70	7.94	0.8 1.2 1.6										
 	HNGX 050712 CH 050712 T7-CH 050716 CH 050716 T7-CH	12.70	7.94	1.2 1.6										
 	RCGX 060600 U1 090700 T6 090700 U1 120700 120700 T6 120700 U2 151000 U2 191000 U2 251200 U3	6.35 9.52 9.52 12.70 12.70 15.88 15.88 19.05 25.0	6.35 8.0 8.0 10.0 10.0 10.29 10.29 12.29 12.29											
 	RNGN 090300 090300 T6 120400 120400 E 120400 T6 120700 120700 E 120700 T6 150700 190700 190700 T6	9.52 12.70 12.70 15.88 15.88 19.05	3.18 4.76 4.76 7.94 7.94											
 	RPGN 120400 T6	12.70	4.76	-	-									
 	RPGX 090700 T6 120700 T6	9.52 12.67	7.94	-	-									
 	SNGA 120404 120408 120408 E 120412 120416	12.70	4.76	0.4 0.8 1.2 1.6	5.16									

• Marked: Standard Items

Insert	Designation	Dimension(mm)				Grade									
		d	t	r	ØD1	AW20	AB20	AB30	TC430	AS300	SC10	AS10	AS20		
 	SNGN 120404	12.70	4.76	0.4	-	●	●	●							
	120408			0.8			●	●	●						
	120408 E														
	120408 T6			1.2			●	●	●	●	●	●	●		
	120412														
	120412 T6														
	120412 T7		7.94		-										
	120416			1.6			●	●	●	●	●	●	●		
	120424			2.4			●	●	●	●	●	●	●		
	120704			0.4											
	120708			0.8			●	●	●	●	●	●	●		
	120708 T6			1.2			●	●	●	●	●	●	●		
	120712						●	●	●	●	●	●	●		
	120712 T6														
	120716			1.6											
	120720			2.0											
 	SNGX 120712 CH	12.70	7.94	1.2	-										
	120712 T7-CH														
	120716 CH			1.6											
	120716 T7-CH		7.94												
	190716														
 	SNGX 120712 T7-CHX	12.70	7.94	1.2	-										
	120716 T7-CHX			1.6											
	SNMG 120408 CE	12.70	4.76	0.8	5.16										
	SPGN 090308	9.52	4.76	0.8											
	120308	12.70	3.18												
	120312														
 	120412	4.76	1.2												
	TNGA 160304	9.52	3.18	0.4	3.81										
	160308			0.8											
	160404		4.76	0.4											
	160408			0.8											
	160408 E														
	160412	12.70	4.76	1.2											
	160416			1.6											
	220404			0.4											
	220408		4.76	0.8											
	220412			1.2											
	220416		4.76	1.6											

* Marked: DCL S-4D clamp is applied only to marked insert.

● Marked: Standard Items

Insert	Designation	Dimension(mm)				Grade							
		d	t	r	ØD1	AW20	AB2010	AB20	AB30	TC450 New	AS500 New	SC10	AS10
	TNGN 110308 110312 160404 160408 160408 E 160412 160416 160420 160704 160708 160712 220408 220412 270616	6.35 9.52 9.52 9.52 9.52 12.70 15.88	3.18 4.76 7.94 4.76 6.35	0.8 1.2 0.4 0.8 1.2 1.6 2.0 0.4 0.8 1.2 0.8 1.2 1.6	-								

TB610, TB650, TB670, TB730, KB90A

Physical Properties

Grade	TB610	TB650	TB670	TB730	KB90A
TRS(Gpa)	0.8 - 0.9	1.0 - 1.1	1.0 - 1.1	0.9 - 2.0	1.1 - 1.2
Hardness(Gpa)	27 - 28	30 - 32	31 - 33	39 - 42	35 - 38

New TB610

- High wear resistant cubic boron nitride with low CBN content
- For precision machining of hardened steels (harder than 45HRC) such as hot and cold working tool steels, die steels, case hardened steels, carburized iron and high speed steel
- For continuous cutting
- For turning



TB650

- High wear resistant cubic boron nitride with low CBN content
- Designed for finishing to roughing applications on hardened steels (harder than 45HRC)
- Can be applied to light interrupted cutting applications
- For turning



New TB670

- High hardness and impact resistance
- Machining for continuous to severe interrupted turning of hardened material (Harder than 40HRC)
- For Alloy steel, tool steel, case hardened steel and chilled cast iron



New TB730

- Tough cubic boron nitride with high CBN content
- For high speed machining of cast iron
- Suitable for machining cemented tungsten carbide, sintered metal and heavy alloys
- Excellent for interrupted cutting of hardened steel



KB90A

- Solid CBN with excellent impact resistance
- For high speed machining of cast iron
- Can be applied to rough to medium machining of hardened steel



Recommended Cutting Conditions *New*

Materials	Grade	TB610	TB650	TB670	TB730	KB90A
	V, f	Cutting speed: V (m/min), Feed: f (mm/rev)				
Gray Cast Iron (180 - 230HB)	V f				500-1,000 0.1-0.3	500-1,000 0.1-0.3
Chilled Cast Iron (> HB 400)	V f		80-150 0.1-0.2	80-150 0.1-0.25	80-150 0.1-0.3	80-150 0.1-0.3
Hardened Steel (46 - 68HRC)	V f	100-250 0.05-0.2	80-200 0.05-0.2	80-180 0.1-0.3	60-150 0.1-0.3	
Sintered Metal (Hv 200-600)	V f		100-300 0.05-0.2	100-300 0.1-0.3	80-250 0.1-0.25	
DCI Roll, HSS Roll	V f		50-100 0.2-0.6	30-80 0.2-0.6		
Super Alloy (Ni-base)	V f				100-300 0.05-0.2	100-300 0.05-0.2

Cutting Examples

Work Material & Description	Insert		Cutting Conditions	Tool Life (pcs/edge)
	Designation	Grade		
Hardened Steel, Sleeve (65 - 68HRC)	VNMA 160404	TB610	V = 140m/min f = 0.09mm/rev ap = 0.1mm Dry, Continuous Cut	980pcs
Carburized Shaft (60 - 62HRC)	TNMA 160408	TB610	V = 200m/min f = 0.1mm/rev ap = 0.15mm Dry, Continuous Cut	1300pcs
Hardened Steel, Ring (60 - 62HRC)	TPGX 110304	TB610	V = 150m/min f = 0.07mm/rev ap = 0.1mm Dry, Continuous Cut	400pcs
Hardened Steel, Ring Gear (82HRA)	CNMA 120408	TB730	V = 110m/min f = 0.08mm/rev ap = 0.1mm Dry, Interrupted Cut	60pcs
GG25, Engine Block (285 - 305HB)	TCGW 110204	TB730	V = 550m/min f = 0.12mm/rev ap = 0.5mm Wet, Continuous Cut	100pcs
Hardened Steel, Shaft with hole (60 - 62HRC)	CNMA 120408	TB730	V = 100m/min f = 0.1mm/rev ap = 0.2mm Dry, Continuous Cut	20pcs
Hardened Steel, Nozzle (58 - 60HRC)	TNMA 160404 LN	TB650	V = 80m/min f = 0.1mm/rev ap = 0.13mm Dry, Continuous Cut	1400pcs
Sintered Metal, Sleeve	TPGH 110304	TB730	V = 170m/min f = 0.13mm/rev ap = 0.5mm Dry, Interrupted Cut	1000pcs
Carburized Steel, Flange Body (50 - 62HRC)	CNMA 120408	TB650	V = 75m/min f = 0.15mm/rev ap = 0.08mm Wet, Interrupted Cut	33pcs
Nitrified Hardened Steel, Sleeve (40 - 50HRC)	CCGW 09T304 LS	TB650	V = 138m/min f = 0.1mm/rev ap = 0.1mm Wet, Continuous Cut	1000pcs
Carburized Steel, Middle Sun Gear (58 - 62HRC)	CNMA 120408 LN	TB650	V = 100 - 120m/min f = 0.15mm/rev ap = 0.3 - 0.4mm Dry, Continuous Cut	100pcs
Carburized Steel, Annulus Gear (58 - 62HRC)	CNMA 120408 LS	TB670	V = 120m/min f = 0.15mm/rev ap = 0.1mm Wet, Continuous Cut	160pcs

Edge Preparation for CBN Inserts

Common Style (no designation)

Grade	Land specification		
	Width (mm)	Angle (°)	Honing(mm)
TB610, TB650, TB670	0.13	20	0.015
TB730	0.13	20	-
KB90A	0.2	20	0.015

Technical information for CBN Inserts

CNMA 120408 **LN** : Regular Size CBN Tip

CNMA 120408 **LS** : Small Size CBN Tip


CNMA 120408 **LS2** : Small Size CBN Tip with two corners







RCGX 090300 **FT** : Full Top CBN

CNMN 090308 **SD** : Solid CBN

CNGA 120408 **WZ-LS2**: Wiper geometry

Application Map of CBN Grades






Insert	Designation	Dimension(mm)					Grade				
		I	d	t	r	ØD1	TB610 ^{New}	TB650	TB670 ^{New}	TB730 ^{New}	KB90A
 	CCGW 060202 LS2	2.2	6.35	2.38	0.2	2.8	●	●	●	●	●
	060204 LS2	2.1			0.4						
	060208 LS2	2.1			0.8						
	09T304 LS2	2.4	9.52	3.97	0.4	4.4	●	●	●	●	●
	09T304 WZ-LS2	2.4			0.8						
	09T308 LS2	2.3			0.8						
	09T308 WZ-LS	2.3	12.70	4.76	0.4	5.5	●	●	●	●	●
	09T308 WZ-LS2	2.3			0.8						
	120404 LS2	2.1			0.4						
 	CNGA 120404 WZ-LS	2.1	12.70	4.76	0.4	5.16	●	●	●	●	●
	120404 WZ-LS2	2.1			0.8						
	120404 WZ-LS4	2.1			1.2						
	120408 WZ-LN	3.9	12.70	4.76	0.4	5.16	●	●	●	●	●
	120408 WZ-LS	2.1			0.8						
	120408 WZ-LS2	2.1			1.2						
 	CNMA 120404 LN	4.2	12.70	4.76	0.4	5.16	●	●	●	●	●
	120404 LN2	4.2			0.8						
	120404 LS	2.2			0.8						
	120404 LS2	2.2	12.70	4.76	0.8	5.16	●	●	●	●	●
	120404 LS4	2.2			1.2						
	120408 LN	4			1.2						
	120408 LS	2.1	12.70	4.76	0.4	5.16	●	●	●	●	●
	120408 LS2	2.1			0.8						
	120408 LS4	2.1			1.2						
	120412 LN	3.9	12.70	4.76	0.4	5.16	●	●	●	●	●
	120412 LS	2.5			0.8						
	120412 LS2	2.5			1.2						
 	CNMN 090308 SD	-	9.52	3.18	0.8	-	●	●	●	●	●
	090312 SD				1.2						
	090316 SD				1.6						
	120416 SD		12.70	4.76							
 	DCGW 070202 LS	2.6	6.35	2.38	0.2	2.8	●	●	●	●	●
	070202 LS2	2.6			0.4						
	070204 LS	2.4			0.8						
	070204 LS2	2.4	9.52	3.97	0.4	4.4	●	●	●	●	●
	070208 LS2	2.1			0.8						
	11T304 LN	3.8			0.4						
	11T304 LS	2.6	9.52	3.97	0.4	4.4	●	●	●	●	●
	11T304 LS2	2.6			0.8						
	11T308 LN	3.4			0.8						
	11T308 LS	2.2	9.52	3.97	0.8	4.4	●	●	●	●	●
	11T308 LS2	2.2			3.97						

● Marked: Standard Items

- Marked: Standard Items

Insert	Designation	Dimension(mm)					Grade				
		I	d	t	r	ØD1	TB610 ^{New}	TB650	TB670 ^{New}	TB730 ^{New}	KB90A
 	TCGW 090204 LS3	2.3	5.56	2.38	0.4	2.5	●			●	
	090208 LS3	2.1			0.8				●		
	110204 LS	2.3			0.4			●			
	110204 LS3	2.3			0.8		●	●	●	●	
	110208 LS	2.1					●			●	
	110208 LS3	2.1						●		●	
	16T304 LS	2.8			0.4			●		●	
	16T304 LS3	2.8					●	●	●	●	
	16T308 LS	2.5			0.8			●		●	
	16T308 LS3	2.5					●		●	●	
 	TNMA 160404 LN	4.3	9.52	4.76	0.4	3.81	●	●	●	●	
	160404 LS	2.2			0.8		●	●	●	●	
	160404 LS3	2.2			1.2		●	●	●	●	
	160404 LS6	2.2			1.6		●	●	●	●	
	160408 LN	4			0.4			●		●	
	160408 LS	2.1			0.8			●		●	
	160408 LS3	2.1			1.2			●		●	
	160408 LS6	2.1			1.6			●		●	
	160412 LS	2.5			0.4		5.16	●	●		
	160412 LS3	2.5			0.8			●		●	
	160416 LN	3.1									
	160416 LS	2.4									
	220404 LN	4.1									
	220408 LS	2.6									
 	TNMIN 110308 SD	-	6.35	3.18	0.8	-					●
 	TPGN 090204 LS3	2.3	5.56	2.38	0.4	-	●				
	110302 LS3	2.8			0.2						●
	110304 LS	2.6			0.4		●	●	●	●	
	110304 LS3	2.6			0.8		●	●	●	●	
	110308 LS	2.3			0.4		●	●	●	●	
	110308 LS3	2.3			0.8		●	●	●	●	
	160304 LS	2.8			0.4		●	●	●	●	
	160304 LS3	2.8			0.8		●	●	●	●	
	160308 LS	2.5			0.4		●	●	●	●	
	160308 LS3	2.5			0.8		●	●	●	●	
	220408 LS	2.6			12.70		4.76				
 	TPGW 080204 LS3	2.1	4.76	2.38	0.4	2.5				●	
	090204 LS3	2.3			0.8				●	●	●
	090208 LS3	2							●		
	110302 LS3	2.8			0.2		●	●	●	●	
	110304 LS	2.6			0.4		●	●	●	●	
	110304 LS3	2.6			0.8		●	●	●	●	
	110308 LS3	2.3			0.4		●	●	●	●	
	160404 LS3	2.8			0.8		4.4				
	160408 LS3	2.5									
 	VBGW 110304 LS2	3.2	6.35	3.18	0.4	2.8				●	
	110308 LS2	2.4			0.8				●	●	
	160402 LS2	3.6			0.2				●	●	
	160404 LN	4.8					3.4	●	●	●	
	160404 LS	3.2			0.4		●	●	●	●	
	160404 LS2	3.2			0.8		4.4				
	160408 LS	2.3									
	160408 LS2	2.3									

● Marked: Standard Items

Insert	Designation	Dimension(mm)					Grade				
		l	d	t	r	ØD1	TB610 ^{New}	TB650	TB670 ^{New}	TB730 ^{New}	
	VNGA 160404 LN	5	9.52	4.76	0.4	3.81	●	●			
	160404 LS	3.2					●	●			
	160404 LS2	3.2					●	●	●	●	
	160408 LN	4.1			0.8		●	●	●		
	160408 LS	2.4					●	●	●	●	
	160408 LS2	2.4					●	●	●		
	160408 LS4	2.4							●		
	WNGA 060408 WZ-LS6	2.1	9.52	4.76	0.8	3.81			●		
	080408 WZ-LS3	2.1					●	●	●		
	080408 WZ-LS6	2.1						●			
	080412 WZ-LS3	2.1			1.2				●		
	WNMA 080408 LS3	2.1	12.70	4.76	0.8	5.16			●		
	080408 LS6	2.1							●		

● Marked: Standard Items

KP500, KP300, KP100

Physical Properties

Grade	Feature	PCD (μm)	TRS (GPa)	Hardness (GPa)
KP100	↑ Toughness (High Co)	4	2.0 - 2.2	80 - 100
KP300	↓ Hardness (High PCD)	10	1.8 - 2.0	90 - 110
KP500		25	1.0 - 1.2	100 - 120

KP500

- Super abrasion resistant grade
- Designed for fine finishing cuts with little or no interruptions
- For high Si aluminum alloy(Si >12.2%), metal matrix composite and sintered tungsten carbide

KP300

- This KP300 is for general machining
- Well combined wear resistance and toughness
- For low to medium Si aluminum alloy (Si ≤ 12.2%), copper alloy and non-ferrous metal

KP100














- Low content poly-crystalline diamond with fine grain
- High edge strength and good surface finish
- For plastic, wood and pure aluminum

Recommended Cutting Conditions

Materials	Grade	KP500	KP300	KP100
	V, f, ap	Cutting speed: V (m/min), Feed: f (mm/rev), Depth of cut: ap (mm)		
Al Alloy (12.2% ≤ Si)	V f ap		600 - 3000 0.05 - 0.3 0.1 - 3.0	
Al Alloy (12.2% > Si)	V f ap	300 - 800 0.05 - 0.3 0.1 - 3.0	300 - 600 0.05 - 0.3 0.1 - 3.0	
Sintered Tungsten Carbide	V f ap	10 - 30 0.05 - 0.15 0.02 - 0.5		
Wood	V f ap			1000 - 3000 0.1 - 0.5 0.2 - 5.0
Cu Alloy	V f ap		600 - 1500 0.05 - 0.3 0.1 - 3.0	
Plastic	V f ap			300 - 1000 0.05 - 0.25 0.05 - 2.0
Carbon (Graphite)	V f ap		100 - 600 0.1 - 1.0 0.2 - 2.0	
MMC	V f ap	10 - 30 0.05 - 0.3 0.1 - 1.0		

Cutting Examples

Work Material & Description	Insert		Cutting Conditions	Tool Life (pcs/edge)
	Designation	Grade		
9% Si Aluminum Alloy, Cylinder Bore	TPGX 110304	KP300	V=410m/min f=0.1mm/rev ap=0.5mm Wet, Continuous cut	6000pcs
20% Si Aluminum Alloy, Brake Disc	RNMN 090300	KP500	V=980m/min f=0.13mm/rev ap=0.5mm Wet, Continuous cut	1300pcs
10% Si Aluminum Alloy, Housing	DCGT 11T304 CB	KP300	V=600m/min f=0.45mm/rev ap=1mm Wet, Interrupted cut	16500pcs

Insert	Designation	Dimension(mm)					Grade			
		I	d	t	r	ØD1	KP100	KP300	KP500	
 	CCGT 060204 CB 09T302 CB 09T304 CB 09T308 CB 120404 CB 120408 CB	3.1	6.35	2.38	0.4	2.8		●		
		4.15	9.52	3.97	0.2	4.4		●		
		4.1			0.4			●		
		4.0	12.70	4.76	0.8	5.5		●		
		4.1			0.4			●		
		4.0	12.70	4.76	0.8			●		
 	CCGW 060202 LN-7 060204 LN-7 060208 LN-7 09T304 LN-7 09T308 LN-7 120404 LN-7 120408 LN-7	3.1	6.35	2.38	0.2	2.8		●		
		3.0			0.4			●		
		4.0	9.52	3.97	0.8	4.4		●		
		3.9			0.4			●		
		4.0	12.70	4.76	0.8	5.5		●		
		3.9			0.8			●		
 	CNMA 120404 LN-10 120408 LN-10 120412 LN-10	4.0	12.70	4.76	0.4	5.16		●		
		3.9			0.8			●	●	
		3.8			1.2			●		
 	DCGT 070202 CB 070204 CB 11T302 CB 11T304 CB 11T308 CB	3.4	6.35	2.38	0.2	2.8		●		
		3.3			0.4			●		
		4.9	9.52	3.97	0.2	4.4		●		
		4.7			0.4			●		
		4.4			0.8			●		
 	DCGW 070202 LN-7 070204 LN-7 11T302 LN-7 11T304 LN-7 11T308 LN-7	3.4	6.35	2.38	0.2	2.8		●		
		3.3			0.4			●		
		3.9	9.52	3.97	0.2	4.4		●		
		3.7			0.4			●		
		3.3			0.8			●		
 	DNMA 150404 LN-10 150408 LN-10 150412 LN-10 150604 LN-10 150608 LN-10	4.0	12.70	4.76	0.4	5.16		●		
		3.7			0.8			●		
		3.47			1.2			●		
		4.0	6.35	4.76	0.4	5.16		●		
		3.7			0.8			●		
 	SNMA 120408 LN-10 120412 LN-10	4.0	12.70	4.76	0.8	5.16		●	●	
		4.0			1.2			●		
		4.0			1.2			●		
 	SPGN 090308 LN-7 120308 LN-7	3.9	9.52	3.18	0.8	-		●		
		3.9			0.8			●		
		12.70			0.8			●		
 	TCGT 090204 CB 110204 CB 16T304 CB 16T308 CB	2.8	5.56	2.38	0.4	2.5		●		
		3.8	6.35	3.97	0.4			●		
		3.9	9.52			4.4		●		
		3.6	0.8				●			
 	TCGW 090204 LN-7 090208 LN-7 110204 LN-7 110208 LN-7 16T304 LN-7 16T308 LN-7	3.3	5.56	2.38	0.4	2.5		●		
		3.0	6.35		0.8			●		
		3.8			0.4	2.8		●		
		3.5			0.8			●		
		3.8	9.52	3.97	0.4	4.4		●		
		3.5	9.52	3.97	0.8			●		
 	TNMA 160404 LN-10 160408 LN-10	4.3	9.52	4.76	0.4	3.81		●		
		4.0			0.8			●		
		4.0			0.8			●		

• CB: PCD chipbreaker type insert.

• Marked: Standard Items

Insert	Designation	Dimension(mm)					Grade			
		I	d	t	r	ØD1	KP100	KP300	KP500	
	TPGN 110302 LN-7	3.9	6.35	3.18	0.2	-	●			
	110304 LN-7	3.8			0.4		●			
	110308 LN-7	3.5			0.8		●			
	160302 LN-7	4.4	9.52		0.2	-	●			
	160304 LN-7	4.3			0.4		●			
	160308 LN-7	4.0			0.8		●			
	VBGW 160402 LN-7	5.2	9.52	4.76	0.2	4.4	●			
	160404 LN-7	5.0			0.4		●			
	160408 LN-7	4.2			0.8		●			
	VCGT 110302 CB	4.7	6.35	3.18	0.2	2.8	●			
	110304 CB	5.0			0.4		●			
	160404 CB	7.3			0.8		●			
	160408 CB	6.4	9.52	4.76	1.2	3.81	●			
	160412 CB	6.2			3.0		●			
	220530 CB	6.4			5.5		●			
	VCGW 160404 LN-7	5.0	9.52	4.76	0.4	4.4	●			
	160408 LN-7	4.1			0.8		●			
	VNGA 160404 LN-10	5.0	9.52	4.76	0.4	3.81	●			
	160408 LN-10	4.1			0.8		●			

• CB: PCD chipbreaker type insert.

● Marked: Standard Items

TaeguTec

SCLCR 2020 K12

TaeguTec

TaeguTec

TaeguTec

TaeguTec

TaeguTec

SK

TCLNR 25

TCLNR 25

T-TURN Toolholder Designation System

1 Clamping System	
P/Lever Lock	C/Top Clamp
S/Screw Clamp	M/Multi Lock
T-Holder	W/Wedge Clamp


4 Insert Clearance Angle	
0°	5°
N	B
7°	11°
C	P

2 Insert Shape		
80°	55°	75°
C	D	E
120°	55°	75°
H	K	R
S	T	V
80°		
		W




P C L N R

3 Approach Angle								
Symbol	Shape	Offset	Symbol	Shape	Offset	Symbol	Shape	Offset
A		x	J		○	V		x
			K		○	W		○
B		x	L		○	X		
			M		x	C*		x
D		x	N		x	H*		○
E		x	R		○	Q*		○
F		○	R		○			
G		○	T		○			
			U		○			

* TaeguTec standard




T-TURN Toolholder Designation System



25 **25** **M** **12** - **10** **11**

8 | Tool Length







L (mm)	Symbol	L (mm)	Symbol
32	A	160	N
40	B	170	P
50	C	180	Q
60	D	200	R
70	E	250	S
80	F	300	T
90	G	350	U
100	H	400	V
110	J	450	W
125	K	500	Y
140	L	Special	X
150	M		




11 | Manufacturer's Type Designation

Unique to manufacturer


T-TURN Toolholder Clamping System

T-Holder Type  <p>① Insert ② Shim Screw ③ Shim ④ Clamp Screw ⑤ Clamp ⑥ Spring</p>	T  <p>① Insert ② Shim ③ Shim Pin ④ Clamp Set</p>
Top Clamp Type  <p>① Insert ② Shim ③ Shim Screw ④ Clamp ⑤ Clamp Screw ⑥ Pin and Spring ⑦ Clamp Spring</p>	C  <p>① Insert ② Shim ③ Lock Pin ④ Clamp ⑤ Clamp Screw</p>
Lever Lock Type  <p>① Insert ② Shim ③ Lever ④ Shim Pin ⑤ Screw</p>	P  <p>① Insert ② Shim ③ Screw ④ Shim Screw</p>
Wedge Clamp Type  <p>① Insert ② Shim ③ Pin Screw ④ Wedge Set</p>	W  <p>① Insert ② Shim Screw ③ Shim ④ Clamp Screw ⑤ Clamp</p>
Ceramic Dimple Holder  <p>① Insert ② Shim Screw ③ Shim ④ Clamp Screw ⑤ Clamp ⑥ Spring</p>	T  <p>① Insert ② Shim Pin ③ Shim ④ Hook Lever ⑤ Screw</p>
Ceramic Holder  <p>① Insert ② Shim Screw ③ Shim ④ Clamp Screw ⑤ Clamp</p>	
	H 


New clamp for multi-function




DCL S-4H



DCL S-4D




DCL S-4F






Clamp	Designation	Components			Insert	Shim
		① Clamp	② CTC Plate	③ PIN		
	DCL S-4H	DCL 4H	DCL 4-PL	PIN 0683	CN□A 1204 DN□A 1504 DN□A 1506 SN□A 1204	TSC 44 TSD 44 TSD 43 TSS 44
	DCL S-4D	DCL 4D	DCL 4-PL	PIN 0683	CN□X 1207 CH DN□X 1507 CH SN□X 1207 CHX	TSC 42 TSD 42 TSS 42
	DCL S-4F	DCL 4F	DCL 4-PL	PIN 0683	CN□N 1204 CN□N 1207 DN□N 1504 DN□N 1507 SN□N 1204 SN□N 1207	TSC 44 TSC 42 TSD 44 TSD 42 TSS 44 TSS 42

Conventional





Multi functional clamp system



Holder: ex) TCLNR 2525 M12

- Existing T-Holder is available only if changing each clamp type
- 3 types of Insert can be mounted in same Tool-holder

BCLCR/L-SH





Designation	Dimension (mm)								Insert	Components			
	R	L	h	h1	b	b1	l	f		Lever	Lever Screw	Snap Ring	Wrench
BCLCR/L 1010 K06-SH	●	●	10		10		125	10		BLCL 2	BLCS 2	BLSR 2	T 6
1212 K06-SH	●	●	12		12		125	12					
1010 K09-SH	●	●	10	3	10	4	125	10	17	CCOT 09T3□□	BLCL 3	BLCS 3	BLSR 3
1212 K09-SH	●	●	12	1	12	2	125	12	17	CCOT 09T3□□	BLCL 3	BLCS 3	L-W 2F

• For inserts, see page A39 - A40

• Marked: Standard Items

• For spare part, see page A167 - A177

BDJCR/L-SH





Designation	Dimension (mm)								Insert	Components			
	R	L	h	h1	b	b1	l	f		Lever	Lever Screw	Snap Ring	Wrench
BDJCR/L 1010 K07-SH	●	●	10		10		125	10		BLCL 2	BLCS 2	BLSR 2	T 6
1212 K07-SH	●	●	12		12		125	12					
1010 K11-SH	●	●	10	3	10	4	125	10	20	DCOT 11T3□□	BLCL 3	BLCS 3	BLSR 3
1212 K11-SH	●	●	12	1	12	2	125	12	20	DCOT 11T3□□	BLCL 3	BLCS 3	L-W 2F

• For inserts, see page A41 - A42

• Marked: Standard Items

• For spare part, see page A167 - A177

BDNCN-SH





Designation	Dimension (mm)								Insert	Components			
	h	h1	b	b1	l	f	e	Lever		Lever Screw	Snap Ring	Wrench	
BDNCN 1010 K07-SH	●	10		10		125	5			BLCL 2	BLCS 2	BLSR 2	T 6
1212 K07-SH	●	12		12		125	6						
1010 K11-SH	●	10	3	10	1	125	5	22	DCOT 11T3□□	BLCL 3	BLCS 3	BLSR 3	L-W 2F
1212 K11-SH	●	12	1	12		125	6	22	DCOT 11T3□□	BLCL 3	BLCS 3	BLSR 3	L-W 2F

• For inserts, see page A41 - A42

• Marked: Standard Items

• For spare part, see page A167 - A177

BVJBR/L-SH





Designation	Dimension (mm)									Insert	Components			
	R	L	h	h1	b	b1	I	f	e		Lever	Lever Screw	Snap Ring	Wrench
BVJBR/L 1010 K11-SH	●	●	10	1	10		125	10	20	VB□T 1103□□	BLCL 2	BLCS 2	BLSR 2	T 6
1212 K11-SH	●	●	12		12		125	12						

• For inserts, see page A46 - A47

• For spare part, see page A167 - A177

● Marked: Standard Items

BVJCR/L-SH





Designation	Dimension (mm)									Insert	Components			
	R	L	h	h1	b	I	f	e	Lever	Lever Screw	Snap Ring	Wrench		
BVJCR/L 1010 K11-SH	●	●	10	1	10	125	10	20	VC□T 1103□□	BLCL 2	BLCS 2	BLSR 2	T 6	
1212 K11-SH	●	●	12		12	125	12							

• For inserts, see page A47

• For spare part, see page A167 - A177

● Marked: Standard Items

CKJNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	I	h1	f		Clamp	Screw	Clamp Spring	Pin & Spring	Shim	Shim Screw
CKJNR/L 2020 K16	●	●	20	20	125	35	25	KNUX 1604 □□ R/L11 1604 □□ R/L12	CL 16KR/L CLS 16K KSP 90 KSP 48 KP 48S CSK 1604R/L	FH M3x0.5x10	L-W 4			
2020 M16	●		20	20	150	35	25							
2525 M16	●	●	25	25	150	32	32							
3225 P16	●		32	25	170	33.3	32							
3232 M16	●		32	32	150	33.3	40							
3232 P16	●	●	32	32	170	33.3	40							
4040 R16	●		40	40	200	33.3	50							

• For inserts, see page A30

• For spare part, see page A167 - A177

● Marked: Standard Items

CKNNR/L





Designation	Dimension (mm)						Insert	Components						
	R	L	h	b	I	l1	f	Clamp	Screw	Clamp Spring	Pin & Spring	Shim	Shim Screw	Wrench
CKNNR/L 2525 M16	●	25	25	150	44.7	14.4	KNUX 1604 □□ R/L11	CL 16KR/L	CLS 16K	KSP 90	KSP 48 KP 48S	CSK 1604R/L	FH M3x0.5x10	L-W 4
3225 M16		32	25	150	44.7	14.4	1604 □□ R/L12							

• For inserts, see page A30

● Marked: Standard Items

• For spare part, see page A167 - A177

CSDPN





Designation	Dimension (mm)						Insert	Components						
	h	b	I	l1	f	Clamp	Screw	Shim	Shim Pin	Snap Ring	Wrench			
CSDPN 1616 H09	16	16	100	24	8.0	SPMR, SPDN 0903 □□	CL 2	CLS 2	CSS 32	CSP 3	CSR 2	L-W 2.5		
2020 K12	20	20	125	29	10	SPMR, SPDN 1203 □□	CL 3	CLS 3	CSS 42	CSP 3	WSR 4	L-W 3		
2525 M12	●	25	25	150	29	12.5	SPMR, SPDN 1203 □□							

• For inserts, see page A43

● Marked: Standard Items

• For spare part, see page A167 - A177

CTCPN





Designation	Dimension (mm)						Insert	Components						
	h	b	I	l1	f	Clamp	Screw	Shim	Shim Pin	Snap Ring	Wrench			
CTCPN 2009 K11	●	20	9	125	20	9.4	TPMR, TPDN 1103 □□	CL 2C	CLS 2C	-	-	CSR 2C	L-W 2.5	
2020 K22	20	20	125	50	19.4	TPMR, TPDN 2204 □□	CLM 12	XNSM 0825	CST 43	CSP 16K	CSR 4	L-W 4		
2513 Q16	●	25	13	180	30	14.1	TPMR, TPDN 1603 □□	CL 3C	CLS 3C	CST 32	CSP 3	CSR 2	L-W 3	
2525 M22	●	25	25	150	50	19.4	TPMR, TPDN 2204 □□	CLM 12	XNSM 0825	CST 43	CSP 16K	CSR 4	L-W 4	

• For inserts, see page A45 - A46

● Marked: Standard Items

• For spare part, see page A167 - A177

CTFPR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	l	l ₁	f		Clamp	Screw	Shim	Shim Pin	Snap Ring	Wrench
CTFPR/L 1616 H11			16	16	100	14.4	20	TPMR, TP□N 1103 □□	CL 2	CLS 2	-	-	CSR 2	L-W 2.5
2020 K11			20	20	125	16	25							
2020 K16	●	20	20	125	20	25	32	TPMR, TP□N 1603 □□	CL 3	CLS 3	CST 32	CSP 3	WSR 4	L-W 3
2525 M16	●	25	25	150	20	32								

• For inserts, see page A45 - A46

• For spare part, see page A167 - A177

● Marked: Standard Items

CTGPR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	l	l ₁	f		Clamp	Screw	Shim	Shim Pin	Snap Ring	Wrench
CTGPR/L 1212 F11			12	12	80	19	16	TPMR, TP□N 1103 □□	CL 2	CLS 2	-	-	CSR 2	L-W 2.5
1616 H11			16	16	100	19	20							
2020 K11		20	20	125	19	25								
2020 K16	●	20	20	125	25	25	32	TPMR, TP□N 1603 □□	CL 3	CLS 3	CST 32	CSP 3	WSR 4	L-W 3
2525 M16	●	25	25	150	25	32								
2525 M22		25	25	150	30	32	40	TPMR, TP□N 2204 □□	CL 4	CLS 4	CST 43	CSP 16K	CSR 4	L-W 4
3232 P22		32	32	170	30	40								

• For inserts, see page A45 - A46

• For spare part, see page A167 - A177

● Marked: Standard Items

MDJNR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	l	l ₁	f		Clamp	Screw	Shim	Lock Pin	Wrench
MDJNR/L 2020 K15	●	20	20	125	45	25	DN□□ 1504 □□	CLM 30	XNSM 0825	S 45	MLP 4		L-W 2.5
2525 M15	●	25	25	150	45	32							L-W 4
MDJNR/L 2020 K15A	●	20	20	125	45	25	DN□□ 1506 □□	CLM 30	XNSM 0825	MSD 43	MLP 4-06		L-W 2.5
2525 M15A	●	25	25	150	45	32							L-W 4
3232 P15A	●	32	32	170	45	40							

• For inserts, see page A28 - A29

• For spare part, see page A167 - A177

● Marked: Standard Items

MDNNN





Designation		Dimension (mm)					Insert	Components				
		h	b	l	l1	f		Clamp	Screw	Shim	Lock Pin	Wrench
MDNNN 2525 M15 3225 P15	● 32	25 25	25 170	150 45	45 12.5	12.5	DN□□ 1504 □□	CLM 30	XNSM 0825	S 45	MLP 4	L-W 2.5 L-W 4
MDNNN 2525 M15A	●	25	25	150	45	12.5	DN□□ 1506 □□	CLM 30	XNSM 0825	MSD 43	MLP 4-06	L-W 2.5 L-W 4

• For inserts, see page A28 - A29

● Marked: Standard Items

• For spare part, see page A167 - A177

MDQNR/L





Designation	R	L	Dimension (mm)					Insert	Components				
			h	b	l	l1	f		Clamp	Screw	Shim	Lock Pin	Wrench
MDQNR/L 2020 K15 2525 M15	● ●	25 ●	20 25	20 150	125 40	40 32	25	DN□□ 1504 □□	CLM 30	XNSM 0825	S 45	MLP 4	L-W 2.5 L-W 4
MDQNR/L 2525 M15A	●	●	25	25	150	40	32	DN□□ 1506 □□	CLM 30	XNSM 0825	MSD 43	MLP 4-06	L-W 2.5 L-W 4

• For inserts, see page A28 - A29

● Marked: Standard Items

• For spare part, see page A167 - A177

MTJNR/L





Designation	R	L	Dimension (mm)					Insert	Components				
			h	b	l	l1	f		Clamp	Screw	Shim	Lock Pin	Wrench
MTJNR/L 2020 K16 2525 M16 2525 M1604	● ● ●	25 25 25	20 25 150	20 150	125 28	28 32	25	TN□□ 1603 □□ TN□□ 1604 □□	CLM 6	XNSM 0520	S 3 S 31	MLP 3	L-W 2 L-W 2.5

• For inserts, see page A33 - A35

● Marked: Standard Items

• For spare part, see page A167 - A177

MVJNR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l1	f		Clamp	Screw	Shim	Lock Pin	Wrench
MVJNR/L 2020 K16	●	●	20	20	125	42	25	VN□□ 1604 □□	CLM 30	XNSM 0825	IVSN 324	MLP 3	L-W 2 L-W 4
2525 M16	●	●	25	25	150	42	32						
3225 P16	●	●	32	25	170	42	32						
3232 P16	●	●	32	32	170	42	40						

• For inserts, see page A36

• For spare part, see page A167 - A177

● Marked: Standard Items

MVQNR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l1	f		Clamp	Screw	Shim	Lock Pin	Wrench
MVQNR/L 2020 K16	●	●	20	20	125	42	25	VN□□ 1604 □□	CLM 30	XNSM 0825	IVSN 324	MLP 3	L-W 2 L-W 4
2525 M16	●	●	25	25	150	42	32						
3232 P16	●	●	32	32	170	42	40						

• For inserts, see page A36

• For spare part, see page A167 - A177

● Marked: Standard Items

MVVNN





Designation	Dimension (mm)							Insert	Components				
	h	b	I	l1	f	Clamp	Screw	Shim	Lock Pin	Wrench			
MVVNN 2020 K16	●	20	20	125	46	10.0	VN□□ 1604 □□	CLM 30	XNSM 0825	IVSN 324	MLP 3	L-W 2 L-W 4	
2525 M16	●	25	25	150	46	12.5							

• For inserts, see page A36

• For spare part, see page A167 - A177

● Marked: Standard Items

MWLNRL





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	l	l ₁	f		Clamp	Screw	Shim	Lock Pin	Snap Ring	Wrench
MWLNL 1616 H06			16	16	100	19.4	16	WN□□0604 □□	CL 2	CLS 2	MSW 32	MLP 3	CSR 2	L-W 2 L-W 2.5
2020 K08			20	20	125	25	25	WN□□ 0804 □□	CL 2	CLS 2	MSW 43	MLP 4	CSR 2	L-W 2.5
2525 M08			25	25	150	25	32							

• For inserts, see page A37 - A38

• For spare part, see page A167 - A177

● Marked: Standard Items

PCBNRL





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	l	l ₁	f		Lever	Screw	Shim	Shim Pin	Wrench
PCBNRL 2020 K12	●	●	20	20	125	28	17.5	CN□□ 1204 □□	LCL 4	LCS 4	LSC 42	LSP 4	L-W 3
2525 M12	●	●	25	25	150	28	22.5						
3225 P12	●	●	32	25	170	28	22.5						
2525 M16	●	●	25	25	150	32	22	CN□□ 1606 □□	LCL 5	LCS 5	LSC 53	LSP 5	L-W 3
3232 P16	●	●	32	32	170	32	27						
3232 P19	●	●	32	32	170	37	27	CN□□ 1906 □□	LCL 6	LCS 6	LSC 63	LSP 6	L-W 4
4040 S19	●	●	40	40	250	37	37						
4040 S25	●	●	40	40	250	50	37	CN□□ 2509 □□	LCL 8	LCS 8	LSC 83	LSP 8	L-W 5
5050 T25	●	●	50	50	300	50	47						

• For inserts, see page A24 - A27

• For spare part, see page A167 - A177

● Marked: Standard Items

PCLNR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l ₁	f		Lever	Screw	Shim	Shim Pin	Wrench
PCLNR/L 1616 H09	●	16	16	100	22	20		CN□□ 0903 □□	LCL 3	LCS 3	LSC 32	LSP 3	L-W 2.5
2020 K09	●	20	20	125	22	25							
2525 M09	●	25	25	150	22	32							
1616 H12	● ●	16	16	100	27	20			LCS 4				
2020 K12	● ●	20	20	125	27	25			LCL 4		LSC 42	LSP 4	L-W 3
2525 M12	● ●	25	25	150	27	32							
3225 P12	● ●	32	25	170	27	32							
3232 P12	● ●	32	32	170	27	40							
2525 M16	● ●	25	25	150	33	32							
3225 P16		32	25	170	33	32		CN□□ 1606 □□	LCL 5	LCS 5	LSC 53	LSP 5	L-W 3
3232 P16	● ●	32	32	170	33	40							
2525 M19	● ●	25	25	150	38	32							
3225 P19		32	25	170	38	32		CN□□ 1906 □□	LCL 6	LCS 6	LSC 63	LSP 6	L-W 4
3232 P19	● ●	32	32	170	38	40							
4040 S19	● ●	40	40	250	38	50							
4040 S25	● ●	40	40	250	47	50		CN□□ 2509 □□	LCL 8	LCS 8	LSC 83	LSP 8	L-W 5
5050 T25	● ●	50	50	300	47	60							

● For inserts, see page A24 - A27

● For spare part, see page A167 - A177

● Marked: Standard Items

PDJNR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l ₁	f		Lever	Screw	Shim	Shim Pin	Wrench
PDJNR/L 1616 H11		16	16	100	30	20							
2020 K11		20	20	125	30	25		DN□□ 1104 □□	LCL 12C	LCS 3	LSD 32	LSP 3A	L-W 2.5
2525 M11	● ●	25	25	150	30	32							
2020 K15	● ●	20	20	125	34	25							
2525 M15	● ●	25	25	150	34	32		DN□□ 1506 □□	LCL 4A	LCS 4	LSD 42	LSP 4	L-W 3
3225 P15	● ●	32	25	170	34	32							
3232 P15	● ●	32	32	170	34	40							
2020 K15A	● ●	20	20	125	34	25		DN□□ 1504 □□	LCL 4A	LCS 4	LSD 42	LSP 4	L-W 3
2525 M15A	● ●	25	25	150	34	32							

● For inserts, see page A28 - A29

● For spare part, see page A167 - A177

● Marked: Standard Items

PDNNR/L





Designation	Dimension (mm)						Insert	Components					
	R	L	h	b	l	l ₁	f	Lever	Screw	Shim	Shim Pin	Wrench	
PDNNR/L 2020 K15	●	●	20	20	125	36.5	10	DN□□ 1506 □□	LCL 4A	LCS 4	LSD 42	LSP 4	L-W 3
2525 M15	●	●	25	25	150	36.5	12						
3232 P15	●	●	32	32	170	36.5	16.8						

• For inserts, see page A28 - A29

• For spare part, see page A167 - A177

● Marked: Standard Items

PRDCN




Designation	Dimension (mm)						Insert	Components				
	h	b	l	l ₁	f	Lever	Screw	Shim	Shim Pin	Wrench		
PRDCN 2020 M10	●	20	20	150	50	10.0	RC□X 100300	LCL 10C	LCS 2	LSR 32	LSP 3A	L-W 2
2525 M10	●	25	25	150	50	12.5						
2020 K12	●	20	20	125	50	10.0	RC□X 120400	LCL 12C	LCS 3	LSR 1203	LSP 3A	L-W 2.5
2525 M12	●	25	25	150	50	12.5						
3225 Q12	●	32	25	180	50	12.5	RC□X 160600	LCL 16C	LCS 16C	LSR 1604	LSP 16C	L-W 2.5
2525 Q16	●	25	25	180	50	12.5						
3225 Q16	●	32	25	180	50	12.5						
3232 Q16	●	32	32	180	50	16.0						
3232 S20	●	32	32	250	60	16.0	RC□X 200600	LCL 20C	LCS 5	LSR 2004	LSP 5	L-W 3
4040 S20	●	40	40	250	80	20.0						
4040 S25	●	40	40	300	80	20.0	RC□X 250700	LCL 25C	LCS 25C	LSR 2506	LSP 6	L-W 4
4040 T25	●	40	40	300	80	20.0						
5050 U32	●	50	50	350	90	25.0	RC□X 320900	LCL 32C	LCS 8	LSR 3206	LSP 8	L-W 5

• For inserts, see page A42

• For spare part, see page A167 - A177

● Marked: Standard Items

PRGCR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	l	l ₁	f		Lever	Screw	Shim	Shim Pin	Wrench
PRGCR/L 2020 K10	●		20	20	125	14.5	25						
2525 M10	●	●	25	25	150	17.5	32	RC□X 100300	LCL 10C	LCS 2	LSR 32	LSP 3A	L-W 2
3225 P10			32	25	170	17	32						
2020 K12	●		20	20	125	18	25						
2525 M12	●	●	25	25	150	18	32	RC□X 120400	LCL 12C	LCS 3	LSR 1203	LSP 3A	L-W 2.5
3225 P12	●	●	32	25	170	18	32						
2525 M16	●		25	25	150	23	32						
3225 P16	●		32	25	170	23	32	RC□X 160600	LCL 16C	LCS 16C	LSR 1604	LSP 16C	L-W 2.5
3232 P16	●		32	32	170	23	40						
4040 P16			40	40	170	23	50						
3232 P20	●	●	32	32	170	27.5	40	RC□X 200600	LCL 20C	LCS 5	LSR 2004	LSP 5	L-W 3
4040 S25	●	●	40	40	250	33.5	50	RC□X 250700	LCL 25C	LCS 25C	LSR 2506	LSP 6	L-W 4
4040 S32	●		40	40	250	41	50	RC□X 320900	LCL 32C	LCS 8	LSR 3206	LSP 8	L-W 5

• For inserts, see page A42

• For spare part, see page A167 - A177

● Marked: Standard Items

PRGNR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	l	l ₁	f		Lever	Screw	Shim	Shim Pin	Wrench
PRGNR/L 2020 K09			20	20	125	22	25	RNMG 090300	LCL 3	LCS 3	LSR 32	LSP 3A	L-W 2.5
2525 M12	●		25	25	150	28	32	RNMG 120400	LCL 4	LCS 4	LSR 42	LSP 4	L-W 3
3225 P15			32	25	170	35	32	RNMG 150600	LCL 5	LCS 5	LSR 53	LSP 5	L-W 3
3232 P19			32	32	170	38	40	RNMG 190600	LCL 6	LCS 6	LSR 63	LSP 6	L-W 4

• For inserts, see page A30

• For spare part, see page A167 - A177

● Marked: Standard Items

PSBNR/L





Designation	Dimension (mm)						Insert	Components				
	R	L	h	b	l	l1	f	Lever	Screw	Shim	Shim Pin	Wrench
PSBNR/L 1616 H09	● ●	16	16	100	21	13						
2020 K09		20	20	125	21	17	SN□□ 0903 □□	LCL 3	LCS 3	LSS 32	LSP 3	L-W 2.5
2020 K12	● ●	20	20	125	28	17						
2525 M12	● ●	25	25	150	28	22	SN□□ 1204 □□	LCL 4	LCS 4	LSS 42	LSP 4	L-W 3
3225 P12	● ●	32	25	170	28	22						
2525 M15	● ●	25	25	150	34	22	SN□□ 1506 □□	LCL 5	LCS 5	LSS 53	LSP 5	L-W 3
3232 P19	● ●	32	32	170	39	27						
4040 S19	● ●	40	40	250	39	35	SN□□ 1906 □□	LCL 6	LCS 6	LSS 63	LSP 6	L-W 4
4040 S25	● ●	40	40	250	48	35						
5050 T25	● ●	50	50	300	48	43	SN□□ 2507 □□	LCL 8	LCS 8	LSS 84	LSP 8	L-W 5

• For inserts, see page A31 - A33

• For spare part, see page A167 - A177

● Marked: Standard Items

PSDNN





Designation	Dimension (mm)						Insert	Components				
	h	b	l	l1	f	Lever	Screw	Shim	Shim Pin	Wrench		
PSDNN 1616 H09	●	16	16	100	21	8.0	SN□□ 0903 □□	LCL 3	LCS 3	LSS 32	LSP 3	L-W 2.5
2020 K12	●	20	20	125	28	10.0						
2525 M12	●	25	25	150	28	12.5	SN□□ 1204 □□	LCL 4	LCS 4	LSS 42	LSP 4	L-W 3
3225 P12	●	32	25	170	28	12.5						
2020 K15		20	20	125	34	10.0	SN□□ 1506 □□	LCL 5	LCS 5	LSS 53	LSP 5	L-W 3
2525 M15	●	25	25	150	34	12.5						
3232 P19		32	25	170	40.5	12.5						
3232 P19	●	32	32	170	40.5	16.0						
4040 S19	●	40	40	250	40.5	20.0	SN□□ 1906 □□	LCL 6	LCS 6	LSS 63	LSP 6	L-W 4
5050 S19		50	50	250	40.5	25.0						
4040 S25	●	40	40	250	49	20.0	SN□□ 2507 □□	LCL 8	LCS 8	LSS 84	LSP 8	L-W 5
5050 T25	●	50	50	300	49	25.0						

• For inserts, see page A31 - A33

• For spare part, see page A167 - A177

● Marked: Standard Items

PSKNR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l ₁	f		Lever	Screw	Shim	Shim Pin	Wrench
PSKNR/L 2020 K09			20	20	125	19	25	SN□□0903□□	LCL 3	LCS 3	LSS 32	LSP 3	L-W 2.5
2020 K12	●	●	20	20	125	25	25	SN□□1204□□	LCL 4	LCS 4	LSS 42	LSP 4	L-W 3
2525 M12	●	●	25	25	150	25	32						
2525 M15			25	25	150	32	32	SN□□1506□□	LCL 5	LCS 5	LSS 53	LSP 5	L-W 3
3232 P15			32	32	170	32	40						
3232 P19	●	●	32	32	170	38	40	SN□□1906□□	LCL 6	LCS 6	LSS 63	LSP 6	L-W 4
4040 S19	●	●	40	40	250	38	50						
4040 S25	●		40	40	250	42	50	SN□□2507□□	LCL 8	LCS 8	LSS 84	LSP 8	L-W 5
5050 T25			50	50	300	42	60						

• For inserts, see page A31 - A33

● Marked: Standard Items

• For spare part, see page A167 - A177

PSSNR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l ₁	f		Lever	Screw	Shim	Shim Pin	Wrench
PSSNR/L 1616 H09	●		16	16	100	21.5	20	SN□□0903□□	LCL 3	LCS 3	LSS 32	LSP 3	L-W 2.5
2020 K09			20	20	125	21.5	25						
2020 K12	●	●	20	20	125	30	25						
2525 K12			25	25	125	30	32						
2525 M12	●	●	25	25	150	30	32	SN□□1204□□	LCL 4	LCS 4	LSS 42	LSP 4	L-W 3
3225 P12	●		32	25	170	30	32						
3232 P12	●		32	32	170	32	40						
3232 P15			32	32	170	37	40	SN□□1506□□	LCL 5	LCS 5	LSS 53	LSP 5	L-W 3
3232 P19	●	●	32	32	170	42	40	SN□□1906□□	LCL 6	LCS 6	LSS 63	LSP 6	L-W 4
4040 S19			40	40	250	42	50						
4040 S25			40	40	250	53	50	SN□□2507□□	LCL 8	LCS 8	LSS 84	LSP 8	L-W 5

• For inserts, see page A31 - A33

● Marked: Standard Items

• For spare part, see page A167 - A177

PTFNR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l1	f		Lever	Screw	Shim	Shim Pin	Wrench
PTFNR/L 1616 H16	●	16	16	100	20	20		TN□□ 1604 □□	LCL 3	LCS 3	LST 31.8	LSP 3A	L-W 2.5
2020 K16	●	20	20	125	20	25							
2525 M16	●	25	25	150	20	32							
2525 M22	●	25	25	150	25	32		TN□□ 2204 □□	LCL 4	LCS 4	LST 42	LSP 4	L-W 3
3232 P22	●	32	32	170	25	40							
4040 S27	●	40	40	250	33	50		TN□□ 2706 □□	LCL 5	LCS 5	LST 53	LSP 5	L-W 3

• For inserts, see page A33 - A35

• For spare part, see page A167 - A177

• Marked: Standard Items

PTGNR/L



Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l1	f		Lever	Screw	Shim	Shim Pin	Wrench
PTGNR/L 1010 E11	●	10	10	70	15	12		TN□□ 1103 □□	LCL 2B	LCS 2B	-	*LSR 2B	L-W 2
1212 F11	●	12	12	80	15	16							
2525 M11	●	25	25	150	30	32							
1616 H16	●	16	16	100	22	20							
2020 K16	●	20	20	125	22	25							
2525 M16	●	25	25	150	22	32		TN□□ 1604 □□	LCL 3	LCS 3	LST 31.8	LSP 3A	L-W 2.5
3232 P16	●	32	25	170	22	32							
3232 P16	●	32	32	170	22	40							
2525 M22	●	25	25	150	29	32							
3232 P22	●	32	25	170	29	32		TN□□ 2204 □□	LCL 4	LCS 4	LST 42	LSP 4	L-W 3
3232 P22	●	32	32	170	29	40							
4040 S27	●	40	40	250	35	50		TN□□ 2706 □□	LCL 5	LCS 5	LST 53	LSP 5	L-W 4



• For inserts, see page A33 - A35

• For spare part, see page A167 - A177

• Marked: Standard Items

*LSR 2B is Snap Ring

PTTNR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l1	f		Lever	Screw	Shim	Shim Pin	Wrench
PTTNR/L 1616 H16	●	16	16	100	24	13		TN□□ 1604 □□	LCL 3	LCS 3	LST 31.8	LSP 3A	L-W 2.5
2020 K16	●	20	20	125	24	17							
2525 M16	●	25	25	150	24	22							
2525 M22	●	25	25	150	34	22		TN□□ 2204 □□	LCL 4	LCS 4	LST 42	LSP 4	L-W 3

• For inserts, see page A33 - A35

• For spare part, see page A167 - A177

• Marked: Standard Items

SCACR/L-SH





Designation	Dimension (mm)							Insert	Components	
	R	L	h	b	l	l ₁	f		Screw	Wrench
SCACR/L 0808 K06-SH			8	8	125	8	8	0		
1010 K06-SH			10	10	125	10	10	0	CC□T 0602 □□	SO 25065I
1010 K09-SH			10	10	125	15	10	2		T 7
1212 K09-SH			12	12	125	15	12	0	CC□T 09T3 □□	SO 35080I
1616 K09-SH	●		16	16	125	16	16	0		T 15

• For inserts, see page A39 - A40

● Marked: Standard Items

• For spare part, see page A167 - A177

SCLCR/L





Designation	Dimension (mm)							Insert	Components			
	R	L	h	b	l	l ₁	f		Screw	Shim	Shim Screw	Wrench
SCLCR/L 0808 F06	●		8	8	80	10	10	CC□T 0602 □□	SO 25065I	-	-	T 7
1010 F06	●	●	10	10	80	10	12					
1212 F09	●	●	12	12	80	16	16	CC□T 09T3 □□	SO 35080I	-	-	
1616 H09	●	●	16	16	100	16	20					T 15
2020 K09	●	●	20	20	125	20	25		SO 35124I	SSC 32	SO 50090S	
2525 M09	●		25	25	150	20	32					
2020 K12	●	●	20	20	125	25	25	CC□T 1204 □□	SO 45130I	SSC 43N	SO 60105S	T 20
2525 M12	●	●	25	25	150	26	32					

• For inserts, see page A39 - A40

● Marked: Standard Items

• For spare part, see page A167 - A177

SCLCR/L-SH




Designation	Dimension (mm)							Insert	Components		
	R	L	h	b	l	l ₁	f		Screw	Wrench	
SCLCR/L 0808 K06-SH			8	8	125	8	8	0	CC□T 0602 □□	SO 25065I	T 7
1010 K06-SH			10	10	125	10	10	0			
1010 K09-SH			10	10	125	15	10	2	CC□T 09T3 □□	SO 35080I	T 15
1212 K09-SH	●		12	12	125	15	12	0			
1616 K09-SH	●		16	16	125	16	16	0			

• For inserts, see page A39 - A40

● Marked: Standard Items

• For spare part, see page A167 - A177



SDJCR/L


Designation	Dimension (mm)							Insert	Components			
	R	L	h	b	I	l ₁	f		Screw	Shim	Shim Screw	Wrench
SDJCR/L 0808 E07	●	●	8	8	70	13	10	DCOT 0702 □□	SO 25065I	-	-	T 7
1212 F07	●	●	12	12	80	15	16					
1616 H07	●	●	16	16	100	15	20	DCOT 11T3 □□	SO 35124I	SSD 32	SO 50090S	T 15
2020 K07	●	●	20	20	125	20	25					
1616 H11	●	●	16	16	100	24	20					
2020 K11	●	●	20	20	125	24	25	DCOT 11T3 □□	SO 35124I	SSD 32	SO 50090S	T 15
2525 M11	●	●	25	25	150	28	32					

- For inserts, see page A41 - A42

- For spare part, see page A167 - A177

- Marked: Standard Items


SDJCR/L-SH


Designation	Dimension (mm)							Insert	Components		
	R	L	h	b	I	l ₁	f		Screw	Wrench	
SDJCR/L 0808 K07-SH	●	8	8	125	12.7	8	0	DCOT 0702 □□	SO 25065I	-	T 7
1010 K07-SH	●	10	10	125	15	10	0				
1010 K11-SH	●	10	10	125	20	10	2	DCOT 11T3 □□	SO 35080I	-	T 15
1212 K11-SH	●	12	12	125	20	12	0				
1616 K11-SH	●	16	16	125	20	16	0				

- For inserts, see page A41 - A42

- For spare part, see page A167 - A177

- Marked: Standard Items

SDJNR/L




Designation	Dimension (mm)							Insert	Components			
	R	L	h	b	I	l ₁	f		Screw	Shim	Shim Screw	Wrench
SDJNR/L 1616 H11	●	16	16	100	25	20	DNMG 1104 □□	SO 35120I	SSD 32	SO 50090S	T 10	
2020 K11	●	20	20	125	25	25						
2525 M11	●	25	25	150	25	32						

- For inserts, see page A28 - A29

- For spare part, see page A167 - A177

- Marked: Standard Items

SDNCN-SH





Designation		Dimension (mm)					Insert	Components	
		h	b	l	l ₁	f		Screw	Wrench
SDNCN 0808 K07-SH		8	8	125	15	4	DCMT 0702 □□	SO 25065I	T 7
1010 K07-SH		10	10	125	15	5			
1010 K11-SH	●	10	10	125	22	5	DCMT 11T3 □□	SO 35080I	T 15
1212 K11-SH	●	12	12	125	22	6			
1616 K11-SH		16	16	125	22	8			

• For inserts, see page A41 - A42

• For spare part, see page A167 - A177

● Marked: Standard Items

SDNCN




Designation		Dimension (mm)					Insert	Components			
		h	b	l	l ₁	f		Screw	Shim	Shim Screw	Wrench
SDNCN 0808 F07	●	8	8	80	15	4	DCMT 0702 □□	SO 25065I	-	-	T 7
1010 F07	●	10	10	80	15	5					
1616 H11	●	16	16	100	22	8	DCMT 11T3 □□	SO 35080I	SSD 32	SO 50090S	T 15
2525 M11	●	25	25	150	22	12.5					

• For inserts, see page A41 - A42

• For spare part, see page A167 - A177

● Marked: Standard Items

SDQNR/L





Designation		Dimension (mm)					Insert	Components				
		R	L	h	b	l	l ₁	f	Screw	Shim	Shim Screw	Wrench
SDQNR/L 1616 H11	●	16	16	100	22	20		DNMG 1104 □□	SO 35120I	SSD 32	SO 50090S	T 10
2020 K11	●	20	20	125	22	25						
2525 M11	●	25	25	150	22	32						

• For inserts, see page A28 - A29

• For spare part, see page A167 - A177

● Marked: Standard Items

SRDCN




Designation		Dimension (mm)					Insert	Components	
		h	b	l	h1	f		Screw	Wrench
SRDCN 1616 H10	●	16	16	100	17.2	8	RC□T 10T3 □□	TS 40097I	T 15
2020 K10	●	20	20	125	22.5	10			
2525 M10	●	25	25	150	27.5	12.5	RC□T 1204 □□	SO 40050I	T 15
2525 M12	●	25	25	150	27.5	12.5			

• For inserts, see page A42

• For spare part, see page A167 - A177

● Marked: Standard Items

SRGCR/L





Designation	R	L	Dimension (mm)					Insert	Components	
			h	b	l	h1	f		Screw	Wrench
SRGCR 1616 H10			16	16	100	16.7	20	RC□T 10T3 □□	TS 40097I	T 15
2020 K10			20	20	125	15	25			
2525 M10	●	●	25	25	150	15	32			

• For inserts, see page A42

• For spare part, see page A167 - A177

● Marked: Standard Items

SSDCN





Designation		Dimension (mm)					Insert	Components			
		h	b	l	h1	f		Screw	Shim	Shim Screw	Wrench
SSDCN 1212 F09	●	12	12	80	15.5	6	SC□T 09T3 □□	SO 35080I	-	-	T 15
1616 H09	●	16	16	100	15.5	8		SO 35124I	SSS 32	SO 50090S	T 15

• For inserts, see page A43

• For spare part, see page A167 - A177

● Marked: Standard Items

SSSCR/L




Designation	Dimension (mm)							Insert	Components			
	R	L	h	b	I	l ₁	f		Screw	Shim	Shim Screw	Wrench
SSSCR/L 1212 F09 1616 H09 2020 K12 2525 M12	•	•	12	12	80	15.5	14	SC□T 09T3 □□	SO 35080I	-	-	T 15
	•	•	16	16	100	15.5	17		SO 35124I	SSS 32	SO 50090S	
	•	•	20	20	125	24	22	SC□T 1204 □□	SO 45130I	SSS 43N	SO 60105S	T 20
	•	•	25	25	150	24	27					

• For inserts, see page A44

● Marked: Standard Items

• For spare part, see page A167 - A177

STFCR/L




Designation	Dimension (mm)							Insert	Components			
	R	L	h	b	I	l ₁	f		Screw	Shim	Shim Screw	Wrench
STFCR/L 1212 F11 1616 H11 1616 H16 2020 K16 2525 M16	•	12	12	80	14	16	16	TC□T 1102 □□	SO 25065I	-	-	T 7
	16	16	100	14	20							
	•	16	16	100	19	20		TC□T 16T3 □□	SO 35124I	SST 32	SO 50090S	T 15
	•	20	20	125	19	25	32					

• For inserts, see page A44

● Marked: Standard Items

• For spare part, see page A167 - A177

STGCR/L





Designation	Dimension (mm)							Insert	Components			
	R	L	h	b	I	l ₁	f		Screw	Shim	Shim Screw	Wrench
STGCR/L 1010 E09 1212 F11 1616 H11 1616 H16 2020 K16 2525 M16		10	10	70	11	12		TC□T 0902 □□	SO 22050I	-	-	T 7
	•	12	12	80	14.3	16			SO 25065I			
	•	16	16	100	14.3	20		TC□T 1102 □□	SO 35124I	SST 32	SO 50090S	T 15
	•	16	16	100	21	20						
	•	20	20	125	21	25		TC□T 16T3 □□				
	•	25	25	150	21	32						

• For inserts, see page A44

● Marked: Standard Items

• For spare part, see page A167 - A177

STGCR/L-SH





Designation	Dimension (mm)							Insert	Components	
	R	L	h	b	I	l ₁	f		Screw	Wrench
STGCR/L 1010 K11-SH			10	10	125	16	10	2		
1212 K11-SH			12	12	125	16	12	0	TC□T 1103 □□	
1616 K11-SH			16	16	125	16	16	0	SO 25065I	T 7

• For inserts, see page A44

• For spare part, see page A167 - A177

● Marked: Standard Items

SVJBR/L





Designation	Dimension (mm)							Insert	Components			
	R	L	h	b	I	l ₁	f		Screw	Shim	Shim Screw	Wrench
SVJBR/L 2020 K16	●	●	20	20	125	35	25					
2525 M16	●	●	25	25	150	35	32					
3225 P16	●	●	32	25	170	35	32					
3232 P16	●	●	32	32	170	35	40					
VB□□ 1604 □□								VB□□ 1604 □□	SO 35124I	SSV 32	TS 5035062S	T 15

• For inserts, see page A46 - A47

• For spare part, see page A167 - A177

● Marked: Standard Items

SVJBR/L-SH





Designation	Dimension (mm)							Insert	Components		
	R	L	h	b	I	l ₁	f		Screw	Wrench	
SVJBR/L 1010 K11-SH	●	●	10	10	125	21	10				
1212 K11-SH	●	●	12	12	125	21	12				
1616 K11-SH	●	●	16	16	125	21	16		SO 25065I		T 7

• For inserts, see page A46 - A47

• For spare part, see page A167 - A177

● Marked: Standard Items

SVJCR/L





Designation	Dimension (mm)							Insert	Components			
	R	L	h	b	l	l ₁	f		Screw	Shim	Shim Screw	Wrench
SVJCR/L 2020 K16	●	●	20	20	125	35	25	VCOT 1604 □□	SO 35124I	SSV 32	SO 50090S	T 15
2525 M16	●	●	25	25	150	35	32					
3225 P16			32	25	170	35	32					
3232 P16			32	32	170	47	40					

• For inserts, see page A47

● Marked: Standard Items

• For spare part, see page A167 - A177

SVJNR/L





Designation	Dimension (mm)							Insert	Components			
	R	L	h	b	l	l ₁	f		Screw	Shim	Shim Screw	Wrench
SVJNR/L 1616 H13			16	16	100	30	20	VN□□ 1304 □□	SO 35120I	SSVN 2.522	TS 5035062S	T 10
2020 K13			20	20	125	35	25					
2525 M13	●	●	25	25	150	43	32					

• For inserts, see page A36

● Marked: Standard Items

• For spare part, see page A167 - A177

SVVBN





Designation	Dimension (mm)							Insert	Components			
	h	b	l	l ₁	f	Screw	Shim	Shim Screw	Wrench			
SVVBN 2020 K16	●	20	20	125	31.5	10.0	VB□□ 1604 □□	SO 35124I	SSV 32	SO 50090S	T 15	
2525 M16	●	25	25	150	31.5	12.5						
3225 P16	●	32	25	170	31.5	12.5						

• For inserts, see page A46 - A47

● Marked: Standard Items

• For spare part, see page A167 - A177

SVVBN-SH





Designation		Dimension (mm)					Insert	Components	
		h	b	l	l ₁	f		Screw	Wrench
SVVBN	1010 K11-SH	10	10	125	22	5	VB□T 1103 □□	SO 25065I	T 7
	1212 K11-SH	● 12	12	125	22	6			
	1616 K11-SH	● 16	16	125	22	8			

• For inserts, see page A46 - A47

• For spare part, see page A167 - A177

● Marked: Standard Items

SVVCN





Designation		Dimension (mm)					Insert	Components			
		h	b	l	l ₁	f		Screw	Shim	Shim Screw	Wrench
SVVCN	2020 K16	● 20	20	125	31.5	10.0	VC□T 1604 □□	SO 35124I	SSV 32	SO 50090S	T 15
	2525 M16	25	25	150	31.5	12.5					
	3225 P16	32	25	170	31.5	12.5					
	3232 P16	32	32	170	32	16.0					

• For inserts, see page A47

• For spare part, see page A167 - A177

● Marked: Standard Items

TCBNR/L





Designation	R	L	Dimension (mm)					Insert	Components					
			h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench
TCBNR/L	● ●	25	25	150	32	22.5	CN□□ 1204 □□	● 80°	DLM 4	DLS 4	TSC 44	SO 40050I	DSP 4	L-W 3
	● ●	32	32	170	42	27	CN□□ 1906 □□		DLM 6	DLS 5	LSC 63	SO 80180I	DSP 5	L-W 4

• For inserts, see page A24 - A27

• For spare part, see page A167 - A177

● Marked: Standard Items

TCLNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	I	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench
TCLNR/L 2020 K09	●	●	20	20	125	25	25	CN□□ 0903 □□	DLM 3	DLS 3	LSC 32	SO 40085I	DSP 3	L-W 2.5
2525 M09	●		25	25	150	25	32							
2020 K12			20	20	125	32	25							
2525 M12	●	●	25	25	150	32	32	CN□□ 1204 □□	DLM 4	DLS 4	TSC 44	SO 40050I	DSP 4	L-W 3
3225 P12	●	●	32	25	170	32	32							
3232 P12	●	●	32	32	170	32	40							
2525 M16	●		25	25	150	36	32	CN□□ 1606 □□	DLM 5	DLS 5	TSC 54	SO 50090I	DSP 5	L-W 4
3232 P19	●	●	32	32	170	42	40	CN□□ 1906 □□	DLM 6	DLS 5	LSC 63	SO 80180I	DSP 5	L-W 4
4040 S19	●	●	40	40	250	42	50							

• For inserts, see page A24 - A27

● Marked: Standard Items

• For spare part, see page A167 - A177

TDJNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	I	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench
TDJNR/L 2020 K11	●	●	20	20	125	30	25	DN□□ 1104 □□	DLM 3	DLS 3	LSD 32	SO 40085I	DSP 3	L-W 2.5
2525 M11	●	●	25	25	150	30	32							
2020 K15	●	●	20	20	125	39	25	DN□□ 1506 □□	DLM 4	DLS 4	TSD 43	SO 40050I	DSP 4	L-W 3
2525 M15	●	●	25	25	150	39	32	DN□□ 1504 □□	DLM 4	DLS 4	TSD 44	SO 40050I	DSP 4	L-W 3
2525 M1504	●	●	25	25	150	39	32							

• For inserts, see page A28 - A29

● Marked: Standard Items

• For spare part, see page A167 - A177

TDNNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	I	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench
TDNNR/L 2525 M11			25	25	150	30	12.5	DNM□ 1104 □□	DLM 3	DLS 3	LSD 32	SO 40085I	DSP 3	L-W 2.5

• For inserts, see page A28 - A29

● Marked: Standard Items

• For spare part, see page A167 - A177

THSNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	l	l1	f	a	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench
THSNR/L 2525 M05	●	25	25	150	32	32	4.2	HN□□0504□□	DLM 4	DLS 4	TSH 44	SO 40050I	DSP 4	L-W 3
		25	25	150	42	32	6.5	HN□□1006□□	DLM 6	DLS 5	TSH 64	SO 50090I	DSP 5	L-W 4
	●	32	32	170	32	40	4.2	HN□□0504□□	DLM 4	DLS 4	TSH 44	SO 40050I	DSP 4	L-W 3
		32	32	170	42	40	6.5	HN□□1006□□	DLM 6	DLS 5	TSH 64	SO 50090I	DSP 5	L-W 4

• For inserts, see page A30

• For spare part, see page A167 - A177

● Marked: Standard Items

TSDNN





Designation	Dimension (mm)						Insert	Components					
	h	b	l	l1	f	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench		
TSDNN 2525 M12	●	25	25	150	34	12.5	SN□□1204□□	DLM 4	DLS 4	TSS 44	SO 40050I	DSP 4	L-W 3
	●	32	32	170	44	16	SN□□1906□□	DLM 6	DLS 5	LSS 63	SO 80180I	DSP 5	L-W 4

• For inserts, see page A31 - A33

• For spare part, see page A167 - A177

● Marked: Standard Items

TSKNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	l	l1	f		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench
TSKNR/L 2525 M12	●	25	25	150	27	32	SN□□1204□□	DLM 4	DLS 4	TSS 44	SO 40050I	DSP 4	L-W 3	

• For inserts, see page A31 - A33

• For spare part, see page A167 - A177

● Marked: Standard Items

TSSNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench
TSSNR/L 2525 M12	●	●	25	25	150	35	32	SN□□1204□□	DLM 4	DLS 4	TSS 44	SO 40050I	DSP 4	L-W 3

• For inserts, see page A31 - A33

• For spare part, see page A167 - A177

● Marked: Standard Items

TTGNR/L TTJNR/L



Designation	Dimension (mm)							Insert	Components						
	R	L	h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench	
TTGNR/L 2525 M16	●	●	25	25	150	25	32	91	TN□□1604□□	DLM3	DLS 3	TST 33	SO 35080I	DSP 3	L-W 2.5
TTJNR/L 2020 K16 2525 M16	●	20	20	125	25	25	93	TN□□1604□□							



• For inserts, see page A33 - A35

• For spare part, see page A167 - A177

• *Entering angle of TTJNR/L is 93 degrees.

● Marked: Standard Items

TWLNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench
TWLNR/L 2020 K06 2525 M06	●	20	20	125	20	25	32	WN□□0604□□	DLM 3	DLS 3	PSW 32	SO 40090I	DSP 3	L-W 2.5
2020 K08 2525 M08	●	20	20	125	30	25	32	WN□□0804□□	DLM 4	DLS 4	TSW 44	SO 40050I	DSP 4	L-W 3

• For inserts, see page A37 - A38

• For spare part, see page A167 - A177

● Marked: Standard Items

TVJNR/L





Designation	Dimension (mm)						Insert	Components						
	R	L	h	b	I	l1	f	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench	
TVJNR/L 2020 K13 2525 M13			20 25	20 25	125 150	49 49	25 32	VN□□ 1304 □□	DLM 3V	DLS 5	MSV 2.522	SC 4-SH	DSP 5	L-W 4
2020 K16 2525 M16	● ●	● ●	20 25	20 25	125 150	49 49	25 32	VN□□ 1604 □□	DLM 3V	DLS 5	TSV 33	SO 35080I	DSP 5	L-W 4

• For inserts, see page A36

• Marked: Standard Items

• For spare part, see page A167 - A177

WTENN





Designation	Dimension (mm)						Insert	Components					
	h	b	I	l1	f	Wedge Clamp	Screw	Snap Ring	Shim	Pin Screw	Wrench		
WTENN 2020 K16 2525 M16	● ●	20 25	20 25	125 150	35 35	10.0 12.5	TN□□ 1604 □□	WC 33	WCS 4	WSR 4	WST 33	WSS 33	L-W 3
2525 M22	●	25	25	150	38	12.5							
3225 P22	●	32	25	170	38	12.5	TN□□ 2204 □□	WC 43	WCS 4	WSR 4	WST 43	WSS 43	L-W 3
3232 P22	●	32	32	170	38	16.0							

• For inserts, see page A33 - A35

• Marked: Standard Items

• For spare part, see page A167 - A177

WTGNR/L





Designation	Dimension (mm)						Insert	Components					
	R	L	h	b	I	l1	f	Wedge Clamp	Screw	Snap Ring	Shim	Pin Screw	Wrench
WTGNR/L 2020 K16 2525 M16	● ●	20 25	20 25	125 150	32 32	25 32	TN□□ 1604 □□	WC 33	WCS 4	WSR 4	WST 33	WSS 33	L-W 3
2525 M22	●	25	25	150	38	32	TN□□ 2204 □□	WC 43	WCS 4	WSR 4	WST 43	WSS 43	L-W 3
3232 P22	●	32	32	170	38	40							

• For inserts, see page A33 - A35

• Marked: Standard Items

• For spare part, see page A167 - A177

WTJNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	I	l ₁	f		Wedge Clamp	Screw	Snap Ring	Shim	Pin Screw	Wrench
WTJNR/L 2020 K16	●	●	20	20	125	32	25	TN□□1604□□	WC 33	WCS 4	WSR 4	WST 33	WSS 33	L-W 3
2525 M16	●	●	25	25	150	32	32							
3225 P16	●	32	25	170	32	32								
3232 P16	●	32	32	170	38	40								
2525 M22	●	●	25	25	150	38	32	TN□□2204□□	WC 43	WCS 4	WSR 4	WST 43	WSS 43	L-W 3
3232 P22	●	●	32	32	170	38	40							

• For inserts, see page A33 - A35

• For spare part, see page A167 - A177

● Marked: Standard Items

CCLNR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Wrench
CCLNR/L 2525 M09			25	25	150	28	32	CN□N 0903□□	3127 C	SH M5 X 0.8 X 16	LSC 32	SO 40085I	L-W 4

• For inserts, see page A58

• For spare part, see page A167 - A177

● Marked: Standard Items

CRDNN





Designation	Dimension (mm)							Insert	Components				
	h	b	I	l ₁	f	Clamp	Clamp Screw	Shim	Shim Screw	Wrench			
CRDNN 2525 M09	●	25	25	150	27	12.5	RN□N 090300	3127 C	SH M5 X 0.8 X 16	LSR 32	SO 40085I	L-W 4	

• For inserts, see page A59

• For spare part, see page A167 - A177

● Marked: Standard Items

CSDNN





Designation		Dimension (mm)					Insert	Components				
		h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Wrench
CSDNN 2525 M09		25	25	125	30	12.5	SN□N 0903□□	3127 C	SH M5 X 0.8 X 16	LSS 32	SO 40085I	L-W 4

• For inserts, see page A66

• For spare part, see page A167 - A177

● Marked: Standard Items

CCLNR/L-CE





Designation	R	L	Dimension (mm)					Insert	Components				
			h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Wrench
CCLNR/L 2020 K12-CE 2525 M12-CE	●		20 25	20 25	125 150	27 27	25 32	CNGN 1207□□	BCL 6	BH M6 X 1 X 20	S 48	BH M5 X 0.8 X 8 BH M5 X 0.8 X 10	L-W 4
2020 K12-CEA 2525 M12-CEA	●		20 25	20 25	125 150	27 27	25 32	CNGN 1204□□	BCL 6	BH M6 X 1 X 20	S 48	BH M5 X 0.8 X 8 BH M5 X 0.8 X 10	L-W 4

• For inserts, see page A58

• For spare part, see page A167 - A177

● Marked: Standard Items

CEGNR/L-CE





Designation	R	L	Dimension (mm)					Insert	Components				
			h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Wrench
CEGNR/L 2525 M13-CE			25	25	150	22	32	ENGN 1307□□	BCL 6	BH M6 X 1 X 20	E 43	BH M5 X 0.8 X 10	L-W 4

• For inserts, see page A59

• For spare part, see page A167 - A177

● Marked: Standard Items



CEQNR/L-CE


Designation	Dimension (mm)						Insert	Components				
	R	L	h	b	I	l ₁	f	Clamp	Clamp Screw	Shim	Shim Screw	Wrench
CEQNR/L 2020 K13-CE 2525 M13-CE	●	20 25	20 25	125 150	32 32	25 32	ENG N 1307 □□	BCL 6	BH M6 X 1 X 20	E 43	BH M5 X 0.8 X 10	L-W 4

• For inserts, see page A59

• For spare part, see page A167 - A177

● Marked: Standard Items



CRDCN - 120


Designation	Dimension (mm)						Insert	Components				
	h	b	I	l ₁	f	Clamp	Clamp Screw	Shim	Shim Screw	Wrench		
CRDCN 2525 M06-120 3225 P06-120	●	25 32	25 25	150 170	28 28	12.5 12.5	RCGX 060600	BCL 6-20A	BH M6 X 1 X 25	CERS 06	SO 22050I	L-W 4
3225 P09-120 3225 P12-120	●	32 32	25 25	170 170	30 32	12.5 12.5	RCGX 090700 RCGX 120700			CERS 09		
	●	32 32	25 25	170 170	32 32	12.5 12.5		BCL 6		CERS 12	BH M2.5 X 0.45 X 10	

• For inserts, see page A59

• For spare part, see page A167 - A177

● Marked: Standard Items

CRDCN - 140




Designation	Dimension (mm)						Insert	Components				
	h	b	I	l ₁	f	Clamp	Clamp Screw	Shim	Shim Screw	Wrench		
CRDCN 2525 M06-140 3225 P06-140	●	25 32	25 25	150 170	28 28	12.5 12.5	RCGX 060300	BCL 6-20A	BH M6 X 1 X 25	CBRS 06	SO 22050I	L-W 4
3225 P09-140 3225 P12-140	●	32 32	25 25	170 170	30 32	12.5 12.5	RCGX 090300 RCGX 120400	BCL 6-20A BCL 6		CBRS 09		
	●	32 32	25 25	170 170	32 32	12.5 12.5				CBRS 12	BH M2.5 X 0.45 X 10	

• For inserts, see page A66

• For spare part, see page A167 - A177

● Marked: Standard Items

CRDNN-CE





Designation		Dimension (mm)					Insert	Components						
		h	b	l	l1	f		Clamp	Clamp Screw	Shim	Shim Screw	Wrench		
CRDNN 2020 K12-CE		20	20	125	32	10.0	RNGN 120700	BCL 6	BH M6 X 1 X 25	S 43	BH M5 X 0.8 X 8	L-W 4		
2525 M12-CE	●	25	25	150	32	12.5					BH M5 X 0.8 X 10			
3225 P12-CE	●	32	25	170	32	12.5					BH M5 X 0.8 X 8			
2020 K12-CEA		20	20	125	32	10.0					BH M5 X 0.8 X 10			
2525 M12-CEA	●	25	25	150	32	12.5		RNGN 120400			S 53			
2525 M12-CEB	●	25	25	150	32	12.5								
2525 M15-CE		25	25	150	32	12.5					RNGN 120300			
							RNGN 150700							

• For inserts, see page A59

● Marked: Standard Items

• For spare part, see page A167 - A177

CRGCR/L - 120





Designation	R	L	Dimension (mm)					Insert	Components								
			h	b	l	l1	f		Clamp	Clamp Screw	Shim	Shim Screw	Wrench				
CRGCR/L 2525 M06-120			25	25	150	28	32	RCGX 060600	BCL 6-20A	BH M6 X 1 X 25	CERS 06	SO 22050I	L-W 4				
3225 P06-120	●		32	25	170	28	32										
3225 P09-120	●		32	25	170	30	32										
3225 P12-120	●		32	25	170	32	32		BCL 6								

• For inserts, see page A59

● Marked: Standard Items

• For spare part, see page A167 - A177

CRGCR/L - 140





Designation	R	L	Dimension (mm)					Insert	Components								
			h	b	l	l1	f		Clamp	Clamp Screw	Shim	Shim Screw	Wrench				
CRGCR/L 2525 M06-140			25	25	150	28	32	RCGX 060300-FT	BCL 6-20A	BH M6 X 1 X 25	CBRS 06	SO 22050I	L-W 4				
3225 P06-140	●		32	25	170	28	32										
3225 P09-140	●		32	25	170	30	32										
3225 P12-140	●		32	25	170	32	32		BCL 6								

• For inserts, see page A66

● Marked: Standard Items

• For spare part, see page A167 - A177

CRGNR/L-CE





Designation	Dimension (mm)							Insert	Components							
	R	L	h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Wrench			
CRGNR/L 2020 K12-CE	•		20	20	125	28	25	RNGN 120700	BCL 6	BH M6 X 1 X 20	S 43	BH M5 X 0.8 X 10	L-W 4			
2525 M12-CE	•		25	25	150	28	32			BH M6 X 1 X 25						
3225 P12-CE			32	25	170	28	32									
2020 K12-CEA			20	20	125	28	25									
2525 M12-CEA	•		25	25	150	28	32									

• For inserts, see page A59

● Marked: Standard Items

• For spare part, see page A167 - A177

CSDNN-CE





Designation	Dimension (mm)							Insert	Components						
		h	b	l	l ₁	f	Clamp	Clamp Screw	Shim	Shim Screw	Wrench				
CSDNN 2525 M12-CE	•	25	25	150	34	12.5	SNGN 1207□□	BCL 6	BH M6 X 1 X 20	S 40	BH M5 X 0.8 X 10	L-W 4			
3225 P12-CE	•	32	25	170	34	12.5			BH M6 X 1 X 25						
2020 K12-CEA		20	20	125	34	10									
2525 M12-CEA	•	25	25	150	34	12.5									

• For inserts, see page A60

● Marked: Standard Items

• For spare part, see page A167 - A177

CSKNR/L-CE





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Wrench
CSKNR/L 2525 M12-CE			25	25	150	28	32	SNGN 1207□□	BCL 6	BH M6 X 1 X 25	S 40	BH M5 X 0.8 X 10	L-W 4
2525 M12-CEA			25	25	150	28	32						

• For inserts, see page A60

● Marked: Standard Items



• For spare part, see page A167 - A177

CSRNR/L-CE





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Wrench
CSRNR/L 2525 M12-CE 3225 P12-CE 2525 M12-CEA	●	25	25	150	22	27		SNGN 1207□□	BCL 6	BH M6 X 1 X 20	S 40	BH M5 X 0.8 X 10	L-W 4
		32	25	170	22	27		SNGN 1204□□					
● For inserts, see page A60 ● For spare part, see page A167 - A177								● Marked: Standard Items					

CSSNR/L-CE





Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Wrench
CSSNR/L 2525 M12-CE 2525 M12-CEA	●	25	25	150	30	32		SNGN 1207□□	BCL 6	BH M6 X 1 X 25 BH M6 X 1 X 20	S 40	BH M5 X 0.8 X 10	L-W 4
	●	25	25	150	30	32		SNGN 1204□□					
● For inserts, see page A60 ● For spare part, see page A167 - A177								● Marked: Standard Items					

CTJNR/L-CE



Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Wrench
CTJNR/L 2020 K16-CE 2525 M16-CE 2020 K16-CEA 2525 M16-CEA	●	20	20	125	26	25		TNGN 1607□□	BCL 6	BH M6 X 1 X 25 BH M6 X 1 X 20 BH M6 X 1 X 25 BH M6 X 1 X 20	S 3	BH M4 X 0.7 X 8	L-W 4
	●	25	25	150	21	32		TNGN 1604□□					
● For inserts, see page A61 ● For spare part, see page A167 - A177								● Marked: Standard Items					

TCBNR/L-CH





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench
TCBNR/L 2525 M12-CH		25	25	150	34.4	22		CNGX 1207□□ CH	CCL 4	CSC 4	S 48	BH M5 X 0.8 X 10	DSP 5	L-W 4
3225 P12-CH		32	25	170	34	22								

• For inserts, see page A58

• For spare part, see page A167 - A177

● Marked: Standard Items

TCKNR/L-CH





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench
TCKNR/L 2525 M12-CH		25	25	150	28	32		CNGX 1207□□ CH	CCL 4	CSC 4	S 48	BH M5 X 0.8 X 10	DSP 5	L-W 4
3225 P12-CH		32	25	170	28	32								

• For inserts, see page A58

• For spare part, see page A167 - A177

● Marked: Standard Items

TCLNR/L-CH





Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench
TCLNR/L 2525 M12-CH	●	●	25	25	150	33	32	CNGX 1207□□ CH	CCL 4	CSC 4	S 48	BH M5 X 0.8 X 10	DSP 5	L-W 4
3225 P12-CH		32	25	170	33	32								

• For inserts, see page A58

• For spare part, see page A167 - A177

● Marked: Standard Items

TDJNR/L-CH





Designation	Dimension (mm)						Insert	Components						
	R	L	h	b	l	l1	f	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench	
TDJNR/L 2525 M15-CH			25	25	150	38	32	DNGX 1507□□ CH	CCL 4	CSC 4	S 45	BH M5 X 0.8 X 10	DSP 5	L-W 4
3225 P15-CH			32	25	170	38	32							

• For inserts, see page A59

• For spare part, see page A167 - A177

● Marked: Standard Items

TDNNN-CH





Designation	Dimension (mm)						Insert	Components					
	h	b	l	l1	f	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench		
TDNNN 2525 M15-CH	25	25	150	40	12.5	DNGX 1507□□ CH	CCL 4	CSC 4	S 45	BH M5 X 0.8 X 10	DSP 5	L-W 4	
3225 P15-CH	32	25	170	40	12.5								

• For inserts, see page A59

• For spare part, see page A167 - A177

● Marked: Standard Items

TSRNR/L-CH





Designation	Dimension (mm)						Insert	Components						
	R	L	h	b	l	l1	f	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench	
TSRNR/L 2525 M12-CH			25	25	150	32	27	SNGX 1207□□ CH	CCL 4	CSC 4	S 40	BH M5 X 0.8 X 10	DSP 5	L-W 4
3225 P12-CH			32	25	170	32	27							

• For inserts, see page A60

• For spare part, see page A167 - A177

● Marked: Standard Items

TSSNR/L-CH


Designation	Dimension (mm)							Insert	Components					
	R	L	h	b	l	l ₁	f		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Wrench
TSSNR/L 2525 M12-CH			25	25	150	35	32	SNGX 1207□□ CH	CCL 4	CSC 4	S 40	BH M5 X 0.8 X 10	DSP 5	L-W 4
3232 P12-CH			32	32	170	35	40	SNGX 1507□□ CH			S 50			
3225 P15-CH			32	25	170	35	32							

• For inserts, see page A60

• For spare part, see page A167 - A177

● Marked: Standard Items

TOPDUTY


TOPFEED

TOPRAIL

TURN•RUSH

CNMX HB SNMX HB

Designation	d	t	r	(mm)
CNMX 160712 HB	15.88	6.92	1.2	
CNMX 160716 HB	15.88	6.92	1.6	
SNMX 150712 HB	15.88	6.92	1.2	
SNMX 150716 HB	15.88	6.92	1.6	





P Carbon Steel C: 0.45%
M Austenitic Stainless Steel
K High Tensile Cast Iron
N Aluminum
S Inconel
H Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated		
		Cermet		CVD Coated						PVD Coated			Uncoated			P20			K10		
		feed (mm/rev)	ap (mm)	PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10
	CNMX 160712 HB	0.30 - 0.80	1.5 - 8.0					●	●												
	160716 HB	0.30 - 0.80	1.5 - 8.0					●	●	250	230										
	SNMX 150712 HB	0.30 - 0.80	1.5 - 8.0					●	●												
	150716 HB	0.30 - 0.80	1.5 - 8.0					●	●	250	230										

● Marked: Standard Items

HCBNR/L





Designation	Dimension (mm)						Insert	Components					
	R	L	h	b	I	f		Lever	Screw	Shim	Shim Pin	Shim Pin Punch	Wrench
HCBNR/L 2525 M1607 3232 P1607	● ● 25 ● ● 32	25 32	25 32	150 170	22 27	CNMX 1607□□ HB	LCL 16-NX	LCS 5-L25.5	LSC 54-NX	LSP 5	SPP 5-6	L-W 3	

• For spare part, see page A167 - A177

● Marked: Standard Items

HCLNR/L




Designation	Dimension (mm)						Insert	Components					
	R	L	h	b	I	f		Lever	Screw	Shim	Shim Pin	Shim Pin Punch	Wrench
HCLNR/L 2525 M1607 3232 P1607	● ● 25 ● ● 32	25 32	150 170	32 40	CNMX 1607□□ HB	LCL 16-NX	LCS 5-L25.5	LSC 54-NX	LSP 5	SPP 5-6	L-W 3		

• For spare part, see page A167 - A177



● Marked: Standard Items

HSBNR/L



Designation	Dimension (mm)						Insert	Components					
	R	L	h	b	l	f		Lever	Screw	Shim	Shim Pin	Shim Pin Punch	Wrench
HSBNR/L 2525 M1507 3232 P1507	● ●	● ●	25	25	150	22	SNMX 1507□□ HB	LCL 16-NX	LCS 5-L25.5	LSS 54-NX	LSP 5	SPP 5-6	L-W 3
● For spare part, see page A167 - A177	● Marked: Standard Items												

HSDNN





Designation	Dimension (mm)						Insert	Components					
	R	L	h	b	l	f		Lever	Screw	Shim	Shim Pin	Shim Pin Punch	Wrench
HSDNN 2525 M1507 3232 P1507	●	●	25	25	150	12.5	SNMX 1507□□ HB	LCL 16-NX	LCS 5-L25.5	LSS 54-NX	LSP 5	SPP 5-6	L-W 3

● For spare part, see page A167 - A177

● Marked: Standard Items

HSKNR/L




Designation	Dimension (mm)						Insert	Components					
	R	L	h	b	l	f		Lever	Screw	Shim	Shim Pin	Shim Pin Punch	Wrench
HSKNR/L 2525 M1507 3232 P1507	● ●	● ●	25	25	150	32	SNMX 1507□□ HB	LCL 16-NX	LCS 5-L25.5	LSS 54-NX	LSP 5	SPP 5-6	L-W 3

● For spare part, see page A167 - A177

● Marked: Standard Items

BNMX HF



Designation	d	t	r	ØD_1	(mm)
BNMX 150720R/L HF	15	8	15	6.2	



Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												Uncoated		
		Cermet		CVD Coated						PVD Coated			Uncoated			P20	K10	K20
		feed (mm/rev)	ap (mm)	PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020
	BNMX 150720R/L HF	0.5 - 2.5	0.5 - 2.5					• 200	• 170									

● Marked: Standard Items

HBXNR/L



Designation	Dimension (mm)						Insert	Components					
	R	L	h	b	l	f		Lever	Screw	Shim	Shim Pin	Shim Pin Punch	Wrench
HBXNR/L 2525 M1507	●	●	25	25	150	30	BNMX 150720R/L-HF	LCL 16-NX	LCS 5-L25.5	LSB 53 R/L	LSP 5	SPP 5-6	L-W 3
HBXNR/L 3232 P1507	●	●	32	32	170	37							


● For spare part, see page A167 - A177

● Marked: Standard Items



CNMD HD HT HY HZ

Designation	d	t	r
CNMD 190624	19.05	6.35	2.4
CNMD 250924	25.40	9.52	2.4




- P Carbon Steel C: 0.45%
- M Austenitic Stainless Steel
- K High Tensile Cast Iron
- N Aluminum
- S Inconel
- H Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)											
		feed (mm/rev)	ap (mm)	Cermet				CVD Coated				PVD Coated			
	CNMD 250924 HD	0.55 - 1.50	4.0 - 15.0					● 270	● 245						
	CNMD 190624 HT	0.35 - 0.90	4.0 - 9.0					●	●						
	250924 HT	0.55 - 1.30	5.0 - 12.0					●	●						
	CNMD 190624 HY	0.50 - 1.10	4.0 - 12.0					●	●						
	250924 HY	0.55 - 1.50	4.0 - 15.0					●	●						
	CNMD 250924 HZ	0.55 - 1.50	4.0 - 15.0					● 260	● 235						

● Marked: Standard Items

SNMD HD HT HY HZ

Designation	d (mm)	t (mm)	r (mm)
SNMD 190624	19.05	6.35	2.4
SNMD 250924	25.40	9.52	2.4
SNMD 310924	31.75	9.525	2.4



- P** Carbon Steel C: 0.45%
M Austenitic Stainless Steel
K High Tensile Cast Iron
N Aluminum
S Inconel
H Hardened Steel


Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												
		feed (mm/rev)	ap (mm)	Cermet			CVD Coated						PVD Coated			Uncoated
	SNMD 250924 HD	0.55 - 1.50	4.0 - 15.0													
For Roughing							● 270	● 245								
	SNMD 250924 HT	0.55 - 1.20	4.0 - 9.0						●	●						
For Finishing									270	245						
	SNMD 190624 HY	0.50 - 1.10	4.0 - 12.0						●	●						
For Roughing									260	235						
	250924 HY	0.55 - 1.50	4.0 - 15.0						●	●						
For Finishing																
	SNMD 250924 HZ	0.55 - 1.50	4.0 - 15.0						● 260	● 235						
For Roughing																
	For Finishing															

● Marked: Standard Items

SNMD 31 HD HT


Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												Uncoated				
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						PVD Coated	Uncoated			P20	K10	K20			
				PV3010	CT3000	TT1300	TT310	TT815	TT815	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
	SNMD 310924 HD	0.60 - 1.50	7.0 - 25.0					• 210	• 180				• 100							
	SNMD 310924 HT	0.50 - 1.40	6.0 - 22.0					• 210	• 180				• 100							

• Marked: Standard Items

HSBNR/L


Designation	Dimension (mm)						Insert	Components				
	R	L	h	b	l	f		Lever	Screw	Shim	Shim Pin	Wrench
HSBNR/L 4040 S3109 5050 T3109	●	●	40	40	250	35	SNM□3109 □□	LCL 32-NX	LCS 8	LSS 104	LSP 8	L-W 5
For spare part, see page A167 - A177												



• Marked: Standard Items

HSDNN


Designation	Dimension (mm)				Insert	Components				
	h	b	l	f		Lever	Screw	Shim	Shim Pin	Wrench
HSDNN 4040 S3109 5050 T3109	● 40	40	250	20	SNM□3109 □□	LCL 32-NX	LCS 8	LSS 104	LSP 8	L-W 5
For spare part, see page A167 - A177	● 50	50	300	25						

• Marked: Standard Items

PCBNR/L-D




Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l ₁	f		Lever	Screw	Shim	Shim Pin	Wrench
PCBNR/L 3232 P1906D 4040 S1906D	● ●	32	32	170	37	27		CN□□ 1906□□	LCL 6	LCS 25C	LSC 64D	LSP 6	L-W 4
4040 S2509D 5050 T2509D	● ●	40	40	250	37	37		CN□□ 2509□□	LCL 8	LCS 8	LSC 84D	LSP 8	L-W 5

• For spare part, see page A167 - A177

● Marked: Standard Items

• LSC 85D Shim can be used for CN□□ 2507□□ Insert.

PCLNR/L-D




Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l ₁	f		Lever	Screw	Shim	Shim Pin	Wrench
PCLNR/L 3225 P1906D 3232 P1906D 4040 S1906D	● ●	32	25	170	38	32		CN□□ 1906□□	LCL 6	LCS 25C	LSC 64D	LSP 6	L-W 4
4040 S2509D 5050 T2509D	● ●	40	40	250	38	50		CN□□ 2509□□	LCL 8	LCS 8	LSC 84D	LSP 8	L-W 5

• For spare part, see page A167 - A177

● Marked: Standard Items

• LSC 85D Shim can be used for CN□□ 2507□□ Insert.

PSBNR/L-D




Designation	Dimension (mm)							Insert	Components				
	R	L	h	b	I	l ₁	f		Lever	Screw	Shim	Shim Pin	Wrench
PSBNR/L 3232 P1906D 4040 S1906D	● ●	32	32	170	39	27		SN□□ 1906□□	LCL 6	LCS 25C	LSS 64D	LSP 6	L-W 4
4040 S2509D 4040 S2509D-A85 ⁽¹⁾ 5050 T2509D	● ●	40	40	250	39	35		SN□□ 2509□□	LCL 8	LCS 8	LSS 84D	LSP 8	L-W 5

• For spare part, see page A167 - A177

● Marked: Standard Items


• LSS 85D Shim can be used for SN□□ 2507□□ Insert.

• (1) 4040 S2509D-A85 in 85°

PSDNN-D


Designation		Dimension (mm)					Insert	Components				
		h	b	l	l1	f		Lever	Screw	Shim	Shim Pin	Wrench
PSDNN 3225 P1906D	●	32	25	170	40.5	12.5	SN□□ 1906□□	LCL 6	LCS 25C	LSS 64D	LSP 6	L-W 4
3232 P1906D	●	32	32	170	40.5	16						
4040 S1906D	●	40	40	250	40.5	20						
4040 S2509D	●	40	40	250	48	20	SN□□ 2509□□	LCL 8	LCS 8	LSS 84D	LSP 8	L-W 5
5050 T2509D	●	50	50	300	48	25						

- For spare part, see page A167 - A177
- Marked: Standard Items
- LSS 85D Shim can be used for SN□□ 2507□□ Insert.

PSKNR/L-D



Designation	R	L	Dimension (mm)					Insert	Components				
			h	b	l	l1	f		Lever	Screw	Shim	Shim Pin	Wrench
PSKNR/L 4040 S2509D	●	●	40	40	250	42	50	SN□□ 2509□□	LCL 8	LCS 8	LSS 84D	LSP 8	L-W 5

- For spare part, see page A167 - A177
- Marked: Standard Items
- LSS 85D Shim can be used for SN□□ 2507□□ Insert.



LNMM HX

Designation	I	d	t	r	ØD1	(mm)
LNMM 401224R/L-HX	40	25.4	12	2.4	9.15	





- P Carbon Steel C: 0.45%
- M Austenitic Stainless Steel
- K High Tensile Cast Iron
- N Aluminum
- S Inconel
- H Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												Uncoated				
		Cermet		CVD Coated						PVD Coated			Uncoated			P20	K10	K20		
		feed (mm/rev)	ap (mm)	PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20
LNMM 401224R/L-HX	0.70 - 1.50	6.0 - 32.0							• 150					• 90						

● Marked: Standard Items

2PLLNR/L



Designation	Dimension (mm)						Insert	Components				
	R	L	h	b	l	f		Lever	Screw	Shim	Shim Pin	Wrench
	●	●	40	40	250	50		LCL 8	LCS 8-L39	LN 4025-T6.35 R/L	LSP 8	L-W 5
2PLLNR/L 4040 S4012 5050 T4012	●	●	40	40	250	50	LNMM 401224R/L-HX	LCL 8	LCS 8-L39	LN 4025-T6.35 R/L	LSP 8	L-W 5


● For spare part, see page A167 - A177

● Marked: Standard Items



LNMX HD LNMX HY

Designation	I	d	t	r	(mm)
LNMX 501432 HD	50.8	25.4	14.2	3.2	
LNMX 501432 HY	50.8	25.4	14.2	3.2	




- P Carbon Steel C: 0.45%
- M Austenitic Stainless Steel
- K High Tensile Cast Iron
- N Aluminum
- S Inconel
- H Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)									
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated					PVD Coated			Uncoated
	LNMX 501432 HD	0.70 - 1.60	6.0 - 40.0					• 150			• 90		
	LNMX 501432 HY	0.65 - 1.50	5.0 - 40.0					• 150			• 90		

● Marked: Standard Items


2PLBNR/L



Designation	Dimension (mm)						Insert	Components					
	R	L	h	b	l	f		Lever	Screw	Shim	Shim Pin	Set Screw	Wrench
2PLBNR/L 5050 T5014	●	●	50	50	300	45	LNMX 501432	LCL 8	LCS 8-L43	LN 5025-T6.35	LSP 8	SS M12X1.75X25	L-W 5


● For spare part, see page A167 - A177

● Marked: Standard Items



LNMX TWF TWM TWR

Designation	l_1	l_2	$\text{Ø}d$	t	(mm)
LNMX 191940	19.05	19.05	6.35	10	4.0
LNMX 301940	30	19.05	6.35	12	4.0




P Carbon Steel C: 0.45%
M Austenitic Stainless Steel
K High Tensile Cast Iron
N Aluminum
S Inconel
H Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)												PVD Coated			Uncoated				
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated						TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10
					PV3010	CT3000	TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20
	LNMX 191940 TWF	0.30 - 1.0	0.3 - 5.0						• 100	• 70													
	LNMX 191940 TWM	0.45 - 1.5	1.5 - 9.0						•	•													
									80	60													
	LNMX 301940 TWR	0.50 - 1.5	1.5 - 15.0						•	•													
									• 80	• 50													

• Marked: Standard Items

TRWR/L




Designation	Dimension (mm)							Cartridge		Components		
	R	L	h	h1	b	l	f	Left	Right	Screw	Pin	Wrench
TRWR/L 50-55 TG	•	•	50	44	55	210	55	TRWR/L 175-CA-19	TRWR/L 177-CA-19	SS M6 X 1 X 16	PIN D5X13	L-W 3

• For spare part, see page A167 - A177

• Marked: Standard Items

TRWR/L - Cartridge




Designation	Dimension (mm)							Insert	Components		
	R	L	h	b	l	l1	f		Lever	Screw	Wrench
TRWR/L 175-CA-19	•	•	32	22.6	43	35	23	LNMX 191940	□□□		
175-CA-30	•	•	32	22.6	43	35	23	LNMX 301940	□□□		
177-CA-19	•	•	32	18.6	43	35	19	LNMX 191940	□□□		
								LCL 5	LCS 5		L-W 3

• For spare part, see page A167 - A177

• Marked: Standard Items

SRR TX



Designation	l_1	l_2	$\text{Ø}d$	t	r	(mm)
SRR-TX	31.75	19.05	7.91	12.7	4.8	



P Carbon Steel C: 0.45%
M Austenitic Stainless Steel
K High Tensile Cast Iron
N Aluminum
S Inconel
H Hardened Steel

Insert	Designation	Recommended Machining Conditions		Grade & Vc (m/min)																	
		feed (mm/rev)	ap (mm)	Cermet	CVD Coated					PVD Coated			Uncoated								
	SRR-TX	0.60 - 1.8	1.5 - 20.0		TT1300	TT7310	TT8115	TT8125	TT8135	TT9215	TT9225	TT9235	TT5100	TT7100	TT5080	TT8020	TT9020	TT9080	P20	K10	K20

TRWR/L...LD



Designation	Dimension (mm)							Insert	Components			
	R	L	h	h_1	b	l	f		Shim1	Shim2	Screw	Wrench
TRWR/L 57.2-76.2 LD	76.2	76.2	57.2	254	76.2	SRR-□□□			SRR-SHIM	SRR-SH-R/L	SRR-SCR	L-W 5

• For spare part, see page A167 - A177

• Insert and holder can be supplied by quotation.

• Marked: Standard Items








1	Coupling Size		2		Clamping System		3			Insert Shape		
		Ød	Symbol	Ød(mm)	P/Lever Lock	C/Top Clamp	80°	55°	75°	C	D	E
	C4	40	C5	50	S/Screw Clamp	M/Multi Lock	120°	55°	120°	H	K	R
	C6	63	T-Holder	W/Wedge Clamp	120°	80°	80°	35°	80°	S	T	V
										W		

C4 - T C L N R

4 Approach Angle									
Symbol	Shape	Offset	Symbol	Shape	Offset	Symbol	Shape	Offset	
A		x	J		o	v		x	
			K		o	w		o	
B		x	L		o	x			
			M		x	c*		x	
D		x	N		x	h*		o	
E		x	R		o	q*		o	
F		o	S		o				
G		o	T		o				
			U		o				

* TaeguTec standard






27 055 - 09

7



8

9

10



TCLNR/L





Designation	Dimension (mm)			Insert	Components							
	R	L	d	f	l	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench
C4-TCLNR/L 27050-09	●	●	40	27	50	CN□□ 0903□□	DLM 3	DLS 3	LSC 32	SO 40085I	DSP 3	NZ 83
C4-TCLNR/L 27050-12	●	●	40	27	50							L-W 2.5
C5-TCLNR/L 35060-12	●	●	50	35	60	CN□□ 1204□□	DLM 4	DLS 4	TSC 44	SO 40050I	DSP 4	NZ 104
C6-TCLNR/L 45065-12	●	●	63	45	65							L-W 3
C4-TCLNR/L 27055-16	●	●	40	27	55	CN□□ 1606□□	DLM 5	DLS 5	TSC 54	SO 50090I	DSP 5	NZ 83
C5-TCLNR/L 35060-19	●	●	50	35	60	CN□□ 1906□□	DLM 6	DLS 5	LSC 63	SO 80180I	DSP 5	NZ 104
C6-TCLNR/L 45065-19	●	●	63	45	65							L-W 4

• For inserts, see page A24 - A27

● Marked: Standard Items

• For spare part, see page A167 - A177

TDJNR/L





Designation	Dimension (mm)			Insert	Components							
	R	L	d	f	l	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench
C4-TDJNR/L 27055-1504	●	●	40	27	55	DN□□ 1504□□	DLM 4	DLS 4	TSD 44		NZ 83	L-W 3
C4-TDJNR/L 27055-1506	●	●	40	27	55	DN□□ 1506□□			TSD 43			
C5-TDJNR/L 35060-1504	●	●	50	35	60	DN□□ 1504□□			TSD 44			
C5-TDJNR/L 35060-1506	●	●	50	35	60	DN□□ 1506□□			TSD 43			
C6-TDJNR/L 45065-1504	●	●	63	45	65	DN□□ 1504□□			TSD 44			
C6-TDJNR/L 45065-1506	●	●	63	45	65	DN□□ 1506□□			TSD 43			

• For inserts, see page A28 - A29

● Marked: Standard Items

• For spare part, see page A167 - A177

TSDNN





Designation	Dimension (mm)			Insert	Components							
		d	f	l	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench	
C4-TSDNN 00050-12	●	40	0	50							NZ 83	L-W 3
C5-TSDNN 00060-12	●	50	0	60								
C6-TSDNN 00065-12	●	63	0	65							NZ 104	

• For inserts, see page A31 - A33

● Marked: Standard Items

• For spare part, see page A167 - A177

TSSNR/L





Designation	Dimension (mm)							Insert	Components							
	R	L	d	f	fs	I	ls		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench	
C4-TSSNR/L 27042-12	●	●	40	27	18.7	42	50.3	SN□□ 1204□□	DLM 4	DLS 4	TSS 44	SO 40050I	DSP 4	NZ 83	L-W 3	
C5-TSSNR/L 35052-12	●	●	50	35	26.7	52	60.3		NZ 104	NZ 104	NZ 104	NZ 104	NZ 104	NZ 104		
C6-TSSNR/L 45056-12	●	●	63	45	36.7	56	64.3									

• For inserts, see page A31 - A33

• For spare part, see page A167 - A177

● Marked: Standard Items

TTGNR/L TTJNR/L



Designation	Dimension (mm)							Insert	Components						
	R	L	d	f	I	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench			
C4-TTGMR/L 27050-16	●	●	40	27	50	TN□□ 1604□□	DLM 3	TST 33	SO 35080I	DSP 3	NZ 83	L-W 2.5			
C5-TTGMR/L 35060-16	●	●	50	35	60						NZ 104				
C6-TTGMR/L 45065-16	●	●	63	45	65						NZ 83				
C4-TTJNR/L 27050-16	●	●	40	27	50						NZ 104				
C5-TTJNR/L 35060-16	●	●	50	35	60						NZ 104				
C6-TTJNR/L 45065-16	●	●	63	45	65						NZ 104				



• For inserts, see page A33 - A35

• For spare part, see page A167 - A177

• *Approach angle for TTJNR/L is 93 degrees.

● Marked: Standard Items

TVJNR/L





Designation	Dimension (mm)							Insert	Components						
	R	L	d	f	I	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench			
C4-TVJNR/L 27062-16	●	●	40	27	62	VN□□ 1604□□	DLM 3V	DLS 5	TSV 33	SO 35080I	DSP 5	NZ 83	L-W 4		
C5-TVJNR/L 35065-16	●	●	50	35	65							NZ 104			
C6-TVJNR/L 45068-16	●	●	63	45	68							NZ 104			

• For inserts, see page A36

• For spare part, see page A167 - A177

● Marked: Standard Items

TWLNR/L





Designation	Dimension (mm)			Insert	Components							
	R	L	d	f	l	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench
C4-TWLNR/L 27050-06	●	●	40	27	50	WN□□ 0604□□	DLM 3	DLS 3	PSW 32	SO 40090I	DSP 3	NZ 83
C4-TWLNR/L 27050-08	●	●	40	27	50							L-W 2.5
C5-TWLNR/L 35060-08	●	●	50	35	60	WN□□ 0804□□	DLM 4	DLS 4	TSW 44	SO 40050I	DSP 4	NZ 104
C6-TWLNR/L 45065-08	●	●	63	45	65							L-W 3

• For inserts, see page A37 - A38

• Marked: Standard Items

• For spare part, see page A167 - A177

SCLCR/L





Designation	Dimension (mm)			Insert	Components						
	R	L	d	f	l	Screw	Shim	Shim Screw	Nozzle	Wrench	
C4-SCLCR/L 27050-09	●	●	40	27	50						NZ 83
C5-SCLCR/L 35060-09	●	●	50	35	60	CC□T 09T3□□	SO 35124I	SSC 32	SO 50090S		NZ 104
C6-SCLCR/L 45065-09	●	●	63	45	65						T 15
C4-SCLCR/L 27050-12	●	●	40	27	50						NZ 83
C5-SCLCR/L 35060-12	●	●	50	35	60	CC□T 1204□□	SO 45130I	SSC 43N	SO 60105S		NZ 104
C6-SCLCR/L 45065-12	●	●	63	45	65						T 20

• For inserts, see page A39 - A40

• Marked: Standard Items

• For spare part, see page A167 - A177

SDJCR/L





Designation	Dimension (mm)			Insert	Components						
	R	L	d	f	l	Screw	Shim	Shim Screw	Nozzle	Wrench	
C4-SDJCR/L 27050-11	●	●	40	27	50						NZ 83
C5-SDJCR/L 35060-11	●	●	50	35	60	DC□T 11T3□□	SO 35124I	SSD 32	SO 50090S		NZ 104
C6-SDJCR/L 45065-11	●	●	63	45	65						T 15

• For inserts, see page A41 - A42

• Marked: Standard Items

• For spare part, see page A167 - A177

SRDCN





Designation		Dimension (mm)				Insert	Components				
		d	f	l	ar		Screw	Shim	Shim Screw	Nozzle	Wrench
C4-SRDCN 00050-10A	●	40	0	50	25	RC□T 10T300	TS 40097I	TRC 3-0	SR TC-3	NZ 83	T 15
C5-SRDCN 00060-10A	●	50	0	60	25					NZ 104	
C6-SRDCN 00065-10A	●	63	0	65	25					NZ 83	
C4-SRDCN 00050-12A	●	40	0	50	28		SO 40050I	TRC 4-0	SR TC-4S	NZ 104	
C5-SRDCN 00060-12A	●	50	0	60	28					NZ 104	
C6-SRDCN 00065-12A	●	63	0	65	28					NZ 104	

• For inserts, see page A42

• For spare part, see page A167 - A177

● Marked: Standard Items

STGCR/L STJCR/L



Designation	R	L	Dimension (mm)			Insert	Components				
			d	f	l		Screw	Shim	Shim Screw	Nozzle	Wrench
C4-STGCR/L 27050-16	●	●	40	27	50	TC□T 16T3□□	SO 35124I	SST 32	SO 50090S	NZ 83	T 15
C5-STGCR/L 35060-16	●	●	50	35	60					NZ 104	
C4-STJCR/L 27050-16	●	●	40	27	50					NZ 83	
C5-STJCR/L 35060-16	●	●	50	35	60					NZ 104	



• For inserts, see page A44

• For spare part, see page A167 - A177

• *Approach angle for STJCR/L is 93 degrees.

● Marked: Standard Items

SVJBR/L





Designation	R	L	Dimension (mm)			Insert	Components				
			d	f	l		Screw	Shim	Shim Screw	Nozzle	Wrench
C4-SVJBR/L 27050-16	●	●	40	27	50	VB□T 1604□□	SO 35124I	SSV 32	TS 5035062S	NZ 83	T 15
C5-SVJBR/L 35060-16	●	●	50	35	60					NZ 104	
C6-SVJBR/L 45065-16	●	●	63	35	65					NZ 104	

• For inserts, see page A46 - A47

• For spare part, see page A167 - A177

● Marked: Standard Items

SVVBN



Designation		Dimension (mm)			Insert / 35°	Components				
		d	f	l		Screw	Shim	Shim Screw	Nozzle	Wrench
C4-SVVBN 00050-16	●	40	0	50	VB□T 1604□□	SO 35124I	SSV 32	TS 5035062S	NZ 83	T 15
C5-SVVBN 00060-16	●	50	0	60					NZ 104	
C6-SVVBN 00065-16	●	63	0	65						


• For inserts, see page A46 - A47

• For spare part, see page A167 - A177


• Marked: Standard Items

T-TURN Boring Bar Designation System







1	Boring Bar
S: Steel Shank	
A: Coolant Through Steel Shank	
C: Carbide Shank	
E: Coolant Through Carbide Shank	
X: Special	





3	Tool Length		
K	125	U	350
M	150	V	400
Q	180	W	450
R	200	Y	500
S	250	X	Special
T	300		



S 32 S - C T F P R - 16 -



S-CKUNR/L





Designation	Dimension (mm)							Insert	Components							
	R	L	d	h	l	l1	f	ØD min	Clamp	Screw	Clamp Spring	Shim	Shim Screw	Pin & Spring	Wrench	
S32T CKUNR/L 16	●		32	30	300	45	22	44								
S40T CKUNR/L 16	●		40	38	300	55	27	54								
S40V CKUNR/L 16			40	38	400	55	27	54	KNUX 1604□□ R/L	CL 16KR/L	CLS 16K	KSP 90	CSK 1604R/L	FHM3 X 0.5 X 10	KSP 48 KP 48S	L-W 4
S50U CKUNR/L 16			50	48	350	60	35	67.2								

• For inserts, see page A30

● Marked: Standard Items

• For spare part, see page A167 - A177

S-CSKPR/L





Designation	Dimension (mm)							Insert	Components						
	R	L	d	h	l	l1	f	ØD min	Clamp	Screw	Snap Ring	Shim	Shim Pin	Wrench	
S16R CSKPR/L 09	●		16	15	200	30	11	20	SPMR, SP□N 0903□□	CL 2C	CLS 2C	CSR 2C	-	-	L-W 2.5
S20S CSKPR/L 09	●		20	18	250	32	13	25							
S20R CSKPR/L 12			20	18	200	34	13	25	SPMR, SP□N 1203□□	CL 3C	CLS 3C	CSR 2	CSS 42	CSP 3	L-W 3
S25T CSKPR/L 12			25	23	300	42	17	32		CL 3	CLS 3S	WSR 4			
S32U CSKPR/L 12			32	30	350	45	22	40		CL 3	CLS 3				

• For inserts, see page A43

● Marked: Standard Items

• For spare part, see page A167 - A177

S-CTFCR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	d	h	l	l1	f	ØD min	Clamp	Screw	Snap Ring	Wrench	
S10K CTFCR/L 06	●		10	9	125	25	6.5	12	TCGR 0601□□	CL 1.25	CLS 1.25	CSR 1.25	L-W 1.5

• For spare part, see page A167 - A177

● Marked: Standard Items

S-CTFPR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	d	h	l	l1	f	ØD min	Clamp	Screw	Snap Ring	Shim	Shim Pin	Wrench
S10K CTFPR/L 06	●		10	9	125	25	6.5	12	TCGR 0601□□					
S12M CTFPR/L 06		●	12	11	150	30	9	16						
S12M CTFPR/L 09	●		12	11	150	25	9	16	TPGN, TP□R 0902□□	CL 1.25	CLS 1.25	CSR 1.25	-	-
S16R CTFPR/L 09		●	16	15	200	25	11	20						L-W 1.5
S12M CTFPR/L 11	●		12	11	150	30	9	16	TPMR, TP□N					
S16M CTFPR/L 11		●	16	15	150	30	11	20	1103□□	CL 2C	CLS 2C	CSR 2C	-	-
S16R CTFPR/L 11	●		16	15	200	30	11	20						L-W 2.5
S20S CTFPR/L 11	●		20	18	250	35	13	25						
S16R CTFPR/L 16	●		16	15	200	40	11	20	TPMR, TP□N 1603□□	CL 3C	CLS 3C	CSR 2	-	-
S20S CTFPR/L 16	●		20	18	250	50	13	25		CLS 3S				L-W 3
S25T CTFPR/L 16	●	●	25	23	300	40	17	32		CL 3	WSR 4	CST 32	CSP 3	
S32T CTFPR/L 16	●	●	32	30	300	45	22	40						
S40T CTFPR/L 16	●	●	40	37	300	70	27	50						
S50U CTFPR/L 16			50	47	350	70	35	63						
S40T CTFPR/L 22			40	37	300	60	27	50	TPMR, TP□N 2204□□	CL 4	CLS 4	CSR 4	CST 43	CSP 16K
S50U CTFPR/L 22			50	47	350	70	35	63						L-W 4

• For inserts, see page A45 - A46

● Marked: Standard Items

• For spare part, see page A167 - A177

S-MWLNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	d	h	l	l1	f	ØD min	Clamp	Screw	Snap Ring	Lock Pin	Wrench	
S25R MWLNR/L 08	●		25	23	200	42	17	32	WN□□ 0804□□	CL 2	CLS 2	CSR 2	MLP 4S	L-W 2.5
S32S MWLNR/L 08	●		32	30	250	45	22	44						

• For inserts, see page A37 - A38

● Marked: Standard Items

• For spare part, see page A167 - A177



S-PCLNR/L


Designation	R	L	Dimension (mm)					Insert	Components						
			d	h	l	l1	f		Lever	Screw	Shim	Shim Pin	Snap Ring	Wrench	
S16R PCLNR/L 09	●	●	16	15	200	30	11	20							
S20S PCLNR/L 09	●	●	20	18	250	32	13	25							
S20T PCLNR/L 09	●	●	20	18	300	35	13	25	CN□□ 0903□□	LCL 3B	LCS 2B	-	-	LSR 3B	L-W 2
S25T PCLNR/L 09	●	●	25	23	300	35	17	32							
S25T PCLNR/L 12	●	●	25	23	300	40	17	32		LCL 4B	LCS 4B	-	-	LSR 4B	L-W 2.5
S32S PCLNR/L 12	●	●	32	30	250	45	22	40		LCL 4	LCS 4S	LSC 42	LSP 4	-	L-W 3
S32T PCLNR/L 12	●	●	32	30	300	45	22	40	CN□□ 1204□□	LCL 4	LCS 4	LSC 42	LSP 4	-	L-W 3
S40T PCLNR/L 12	●	●	40	37	300	55	27	50							
S50U PCLNR/L 12	●	●	50	47	350	70	35	63							
S50U PCLNR/L 16	●	●	50	47	350	70	35	63	CN□□ 1606□□	LCL 5	LCS 5	LSC 53	LSP 5	-	L-W 3
S50U PCLNR/L 19	●	●	50	47	350	70	35	63	CN□□ 1906□□	LCL 6	LCS 6	LSC 63	LSP 6	-	L-W 4

• For inserts, see page A24 - A27

• For spare part, see page A167 - A177

● Marked: Standard Items



S-PDUNR/L


Designation	R	L	Dimension (mm)					Insert	Components					
			d	h	l	l1	f		Lever	Screw	Shim	Shim Pin	Wrench	
S32T PDUNR/L 15	●	●	32	30	300	45	22	40		LCL 4A	LCS 4S	LSD 42	LSP 4	L-W 3
S40T PDUNR/L 15	●	●	40	37	300	55	27	50	DN□□ 1506□□	LCL 4A	LCS 4	LSD 42	LSP 4	L-W 3
S50U PDUNR/L 15	●	●	50	47	350	70	35	63		LCL 4A	LCS 4S	LSD 42	LSP 4	L-W 3
S32T PDUNR/L 15-A	●	●	32	30	300	45	22	40	DN□□ 1504□□					

• For inserts, see page A28 - A29

• For spare part, see page A167 - A177

● Marked: Standard Items

S-PDZNR/L




Designation	R	L	Dimension (mm)					Insert	Components						
			d	h	l	l1	f		Lever	Screw	Shim	Shim Pin	Wrench		
S32T PDZNR/L 15	●	●	32	30	300	30	25	9	45						
S40T PDZNR/L 15	●	●	40	37	300	35	29	9	50	DN□□ 1506□□	LCL 4A	LCS 4S	LSD 42	LSP 4	L-W 3
S50U PDZNR/L 15	●	●	50	47	350	40	35	10	63		LCS 4				

• For inserts, see page A28 - A29

• For spare part, see page A167 - A177

● Marked: Standard Items

S-PSKNR/L



Designation	Dimension (mm)							Insert	Components						
	R	L	d	h	l	l1	f	ØD min	Lever	Screw	Shim	Shim Pin	Snap Ring	Wrench	
S25T PSKNR/L 12	●		25	23	300	39	17	32	SN□□ 1204□□	LCL 4B	LCS 4B	-	-	LSR 4B	L-W 2.5
S32T PSKNR/L 12	●		32	30	300	45	22	40		LCL 4S	LSS 42	LSP 4	-	L-W 3	
S40T PSKNR/L 12	●		40	37	300	55	27	50		LCS 4					
S50U PSKNR/L 19			50	47	350	66	35	63	SN□□ 1906□□	LCL 6	LCS 6	LSS 63	LSP 6	-	L-W 4



• For inserts, see page A31 - A33

• For spare part, see page A167 - A177

● Marked: Standard Items

• L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

S-PTFNR/L



Designation	Dimension (mm)							Insert	Components						
	R	L	d	h	l	l1	f	ØD min	Lever	Screw	Shim	Shim Pin	Snap Ring	Wrench	
S20Q PTFNR/L 11	●		20	18	180	40	13	25	TN□□ 1103□□	LCL 2B	LCS 2B	-	-	LSR 2B	L-W 2
S25T PTFNR/L 16	●	●	25	23	300	40	17	32		LCL 3BH	LCS 3B	-	-	LSR 3B	L-W 2
S32T PTFNR/L 16	●	●	32	30	300	45	22	40		LCL 3	LCS 3	LST 31.8	LSP 3A	-	L-W 2.5
S40T PTFNR/L 16	●		40	37	300	60	27	50	TN□□ 1604□□	LCL 3	LCS 3	LST 31.8	LSP 3A	-	
S50U PTFNR/L 16	●		50	47	350	70	35	63		LCL 4	LCS 4	LST 42	LSP 4	-	
S40T PTFNR/L 22			40	37	300	70	27	50	TN□□ 2204□□						L-W 3
S50U PTFNR/L 22			50	47	350	70	35	63							


• For inserts, see page A33 - A35

• For spare part, see page A167 - A177

● Marked: Standard Items

• L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

C-SCLCR/L



Designation	R	L	Dimension (mm)					Insert	Components		Shape	
			d	h	l	l1	f		Screw	Wrench		
C04G SCLCR/L 03-D05	●	●	4	3.75	90		2.5	5	CC□T 0301□□	TS 16031I	T 6	Fig.1
C05H SCLCR/L 03-D06	●	●	5	4.75	100		3	6				
C06J SCLCR/L 04-D07	●	●	6	5.5	110		3.5	7				
C07K SCLCR/L 04-D08	●	●	7	6.5	125		4	8				
C08K SCLCR/L 06	●		8	7	125	15	6	11	CC□T 0602□□	SO 25050I	T 7	Fig.2
C10K SCLCR/L 06	●		10	9	125	15	7	13				
C12K SCLCR/L 06	●		12	11	125	20	9	16				
C12M SCLCR/L 06	●		12	11	150	20	9	16				
C12M SCLCR/L 09	●		12	11	150	20	9	16	CC□T 09T3□□	SO 35080I	T 15	Fig.2
C16R SCLCR/L 09	●		16	15	200	25	11	20				
C20S SCLCR/L 09	●		20	18	250	25	13	25				


• For inserts, see page A39 - A40 • For spare part, see page A167 - A177

● Marked: Standard Items

Designates Carbide Shank

● L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

C-STFCR/L



Designation	R	L	Dimension (mm)					Insert	Components		Shape		
			d	h	l	l1	f		Screw	Wrench			
C10K STFCR/L 09			10	9	125	15	7	13	TC□T 0902□□	SO 22050I	T 7	Fig.1	
C10K STFCR/L 11			10	9	125	15	7	13					
C12M STFCR/L 11	●		12	11	150	20	9	16		SO 25050I	T 7		
C16R STFCR/L 11	●		16	15	200	25	11	20		SO 25065I			


• For inserts, see page A44 • For spare part, see page A167 - A177

● Marked: Standard Items

Designates Carbide Shank

● L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

C-STFPR/L



Designation	R	L	Dimension (mm)					Insert	Components		Shape	
			d	h	l	l1	f		Screw	Wrench		
C10K STFPR/L 11	●		10	9	125	15	6	12	TPGT1103□□	SO 30055I	T 9	Fig.1
C12M STFPR/L 11	●		12	11	150	20	8	16		SO 30100I		

• For inserts, see page A45 • For spare part, see page A167 - A177

● Marked: Standard Items

Designates Carbide Shank

● L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

S-SCLCR/L




Fig.1




Fig.2





Fig.3



Designation	Dimension (mm)							Insert	Components				Shape
	R	L	d	h	l	l ₁	f	ØD min	Screw	Shim	Shim Screw	Wrench	
S04F SCLCR/L 03-D05	●	●	4	3.75	80		2.5	5	CC□T 0301□□	TS 16031I	-	-	T 6
S05G SCLCR/L 03-D06	●	●	5	4.75	90		3	6					
S06H SCLCR/L 04-D07	●	●	6	5.5	100		3.5	7	CC□T 0401□□	TS 20038I/HG-P	-	-	T 6P
S07J SCLCR/L 04-D08	●	●	7	6.5	110		4	8					
S10H SCLCR/L 03-D05	●	●	10	9	100	15	2.5	5	CC□T 0301□□	TS 16031I	-	-	T 6
S08K SCLCR/L 06	●	●	8	7	125	18	6	11		SO 25050I			
S10K SCLCR/L 06	●	●	10	9	125	20	7	13	CC□T 0602□□		-	-	T 7
S12M SCLCR/L 06	●	●	12	11	150	25	9	16		SO 25065I			
S16R SCLCR/L 06	●	●	16	15	200	30	11	20					
S12M SCLCR/L 09	●	●	12	11	150	23	9	16					
S16M SCLCR/L 09	●	●	16	15	150	30	11	20					
S16R SCLCR/L 09	●	●	16	15	200	30	11	20	CC□T 09T3□□	SO 35080I	-	-	T 15
S20R SCLCR/L 09	●	●	20	18	200	32	13	25					
S20S SCLCR/L 09	●	●	20	18	250	32	13	25					
S25T SCLCR/L 12	●	●	25	23	300	42	17	32	CC□T 1204□□	SO 45100I	-	-	T 20
S32T SCLCR/L 12	●	●	32	30	300	45	22	40		SO 45130I	SSC 43N	SO 60105S	T 20
S40T SCLCR/L 12	●	●	40	37	300	55	27	50					



• For inserts, see page A39 - A40

● Marked: Standard Items

• For spare part, see page A167 - A177

● L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

S-SCLPR/L



Designation	Dimension (mm)							Insert	Components			Wrench
	R	L	d	h	l	l ₁	f	ØD min	Screw			
S10K SCLPR/L 08	●	●	10	9	125	20	6	12	CP□T 0802□□	SO 30055I		T 9
S10M SCLPR/L 08	●	●	10	9	150	20	6	12				
S12M SCLPR/L 08	●	●	12	11	150	23	8	16				
S16N SCLPR/L 09	●	●	16	15	160	30	10	20	CP□T 0903□□	SO 35080I		T 15
S16R SCLPR/L 09	●	●	16	15	200	30	10	20				
S20N SCLPR/L 09	●	●	20	18	160	32	12.5	25				
S20S SCLPR/L 09	●	●	20	18	250	32	12.5	25				



• For inserts, see page A41

● Marked: Standard Items

• For spare part, see page A167 - A177

● L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

A-SCLPR/L



Designation	Dimension (mm)							Insert	Components	
	R	L	d	h	l	l1	f		Screw	Wrench
A08H SCLPR/L 06	●	●	8	7	100	15	6	11	SO 25050I	T 7
A10K SCLPR/L 06	●	●	10	9	125	15	7	13	CP□T 0602□□	
A12M SCLPR/L 0903	●	●	12	11	150	19	9	16	TS 35070I/HG	T 15
A16Q SCLPR/L 0903	●	●	16	15	180	21.5	11	20	CP□T 0903□□	
A20R SCLPR/L 0903	●	●	20	18	200	22	13	25	TS 35070I/HG	T 15
A12M SCLPR/L 09T3	●	●	12	11	150	19	9	16	CP□T 09T3□□	
A16Q SCLPR/L 09T3	●	●	16	15	180	20	11	20	TS 35070I/HG	T 15
A20R SCLPR/L 09T3	●	●	20	18	200	22	13	25		



• For inserts, see page A41

• For spare part, see page A167 - A177

● Marked: Standard Items

• L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

E-SCLPR/L



Designation	Dimension (mm)							Insert	Components	
	R	L	d	h	l	l1	f		Screw	Wrench
E08K SCLPR/L 06	●	●	8	7	125	15	6	11	SO 25050I	T 7
E10K SCLPR/L 06	●	●	10	9	125	15	7	13	CP□T 0602□□	
E12M SCLPR/L 0903	●	●	12	11	150	19	9	16	TS 35070I/HG	T 15
E16R SCLPR/L 0903	●	●	16	15	200	21.73	11	20	CP□T 0903□□	
E12M SCLPR/L 09T3	●	●	12	11	150	19	9	16	CP□T 09T3□□	
E16R SCLPR/L 09T3	●	●	16	15	200	21.5	11	20	TS 35070I/HG	T 15

• For inserts, see page A41



• For spare part, see page A167 - A177

● Marked: Standard Items

• L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

■ Designates Carbide Shank

A-SDLNR/L





Designation	Dimension (mm)							Insert	Components				
	R	L	d	h	l	l1	f		Screw	Shim	Shim Screw	Wrench	Seal
A20S SDLNR/L 11	●	20	18	250	31	13	24	DNM□1104□□	SO 35120I	-	-	T 10	PL 20
A25T SDLNR/L 11	●	25	23	300	30	17	31	SSD 32	SO 50090S				PL 25

• For inserts, see page A28 - A29

• For spare part, see page A167 - A177

● Marked: Standard Items

S-SDQCR/L



Designation	Dimension (mm)							Insert	Components	
	R	L	d	h	l	l1	f		Screw	Wrench
S10K SDQCR/L 07	●		10	9	125	20	7	13	DC□T 0702□□	SO 25050I
S10M SDQCR/L 07	●		10	9	150	20	7	13		
S12M SDQCR/L 07	●	●	12	11	150	22	9	16		T 7
S16R SDQCR/L 07	●	●	16	15	200	27	11	20		SO 25065I
S20N SDQCR/L 11	●		20	18	160	40	13	25	DC□T 11T3□□	SO 35080I
S20S SDQCR/L 11	●	●	20	18	250	40	13	25		
S25T SDQCR/L 11	●	●	25	23	300	50	17	32		



• For inserts, see page A41 - A42

• For spare part, see page A167 - A177

● Marked: Standard Items

• L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

A-SDQNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	d	h	l	l1	f		Screw	Shim	Shim Screw	Wrench	Seal	
A16S SDQNR/L 11	●		16	15	250	30	13	23	DNM□ 1104□□	SO 35120I	-	-	T 10	PL 16
A20S SDQNR/L 11	●		20	18	250	31	15	27			SSD 32	SO 50090S		PL 20
A25T SDQNR/L 11	●		25	23	300	35	19	33						PL 25
A32T SDQNR/L 11	●		32	30	300	44	26	44						PL 32

• For inserts, see page A28 - A29

• For spare part, see page A167 - A177

● Marked: Standard Items

S-SDUCR/L



Designation	Dimension (mm)							Insert	Components							
	R	L	d	h	l	l1	f		Screw	Wrench						
S10K SDUCR/L 07	●		10	9	125	20	7	13	DC□T 0702□□	SO 25050I	T 7	T 7	T 7			
S12M SDUCR/L 07	●	●	12	11	150	23	9	16								
S16M SDUCR/L 07	●		16	15	150	30	11	20		SO 25065I						
S16R SDUCR/L 07	●	●	16	15	200	30	11	20	DC□T 11T3□□	SO 35080I						
S16R SDUCR/L 11	●	●	16	15	200	27	11	20								
S20S SDUCR/L 11	●	●	20	18	250	32	13	25								
S25T SDUCR/L 11	●	●	25	23	300	42	17	32								
S32T SDUCR/L 11	●	●	32	30	300	55	22	40								



• For inserts, see page A41 - A42

• For spare part, see page A167 - A177

● Marked: Standard Items

• L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

A-SDUNR/L





Designation	R	L	Dimension (mm)					Insert	Components				
			d	h	I	l1	f		Screw	Shim	Shim Screw	Wrench	Seal
A20S SDUNR/L 11			20	18	250	30	15	27		-	-		PL 20
A25T SDUNR/L 11	●		25	23	300	30	19	33	DNM□ 1104□□	SO 35120I	SSD 32	SO 50090S	T 10
A32T SDUNR/L 11			32	30	300	44	26	44					PL 25
													PL 32

• For inserts, see page A28 - A29

• For spare part, see page A167 - A177

• Marked: Standard Items

S-SDZCR/L





Designation	R	L	Dimension (mm)					Insert	Components				
			d	h	I	l1	f		Screw	Shim	Shim Screw	Wrench	
S16R SDZCR/L 07	●		16	15	200	23	13	22					
S20S SDZCR/L 07	●		20	18	250	28	15	27	DC□T 0702□□	SO 25065I	-	-	T 7
S25T SDZCR/L 07	●		25	23	300	33	18	33					
S20S SDZCR/L 11	●		20	18	250	24	15	27	DC□T 11T3□□	SO 35080I	-	-	
S32T SDZCR/L 11	●		32	30	300	34	22	40		SO 35124I	SSD 32	SO 50090S	T 15

• For inserts, see page A41 - A42

• For spare part, see page A167 - A177

• L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder
• Marked: Standard Items

S-SSKCR/L





Designation	R	L	Dimension (mm)					Insert	Components		
			d	h	I	l1	f		Screw	Wrench	
S16R SSKCR/L 09	●		16	15	200	28	11	20			
S20S SSKCR/L 09	●		20	18	250	30	13	25	SC□T 09T3□□	SO 35080I	T 15
S25T SSKCR/L 12			25	23	300	39	17	32	SC□T 1204□□	SO 45100I	T 20

• For inserts, see page A43

• For spare part, see page A167 - A177

• Marked: Standard Items

S-STFCR/L



Designation	R	L	Dimension (mm)					Insert	Components				
			d	h	I	l ₁	f		Screw	Shim	Shim Screw	Wrench	
S08K STFCR/L 09	●		8	7	125	20	6	11	TC□T 0902□□	TS 22046I	-	-	T 7
S10K STFCR/L 09	●	●	10	9	125	22.5	7	13		SO 22050I	-	-	
S12M STFCR/L 09	●	●	12	11	150	30	9	16	TC□T 1102□□	SO 25065I	-	-	T 7
S16R STFCR/L 09			16	15	200	35	11	20		SO 35080I	-	-	
S12M STFCR/L 11	●	●	12	11	150	25	9	16	TC□T 16T3□□	SO 35124I	SST 32	SO 50090S	T 15
S16R STFCR/L 11	●	●	16	15	200	35	11	20		SO 35124I	SST 32	SO 50090S	
S20S STFCR/L 11	●	●	20	18	250	36	13	25	TC□T 16T3□□	SO 35124I	SST 32	SO 50090S	T 15
S20S STFCR/L 16	●		20	18	250	36	13	25		SO 35124I	SST 32	SO 50090S	
S25T STFCR/L 16	●		25	23	300	49	17	32	TC□T 16T3□□	SO 35124I	SST 32	SO 50090S	T 15
S32T STFCR/L 16	●		32	30	300	45	22	40		SO 35124I	SST 32	SO 50090S	
S40T STFCR/L 16	●		40	37	300	60	27	50					



• For inserts, see page A44

• For spare part, see page A167 - A177

• Marked: Standard Items

• L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

S-STFPR/L



Designation	R	L	Dimension (mm)					Insert	Components			
			d	h	I	l ₁	f		Screw	Wrench		
S08K STFPR/L 09-X01	●		8	7	125	15	6	11	TPGX 0902□□	SO 25061I	T 8	
S08K STFPR/L 09	●		8	7	125	14	6	11		TS 22046I	T 7	
S10K STFPR/L 11	●		10	9	125	25	6	12	TP□T 1103□□	SO 30055I	T 9	
S10M STFPR/L 11	●		10	9	150	25	6	12		SO 30100I	T 9	
S12M STFPR/L 11	●	●	12	11	150	30	8	16	TP□T 1103□□	SO 30040I	T 9	
S16N STFPR/L 11	●		16	15	160	35	10	20		SO 35080I	T 15	
S16R STFPR/L 11	●		16	15	200	35	10	20	TP□T 1604□□	SO 35124I	T 15	
S16N STFPR/L 16	●		16	15	160	30	10	20		SO 35124I	T 15	
S20N STFPR/L 16	●		20	18	160	35	12.5	25				
S20S STFPR/L 16	●		20	18	250	36	12.5	25				



• For inserts, see page A44

• For spare part, see page A167 - A177

• Marked: Standard Items

• L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

• TPGX type inserts are available with alternate screw.
(TPGX 1103 → SO 30081I)

A-STFPR/L




Designation	Dimension (mm)							Insert	Components	
	R	L	d	h	I	f	ØD min		Screw	Wrench
A08H STFPR/L 09	●	●	8	7	100	6	11	TP□T 0902□□	TS 22046I	T 7
A10K STFPR/L 1102	●	●	10	9	125	7	13	TP□T 1102□□	SO 25050I	T 7
A12M STFPR/L 1102	●	●	12	11	150	9	16	TP□T 1103□□	SO 30055I	T 9
A16Q STFPR/L 1102	●	●	16	15	180	11	20	TP□T 1103□□	SO 30055I	T 9
A12M STFPR/L 1103	●	●	12	11	150	9	16	TP□T 1103□□	TS 35070I/HG	T 15
A16Q STFPR/L 1103	●	●	16	15	180	11	20	TP□T 16T3□□		
A20R STFPR/L 16T3	●	●	20	18	200	13	25	TP□T 16T3□□		

- For inserts, see page A45

- For spare part, see page A167 - A177

- Marked: Standard Items

- L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

E-STFPR/L


Designation	Dimension (mm)							Insert	Components	
	R	L	d	h	I	f	ØD min		Screw	Wrench
E08K STFPR/L 09	●	●	8	7	125	6	11	TP□T 0902□□	TS 22046I	T 7
E10K STFPR/L 1102	●	●	10	9	125	7	13	TP□T 1102□□	SO 25050I	T 7
E12M STFPR/L 1102	●	●	12	11	150	9	16	TP□T 1102□□	SO 30055I	T 9
E16R STFPR/L 1102	●	●	16	15	200	11	20	TP□T 1103□□	SO 30055I	T 9
E12M STFPR/L 1103	●	●	12	11	150	9	16	TP□T 1103□□	SO 30055I	T 9
E16R STFPR/L 1103	●	●	16	15	200	11	20	TP□T 1103□□		



- For inserts, see page A45

- For spare part, see page A167 - A177

- Marked: Standard Items

- L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

Designates Carbide Shank

C-STUBR/L


Designation	Dimension (mm)							Insert	Components	
	R	L	d	h	I	f	ØD min		Screw	Wrench
C06J STUBR/L 06-D08	●	●	6	5.5	110	4	8	TB□T 0601□□	TS 20043I/HG-P	T 6P

- For inserts, see page A44



- For spare part, see page A167 - A177

- Marked: Standard Items

- L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

Designates Carbide Shank

S-STUBR/L





Designation	Dimension (mm)							Insert	Components		
	R	L	d	h	I	f	ØD min		Screw	Wrench	
S06H STUBR/L 06-D08	●	●	6	5.5	100	4	8	TB□T 0601□□	TS 20043I/HG-P	T 6P	

• For inserts, see page A44

• For spare part, see page A167 - A177

● Marked: Standard Items
• L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

A-SVLNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	d	h	I	l1	f	ØD min	Screw	Shim	Shim Screw	Wrench	Seal	
A25T SVLNR/L 13	●		25	23	300	40	16	31	VNM□ 1304□□	SO 35120I	SSVN 2.522	TS 5035062S	T 10	PL 25
A32T SVLNR/L 13	●		32	30	300	45	20	38						PL 32

• For inserts, see page A36

• For spare part, see page A167 - A177

● Marked: Standard Items

A-SVPNR/L





Designation	Dimension (mm)							Insert	Components					
	R	L	d	h	I	l1	f	ØD min	Screw	Shim	Shim Screw	Wrench	Seal	
A25T SVPNR/L 13	●		25	23	300	45	19	33	VNM□ 1304□□	SO 35120I	SSVN 2.522	TS 5035062S	T 10	PL 25
A32T SVPNR/L 13	●		32	30	300	47	26	44						PL 32

• For inserts, see page A36

• For spare part, see page A167 - A177

● Marked: Standard Items

S-SVQBR/L




Designation	Dimension (mm)								Insert	Components			
	R	L	d	h	l	l1	f	ØD min		Screw	Shim	Shim Screw	Wrench
S25T SVQBR/L 16	●	●	25	23	300	40	17	32	VB□T 1604□□	SO 35080I	-	-	
S32T SVQBR/L 16	●	●	32	30	300	45	22	40		SO 35124I	SSV 32	SO 50090S	T 15
S40T SVQBR/L 16	●	●	40	38	300	55	27	50					

- For inserts, see page A46 - A47

- For spare part, see page A167 - A177

- Marked: Standard Items

- L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder



S-SVQCR/L


Designation	Dimension (mm)								Insert	Components			
	R	L	d	h	l	l1	f	ØD min		Screw	Shim	Shim Screw	Wrench
S32T SVQCR/L 16	●	●	32	30	300	45	22	40	VC□T 1604□□	SO 35124I	SSV 32	SO 50090S	T 15
S40T SVQCR/L 16	●	●	40	38	300	55	27	50					

- For inserts, see page A47

- For spare part, see page A167 - A177

- Marked: Standard Items

S-SVUBR/L


Designation	Dimension (mm)								Insert	Components			
	R	L	d	h	l	l1	f	ØD min		Screw	Shim	Shim Screw	Wrench
S32T SVUBR/L 16	●	●	32	30	300	45	22	40	VB□T 1604□□	SO 35124I	SSV 32	SO 50090S	T 15
S40T SVUBR/L 16	●	●	40	38	300	55	27	50					

- For inserts, see page A46 - A47

- For spare part, see page A167 - A177

- Marked: Standard Items

- L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

S-SVUCR/L




Fig.1





Fig.2





Designation	Dimension (mm)							Insert	Components				Shape	
	R	L	d	h	l	l1	f	ØD min	Screw	Shim	Shim Screw	Wrench		
S12M SVUCR/L 08-D16	●	●	12	11	150	26	11	16	VCUT 0802□□	TS 20038I/HG-P	-	-	T 6P	Fig.2
S16Q SVUCR/L 11-D20	●	●	16	15	180	32	15.5	20	VCUT 1103□□	SO 25065I	-	-	T 7	
S20R SVUCR/L 11-D25	●	●	20	18	200	40	17.5	25						
S32T SVUCR/L 16	●		32	30	300	45	22	40	VCUT 1604□□	SO 35124I	SSV 32	SO 50090S	T 15	Fig.1
S40T SVUCR/L 16		40	38	300	60	27	50							

• For inserts, see page A47

• For spare part, see page A167 - A177

● Marked: Standard Items

S-SVJCR/L





Designation	Dimension (mm)							Insert	Components			Wrench	
	R	L	d	h	l	l1	f	ØD min	Screw				
S12M SVJCR/L 08-D16	●	●	12	11	150	26	2	16	VCUT 0802□□	TS 20038I/HG-P			T 6P
S16Q SVJCR/L 08-D20	●	●	16	15	180	36	2	20					

• For inserts, see page A47

• For spare part, see page A167 - A177

● Marked: Standard Items
● L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

S-SVPCR/L



Designation	Dimension (mm)							Insert	Components			Wrench
	R	L	d	h	l	f	ØD min		Screw			
S10K SVPCL 08-D16	●	●	10	9	125	8	16	VCUT 0802□□	TS 20038I/HG-P			T 6P
S12M SVPCL 11-D20	●	●	12	11	150	10	20	VCUT 1103□□	SO 25065I			T 7

• For inserts, see page A47

• For spare part, see page A167 - A177

● Marked: Standard Items

S-SWUBR/L




Fig.1





Fig.2



Designation	Dimension (mm)							Insert	Components		Shape	
	R	L	d	h	I	l ₁	f	ØD min	Screw	Wrench		
S05G SWUBR/L 06-D06	●	●	5	4.75	90		3	6	WB□T 060102	TS 20038I/HG-P	T 6P	Fig.1
S06H SWUBR/L 06-D07	●	●	6	5.5	100		3.5	7				
S07J SWUBR/L 06-D08	●	●	7	6.5	110		4	8				Fig.2
S10H SWUBR/L 06-D06	●	●	10	9	100	18	3	6				



• For inserts, see page A48

• For spare part, see page A167 - A177

● Marked: Standard Items

• L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

C-SWUBR/L



Designation	Dimension (mm)							Insert	Components		Shape
	R	L	d	h	I	f	ØD min		Screw	Wrench	
C05H SWUBR/L 06-D06	●	●	5	4.75	100	3	6	WB□T 060102	TS 20038I/HG-P	T 6P	Fig.1
C06J SWUBR/L 06-D07	●	●	6	5.5	110	3.5	7				
C07K SWUBR/L 06-D08	●	●	7	6.5	125	4	8				

• For inserts, see page A48



• For spare part, see page A167 - A177

● Marked: Standard Items

• L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder

■ Designates Carbide Shank

S-WTFNR/L





Designation	Dimension (mm)							Insert	Components					Shape	
	R	L	d	h	I	l ₁	f	ØD min	Wedge Clamp	Screw	Snap Ring	Shim	Pin Screw	Wrench	
S25T WTFNR/L 16	●	●	25	23	300	50	17	32	TN□□ 1604□□	WC 33	WCS 4B	WSR 4B	-	WSS 33-1	L-W 3
S32T WTFNR/L 16	●	●	32	30	300	55	22	40			WCS 4	WSR 4	WST 33	WSS 33	
S40T WTFNR/L 16	●	40	37	300	60	27	50								
S40T WTFNR/L 22	●	40	37	300	60	27	50	TN□□ 2204□□	WC 43	WCS 4	WSR 4	WST 43	WSS 43	L-W 3	
S50U WTFNR/L 22	●	50	47	350	65	35	63								

• For inserts, see page A33 - A35

• For spare part, see page A167 - A177

● Marked: Standard Items

A-TCLNR/L





Designation	Dimension (mm)								Insert	Components						
	R	L	d	h	I	l1	f	ØD min		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench
A25T TCLNR/L 12	●	●	25	23	300	45	17	32	CNM□ 1204□□	DLM 4	DLS 4	LSC 42	TS 50A105I	DSP 4	NZ 62	L-W 3
A32T TCLNR/L 12	●	●	32	30	300	45	22	40				TSC 44	SO 40050I		NZ 104	
A40T TCLNR/L 12	●	●	40	37	300	45	27	50								
A50U TCLNR/L 12	●	●	50	47	350	45	35	63								

• For inserts, see page A24 - A27

• For spare part, see page A167 - A177

● Marked: Standard Items

A-TDUNR/L





Designation	Dimension (mm)								Insert	Components						
	R	L	d	h	I	l1	f	ØD min		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench
A32T TDUNR/L 15	●	32	30	300	45	22	40	DNM□ 1506□□	DLM 4	DLS 4	LSD 42	TS 50A105I	DSP 4	NZ 62	L-W 3	
A40T TDUNR/L 15	●	40	37	300	45	27	50				TSD 43	SO 40050I		NZ 104		
A50U TDUNR/L 15	●	50	47	350	45	35	63									

• For inserts, see page A28 - A29

• For spare part, see page A167 - A177

● Marked: Standard Items

A-THSNR/L





Designation	Dimension (mm)								Insert	Components						
	R	L	d	h	I	l1	f	ØD min		Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench
A32T THSNR/L 05			32	30	300	40	22	40	4.2	HN□G 0504□□	DLM 4	DLS 4	TSH 42	DSP 4	NZ 62	L-W 3
A40T THSNR/L 05			40	37	300	45	27	50	4.2				TSH 44	SO 40050I	NZ 104	
A50U THSNR/L 05			50	47	350	45	35	63	4.2							

• For inserts, see page A30

• For spare part, see page A167 - A177

● Marked: Standard Items



A-TSKNR/L



Designation	Dimension (mm)							Insert	Components							
	R	L	d	h	l	l1	f	ØD min	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench	
A25T TSKNR/L 12			25	23	300	45	17	32	SNM□1204□□	DLM 4	DLS 4	LSS 42	TS 50A105I	DSP 4	NZ 62	L-W 3

- For inserts, see page A31 - A33
- For spare part, see page A167 - A177
- Marked: Standard Items
- L-hand Insert for R-hand Toolholder, R-hand Insert for L-hand Toolholder



A-TWLNR/L



Designation	Dimension (mm)							Insert	Components						
	R	L	d	h	l	l1	f	ØD min	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench
A20S TWLNR/L 06	●		20	18	250	35	13	25	WNM□0604□□	DLM 3	DLS 3	-	-	DSP 3	NZ 62
A25T TWLNR/L 06	●		25	23	300	40	17	32				PSW 32	SO 40090I		
A32T TWLNR/L 06			32	30	300	45	22	40		DLM 4	DLS 4	PSW 42	TS 50A105I	DSP 4	NZ 104
A25T TWLNR/L 08	●	●	25	23	300	40	17	32				TSW 44	SO 40050I		
A32T TWLNR/L 08	●	●	32	30	300	45	22	40	WNM□0804□□	DLM 4	DLS 4	PSW 42	TS 50A105I		
A40T TWLNR/L 08	●	●	40	37	300	45	27	50				TSW 44	SO 40050I		

- For inserts, see page A37 - A38
- For spare part, see page A167 - A177
- Marked: Standard Items


S-TCLNR/L-CH



Designation	Dimension (mm)							Insert	Components						
	R	L	d	h	l	l1	f	ØD min	Clamp	Clamp Screw	Shim	Shim Screw	Spring	Nozzle	Wrench
S40T TCLNR/L 1207-CH			40	37	300	50	27	70	CNGX 1207□□ CH	CCL 4	CSC 4	S 48	BH M5×0.8×1.0	DSP 5	L-W 4
S50U TCLNR/L 1207-CH	●		50	47	350	50	32	70							

- For inserts, see page A58
- For spare part, see page A167 - A177
- Marked: Standard Items

TSL (SLEEVE)



Designation		Dimension (mm)				Components	
		d1	h	I	D	Set Screw	Wrench
TSL 16-04	●	4	15	100	16	SS M4 X 0.7 X 4	L-W 2
TSL 16-05	●	5	15	100	16		
TSL 16-06	●	6	15	100	16		
TSL 16-07	●	7	15	100	16		


• For spare part, see page A167 - A177

HE - D32 - PCLNR 12

1 Head



2 Shank Diameter

3 Designation follows Boring Bar System, see page A133



- Triangular detachable anti-rotator induces auto-centering and durability
- High repeatability during head change
- Possibility of inner coolant
- Head for ISO Turning

HE-SCLCR/L





Designation	Dimension (mm)						Insert	Components				
	R	L	d	I	f	ØD min		Screw	Shim	Shim Screw	Nozzle	Wrench
HE-D25-SCLCR/L 09	● ●	25	25	17	32	CC□T 09T3□□	SO 35080I	-	-	-	T 15	
HE-D32-SCLCR/L 12	● ●	32	35	22	40	CC□T 1204□□	SO 45130I	SSC 43N	SO 60105S	NZ 62	T 20	

- For inserts, see page A39 - A40
- For spare part, see page A167 - A177

● Marked: Standard Items

HE-SDUCR/L





Designation	Dimension (mm)						Insert	Components		
	R	L	d	I	f	ØD min		Screw	Nozzle	Wrench
HE-D25-SDUCR/L 11	● ●	25	25	17	32	DC□T 11T3□□	SO 35080I	-	-	T 15
HE-D32-SDUCR/L 11	● ●	32	35	22	40			NZ 62		

- For inserts, see page A41 - A42
- For spare part, see page A167 - A177

● Marked: Standard Items

HE-SDQCR/L





Designation	Dimension (mm)						Insert	Components		
	R	L	d	I	f	ØD min		Screw	Nozzle	Wrench
HE-D25-SDQCR/L 11	● ●	25	25	17	32	DC□T 11T3□□	SO 35080I	-	-	T 15

- For inserts, see page A41 - A42
- For spare part, see page A167 - A177

● Marked: Standard Items

HE-SVUBR/L





Designation	Dimension (mm)					Insert	Components					
	R	L	d	l	f	ØD min.	Screw	Shim	Shim Screw	Nozzle	Wrench	
HE-D32-SVUBR/L 16	●	●	32	35	22	40	VB□T 1604□□	SO 35124I	SSV 32	SO 50090S	NZ 62	T 15

- For inserts, see page A46 - A47
- For spare part, see page A167 - A177

● Marked: Standard Items

HE-PCLNR/L





Designation	Dimension (mm)					Insert	Components						
	R	L	d	l	f	ØD min.	Lever	Screw	Shim	Shim Pin	Nozzle	Wrench	
HE-D32-PCLNR/L 12	●	●	32	35	22	40	CN□□ 1204□□	LCL 4	LCS 4S	LSC 42	LSP 4	NZ 62	L-W 3

- For inserts, see page A24 - A27
- For spare part, see page A167 - A177

● Marked: Standard Items

HE-PDUNR/L





Designation	Dimension (mm)					Insert	Components						
	R	L	d	l	f	ØD min.	Lever	Screw	Shim	Shim Pin	Nozzle	Wrench	
HE-D32-PDUNR/L 15	●	●	32	35	22	40	DN□□ 1506□□	LCL 4A	LCS 4S	LSD 42	LSP 4	NZ 62	L-W 3

- For inserts, see page A28 - A29
- For spare part, see page A167 - A177

● Marked: Standard Items

HE-PTFNR/L




Designation	Dimension (mm)						Insert	Components					
	R	L	d	I	f	ØD min		Lever	Screw	Shim	Shim Pin	Nozzle	Wrench
HE-D32-PTFNR/L 16	●	●	32	35	22	40	TN□□1604□□	LCL 3	LCS 3	LST 31.8	LSP 3A	NZ 62	L-W 2.5

• For inserts, see page A33 - A35

• For spare part, see page A167 - A177

● Marked: Standard Items

SK-SHANK



Designation	Dimension (mm)					Components			
		d	I	h	a	Key	Key Screw	Clamp Screw	Wrench
SK-D25	●	25	170	23	23	SDK T10-5	SO 50090S	SH M4 X 0.7 X 16	L-W 3
SK-D32	●	32	215	30	30				

• For spare part, see page A167 - A177

● Marked: Standard Items



CARTRIDGES



LEVER LOCK



TOP CLAMP



SCREW CLAMP

T-TURN Cartridge Designation System








1 Clamping System	2 Insert Shape	3 Approach Angle	4 Insert Clearance Angle
P/Lever Lock	T	L	C
C/Top Clamp	80°	S	P
S/Screw Clamp	C	F	N
		K	T
		G	
		W	

P C L N R - 16 C A - 12












5 Hand of Tool	6 Shank Height	7 Type of Tool	9 Cutting Edge Length	
		C: Cartridge		
Right hand				
R				
		A: Letter for alternative designs		
Left hand				
L				
8 Type of Design				

T-TURN Cartridge Program

Top Clamp Type








Entering Angle	Style	Cartridge Size			
		10CA	12CA	16CA	
75°		CSKPR/L	10CA 09	12CA 12	16CA 12
45°		CSSPR/L		12CA 12	16CA 12
90°		CTFPR/L	10CA 11	12CA 16	16CA 16
90°		CTGPR/L	10CA 11	12CA 16	16CA 16
45°		CTSPR/L	10CA 11	12CA 16	16CA 16
60°		CTTPR/L	10CA 11	12CA 16	16CA 16
60°		CTWPR/L	10CA 11	12CA 16	16CA 16


Lever Lock Type

Entering Angle	Style	Cartridge Size				
		10CA	12CA	16CA	20CA	25CA
90°		PCFNR/L		16CA 12		25CA 19
90°		PCGNR/L		16CA 12		25CA 19
95°		PCLNR/L		16CA 12		25CA 19
75°		PSKNR/L	10CA 09	12CA 12	16CA 12	20CA 15
75°		PSRNR/L			16CA 12	20CA 15
45°		PSSNR/L		12CA 12	16CA 12	20CA 15
90°		PTFNR/L	10CA 11	12CA 16	16CA 16	20CA 22
90°		PTGNR/L	10CA 11	12CA 16	16CA 16	20CA 22
45°		PTSNR/L	10CA 11	12CA 16	16CA 16	20CA 22
60°		PTTNR/L	10CA 11	12CA 16	16CA 16	20CA 22
60°		PTWNR/L	10CA 11	12CA 16	16CA 16	20CA 22

T-TURN Cartridge Program

Screw Clamp Type

Entering Angle	Style	Cartridge Size		
		10CA	12CA	16CA
75°		SSKCR/L	10CA 09 12CA 09	
45°		SSSCR/L	10CA 09 12CA 12	
90°		STFCR/L	10CA 11 12CA 16	16CA 16
90°		STGCR/L	10CA 11 12CA 16	16CA 16
45°		STSCR/L	10CA 11 12CA 16	16CA 16
60°		STTCR/L	10CA 11 12CA 16	16CA 16
60°		STWCR/L	10CA 11 12CA 16	16CA 16


CSKPR/L CSSPR/L


Entering Angle	Designation	Dimension (mm)											Insert Type
		h	h ₁	b	l ₁	l ₂	f	γ	λ	t	v	ØDmin	
75°	CSKPR/L 10CA 09	15	10	11	50	30	14	6°	2°	5	20°	40	SPMR SP□N
	12CA 12	20	12	15	55	35	20	6°	2°	6	20°	50	
	16CA 12	21	16	20	63	38	25	6°	2°	0	45°	55	
45°	CSSPR/L 12CA 12	20	12	15	47	27	20	4°	4°	6	20°	50	1203□□
	16CA 12	21	16	20	53	28	25	3°	3°	0	45°	55	

- For inserts, see page A43

- For spare part, see page A165

- All cartridges are to be ordered as specials.

CTFPR/L CTGPR/L CTSPR/L CTTPR/L CTWPR/L



Entering Angle	Designation	Dimension (mm)											Insert Type
		h	h ₁	b	l ₁	l ₂	f	γ	λ	t	v	ØDmin	
90°	CTFPR/L 10CA 11	15	10	11	50	30	14	6°	0°	5	20°	40	TPMR TP□N
	12CA 16	20	12	15	55	35	20	6°	0°	6	20°	50	
	16CA 16	21	16	20	63	38	25	6°	0°	0	45°	55	
90°	CTGPR/L 10CA 11	15	10	11	50	30	14	0°	4°	5	20°	40	1103□□
	12CA 16	20	12	15	55	35	20	0°	4°	6	20°	50	
	16CA 16	21	16	20	63	38	25	0°	4°	0	45°	60	
45°	CTSPR/L 10CA 11	15	10	11	44	24	14	3°	3°	5	20°	40	1103□□
	12CA 16	20	12	15	47	27	20	3°	3°	6	20°	50	
	16CA 16	21	16	20	53	28	25	3°	3°	0	45°	55	
60°	CTTPR/L 10CA 11	15	10	11	50	30	9	3°	4°	5	20°	40	1103□□
	12CA 16	20	12	15	55	35	13	3°	4°	6	20°	50	
	16CA 16	21	16	20	63	38	15	2°	3°	0	45°	60	
60°	CTWPR/L 10CA 11	15	10	11	44	24	14	5°	3°	5	20°	40	1103□□
	12CA 16	20	12	15	47	27	20	5°	3°	6	20°	50	
	16CA 16	21	16	20	53	28	25	3°	2°	0	45°	55	

- For inserts, see page A45 - A46

- For spare part, see page A165

- All cartridges are to be ordered as specials.

PCFNR/L PCGNR/L PCLNR/L




Entering Angle	Designation	Dimension (mm)												Insert Type
		h	h1	b	l1	l2	l3	f	γ	λ	t	v	ØDmin	
90°	PCFNR/L 16CA 12 25CA 19	25	16	20	63	38	-	25	- 6°	- 8°	0	45°	55	1204□□ 1906□□
		38	25	25	100	50	70	32	- 6°	- 8°	0	45°	100	
90°	PCGNR/L 16CA 12 25CA 19	25	16	20	63	38	-	25	- 10°	- 6°	0	45°	55	CN□□ 1204□□ 1906□□
		38	25	25	100	50	70	32	- 8°	- 6°	0	45°	100	
95°	PCLNR/L 16CA 12 25CA 19	25	16	20	63	38	-	25	- 8°	- 8°	0	45°	55	1204□□ 1906□□
		38	25	25	100	50	70	32	- 8°	- 8°	0	45°	100	

• For inserts, see page A24 - A27

• For spare part, see page A165

• All cartridges are to be ordered as specials.

PSKNR/L PSRNR/L PSSNR/L




Entering Angle	Designation	Dimension (mm)												Insert Type
		h	h1	b	l1	l2	l3	f	γ	λ	t	v	ØDmin	
75°	PSKNR/L 10CA 09 12CA 12 16CA 12 20CA 15 25CA 19	17	10	11	50	30	-	14	- 4°	- 8°	5	20°	40	0903□□ 1204□□ 1506□□ 1906□□
		20	12	15	55	35	-	20	- 4°	- 9°	6	20°	50	
		25	16	20	63	38	-	25	- 4°	- 8°	0	45°	55	
		30	20	20	70	40	-	25	- 4°	- 9°	0	45°	70	
		38	25	25	100	50	70	32	- 4°	- 8°	0	45°	100	
75°	PSRNR/L 16CA 12 20CA 15	25	16	20	63	38	-	25	- 11°	- 3°	0	45°	60	1204□□ 1506□□
		30	20	20	70	40	-	25	- 11°	- 3°	0	45°	70	
45°	PSSNR/L 12CA 12 16CA 12 20CA 15	20	12	15	47	27	-	20	- 9°	- 5°	6	20°	50	1204□□ 1506□□
		25	16	20	53	28	-	25	- 9°	- 5°	0	45°	55	
		30	20	20	60	30	-	25	- 9°	- 5°	0	45°	70	

• For inserts, see page A31 - A33

• For spare part, see page A165

• All cartridges are to be ordered as specials.

PTFNR/L PTGNR/L PTSNR/L PTTNR/L PTWNR/L




Entering Angle	Designation	Dimension (mm)												Insert Type
		h	h1	b	l1	l2	l3	f	γ	λ	t	v	ODmin	
90°	PTFNR/L	10CA 11	17	10	11	50	30	-	14	- 6°	- 8°	5	20°	40
		12CA 16	20	12	15	55	35	-	20	- 6°	- 9°	6	20°	50
		16CA 16	25	16	20	63	38	-	25	- 6°	- 8°	0	45°	55
		20CA 22	30	20	20	70	40	-	25	- 6°	- 8°	0	45°	70
		25CA 27	38	25	25	100	50	70	32	- 6°	- 9°	0	45°	100
90°	PTGNR/L	10CA 11	17	10	11	50	30	-	14	- 10°	- 6°	5	20°	40
		12CA 16	20	12	15	55	35	-	20	- 10°	- 6°	6	20°	50
		16CA 16	25	16	20	63	38	-	25	- 10°	- 6°	0	45°	60
		20CA 22	30	20	20	70	40	-	25	- 8°	- 6°	0	45°	70
45°	PTSNR/L	10CA 11	17	10	11	44	24	-	14	- 5°	- 9°	5	20°	40
		12CA 16	20	12	15	47	27	-	20	- 5°	- 9°	6	20°	50
		16CA 16	25	16	20	53	28	-	25	- 8°	- 8°	0	45°	55
		20CA 22	30	20	20	60	30	-	25	- 8°	- 8°	0	45°	70
60°	PTTNR/L	10CA 11	17	10	11	50	30	-	9	- 6°	- 7°	5	20°	40
		12CA 16	20	12	15	55	35	-	13	- 6°	- 7°	6	20°	50
		16CA 16	25	16	20	63	38	-	15	- 7°	- 8°	0	45°	60
		20CA 22	30	20	20	70	40	-	15	- 7°	- 8°	0	45°	70
60°	PTWNR/L	10CA 11	17	10	11	44	24	-	14	- 1°	- 10°	5	20°	40
		12CA 16	20	12	15	47	27	-	20	- 3°	- 9°	6	20°	50
		16CA 16	25	16	20	53	28	-	25	- 2°	- 8°	0	45°	55
		20CA 22	30	20	20	60	30	-	25	- 2°	- 8°	0	45°	70

• For inserts, see page A33 - A35

• For spare part, see page A165

• All cartridges are to be ordered as specials.

SSKCR/L SSSCR/L





Entering Angle	Designation	Dimension (mm)												Insert Type
		h	h1	b	l1	l2	l3	f	γ	λ	t	v	ODmin	
75°	SSKCR/L	10CA 09	15	10	11	50	30	-	14	- 1°	- 4°	5	20°	40
		12CA 12	20	12	15	55	35	-	20	- 1°	- 4°	6	20°	50
45°	SSSCR/L	10CA 09	15	10	11	44	24	-	14	- 4°	- 4°	5	20°	40
		12CA 12	20	12	15	47	27	-	20	- 4°	- 4°	6	20°	50

• For inserts, see page A43

• For spare part, see page A165

• All cartridges are to be ordered as specials.

STFCR/L STGCR/L STSCR/L STTCR/L STWCR/L


Entering Angle	Designation	Dimension (mm)											Insert Type
		h	h1	b	l1	l2	f	γ	λ	t	v	ØDmin	
90°	STFCR/L 10CA 11	15	10	11	50	30	14	0°	-3°	5	20°	40	1102□□
		12CA 16	20	12	15	55	35	20	0°	-3°	6	20°	50
		16CA 16	21	16	20	63	38	25	0°	-6°	0	45°	55
90°	STGCR/L 10CA 11	15	10	11	50	30	14	0°	-3°	5	20°	40	1102□□
		12CA 16	20	12	15	55	35	20	0°	-3°	6	20°	50
		16CA 16	21	16	20	63	38	25	-3°	-5°	0	45°	60
45°	STSCR/L 10CA 11	15	10	11	44	24	14	-3°	-3°	5	20°	40	TC□□
		12CA 16	20	12	15	47	27	20	-4°	-4°	6	20°	50
		16CA 16	21	16	20	53	28	25	-2°	-6°	0	45°	55
60°	STTCR/L 10CA 11	15	10	11	50	30	9	-3°	-4°	5	20°	40	1102□□
		12CA 16	20	12	15	55	35	13	-3°	-2°	6	20°	50
		16CA 16	21	16	20	63	38	15	-4°	-3°	0	45°	60
60°	STWCR/L 10CA 11	15	10	11	44	24	14	-2°	-3°	5	20°	40	1102□□
		12CA 16	20	12	15	47	27	20	-4°	-2°	6	20°	50
		16CA 16	21	16	20	53	28	25	-5°	-3°	0	45°	55

• For inserts, see page A44

• For spare part, see page A165

• All cartridges are to be ordered as specials.

Components for Lever Lock Type

Cartridge Designation	Lever	Screw	Shim	Shim Pin	Snap Ring	Axial Adj.Screw	Radial Adj.Screw	Mounting Screw	Washer	Wrench	
PCLNR/L	16CA 12	LCL 4	LCS 4S	LSC 42	LSP 4	-	ASM 6	RSS M5	BH M8 X 1.25 X 30	MW 8.4 X 18	L-W 3
PCFNR/L	25CA 19	LCL 6	LCS 6	LSC 63	LSP 6	-	ASM 6		BH M10 X 1.5 X 40	MW 10.4 X 21	L-W 4
PCGNR/L	10CA 09	LCL 3B	LCS 2B	-	-	LSR 3B	AJM 5F		BH M6 X 1 X 20	-	L-W 2
PSKNR/L PSSNR/L PSRNR/L	12CA 12	LCL 4B	LCS 4B	-	-	LSR 4B	AJM 5F	RSS M4	BH M6 X 1 X 25	MW 6.4 X 12	L-W 2.5
	16CA 12	LCL 4	LCS 4S	LSS 42	LSP 4	-	ASM 6		BH M8 X 1.25 X 30	MW 8.4 X 18	L-W 3
	20CA 15	LCL 5	LCS 5	LSS 53	LSP 5	-	ASM 6	RSS M5	BH M8 X 1.25 X 35		L-W 4
	25CA 19	LCL 5	LCS 5	LSS 53	LSP 5	-	ASM 6		BH M10 X 1.5 X 40	MW 10.4 X 20	L-W 4
	10CA 11	LCL 2B	LCS 2B	-	-	LSR 2B	AJM 5F	RSS M4	BH M6 X 1 X 20	-	L-W 2
PTFNR/L PTWNR/L PTSNR/L PTGNR/L PTTNR/L	12CA 16	LCL 3BH	LCS 3B	-	-	LSR 3B	AJM 5F		BH M6 X 1 X 25	MW 6.4 X 12	L-W 2
	16CA 16	LCL 3	LCS 3	LST 31.8	LSP 3A	-	ASM 6	RSS M5	BH M8 X 1.25 X 30	MW 8.4 X 18	L-W 2.5
	20CA 22	LCL 4	LCS 4	LST 42	LSP 4	-	ASM 6		BH M8 X 1.25 X 35		L-W 3
	25CA 27	LCL 5	LCS 5	LST 53	LSP 5	-	ASM 6		BH M10 X 1.5 X 40	MW 10.4 X 20	L-W 3

Components for Screw Clamp Type

Cartridge Designation	Screw	Shim	Shim Pin	Axial Adj.Screw	Radial Adj.Screw	Mounting Screw	Washer	Wrench	
SSKCR/L SSSCR/L	10CA 09	SO 35080I	-	-	AJM 5F	RSS M4	BH M6 X 1 X 16	-	T 15
	12CA 12	SO 45100I	-	-	AJM 5F	RSS M4	BH M6 X 1 X 25	MW 6.4 X 12	T 20
STFCR/L STWCR/L STSCR/L STTCR/L STGCR/L	10CA 11	SO 25065I	-	-	AJM 5F	RSS M4	BH M6 X 1 X 16	-	T 7
	12CA 16	SO 35080I	-	-	AJM 5F	RSS M4	BH M6 X 1 X 25	MW 6.4 X 12	T 15
	16CA 16	SO 35124I	SST 32	SO 50090S	ASM 6	RSS M5	BH M8 X 1.25 X 30	MW 8.4 X 18	T 15








Components for Top Clamp Type

Cartridge Designation	Clamp	Screw	Shim	Shim Pin	Snap Ring	Axial Adj.Screw	Radial Adj.Screw	Mounting Screw	Washer	Wrench	
CSKPR/L CSSPR/L	10CA 09	CL 2C	CLS 2C	-	-	CSR 2C	AJM 5F	RSS M4	BH M6 X 1 X 20	-	L-W 2.5
	12CA 12	CL 3C	CLS 3C	-	-	CSR 2	AJM 5F	RSS M4	BH M6 X 1 X 25	MW 6.4 X 12	L-W 3
	16CA 12	CL 3C	CLS 3C	CSS 42	CSP 3	CSR 2	ASM 6	RSS M5	BH M8 X 1.25 X 30	MW 8.4 X 18	L-W 3
CTFPR/L CTWPR/L CTSPR/L CTTPR/L CTGPR/L	10CA 11	CL 2C	CLS 2C	-	-	CSR 2C	AJM 5F	RSS M4	BH M6 X 1 X 20	-	L-W 2.5
	12CA 16	CL 3C	CLS 3C	-	-	CSR 2	AJM 5F	RSS M4	BH M6 X 1 X 25	MW 6.4 X 12	L-W 3
	16CA 16	CL 3C	CLS 3C	CST 32	CSP 3	CSR 2	ASM 6	RSS M5	BH M8 X 1.25 X 30	MW 8.4 X 18	L-W 3

USER GUIDE

Components for Holder and Boring Bar	A167
Trouble Shooting	A178
Insert Selection for Cast Iron Materials	A180
Insert Geometry for Workpiece Shape	A182
Insert Selection & Recommended Cutting Parameters	A183
Comparison of Chipbreaker	A191

Screw

Shape	Description	Dimensions (mm)						
		a	d	h	l	b	c	T
	BH M2.5X0.45X10 BH M4X0.7X8 BH M5X0.8X8 BH M5X0.8X10 BH M6X1X20 BH M6X1X25	M2.5X0.45 M4X0.7 M5X0.8 M5X0.8 M6X1.0 M6X1.0	4.75 7.5 9.5 3.55 10.5 4.2	1.5 2.75 3.55 10 20 25	10 8 10 20 4.0	1.5 2.5 3.0 3.0 4.0		
	SO 22050I SO 25050I SO 25061I SO 25065I SO 30040I SO 30055I SO 30100I SO 35080I SO 35120I SO 35124I SO 40050I SO 40085I SO 45100I SO 45130I SO 50090I TS 40097I TS 50A105I	M2.2X0.45 M2.5X0.45 M2.5X0.45 M2.5X0.45 M3X0.5 M3X0.5 M3.5X0.6 M3.5X0.6 M4X0.7 M4X0.75 M4.5X0.75 M5X0.8 M4X0.7 M5X0.8	3.1 3.45 3.7 3.45 4.3 2.1 5.3 4.7 5.3 5.8 5.45 7 4.5 5.2 7	2.6 2.2 2 2.9 2.86 3.4 3.2 6.5 5 3 3.5 6.3 10.6 7.6 2.6 4.7	3.4 3 4 3.6 5.44 4.9 5.3 5.5 6.7 8.3 5 6.3 10.6 7.6 7.1 5.8		60° 90° 60° T 7 T 8 T 7 T 9 T 15 T 10 T 15 T 20 43° 60°	T 7 T 8 T 7 T 9 T 15 T 10 T 15 T 20 T 15 T 20
	SO 50090S SO 60105S	M5X0.5 M6X0.5	6.3 8.5	3.1 4.7	5.4 5.8	3.5 5	M3.5X0.6 M4.5X0.75	
	SO 80180I	M8X1.25	10.7	4.7	13.3	4	60°	
	LCS 2 LCS 2B LCS 3 LCS 3B LCS 4 LCS 4B LCS 4S LCS 5 LCS 5-L25.5 LCS 6 LCS 8 LCS 8-L39 LCS 8-L43 LCS 16C LCS 25C	M5X0.8 M5X0.8 M6X1.0 M5X0.8 M8X1.0 M6X1.0 M8X1.0 M8X1.0 M8X1.0 M10X1.0 M12X1.0 M12X1.0 M12X1.0 M6X1.0 M10X1.0	8 4.5 6 8 8 6 8 8 7.95 10 12 11.95 10.85 6 10	14 10 9.7 12 21 8.5 9.2 12 14.5 15 18 21 25 27 36 39 5 10	2 2 2.5 2 3 2.5 3 3 3 2.5 2 3 3 3 4 5 5 10	2.2 1.5 3.5 2.5 6 1 3 5.5 5.4 6 10 10 10 4 6		
	CLS 1.25 CLS 2 CLS 2C CLS 3 CLS 3C CLS 3S CLS 16K	M3X0.5 M5X0.8 M4X0.7 M6X1.0 M5X0.8 M6X1.0 1/4-20 UNC	4.5 6.5 6.5 8.5 8 8.5 10	9 15 14.4 21.5 19 16.2 25	4.7 6.3 7.6 9.8 9.5 4.5 12	1.5 2.5 2.5 2.2 3 3 4	1.3 1.2 1.9 2.2 2.5 2.2 4	
	CSC 4	1/4-20 UNC	11	30	17	4	5	










Screw

Shape	Description	Dimensions (mm)						
		a	d	h	l	b	c	T
	DLS 3	M4X0.7	6	8	16.8	2.5	3	
	DLS 4	M5X0.8	8	8.5	21	3	3.5	
	DLS 5	M6X1.0	10	12	26.5	4	4.5	
	WCS 4	M6X1.0	11	12	26	3	3	
	WCS 4B	M6X1.0	11	8	22.5	3	3	
	WSS 33	M5X0.8	3.7	8	16.5	2.5	5	
	WSS 43	M6X1.0	5	8	18	3	5	
	TS 5035062S	M5X0.5	6.44	2.24	3.96	3.5	M3.5X0.6	
	FH M3X0.5X10	M3X0.5	6	2	8	2	90°	
	SC 4	M4X0.7	6.35	11	7.3		2.7	T 15
	SC 4-SH	M4X0.7	6.35	11	7.3		2.1	T 15
	XNSM 0520	M5X0.8		20	7	2.5	6.0	
	XNSM 0620	M6X1.0		20	7	3	7.0	
	XNSM 0825	M8X1.0		25	12.5	4	6.5	
	BLCS 2	2.5	M3X0.35	3.5	1			T 6
	BLCS 3	3	M4X0.5	4.5	1.2	2		
	RSS M4	M4X0.5		5		2		
	RSS M5	M5X0.5		5		2.5		

Shim

Shape	Description	Dimensions (mm)					
		a	b	c	d	e	t
	CSK 1604R/L	9.3	14.7	55°	3.4		4.76
	CSS 32	8.15		90°	2.5	11°	3.18
	CSS 42	11.2			2.5		3.18
	CST 32	8.15	11.8	60°	2.5	11°	3.18
	CST 42	10.7	15.6		3.4		3.18
	CST 43	10.7	15.6		3.4		4.76
	S 3	9.525	13.08	60°	5.4		4.76
	S 31						3.18
	WST 33	8.63	11.95		5.2		4.76
	WST 43	11.8	16.7		6.2		4.76
	S 45	12.7	23.5	55°	7.7		4.76
	MSW 32	8.7	10.7	80°	5.4		3.18
	MSW 43	12.7	15.5		7.7		4.76
	LSC 32	8.5	12.33	80°	5		3.18
	LSC 42	11.6	16.93		6.6		
	LSC 53	14.8	21.91		8.2		
	LSC 63	17.9	25.85		9.75		4.76
	LSC 83	24.4	36.63		12.75		
	LSC 84	24.4	36.63		12.75		6.35
	LSC 85	24.4	36.63		12.75		7.94
	LSC 64D	19.05	26.85		9.75		6.35
	LSC 84D	25.4	36.73		12.75		6.35
	LSC 85D	25.4	36.73		12.75		7.94
	LSD 32	8.4	17	55°	4.9		3.18
	LSD 42	11.59	28.06		6.6		
	LSD 43	11.59	28.06		6.6		4.76
	SSD 32	8.4	17		5.4		3.18
	LSR 1203	9.8			4.9		3.18
	LSR 1604	13.5			6.6		4.76
	LSR 2004	17.2			8.2		4.76
	LSR 2506	22			9.7		6.35
	LSR 3206	28			12.7		6.35
	LSR 32	8.5			4.9		3.18
	LSR 42	11.6			6.6		3.18
	LSR 53	14.6			8.2		4.76





Shim

Shape	Description	Dimensions (mm)						
		a	b	c	d	e	t	
	LSS 32	8.5		90°	5		3.18	
	LSS 42	11.75			6.6			
	LSS 53	14.8			8.2			
	LSS 63	17.9			9.75		4.76	
	LSS 84	24.4			12.75			
	LSS 85	24.4			12.75		6.35	
	LSS 64D	19.05			9.75		7.94	
	LSS 84D	25.4			12.75		6.35	
	LSS 85D	25.4			12.75		6.35	
	LSS 104	31.75			12.75		7.94	
	SSS 32	8.4			12.75		6.35	
	SSS 43N	11.2			5.4		3.18	
	LST 31.8	8.49	11.94		7.5		4.76	
	LST 32	8.63	11.95		5		2.7	
	LST 42	11.7	16.75	60°	4.9		3.18	
	LST 53	14.58	21.47		6.6		3.18	
	LST 63	17.85	26.18		8.2		4.76	
	SST 32	8.4	11.8		9.7			
	LST 32	8.63	11.95		5.4		3.18	
	LST 42	11.7	16.75		5.4		3.18	
	SSV 32	8.3	26.2	35°	5.4		3.18	
	IVSN 324	9.2	27.8		5.4		3.18	
	MSV 2.522	7.9	22.45		5.4		3.18	
	SSVN 2.522				5.4			
	TSC 42	12.7	17.99	80°	4.5		3.18	
	TSC 43		17.99		4.5		4.76	
	TSC 44		17.99		4.5		6.35	
	TSC 54	15.78	22.76		5.5		6.35	
	TSD 42	12.7	24.71	55°	4.5		3.18	
	TSD 43				4.5		4.76	
	TSD 44				4.5		6.35	
	TSH 42	12.7	14.05	60°	4.5		3.18	
	TSH 43	12.7	14.05		4.5		4.76	
	TSH 44	12.7	14.17		4.5		6.35	
	TSH 64	19.05	21.25		5.5			
	TSS 42	12.7		90°	4.5		3.18	
	TSS 43	12.7			4.5		4.76	
	TSS 44	12.7			4.5		6.35	
	TSS 54	15.78			5.5			
	TST 33	9.525	13.09	60°	4		4.76	
	TST 43	12.7	17.45		4.5			
	TSW 44	12.7	15.23	80°	4.5		6.35	






Shim

Shape	Description	Dimensions (mm)					
		a	b	c	d	e	t
	TSV 33	9.525	27	35°	4		4.76
	S 40	12.7					
	S 50	15.875		90°	7.7		4.76
	S 48	12.7	17.82	80°	7.7		4.76
	E 43	12.7	19.33	75°	7.7		4.76
	CBRS 06	5.6			2.5		4.5
	CBRS 09	8.8			3		6
	CBRS 12	11					6.5
	CERS 06	5.6			2.5		4.7
	CERS 09	8			3		6
	CERS 12	11					7
	PSW 32	8.7	10.7		4.5		
	PSW 42	11.7	14.4		5.5		3.18
	LSC 54-NX	15.875	23.25	80°	8.2		5.78
	LSC 53-NX	15.875	23.25	80°	8.2		4.19
	LSC 53-NXS	14.55	21.30	80°	8.2		4.19
	LSS 54-NX	15.875	21.02	90°	8.1		5.78
	LSS 53-NX	15.875	21.02	90°	8.1		4.19
	LSS 53-NXS	14.55	19.58	90°	8.2		4.19
	LSB 53R/L	14.9	17	R15	8.15		5
	LN 5025-T6.35	49.9	25.3	90°	12.7	25	6.35
	LN 4025-T6.35-R/L	40	25.4	80°	12.7	16	6.35





Lever

Shape	Description	Dimensions (mm)				
		a	b	c	d	h
	LCL 3	10.2	3.7	4.4	3.6	12.2
	LCL 4	13.2	4.8	6	4.8	13.2
	LCL 4A	16				14.6
	LCL 5	19	6	7.6	6	17.5
	LCL 6	20.5	7.4	9.2	7.5	21
	LCL 8	25.4	8.6	12.2	8.7	25.4
	BLCL 2	7.5	2.2	3	2.6	7.8
	BLCL 3	9.9	3	3.8	3.7	11
	LCL 2B	7.7	2.7	3.6	2.1	6.5
	LCL 3B	10	3.2	4.6	3.6	8
	LCL 3BH					9.6
	LCL 4B	13.6	4.8	6	4.8	10.4
	LCL 10C	10.8	3.4	4.6	3	11.6
	LCL 12C	13	3.8	4.6	3.5	13.2
	LCL 16C	18.3	4.7	6.2	4.5	18
	LCL 20C	20.4	6	7.6	5.6	18.8
	LCL 25C	24.2	7.5	9.4	7.5	24
	LCL 32C	30	8.6	12.5	8	27
	LCL 25CH	24.2	7.5	9.4	7.5	24
	LCL 32CH	30	8.6	12.5	8	27
	LCL 16-NX	19	5	7.6	5	19.7
	LCL 25-NX	25.4	7.5	12.2	7.5	26.5
	LCL 32-NX	30	8.6	12.5	8	28.2

Clamp

Shape	Description	Dimensions (mm)					
		a	b	c	d	e	h
	CL 1.25	9.5	2	5.4	3.4	5.2	4.5
	CL 2	14	2	7.8	5.2	8.7	7
	CL 3	16.5	2	9	6.2	10	9
	CL 4	21.5	3.08	11	8	13.4	11.6
	CL 2C	13.2	1.8		4.5	7.7	6.8
	CL 3C	17	2.2		5.5	9.3	9.3
	CLM 12	22.35	6.3	10.9	M8x1.0	16.9	16.8
	CLM 20	18.5	5.6	9.5	M6X1.0	13.75	9.65
	CLM 30	25.4	6.3	10.9	M8x1.0	19.95	16.8
	DLM 3	21.2	1.5	11	4.2	7.24	12.5
	DLM 3V	33.4	2	14	6.2	11.66	16.1
	DLM 4	25.8	2	14.5	5.4	7.4	13.5
	DLM 5	30	1.9	17	6.2	8.1	17
	DLM 6	33	2	18	6.2	8.5	19
	BCL 6	21	6.36	10	6.6	13.7	12
	BCL 6-20A	21	5	10	6.6	13.7	12

Clamp

Shape	Description	Dimensions (mm)					
		a	b	c	d	e	h
	3127 C	17.45	5.6	11.1	5.5	11.1	6.35
	CCL 4	29.5	2	14	6.8	9.7	18.5
	CL 16KR CL 16KL	25.6	23.4	12.2	7.8	10.6	13.2
	WC 33 WC 43	16.4	18	4.6	24	6.4	8.7

Shim Pin

Shape	Description	Dimensions (mm)					
		a	b	c	d	h	t
	CSP 3	9.8	0.9	2.4	3.5	2.5	0.3
	CSP 16K	11.5	1	3.6	5.6	4	0.5
	LSP 3	6.9	0.9	4.9		3.2	0.3
	LSP 3A	5.3		6.6		4.3	0.4
	LSP 4	5.8	1	8.2		5.4	0.5
	LSP 5	8.8		9.7		6	0.6
	LSP 6	11	2	13		9	0.7
	LSP 8	12		6.6		4.3	0.4
	LSP 16C	7.7	0.7				




Shim Pin Punch

Shape	Description	Dimensions (mm)						
		a	b	c	d	e	f	h
	SPP 5-6	12.1	6.6	18	14	8.1	20	70
	SPP 8	17	9.3					73




Lock Pin

Shape	Description	Dimensions (mm)						
		a	b	c	d	e	f	m
	MLP 3	14.5	4.7	M4 X 0.7	4.8	3.7	6.3	2
	MLP 4	21.21	5.16	M6 X 1.0	7.37	5.03	8.71	2.5
	MLP 4S	13.7	5		0		7	
	MLP 4-06	18.5	6.7		7.4	5	8.7	
	KP 48S	9.5	6.2	4	5	2.6		


Snap Ring

Shape	Description	Dimensions (mm)				
		a	b	c	d	t
	CSR 1.25	3	2.78	4		0.3
	CSR 2	4.7	7	6.5		0.4
	CSR 2C	4.3	3	5.6		0.3
	LSR 2B	3.8	3.3	2	3	
	LSR 3B	4.3	3.4	3	3.8	
	LSR 4B	5.9	4.9	4.3	4.8	0.1
	BLSR 2	3	2.5	1.5	2	
	BLSR 3	3.9	3.3	1.8	2.2	
	CSR 4	8.4	8	10		0.8
	WSR 4	7.5	5.8	6.3		0.7


Wrench

Shape	Description	Dimensions (mm)				
		a	b	c	d	t
	L-W 1.5	45	14			1.5
	L-W 2	50	16			2
	L-W 2.5	56	18			2.5
	L-W 3	63	20			3
	L-W 4	70	25			4
	L-W 5	80	28			5
	L-W 6	90	32			6
	L-W 8	100	36			8
	L-W 10	112	40			10
	L-W 12	125	45			12
	L-W 14	140	56			14
	L-W 17	160	63			17
	L-W 19	180	70			19
	T 5					T 5
	T 6	34	15	15		T 6
	T 7					T 7
	T 8	39	19	19		T 8
	T 9	42				T 9
	T 10	22	14		T 10	
	T 15	45	27			T 15
	T 20	49		30		T 20
	T 25	53	35	18		T 25
	L-W 1.5F	35	15	15	13	1.5
	L-W 2F	38	15	15	13	2

Spring

Shape	Description	Dimensions (mm)		
		a	b	t
	DSP 3	8	5.6	0.6
	DSP 4	13	7	0.65
	DSP 5		9	0.75
	KSP 40	7.5	4	0.45
	KSP 48	13.5		
	KSP 90	12.7	9	0.9

Coolant Nozzle

Shape	Description	Dimensions (mm)			
		a	b	c	d
	NZ 62	4.5	4	2.5	6
	NZ 83	6	5.5	3.5	8
	NZ 104	7		4	10
	NZ 125	8	7.5	5	12
	NZ 146	10	9	6	14

Cause	
Crater Wear	 <ul style="list-style-type: none"> Excessive cutting speed or feed rate (alloy steel and over 0.3% carbon steel) Workpiece material contains high hardness chemical elements (tool steel, die steel)
Flank Wear	 <ul style="list-style-type: none"> Excessive cutting speed (alloy steel and over 0.3% carbon steel) Workpiece material contains high hardness chemical elements (tool steel, die steel) Increase cutting speed if abnormal flank wear is caused by a very slow cutting speed
Deformation	 <ul style="list-style-type: none"> Excessive cutting speed or feed rate
Chipping	 <ul style="list-style-type: none"> Excessive feed rate Interrupted cutting
Notching	 <ul style="list-style-type: none"> Machining scaled part From machining work hardened materials
Built-Up-Edge	 <ul style="list-style-type: none"> Slow cutting speed Sticky materials
Mechanical Fracture	 <ul style="list-style-type: none"> Excessive feed rates when interrupted cutting
Thermal Cracking	 <ul style="list-style-type: none"> Repeated thermal shock (interrupted cutting)

T-TURN Insert Failure Trouble Shooting

Solution

- Reduce cutting speed or feed rate or use more wear resistant grade
 - Use coolant
 - Use more positive rake geometry
-
- Reduce cutting speed or feed rate or use more wear resistant grade
 - Use coolant

- Reduce cutting speed or feed rate or use more wear resistant grade
 - Use coolant
 - Use more positive rake geometry
-
- Reduce cutting speed or feed rate or use more wear resistant grade
 - Use coolant

- Reduce cutting speed or feed rate or use more wear resistant grade
- Use coolant
- Use stronger insert geometry

- Reduce feed rate
- Use tougher grade
- Use stronger insert geometry
- Remove coolant completely or apply coolant correctly

- Use tougher grade
- Use stronger insert geometry
- Increase lead angle
- Use tougher grade
- Use more positive rake geometry
- Increase lead angle

- Increase cutting speed
 - Use more positive rake geometry
-
- Use more positive rake geometry
 - Use tougher grade

- Use tougher grade
- Use stronger insert geometry
- Reduce feed rate
- Remove coolant completely or apply coolant correctly
- Increase cutting speed

- Use tougher grade
- Use stronger insert geometry
- Reduce feed rate
- Remove coolant completely or apply coolant correctly

Change Grade

Harder

PV3010 > CT3000

TT1300 > TT7310 > TT8115 > TT9215 > TT8125 > TT5080 > TT5100 > TT9225 > TT8135 > TT7100 > TT9235 > TT9080 > TT8020

Change Chipbreaker

Less B.U.E*
Less Heat

SF													
FA	FG	ML	EM	MP	ET	PC	MT	WT	MC	MG-	RT	RH	HD
												HB	RX
													HT

Chip Control

Tight

Open

FC													HD
SF													HT
FA	FG	MC	PC	VF	ML	MP	MT	MG-	ET	RT	RH	HY	
												HB	RX

*B.U.E: Built-Up-Edge



The Best Solution for Cast Iron Machining

Satisfaction guaranteed with
TaeguTec's T-CAST turning grades
for cast iron machining

Ceramic

AW20, AB30, AS500, SC10, AS10

High Productivity

CBN

TB650, KB90A, TB730

Ultra High Cutting Speed and
High Surface Finish, Longer Tool Life

Cermet and PVD Coated

CT3000, PV3010

Improved Surface Finish

T-CAST

Grades

General Machining

CVD Carbide Coated

TT1300, TT7310



Grade Selection by Workpiece Material

- Gray cast iron (180 - 220HBN)
- Ductile cast iron (200 - 240HBN)

Workpiece condition	Grades											
	TB650	KB90A	TB730	AW20	AB30	AS500	SC10	AS10	PV3010	CT3000	TT1300	TT7310
Scale and severe interruption	●	●	●			●		● ●			●	● ●
Scale and light interruption	●	●	●		● ●	● ●	● ●	● ●			● ●	● ●
No scale, continuous cut	●	●	●	●	● ●	● ●	●	●	● ●	● ●	● ●	●

Recommended Cutting Parameters

Materials	Grades											
	TB650	KB90A	TB730	AW20	AB30	AS500	SC10	AS10	PV3010	CT3000	TT1300	TT7310
	Cutting speed (m/min), Feed rate (mm/rev)											
Gray cast iron (180 - 220HBN)		800 - 1200 0.1 - 0.5	800 - 1200 0.1 - 0.3	400 - 1000 0.07 - 0.2	300 - 800 0.1 - 0.25	400 - 1000 0.2 - 0.6	300 - 1000 0.2 - 0.6	300 - 800 0.2 - 0.6	100 - 350 0.1 - 0.25	100 - 300 0.1 - 0.25	150 - 450 0.1 - 0.7	100 - 300 0.1 - 0.7
Ductile cast iron (200 - 240HBN)	200 - 500 0.05 - 0.2				250 - 500 0.05 - 0.2	200 - 600 0.1 - 0.5	250 - 600 0.2 - 0.6	250 - 500 0.2 - 0.6	100 - 300 0.1 - 0.25	100 - 250 0.1 - 0.25	120 - 350 0.1 - 0.5	100 - 250 0.1 - 0.5


Chipbreaker and Grade Selection by Workpiece Material

- Gray cast iron (180 - 220HBN)

Workpiece condition	Depth of cut	Chipbreaker/Grade					
		Recommended cutting conditions (V,f)					
Roughing (Scale & severe interruption)	4.0 - 6.0	RT/TT1300 300, 0.4	RT/TT7310 240, 0.4				
	6.0 -	RT/TT1300 270, 0.4	RT/TT7310 220, 0.4				
Medium (Scale & light interruption)	1.0 - 2.5	- NMN/KB90A 760, 0.3	- NMN/KB90A 760, 0.3	- NGA/AS500 540, 0.35	MT/TT1300 360, 0.35	RT/TT1300 320, 0.4	
	2.5 - 4.0	- NMN/KB90A 720, 0.35	- NGA/AS10 540, 0.35	RT/TT1300 300, 0.4			
Finishing (No scale & continuous cutting)	- 1.0	- NMN/KB90A 800, 0.2	- NGA/AW20 800, 0.2	NGA/AB30 700, 0.2	NGA/AS500 600, 0.25	MT/TT1300 400, 0.25	

- Ductile cast iron (200 - 240HBN)

Workpiece condition	Depth of cut	Chipbreaker/Grade					
		Recommended cutting conditions (V,f)					
Roughing (Scale & severe interruption)	4.0 - 6.0	RT/TT7310 225, 0.4					
	6.0 -	RT/TT7310 210, 0.4					
Medium (Scale & light interruption)	1.0 - 2.5	- NMA/TB650 500, 0.2	- NGA/AB30 470, 0.2	MT/TT1300 305, 0.3	RT/TT1300 270, 0.35		
	2.5 - 4.0	- NGA/AS10 440, 0.3	MT/TT7310 260, 0.35	RT/TT7310 235, 0.35			
Finishing (No scale & continuous cutting)	- 1.0	- NMA/TB650 550, 0.2	- NGA/AB30 520, 0.2	MT/TT1300 320, 0.2	MT/PV3010 320, 0.2	MT/CT3000 290, 0.2	



Recommended Cutting Parameters

		Insert style		N : Negative inserts		P : Positive inserts									
		Application		F : Finishing		M : Medium		R : Roughing							
		Depth of cut (mm)		Workpiece, stability and machine condition											
-Best: no scale, no interruption, good rigidity -Normal: a little scale, a little interruption, good rigidity -Poor: heavy scale, severe interruptions, poor rigidity															
				0.15% Carbon Steel (150 ≈ BHN)				0.45% Carbon Steel (180 - 200BHN)							
N	F	- 1.0	Best	1	PV3010	FC	475	0.12	PV3010	FG	355	0.15			
				2	CT3000	FC	430	0.12	TT8115	FG	340	0.15			
	M	1.0 - 2.5	Best	1	TT5100	ML	330	0.20	TT8115	MP	330	0.30			
				2	TT8125	ML	420	0.20	TT8125	MP	300	0.30			
		2.5 - 4.0	Normal	1	TT5100	MP	315	0.24	TT8115	PC	310	0.30			
				2	TT8125	MP	400	0.24	TT8125	PC	280	0.30			
	R	4.0 - 7.0	Poor	1	TT8020	MT	235	0.24	TT8135	RT	190	0.32			
				2											
		7.0 -	Normal	1	TT5100	PC	300	0.28	TT8115	PC	310	0.35			
				2	TT8125	PC	385	0.28	TT8125	PC	280	0.35			
			Poor	1	TT5100	MT	285	0.28	TT8125	PC	280	0.35			
				2	TT8125	MT	370	0.28	TT8125	MT	265	0.40			
P	F	- 1.0	Best	1	TT8020	MT	215	0.24	TT8135	RT	180	0.36			
				2											
	M	1.0 - 3.5	Normal	1	TT5100	RT	230	0.45	TT8125	RT	260	0.56			
				2	TT8125	RT	320	0.45	TT8115	RT	290	0.56			
		Poor	Normal	1	TT8020	RT	180	0.36	TT8135	RT	180	0.45			
				2											
			Poor	1	TT5100	RH	210	0.57	TT8125	RH	245	0.71			
				2											
	R	4.0 - 7.0	Normal	1	TT8020	RH	165	0.46	TT8135	RH	165	0.57			
				2											
		7.0 -	Normal	1	TT5100	RH	165	0.46	TT8135	RH	150	0.57			
				2											
			Poor	1	TT8020	MT	285	0.17	TT8115	MT	310	0.20			
				2	TT8125	MT	370	0.17	TT8125	MT	280	0.20			
				1	TT5100	MT	275	0.17	TT8125	MT	280	0.20			
				2	TT8125	MT	350	0.17	TT5100	MT	215	0.20			
	F	- 1.0	Best	1	TT8020	MT	220	0.17	TT8135	MT	190	0.20			
				2											
	M	1.0 - 3.5	Normal	1	TT5100	MT	285	0.17	TT8115	MT	310	0.20			
				2	TT8125	MT	370	0.17	TT8125	MT	280	0.20			
	R	4.0 - 7.0	Normal	1	TT5100	MT	275	0.17	TT8125	MT	280	0.20			
				2	TT8125	MT	350	0.17	TT5100	MT	215	0.20			
	P	4.0 - 7.0	Normal	1	TT8020	MT	220	0.17	TT8135	MT	190	0.20			
				2											

Recommended Cutting Parameters

		Insert style		N	Positive inserts												
		Application		F	Finishing	M	Medium	R	Roughing								
		Depth of cut (mm)		Workpiece, stability and machine condition													
		- Best: no scale, no interruption, good rigidity - Normal: a little scale, a little interruption, good rigidity - Poor: heavy scale, severe interruptions, poor rigidity															
		First and second choice grade, chipbreaker, cutting speed & feed rate in mm/rev															
		Workpiece Material															
		Low Carbon (0.13 - 0.18%) Alloy Steel (150 - 180BHN)				Cr-Mo Alloy Steel (200 - 220BHN)				Ni-Cr-Mo Alloy Steel (200 - 220BHN)							
N	M	F	- 1.0	Best	1	PV3010	FC	420	0.12	PV3010	FG	330	0.15	PV3010	FG	320	0.15
					2	CT3000	FC	380	0.12	TT8115	FG	315	0.15	TT8115	FG	305	0.15
		M	1.0 - 2.5	Best	1	TT5100	ML	295	0.20	TT8115	MP	305	0.30	TT8115	MP	295	0.30
					2	TT8125	ML	375	0.20	TT8125	MP	280	0.30	TT8125	MP	270	0.30
				Normal	1	TT5100	PC	285	0.24	TT8115	PC	290	0.30	TT8115	PC	280	0.30
					2	TT8125	PC	365	0.24	TT8125	MC	260	0.30	TT8125	PC	250	0.30
		R	2.5 - 4.0	Poor	1	TT8020	MT	205	0.24	TT8135	RT	180	0.32	TT8135	RT	170	0.32
					2												
				Normal	1	TT5100	PC	265	0.28	TT8115	PC	290	0.35	TT8115	PC	280	0.35
					2	TT8125	PC	340	0.28	TT8125	PC	260	0.35	TT8125	PC	250	0.35
					1	TT5100	MT	255	0.28	TT8125	MT	260	0.35	TT8125	MT	250	0.35
		P	4.0 - 7.0	Poor	2	TT8125	MT	315	0.28	TT8125	MG-	245	0.40	TT8125	MG-	240	0.40
					1	TT8020	MT	190	0.24	TT8135	RT	180	0.36	TT8135	RT	170	0.36
				Normal	2												
					1	TT5100	RT	205	0.45	TT8125	RT	240	0.56	TT8125	RT	235	0.56
		M	7.0 -	Poor	2	TT8125	RT	250	0.45	TT8115	RT	270	0.56	TT8115	RT	260	0.56
					1	TT8020	RT	160	0.36	TT8135	RT	160	0.45	TT8135	RT	160	0.45
				Normal	2												
					1	TT5100	RH	185	0.57	TT8125	RH	225	0.71	TT8125	RH	220	0.71
					2						RT	225	0.64	TT8125	RT	220	0.64
		F	1.0 - 3.5	Poor	1	TT8020	RH	150	0.46	TT7100	RH	140	0.57	TT8135	RH	150	0.57
					2												
				Normal	1	PV3010	FG	420	0.12	PV3010	FG	330	0.15	PV3010	FG	320	0.15
					2	CT3000	FG	380	0.12	CT3000	FG	295	0.15	CT3000	FG	285	0.15
					1	TT5100	MT	265	0.17	TT8115	MT	285	0.20	TT8115	MT	275	0.20
		P	1.0 - 3.5	Best	2	TT8125	MT	345	0.17	TT8125	MT	255	0.20	TT8125	MT	250	0.20
					1	TT5100	MT	255	0.17	TT8125	MT	255	0.20	TT8125	MT	250	0.20
				Normal	2	TT8125	MT	330	0.17	TT5100	MT	195	0.20	TT5100	MT	190	0.20
					1	TT8020	MT	205	0.17	TT8135	MT	180	0.20	TT8135	MT	170	0.20
				2													

Recommended Cutting Parameters

		Insert style		N : Negative inserts		P : Positive inserts									
		Application		F : Finishing		M : Medium		R : Roughing							
		Depth of cut (mm)		Workpiece, stability and machine condition											
-Best: no scale, no interruption, good rigidity -Normal: a little scale, a little interruption, good rigidity -Poor: heavy scale, severe interruptions, poor rigidity															
				First and second choice grade, chipbreaker, cutting speed & feed rate in mm/rev				Workpiece Material							
				Bearing Steel (200 - 220BHN)				Carbon Tool Steel (200 - 220BHN)							
N	F	- 1.0	Best	1	PV3010	FG	330	0.15	PV3010	FG	330	0.15			
	M	1.0 - 2.5	Best	1	TT8115	MP	305	0.30	TT8115	MP	305	0.30			
				2	TT8125	MP	280	0.30	TT8125	MP	280	0.30			
			Normal	1	TT8115	PC	290	0.30	TT8115	PC	290	0.30			
				2	TT8125	PC	260	0.30	TT8125	PC	260	0.30			
			Poor	1	TT8135	RT	180	0.32	TT8135	RT	180	0.32			
				2											
	M	2.5 - 4.0	Best	1	TT8115	PC	290	0.35	TT8115	MT	290	0.35			
				2	TT8125	PC	260	0.35	TT8125	MT	260	0.35			
			Normal	1	TT8125	MT	260	0.35	TT8125	MT	260	0.35			
				2	TT8125	MG-	245	0.40	TT8125	MG-	245	0.40			
			Poor	1	TT8135	RT	180	0.36	TT8135	RT	180	0.36			
				2											
P	R	4.0 - 7.0	Normal	1	TT8125	RT	240	0.56	TT8125	RT	240	0.56			
				2	TT8115	RT	270	0.56	TT8115	RT	270	0.56			
			Poor	1	TT8135	RT	160	0.45	TT8135	RT	160	0.45			
				2											
			Normal	1	TT8125	RH	225	0.71	TT8125	RH	225	0.71			
				2											
			Poor	1	TT8135	RH	150	0.57	TT8135	RH	150	0.57			
				2											
	F	- 1.0	Best	1	PV3010	FG	330	0.15	PV3010	FG	330	0.15			
	M	1.0 - 3.5		2	CT3000	FG	295	0.15	CT3000	FG	295	0.15			
		Best	1	TT8115	MT	285	0.20	TT8115	MT	285	0.20				
			2	TT8125	MT	255	0.20	TT8125	MT	255	0.20				
		Normal	1	TT8125	MT	255	0.20	TT8125	MT	255	0.20				
			2	TT5100	MT	195	0.20	TT5100	MT	195	0.20				
		Poor	1	TT8135	MT	180	0.20	TT8135	MT	180	0.20				
			2												

Recommended Cutting Parameters

Diagram illustrating the selection process:

- Insert style: **N** : Negative inserts **P** : Positive inserts
- Application: **F** : Finishing **M** : Medium **R** : Roughing
- Depth of cut (mm)
- Workpiece, stability and machine condition
 - Best:** no scale, no interruption, good rigidity
 - Normal:** a little scale, a little interruption, good rigidity
 - Poor:** heavy scale, severe interruptions, poor rigidity
- First and second choice grade, chipbreaker, cutting speed & feed rate in mm/rev

Workpiece Material																
	High Speed Steel (220 - 260BHN)				Cold Working Die Steel (240 - 260BHN)				Hard Material (40 ≤ HRC)							
N	F	- 1.0	Best	1	PV3010	FG	230	0.10	TT8115	FG	240	0.14	AB2010		120	0.10
				2	CT3000	FG	210	0.10	TT8125	FG	210	0.14	TB610		120	0.10
	M	1.0 - 2.5	Best	1	TT5080	ML	180	0.15	TT8115	MP	230	0.28	AB2010		120	0.15
				2	TT5100	ML	160	0.15	TT8125	MP	210	0.28	TB670		120	0.15
			Normal	1	TT5080	MP	170	0.20	TT8115	PC	215	0.28	AB20		100	0.15
				2	TT5100	MP	150	0.20	TT8125	PC	195	0.28	TB730		100	0.15
	R	2.5 - 4.0	Poor	1	TT5100	MT	135	0.25	TT8135	RT	130	0.29	AB30		80	0.10
				2									KB90A		80	0.10
			Best	1	TT5080	MP	170	0.20	TT8115	PC	215	0.32	AB20		100	0.15
				2	TT5100	MP	145	0.20	TT8125	PC	195	0.32	KB90A		100	0.15
			Normal	1	TT5080	MT	160	0.25	TT8125	MT	175	0.32	AB20		100	0.15
				2	TT5100	MT	135	0.25	TT8125	MG-	185	0.37	KB90A		100	0.15
			Poor	1	TT8135	RT	140	0.25	TT8135	RT	130	0.33	AB30		80	0.10
				2									KB90A		80	0.10
P	F	- 1.0	Best	1	PV3010	FG	230	0.10	PV3010	FG	250	0.14	TB670		150	0.10
				2	CT3000	FG	210	0.10	CT3000	FG	225	0.14	AB20		120	0.10
	M	1.0 - 3.5	Best	1	TT5080	MT	165	0.15	TT8115	MT	215	0.18	TB670		150	0.12
				2	TT5100	MT	145	0.15	TT8125	MT	195	0.18	AB20		120	0.12
			Normal	1	TT5080	MT	160	0.15	TT8125	MT	215	0.18	AB20		100	0.12
				2	TT5100	MT	140	0.15	TT5100	MT	195	0.18	TB670		100	0.12
			Poor	1	TT8135	MT	135	0.15	TT8135	MT	160	0.18	AB30		80	0.08
				2									KB90A		80	0.08

Recommended Cutting Parameters

Diagram illustrating the selection process for Recommended Cutting Parameters:

- Insert style:** N : Negative inserts, P : Positive inserts
- Application:** F : Finishing, M : Medium, R : Roughing
- Depth of cut (mm):** -1.0, 1.0 - 2.5, 2.5 - 4.0, 4.0 - 7.0, 7.0 -
- Workpiece, stability and machine condition:**
 - Best:** no scale, no interruption, good rigidity
 - Normal:** a little scale, a little interruption, good rigidity
 - Poor:** heavy scale, severe interruptions, poor rigidity
- First and second choice grade, chipbreaker, cutting speed & feed rate in mm/rev:**

Workpiece Material									
Martensitic/Ferritic Stainless Steel (180 - 200BHN)					Austenitic Stainless Steel (180 - 200BHN)				
N	F	- 1.0	Best	1	PV3010	SF	330	0.12	PV3010
				2	TT9215	EA	260	0.12	TT9215
	M	1.0 - 2.5	Best	1	TT9215	EM	230	0.20	TT9215
				2					
		2.5 - 4.0	Normal	1	TT9225	EM	210	0.24	TT9225
				2	TT9235	MP	180	0.24	TT9235
			Poor	1	TT9235	MT	170	0.24	TT9235
				2					
	R	4.0 - 7.0	Best	1	TT9225	EM	200	0.24	TT9225
				2					
		7.0 -	Normal	1	TT9225	MP	190	0.28	TT9225
				2	TT9235	MT	165	0.28	TT9235
			Poor	1	TT9235	MT	165	0.24	TT9235
				2					
P	F	- 1.0	Best	1	PV3010	FG	330	0.12	PV3010
				2	TT9215	FG	270	0.12	TT9215
	M	1.0 - 3.5	Best	1	TT9225	PC	195	0.17	TT9225
				2					
		Normal	Normal	1	TT9225	PC	185	0.17	TT9225
				2	TT9235	MT	160	0.17	TT9235
		Poor	Poor	1	TT9235	MT	150	0.17	TT9235
				2					

Recommended Cutting Parameters

		Insert style		N	Positive inserts							
		Application		F	Finishing	M	Medium	R	Roughing			
		Depth of cut (mm)										
Workpiece, stability and machine condition												
-Best: no scale, no interruption, good rigidity -Normal: a little scale, a little interruption, good rigidity -Poor: heavy scale, severe interruptions, poor rigidity												
First and second choice grade, chipbreaker, cutting speed & feed rate in mm/rev												
Workpiece Material												
Ni Based Super Alloy Inconel 718 (300 - 350BHN)												
N	F	- 1.0	Best	1	TC430		250	0.15	TT5080	EA	100	0.15
				2	TT5080	EA	60	0.15				
	M	1.0 - 2.5	Best	1	TC430		250	0.15	TT5080	EM	90	0.20
				2	TT5080	EM	60	0.20				
			Normal	1	TT5080	MP	50	0.20	TT5080	MP	80	0.20
				2								
	R	2.5 - 4.0	Poor	1	TT8020	MT	35	0.20	TT8020	MT	50	0.20
				2								
			Best	1	TT5080	EM	50	0.20	TT5080	EM	80	0.20
				2								
			Normal	1	TT5080	MP	45	0.20	TT5080	MP	70	0.20
				2								
			Poor	1	TT8020	MT	30	0.20	TT8020	MT	45	0.20
				2								
P	F	- 1.0	Best	1	TT5080	FG	60	0.10	TT5080	FG	100	0.10
				2								
	M	1.0 - 3.5	Best	1	TT5080	PC	50	0.15	TT5080	PC	80	0.15
				2								
			Normal	1	TT5080	PC	45	0.15	TT5080	PC	75	0.15
				2								
	R	7.0 -	Poor	1	TT8020	MT	30	0.15	TT8020	MT	50	0.15
				2								

Recommended Cutting Parameters

		Insert style		N : Negative inserts		P : Positive inserts																																																																																																																																																																																																																																																																																																																									
		Application		F : Finishing		M : Medium																																																																																																																																																																																																																																																																																																																									
		Depth of cut (mm)				R : Roughing																																																																																																																																																																																																																																																																																																																									
		Workpiece, stability and machine condition																																																																																																																																																																																																																																																																																																																													
<p>-Best: no scale, no interruption, good rigidity -Normal: a little scale, a little interruption, good rigidity -Poor: heavy scale, severe interruptions, poor rigidity</p>																																																																																																																																																																																																																																																																																																																															
<table border="1"> <thead> <tr> <th colspan="4">First and second choice grade, chipbreaker, cutting speed & feed rate in mm/rev</th> <th colspan="4">Workpiece Material</th> </tr> <tr> <th colspan="4"></th> <th colspan="2">Gray Cast Iron (180 - 220BHN)</th> <th colspan="2">Ductile Cast Iron (200 - 240BHN)</th> </tr> </thead> <tbody> <tr> <td rowspan="10">N</td> <td rowspan="2">F</td> <td rowspan="2">- 1.0</td> <td rowspan="2">Best</td> <td>1</td> <td>AS500</td> <td></td> <td>600</td> <td>0.25</td> <td>AS500</td> <td></td> <td>440</td> <td>0.20</td> </tr> <tr> <td>2</td> <td>TT1300</td> <td>MT</td> <td>400</td> <td>0.25</td> <td>TT1300</td> <td>MT</td> <td>320</td> <td>0.20</td> </tr> <tr> <td rowspan="10">M</td> <td rowspan="4">1.0 - 2.5</td> <td rowspan="2">Best</td> <td>1</td> <td>AS500</td> <td></td> <td>570</td> <td>0.35</td> <td>AS500</td> <td></td> <td>420</td> <td>0.30</td> </tr> <tr> <td>2</td> <td>TT1300</td> <td>MT</td> <td>380</td> <td>0.35</td> <td>TT1300</td> <td>MT</td> <td>305</td> <td>0.30</td> </tr> <tr> <td rowspan="2">Normal</td> <td>1</td> <td>AS10</td> <td></td> <td>540</td> <td>0.35</td> <td>AS10</td> <td></td> <td>400</td> <td>0.30</td> </tr> <tr> <td>2</td> <td>TT1300</td> <td>MT</td> <td>360</td> <td>0.35</td> <td>TT1300</td> <td>MT</td> <td>290</td> <td>0.30</td> </tr> <tr> <td rowspan="4">Poor</td> <td>1</td> <td>TT1300</td> <td>RT</td> <td>320</td> <td>0.40</td> <td>TT7310</td> <td>RT</td> <td>250</td> <td>0.35</td> </tr> <tr> <td>2</td> <td>TT7310</td> <td>RT</td> <td>270</td> <td>0.40</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="4">2.5 - 4.0</td> <td>1</td> <td>AS10</td> <td></td> <td>540</td> <td>0.35</td> <td>AS10</td> <td></td> <td>400</td> <td>0.30</td> </tr> <tr> <td>2</td> <td>TT1300</td> <td>MT</td> <td>360</td> <td>0.35</td> <td>TT1300</td> <td>MT</td> <td>275</td> <td>0.30</td> </tr> <tr> <td rowspan="2">Normal</td> <td>1</td> <td>AS10</td> <td></td> <td>510</td> <td>0.35</td> <td>AS10</td> <td></td> <td>380</td> <td>0.30</td> </tr> <tr> <td>2</td> <td>TT1300</td> <td>RT</td> <td>320</td> <td>0.40</td> <td>TT7310</td> <td>MT</td> <td>260</td> <td>0.35</td> </tr> <tr> <td rowspan="4">Poor</td> <td>1</td> <td>TT1300</td> <td>RT</td> <td>300</td> <td>0.40</td> <td>TT7310</td> <td>RT</td> <td>235</td> <td>0.35</td> </tr> <tr> <td>2</td> <td>TT7310</td> <td>RT</td> <td>255</td> <td>0.40</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="4">4.0 - 7.0</td> <td>1</td> <td>TT1300</td> <td>RT</td> <td>300</td> <td>0.60</td> <td>TT7310</td> <td>RT</td> <td>240</td> <td>0.52</td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="2">Normal</td> <td>1</td> <td>TT7310</td> <td>RT</td> <td>240</td> <td>0.60</td> <td>TT7310</td> <td>RT</td> <td>225</td> <td>0.52</td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="4">R</td> <td rowspan="2">7.0 -</td> <td rowspan="2">Normal</td> <td>1</td> <td>TT1300</td> <td>RT</td> <td>270</td> <td>0.80</td> <td>TT7310</td> <td>RT</td> <td>210</td> <td>0.70</td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="2">Poor</td> <td>1</td> <td>TT7310</td> <td>RT</td> <td>220</td> <td>0.80</td> <td>TT7310</td> <td>RT</td> <td>200</td> <td>0.70</td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="8">P</td> <td rowspan="4">F</td> <td rowspan="2">- 1.0</td> <td rowspan="2">Best</td> <td>1</td> <td>TT1300</td> <td>MT</td> <td>400</td> <td>0.18</td> <td>TT1300</td> <td>MT</td> <td>320</td> <td>0.15</td> </tr> <tr> <td>2</td> <td>TB730</td> <td></td> <td>700</td> <td>0.15</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="4">M</td> <td rowspan="2">1.0 - 3.5</td> <td rowspan="2">Best</td> <td>1</td> <td>TT1300</td> <td>MT</td> <td>380</td> <td>0.25</td> <td>TT1300</td> <td>MT</td> <td>305</td> <td>0.20</td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td rowspan="2">Normal</td> <td>1</td> <td>TT1300</td> <td>MT</td> <td>360</td> <td>0.25</td> <td>TT1300</td> <td>MT</td> <td>290</td> <td>0.20</td> </tr> <tr> <td>2</td> <td>TT7310</td> <td>MT</td> <td>305</td> <td>0.25</td> <td>TT7310</td> <td>MT</td> <td>250</td> <td>0.20</td> </tr> <tr> <td rowspan="2">Poor</td> <td>1</td> <td>TT7310</td> <td>MT</td> <td>290</td> <td>0.25</td> <td>TT7310</td> <td>MT</td> <td>235</td> <td>0.20</td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>								First and second choice grade, chipbreaker, cutting speed & feed rate in mm/rev				Workpiece Material								Gray Cast Iron (180 - 220BHN)		Ductile Cast Iron (200 - 240BHN)		N	F	- 1.0	Best	1	AS500		600	0.25	AS500		440	0.20	2	TT1300	MT	400	0.25	TT1300	MT	320	0.20	M	1.0 - 2.5	Best	1	AS500		570	0.35	AS500		420	0.30	2	TT1300	MT	380	0.35	TT1300	MT	305	0.30	Normal	1	AS10		540	0.35	AS10		400	0.30	2	TT1300	MT	360	0.35	TT1300	MT	290	0.30	Poor	1	TT1300	RT	320	0.40	TT7310	RT	250	0.35	2	TT7310	RT	270	0.40					2.5 - 4.0	1	AS10		540	0.35	AS10		400	0.30	2	TT1300	MT	360	0.35	TT1300	MT	275	0.30	Normal	1	AS10		510	0.35	AS10		380	0.30	2	TT1300	RT	320	0.40	TT7310	MT	260	0.35	Poor	1	TT1300	RT	300	0.40	TT7310	RT	235	0.35	2	TT7310	RT	255	0.40					4.0 - 7.0	1	TT1300	RT	300	0.60	TT7310	RT	240	0.52	2									Normal	1	TT7310	RT	240	0.60	TT7310	RT	225	0.52	2									R	7.0 -	Normal	1	TT1300	RT	270	0.80	TT7310	RT	210	0.70	2									Poor	1	TT7310	RT	220	0.80	TT7310	RT	200	0.70	2									P	F	- 1.0	Best	1	TT1300	MT	400	0.18	TT1300	MT	320	0.15	2	TB730		700	0.15					M	1.0 - 3.5	Best	1	TT1300	MT	380	0.25	TT1300	MT	305	0.20	2								Normal	1	TT1300	MT	360	0.25	TT1300	MT	290	0.20	2	TT7310	MT	305	0.25	TT7310	MT	250	0.20	Poor	1	TT7310	MT	290	0.25	TT7310	MT	235	0.20	2								
First and second choice grade, chipbreaker, cutting speed & feed rate in mm/rev				Workpiece Material																																																																																																																																																																																																																																																																																																																											
				Gray Cast Iron (180 - 220BHN)		Ductile Cast Iron (200 - 240BHN)																																																																																																																																																																																																																																																																																																																									
N	F	- 1.0	Best	1	AS500		600	0.25	AS500		440	0.20																																																																																																																																																																																																																																																																																																																			
				2	TT1300	MT	400	0.25	TT1300	MT	320	0.20																																																																																																																																																																																																																																																																																																																			
	M	1.0 - 2.5	Best	1	AS500		570	0.35	AS500		420	0.30																																																																																																																																																																																																																																																																																																																			
				2	TT1300	MT	380	0.35	TT1300	MT	305	0.30																																																																																																																																																																																																																																																																																																																			
			Normal	1	AS10		540	0.35	AS10		400	0.30																																																																																																																																																																																																																																																																																																																			
				2	TT1300	MT	360	0.35	TT1300	MT	290	0.30																																																																																																																																																																																																																																																																																																																			
		Poor	1	TT1300	RT	320	0.40	TT7310	RT	250	0.35																																																																																																																																																																																																																																																																																																																				
			2	TT7310	RT	270	0.40																																																																																																																																																																																																																																																																																																																								
			2.5 - 4.0	1	AS10		540	0.35	AS10		400	0.30																																																																																																																																																																																																																																																																																																																			
				2	TT1300	MT	360	0.35	TT1300	MT	275	0.30																																																																																																																																																																																																																																																																																																																			
Normal		1		AS10		510	0.35	AS10		380	0.30																																																																																																																																																																																																																																																																																																																				
		2		TT1300	RT	320	0.40	TT7310	MT	260	0.35																																																																																																																																																																																																																																																																																																																				
Poor	1	TT1300	RT	300	0.40	TT7310	RT	235	0.35																																																																																																																																																																																																																																																																																																																						
	2	TT7310	RT	255	0.40																																																																																																																																																																																																																																																																																																																										
	4.0 - 7.0	1	TT1300	RT	300	0.60	TT7310	RT	240	0.52																																																																																																																																																																																																																																																																																																																					
		2																																																																																																																																																																																																																																																																																																																													
Normal		1	TT7310	RT	240	0.60	TT7310	RT	225	0.52																																																																																																																																																																																																																																																																																																																					
		2																																																																																																																																																																																																																																																																																																																													
R	7.0 -	Normal	1	TT1300	RT	270	0.80	TT7310	RT	210	0.70																																																																																																																																																																																																																																																																																																																				
			2																																																																																																																																																																																																																																																																																																																												
	Poor	1	TT7310	RT	220	0.80	TT7310	RT	200	0.70																																																																																																																																																																																																																																																																																																																					
		2																																																																																																																																																																																																																																																																																																																													
P	F	- 1.0	Best	1	TT1300	MT	400	0.18	TT1300	MT	320	0.15																																																																																																																																																																																																																																																																																																																			
				2	TB730		700	0.15																																																																																																																																																																																																																																																																																																																							
		M	1.0 - 3.5	Best	1	TT1300	MT	380	0.25	TT1300	MT	305	0.20																																																																																																																																																																																																																																																																																																																		
					2																																																																																																																																																																																																																																																																																																																										
	Normal		1	TT1300	MT	360	0.25	TT1300	MT	290	0.20																																																																																																																																																																																																																																																																																																																				
			2	TT7310	MT	305	0.25	TT7310	MT	250	0.20																																																																																																																																																																																																																																																																																																																				
	Poor	1	TT7310	MT	290	0.25	TT7310	MT	235	0.20																																																																																																																																																																																																																																																																																																																					
		2																																																																																																																																																																																																																																																																																																																													

Recommended Cutting Parameters

Diagram illustrating the selection process for Recommended Cutting Parameters:

- Insert style:** N : Negative inserts, P : Positive inserts
- Application:** F : Finishing, M : Medium, R : Roughing
- Depth of cut (mm):** - 1.0, 1.0 - 2.5, 2.5 - 4.0
- Workpiece, stability and machine condition:**
 - Best:** no scale, no interruption, good rigidity
 - Normal:** a little scale, a little interruption, good rigidity
 - Poor:** heavy scale, severe interruptions, poor rigidity
- First and second choice grade, chipbreaker, cutting speed & feed rate in mm/rev:**

Workpiece Material																
	F	- 1.0	Best	Low Si Aluminum Alloy (12.2% \geq Si)				High Si Aluminum Alloy (12.2% < Si)				Copper Alloy				
				1	KP300	-	1300	0.10	KP500	-	600	0.10	KP300	-	1100	0.10
N	M	1.0 - 2.5	Best	1	KP300	-	1300	0.15	KP500	-	600	0.15	KP300	-	1100	0.15
				2	K10	ML	500	0.15	K10	ML	150	0.15	TT5100	ML	500	0.15
			Normal	1	KP300	-	1300	0.15	KP500	-	600	0.15	KP300	-	1100	0.15
				2	K10	ML	500	0.35	K10	ML	150	0.30	TT5100	ML	400	0.25
			Poor	1	KP300	-	1000	0.15	KP500	-	600	0.15	KP300	-	900	0.15
				2	K10	ML	400	0.35	K10	ML	120	0.30	TT5100	MP	320	0.25
			Best	1	KP300	-	1300	0.15	KP500	-	600	0.15	KP300	-	1100	0.15
				2	K10	ML	500	0.35	K10	ML	150	0.30	TT5100	MP	400	0.30
			Normal	1	KP300	-	1300	0.15	KP500	-	600	0.15	KP300	-	1100	0.15
				2	K10	ML	500	0.35	K10	ML	150	0.30	TT5100	MP	400	0.30
			Poor	1	KP300	-	1000	0.15	KP500	-	600	0.15	KP300	-	900	0.15
				2	K10	ML	400	0.35	K10	ML	120	0.30	TT5100	MT	320	0.30
P	F	1.0 - 3.5	Best	1	KP300	-	1300	0.10	KP500	-	600	0.10	KP300	-	1100	0.10
				2	K10	FL	500	0.15	K10	FL	150	0.13	TT5100	FG	400	0.15
			Normal	1	KP300	-	1300	0.15	KP500	-	600	0.15	KP300	-	1100	0.15
				2	K10	FL	500	0.25	K10	FL	150	0.22	TT5100	FG	400	0.20
			Poor	1	KP300	-	1300	0.15	KP500	-	600	0.15	KP300	-	1100	0.15
				2	K10	FL	400	0.25	K10	FL	120	0.25	TT5100	FG	400	0.20
			Best	1	KP300	-	1000	0.15	KP500	-	500	0.15	KP300	-	900	0.15
				2	K10	FL	400	0.25	K10	FL	120	0.25	TT5100	MT	320	0.20



Description			TaeguTec	Sandvik	Kennametal	Seco	Walter	Valenite	Mitsubishi	Sumitomo	Kyocera	Tungaloy	Korloy	Iscar
Negative Insert	For Steel	Double sided	WS	WF, WL	FW	W-MF2	NF	W3	SW	LUW, SEW	WP	AFW	LW	
			WT	WMX, WM	MW	W-M3	NM	W6	MW	GUW	WQ	ASW	VW, HW	WG
			FA		FF	FF1		F2	FH	FL, FA	GP, DP	TF	HU	SF
			FG	QF	FP	FN	MF2	NF3		SH	SU	ZF	VG, HF, GF	NF
								NFT		SE	TSF	VF		
			FC	PF, LC				NS6		FY, SA	LU	CJ	VL, VB, HC	
			VF	K		95			ES	GX, HM		S		
			ML	GP-	GP-K, MS- MS GP		G-NMT, NS4 NS5, G1		FJ, SY	A3, AH	CB, 17	HA	12 PP	
			MP	QM	P	MF3	NM4	M2					HS, GS	TF VL
			MC	SM	MN	MR3	NM4						HC	
		Single sided	PC	PM		M3	NM6		MP, MV	GE, GU	PS	TM	VM	
			MT		MP RP			M3	MA	UX, UG	HS		HM, GM	GN
			MG-		UN	M4	MG-		MG-	UZ	MG-C	38 DM, MG- 33, 37	B20, B25	MG-
				PR HM	UM RN MG-	M5 MR7	NM5, NM7 NRT NM6, NM9	R3	MH, GJ	ME MU, MX	GT, PT PH, HT			
			RT						GH HAS, HDS		TH	HR, GR	NR	
			RX	PR	RM		NRF				PX			
			RH	QR MR	RP	R6, RR9 R5, R4, 37 RR6	NR6 NR5, NR8 NR7	R6	HZ	MP		TRS 57	GH	RP NM
			HT, HD HY, HZ	HR, 31	RH	R8, 56, 57 R7	NRR		HC5 HX, HBS HV, HDS, HXD	HF		65 TU	VT, HH VH, B40	
	Stainless Steel	Double sided	EA, SF	MF	FP	MF1	NF4	F5	FS	SU	MQ, GU		HA	
			EM	MM	UP	MF4	NM4		MS	EX	MU			
			ET	MR MM-MR SF, SGF	RP	MR6, MF5 MM-RR6	NR4	M5		GU	HU	SM	GS	TNM
			SU	MX-SM, 23, SM SR, SMR							HMM, SA			
	Cast Iron	Double sided	MT	KF, KM	FN				MA	UZ	MG-C	CF CM		
			MG-		RP		NM5		MG-		C		B25	
			RT	KR	UN				GH	GZ	ZS, GC	CH	GR	
Positive Insert	for Steel	WT	WM	MW	W-F2				MW				WG	
		FA	PF, UF	UF, 11, GM	FF1	PF4 PF5			FV	LU	GK, GP, DP	01, PF, PSF	HFP	38, PF
		SA							SMG	FP	CF, GF GQ, GR	JS		
		FG	UM	FP LF	F1	PS4 PS5	PM3 PM4		FK	SU			VF HMP, C05	SM 16, GT-
		PC		MP		PF2			SC, SK	SC, SK	HQ		PSS PS	
		MT	PR, UR	MF	F2	E47, MT-	PM5	MQ, MV MT-G	SF, MU		MT-	PM	C25	14, 17 19, MT-
		PMR-	PMR-	PMR-		PMR-		PMR-	UJ		GP, HQ G, PMR-			
		for Aluminum	FL	AL	HP	AL	PM2	IL	AZ	AG	AH	AL	AR	AF, AS

