

TYPE K-488F VHF RADIO INTERFERENCE^V INTENSITY METER FIELD

This meter measures directly radio interference and field intensity in VHF band, such as TV and FM broad casting bands, etc.

It combines high accuracy, simplicity of operation and portability.

Specifications

Frequency range:	25 - 300 MC 6 bands		
Measuring range:	Field intensity (direct-reading): 20 - 120 db (25 - 200 MC) ($1\mu\text{V/m} = 0\text{ db}$) 24 - 120 db (200 - 300 MC)		
Accuracy:	$\pm 2\text{ db}$		
IF characteristics:	Center freq. 1st IF 23 MC 2nd IF 4.5 MC Band width 80 KC $\pm 8\text{ KC}$ (-6 db) More than 40 db		
Image rejection:	Half wave length dipole antenna		
Antenna type:	Mean value: charge & discharge less than $2.5\mu\text{S}$		
Time constant of detector:	Quasi-peak value: charge $0.12\text{ mS} \pm 0.06\text{ mS}$ discharge $600\text{ mS} \pm 120\text{ mS}$		
Over load factor:	12 db		
Appendant circuits:	Recorder terminal: 5 mA 500 Ω - 1.2 K Ω available Detection output terminal		
Power source:	AC 100 or 220 V 95 VA DC 12 V 8A		
Accessory:	Antenna holder, elements & tripod	1 set	
	Connecting cables	1 set	
Dimensions & Weight:	Measuring unit		
18.23" x 10.75" x 10.83"	463 x 273 x 275 mm	23 Kg	50.715 lb.
6.02" x 9.17" x 11.02"	153 x 233 x 280 mm	8.5 Kg	18.7425 lb.
36.22" x 5.51" x 8.66"	920 x 140 x 220 mm	10 Kg	22.05 lb.
6.3" x 6.3" x 43.31"	Antenna tripod 1609 x 1100 mm	7 Kg	15.435 lb.

KYORITSU ELECTRICAL WORKS, LTD.

Head Office & Fac: No.36-13 Minami 5-chome Koenji Suginami-ku Tokyo Japan

TEL: Tokyo (314) 2331 REP

Business Office: Chuo Kogyo BLDG, No. 14 Momozono-cho Nakano-ku Tokyo Japan

TEL: Tokyo (381) 7191 REP. 23 or 24 EXT