



Product Specification Sheet

Metric Threaded with Flange Standard Lead Screw Assembly 8 mm x 12 mm A

Call 855-HELIXLT or visit us online at www.helixlinear.com to configure and order your Metric Threaded with Flange Standard Lead Screw Assembly 8 mm x 12 mm A today!









Netric Lead Screw	
Product Info Part Number	032472A
Thread Direction	RH/LH
Screw Material	Alloy
Details	10.00
Lead [mm]	12.00
Starts	5
Pitch [mm]	2.4
Diameter [mm]	8
End Code for Types 1,2,3,5 [* Journals may show tracings of the thread]	5
End Code for Type 4 [* Journals may show tracings of the thread]	2
Diameter Code	032
Lead Code	472
Dimensions	
A [mm]	5.90
B [mm]	8.10
Performance Specifications	
Efficiency [%]	65-81
Lead Accuracy +/- [in/in]	0.0003
Netric Threaded with Flange Standard Lead Nut	
Product Info	
Part Number	NTA032472F
Thread Direction	RH/LH
Туре	Acetal
Details	
Lead [mm]	12.0
Starts	5
Pitch [mm]	2.40
Diameter [mm]	8
Diameter Code	032
Lead Code	472
Forces and Torques	
Torque to Raise 1 lb. [in-lb]	0.103
Flange Part Numbers	0.103
Flange Part Number	HF37
Weight	
Flange Weight [lb]	0.64
Nut Weight [oz]	0.22
Performance Specifications	0.22
renormance specifications	65-81
	00-01
Efficiency [%]	
	0.0003