



Super

GLAND

IP68 Protection at 10 bar (145 psi)

102 metres submersible

Important features of this gland are:

- The unique cartridge seal has a collet to provide optimal strain relief. When the nut is tightened this seal forms a double pressure O-ring type seal.
- The special nut thread prevents nut bounce and also resists vibration loosening.
- The cable is supported at entry to maintain seal integrity and also prevent conductor fatigue.



Patented

Super GLAND is also available with a WAVE SEAL™ IP 68 washer fitted under the body hexagon for perfect surface sealing

Typical applications

Automated vegetable washing plants
Chicken processing plants
Container side lifters
Dairy sheds
Fish processing plants
Fishing vessels
Irrigation monitors
Milk processing plants
Refrigeration containers

TECHNICAL DATA


Material: High strength Nylon

Colour: Black or Grey

Working temp: -40°C to 100°C
Short term 130°C

UV resistance: Excellent

Chemical resistance: Excellent resistance to oils, petrol, alcohols, seawater, caustic soda, weak acids, alkalis, bases and salts.

Cat No.	Thread size	Thread length		Cable Range OD	Pack size
GMIL12	M12 x 1.5	10	16	2.5 - 6	50
GMIL16	M16 x 1.5	15	22	4.5 - 9	50
GMIL20	M20 x 1.5	15	27	7.5 - 13.2	50
GMIL25	M25 x 1.5	15	32	13 - 18	25
GMIL32	M32 x 1.5	15	46	17.5 - 25	20