

ROUND CABLE EMI CORES / LF TYPE

DIMENSIONS (UNIT:mm)

Part No.	Fig.	A (±1)	B (±1)	C (±1)	D (±1)	E (±1)	Impedance (Ω) Min		Use Cable Dia. Max
							25 MHz	100 MHz	
LF-35	5	15.0	15.0	4.0	25.2	---	55	95	Φ4
LF-50	5	16.5	16.5	5.2	29.5	---	70	120	Φ5
LF-501	2	15.0	14.0	5.2	23.0	---	70	120	Φ5
LF-502	1	13.0	11.8	5.0	25.5	---	60	100	Φ5
LF-503	1	17.0	15.0	5.2	30.0	---	130	210	Φ5
LF-60	6	18.5	14.0	6.0	15.5	---	60	80	Φ6
LF-65	2	20.5	20.0	6.5	33.0	---	120	200	Φ6.5
LF-70	4	15.5	14.0	7.0	18.0	22.0	40	75	Φ7
LF-702	1	17.0	15.0	7.0	30.0	---	70	130	Φ7
LF-75	5	21.0	21.0	7.5	39.0	---	90	150	Φ7.5
LF-801	3	19.5	23.0	8.1	17.0	23.0	42	85	Φ8
LF-802	3	19.5	23.0	8.1	20.0	26.0	50	110	Φ8
LF-90	7	21.0	17.0	20.0	9.0	---	45	90	Φ9
LF-901	4	20.5	19.5	9.0	31.5	35.5	80	130	Φ9
LF-902	1	19.5	18.0	9.0	35.0	---	80	130	Φ9
CT-0933	1	22.5	22.5	9.5	43.0	---	105	190	Φ9.5
CT-0933-2B	1	22.0	23.5	12.2	43.0	---	100	180	Φ12
LF-100	2	25.5± 1.0	23.5± 1.0	10.0± 0.5	33.0± 1.0	---	80	130	Φ10
LF-101	3	24.5± 1.0	28.5± 1.0	10.2± 0.5	13.5± 1.0	20.0± 1.0	35	75	Φ10
LF-102	1	21.5± 1.0	20.0± 1.0	10.0± 1.0	35.0± 1.0	---	144	240	Φ10
LF-103	4	20.5± 1.0	20.5± 1.0	10.0± 0.5	32.0± 1.0	36.0± 1.0	100	160	Φ10
LF-110	4	20.5± 1.0	21.0± 1.0	11.0± 0.5	32.0± 1.0	36.0± 1.0	60	110	Φ11
LF-1101	1	21.0± 1.0	20.0± 1.0	11.0± 0.5	36.0± 1.0	---	80	170	Φ11
LF-120	3	28.0± 1.0	32.0± 1.0	11.5± 0.5	18.0± 1.0	24.0± 1.0	50	100	Φ11.5
LF-130	2	32.5± 1.0	30.0± 1.0	13.0± 0.5	33.0± 1.0	---	105	170	Φ13
LF-1301	1	23.5± 1.0	22.5± 1.0	13.0± 0.5	36.0± 1.0	---	70	120	Φ13
LF-1302	4	31.5± 1.0	30.5± 1.0	13.0± 0.5	34.0± 1.0	39.5± 1.0	80	130	Φ13
LF-150	3	29.0± 1.0	33.0± 1.0	15.0± 0.5	15.5± 1.0	21.5± 1.0	30	70	Φ15
LF-190	2	29.5± 1.0	29.4± 1.0	19.4± 0.5	42.0± 1.0	---	90	160	Φ19



CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>