

GENERAL INSTRUMENT



**DISCRETE SEMICONDUCTORS
DATA BOOK**


Introduction

General Instrument Corporation is a major international company manufacturing a wide range of products from data system, cable TV, component product to semiconductors. The Corporation, which has been in existence over 50 years, has factories throughout the world serving all markets.

The discrete semiconductor division has factories in United States and Far East, and is one of the leading manufacturers of rectifiers and bridges. This catalog details our range of low and medium power rectifier products and bridge assemblies, including SUPERECTIFIERS, plastic encapsulated rectifiers, glass passivated rectifiers, bridges and special assemblies. The information, contained in this booklet, is intended to provide the necessary technical and support data to assist the designer.

Particular emphasis has been focused on the SUPERECTIFIER product family, a new concept in rectifier technology, launched some three years ago. Featuring a metallurgically bonded junction, glass passivation and flame retardant epoxy encapsulation to provide the ultimate in rectifier quality and reliability.

It is our policy to maintain high standards of product manufacture and the GI logo printed on every component ensures that it reaches the high level of quality and reliability. In the complex and competitive semiconductor industry, high standards of quality are of the utmost importance since they constitute, for the customer, the assurance of reliable product performance.



Not every application problem can be solved using a standard device, in this case we often develop special products to meet the customer requirements. If in doubt, call your local Sales Office or our Application Engineering Laboratory (listed on page 111) for further information.



SYMBOLS

SYMBOLS

| | |
|---------------|--|
| I_F | Forward Current |
| $I_{F(AV)}$ | Average Forward Rectified Current |
| I_{FSM} | Peak Forward Surge Current |
| I_O | Mean Forward Current |
| I_R | Reverse Current |
| I_{rr} | Reverse Recovery Current |
| I^2t | I^2t Rating for Fusing |
| $R_{TH(J-A)}$ | Thermal Resistance (Junction to Ambient) |
| $R_{TH(J-C)}$ | Thermal Resistance (Junction to Case) |
| T_A | Ambient Temperature |
| T_C | Case Temperature |
| T_L | Lead Temperature |
| t_{rr} | Reverse Recovery Time |
| V_{BR} | Breakdown Voltage |
| V_F | Forward Voltage |
| V_{FR} | Forward Recovery Voltage |
| V_R | Reverse Voltage |
| V_{RMS} | RMS Input Voltage |
| V_{RRM} | Repetitive Peak Reverse Voltage |
| V_Z | Zener Voltage |
| Z_K | Dynamic Impedance |

DRAWINGS

All dimensions in mm.
Figures not to scale.

TEMPERATURES

Ratings at 25°C ambient temperature unless otherwise specified.

Forward derating curves are measured while leads are held to ambient temperature in a distance of 10 mm to the case except all KBPC-Bridges, where case temperature is measured.

This General Instrument data book — containing short form data sheets — is not a document for official acceptance tests. Relevant is only the detailed data sheet, which is available on request.
The Manufacturer reserves the right to change the contained data at any time in order to improve performance and supply the best product possible.



CONTENTS

| General Information | Page |
|--|-------------|
| Introduction | 3 |
| Symbols | 4 |
| Contents | 5 |
| Numerical Index | 6 |
| Application Survey | 8 |
| Plastic Rectifiers | |
| Introduction | 11 |
| Quick Guide | 14 |
| Miniature Plastic Rectifiers 1 AMP | 15 |
| Plastic Power Rectifier 1.2 to 5 AMP | 16 |
| High Current Plastic Rectifiers 6 to 25 AMP | 19 |
| High Voltage Plastic Rectifiers 1 to 15 KV | 24 |
| Glass Rectifiers | |
| Introduction | 29 |
| Quick Guide | 32 |
| Glass passivated Diodes 0.4 AMP | 33 |
| Glass passivated Rectifiers 1 to 3 AMP | 34 |
| Glass passivated Fast Recovery Rectifiers | 41 |
| Glass passivated High Voltage Rectifiers 1.4 to 5 KV | 46 |
| List of approved JAN-JANTX devices | 49 |
| Superrectifiers | |
| Introduction | 51 |
| Quick Guide | 54 |
| Miniature Superrectifiers 0.4 to 1 AMP | 55 |
| Power Superrectifiers 1 to 3 AMP | 60 |
| Fast Recovery Superrectifiers 0.1 to 3 AMP | 69 |
| Controlled Avalanche Superrectifiers | 76 |
| Zener Superrectifiers | 77 |
| Bridge Rectifiers | |
| Introduction | 79 |
| Quick Guide | 81 |
| Miniature Bridge Rectifiers 0.5 to 1.5 AMP | 82 |
| In Line Bridge Rectifiers 1.5 to 5 AMP | 90 |
| High Current Bridge Rectifiers 3 to 35 AMP | 96 |
| Quality Assurance | |
| Introduction | 105 |
| Test Conditions | 106 |
| High Reliability-Test capabilities | 107 |
| Packaging Information | 108 |
| Sales Offices | 111 |



NUMERICAL INDEX

| Type | Page | Type | Page | Type | Page | Type | Page |
|----------|------|----------|------|----------------|------|----------------|------|
| 1N645 | 33 | 1N4943 | 41 | 1N5626 | 39 | B250C1000 | 84 |
| 1N645GP | 55 | 1N4944 | 41 | 1N5626GP | 67 | B250C1500 | 85 |
| 1N646 | 33 | 1N4944GP | 72 | 1N5627 | 39 | B250C1500C | 86 |
| 1N646GP | 55 | 1N4945 | 41 | 1N5627GP | 67 | B250C3700/2200 | 94 |
| 1N647 | 33 | 1N4946 | 41 | 2KBP005 | 91 | B250C5000/3300 | 95 |
| 1N647GP | 55 | 1N4946GP | 72 | 2KBP02 | 91 | B380C500 | 82 |
| 1N648 | 33 | 1N4947 | 41 | 2KBP04 | 91 | B380C800 | 83 |
| 1N648GP | 55 | 1N4947GP | 72 | 2KBP06 | 91 | B380C1000 | 84 |
| 1N649 | 33 | 1N4948 | 41 | 2KBP08 | 91 | B380C1500 | 85 |
| 1N649GP | 55 | 1N4948GP | 72 | 2KBP10 | 91 | B380C1500C | 86 |
| 1N1730A | 24 | 1N5059 | 36 | 2W005 | 89 | B380C3700/2200 | 94 |
| 1N1731A | 24 | 1N5059GP | 60 | 2W02 | 89 | B380C5000/3300 | 95 |
| 1N1732A | 24 | 1N5060 | 36 | 2W04 | 89 | BA157GP | 71 |
| 1N1733A | 24 | 1N5060GP | 60 | 2W06 | 89 | BA158GP | 71 |
| 1N1734A | 24 | 1N5061 | 36 | 2W08 | 89 | BA159DGP | 71 |
| 1N3611 | 34 | 1N5061GP | 60 | 2W10 | 89 | BA159GP | 71 |
| 1N3611GP | 56 | 1N5062 | 36 | AGP15-200 | 76 | BY126GP | 64 |
| 1N3612 | 34 | 1N5062GP | 60 | AGP15-400 | 76 | BY127GP | 64 |
| 1N3612GP | 56 | 1N5391GP | 62 | AGP15-600 | 76 | BY133GP | 61 |
| 1N3613 | 34 | 1N5392GP | 62 | AGP15-800 | 76 | BY134GP | 61 |
| 1N3613GP | 56 | 1N5393GP | 62 | AR25A | 20 | BY135GP | 61 |
| 1N3614 | 34 | 1N5394GP | 62 | AR25B | 20 | BY206GP | 70 |
| 1N3614GP | 56 | 1N5395GP | 62 | AR25D | 20 | BY207GP | 70 |
| 1N3957GP | 56 | 1N5396GP | 62 | AR25G | 20 | BY226GP | 65 |
| 1N4001 | 15 | 1N5397GP | 62 | AR25J | 20 | BY227GP | 65 |
| 1N4001GP | 57 | 1N5398GP | 62 | AR25K | 20 | BY228 | 47 |
| 1N4002 | 15 | 1N5399GP | 62 | AR25M | 20 | BY251P | 17 |
| 1N4002GP | 57 | 1N5400 | 16 | B40C500 | 82 | BY252P | 17 |
| 1N4003 | 15 | 1N5401 | 16 | B40C800 | 83 | BY253P | 17 |
| 1N4003GP | 57 | 1N5402 | 16 | B40C1000 | 84 | BY254P | 17 |
| 1N4004 | 15 | 1N5403 | 16 | B40C1500 | 85 | BY255P | 17 |
| 1N4004GP | 57 | 1N5404 | 16 | B40C1500C | 86 | BY296P | 22 |
| 1N4005 | 15 | 1N5405 | 16 | B40C3700/2200 | 94 | BY297P | 22 |
| 1N4005GP | 57 | 1N5406 | 16 | B40C5000/3300 | 95 | BY298P | 22 |
| 1N4006 | 15 | 1N5407 | 16 | B80C500 | 82 | BY299P | 22 |
| 1N4006GP | 57 | 1N5408 | 16 | B80C800 | 83 | BY500-100 | 23 |
| 1N4007 | 15 | 1N5614 | 42 | B80C1000 | 84 | BY500-200 | 23 |
| 1N4007GP | 57 | 1N5615 | 43 | B80C1500 | 85 | BY500-400 | 23 |
| 1N4245 | 35 | 1N5616 | 42 | B80C1500C | 86 | BY500-600 | 23 |
| 1N4245GP | 58 | 1N5617 | 43 | B80C3700/2200 | 94 | BY500-800 | 23 |
| 1N4246 | 35 | 1N5618 | 42 | B80C5000/3300 | 95 | BYX55-350P | 21 |
| 1N4246GP | 58 | 1N5619 | 43 | B125C500 | 82 | BYX55-600P | 21 |
| 1N4247 | 35 | 1N5620 | 42 | B125C800 | 83 | CG1 | 46 |
| 1N4247GP | 58 | 1N5621 | 43 | B125C1000 | 84 | DG1 | 46 |
| 1N4248 | 35 | 1N5622 | 42 | B125C1500 | 85 | G1A | 37 |
| 1N4248GP | 58 | 1N5623 | 43 | B125C1500C | 86 | G1B | 37 |
| 1N4249 | 35 | 1N5624 | 39 | B125C3700/2200 | 94 | G1D | 37 |
| 1N4249GP | 58 | 1N5624GP | 67 | B125C5000/3300 | 95 | G1G | 37 |
| 1N4942 | 41 | 1N5625 | 39 | B250C500 | 82 | G1J | 37 |
| 1N4942GP | 72 | 1N5625GP | 67 | B250C800 | 83 | G1K | 37 |



NUMERICAL INDEX

| Type | Page | Type | Page | Type | Page | Type | Page |
|-----------|------|------------|------|------------|------|-----------|------|
| G1M | 37 | HVPR10-12 | 26 | KBPC6 10t | 99 | RG3K | 45 |
| G2A | 38 | HVPR10-14 | 26 | KBPC8 005 | 100 | RG3M | 45 |
| G2B | 38 | HVPR15-4 | 27 | KBPC8 02 | 100 | RGP01-10 | 69 |
| G2D | 38 | HVPR20 | 25 | KBPC8 04 | 100 | RGP01-12 | 69 |
| G2G | 38 | HVPR30 | 25 | KBPC8 06 | 100 | RGP01-14 | 69 |
| G2J | 38 | HVPR40 | 25 | KBPC8 08 | 100 | RGP01-16 | 69 |
| G2K | 38 | HVPR50 | 25 | KBPC8 10 | 100 | RGP10A | 73 |
| G2M | 38 | HVPR60 | 25 | KBPC10 005 | 101 | RGP10B | 73 |
| G3A | 40 | HVPR80 | 25 | KBPC10 02 | 101 | RGP10D | 73 |
| G3B | 40 | KBF005 | 92 | KBPC10 04 | 101 | RGP10G | 73 |
| G3D | 40 | KBF02 | 92 | KBPC10 06 | 101 | RGP10J | 73 |
| G3G | 40 | KBF04 | 92 | KBPC10 08 | 101 | RGP10K | 73 |
| G3J | 40 | KBF06 | 92 | KBPC10 10 | 101 | RGP10M | 73 |
| G3K | 40 | KBF08 | 92 | KBPC25 005 | 102 | RGP15A | 74 |
| G3M | 40 | KBF10 | 92 | KBPC25 02 | 102 | RGP15B | 74 |
| GP10A | 59 | KBL005 | 93 | KBPC25 04 | 102 | RGP15D | 74 |
| GP10B | 59 | KBL02 | 93 | KBPC25 06 | 102 | RGP15G | 74 |
| GP10D | 59 | KBL04 | 93 | KBPC25 08 | 102 | RGP15J | 74 |
| GP10G | 59 | KBL06 | 93 | KBPC25 10 | 102 | RGP15K | 74 |
| GP10J | 59 | KBL08 | 93 | KBPC35 005 | 103 | RGP15M | 74 |
| GP10K | 59 | KBL10 | 93 | KBPC35 02 | 103 | RGP30A | 75 |
| GP10M | 59 | KBP005 | 90 | KBPC35 04 | 103 | RGP30B | 75 |
| GP15A | 63 | KBP02 | 90 | KBPC35 06 | 103 | RGP30D | 75 |
| GP15B | 63 | KBP04 | 90 | KBPC35 08 | 103 | RGP30G | 75 |
| GP15D | 63 | KBP06 | 90 | KBPC35 10 | 103 | RGP30J | 75 |
| GP15G | 63 | KBP08 | 90 | P300A | 18 | RGP30K | 75 |
| GP15J | 63 | KBP10 | 90 | P300B | 18 | RGP30M | 75 |
| GP15K | 63 | KBPC005 | 96 | P300D | 18 | W005 | 88 |
| GP15M | 63 | KBPC02 | 96 | P300G | 18 | W02 | 88 |
| GP20A | 66 | KBPC04 | 96 | P300J | 18 | W04 | 88 |
| GP20B | 66 | KBPC06 | 96 | P300K | 18 | W06 | 88 |
| GP20D | 66 | KBPC08 | 96 | P300M | 18 | W08 | 88 |
| GP20G | 66 | KBPC10 | 96 | P600A | 19 | W10 | 88 |
| GP20J | 66 | KBPC1 005 | 97 | P600B | 19 | WL005 | 87 |
| GP20K | 66 | KBPC1 02 | 97 | P600D | 19 | WL02 | 87 |
| GP20M | 66 | KBPC1 04 | 97 | P600G | 19 | WL04 | 87 |
| GP30A | 68 | KBPC1 06 | 97 | P600J | 19 | WL06 | 87 |
| GP30B | 68 | KBPC1 08 | 97 | P600K | 19 | WL08 | 87 |
| GP30D | 68 | KBPC1 10 | 97 | RG1A | 44 | WL10 | 87 |
| GP30G | 68 | KBPC6 005 | 98 | RG1B | 44 | ZGP10-160 | 77 |
| GP30J | 68 | KBPC6 02 | 98 | RG1D | 44 | ZGP10-170 | 77 |
| GP30K | 68 | KBPC6 04 | 98 | RG1G | 44 | ZGP10-180 | 77 |
| GP30M | 68 | KBPC6 06 | 98 | RG1J | 44 | ZGP10-190 | 77 |
| HVG2 | 48 | KBPC6 08 | 98 | RG1K | 44 | ZGP10-200 | 77 |
| HVG3 | 48 | KBPC6 10 | 98 | RG1M | 44 | | |
| HVG4 | 48 | KBPC6 005t | 99 | RG3A | 45 | | |
| HVG5 | 48 | KBPC6 02t | 99 | RG3B | 45 | | |
| HVPR10-06 | 26 | KBPC6 04t | 99 | RG3D | 45 | | |
| HVPR10-08 | 26 | KBPC6 06t | 99 | RG3G | 45 | | |
| HVPR10-10 | 26 | KBPC6 08t | 99 | RG3J | 45 | | |



APPLICATIONS SURVEY

| | | PLASTIC RECTIFIERS | | | | | | | | | | | | GLASS RECTIFIERS | | | | | | | | | | | |
|--------------------------|--|--------------------|--------|------------------|-----------------|------------------|--------|------------------|------------------|------------------------|----------------|----------------|------------------|------------------|----------------------|------------------|--------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| TYPE | | 1N4001 1N4002 | 1N4007 | 1N5400 1N5408 | P3004 P3004M | BY251P BY251P | BY255P | BY206P BY206P | BY209P BY209P | BY220-100 BY220-600 | PR20A PR20M | AP25A AP25M | HYPR20 HYPR20 | HYPR10 HYPR10 | HYPR15-4 HYPR15-4 | 1N4045 1N4045 | 1N4049 | 1N5411 1N5411 | 1N5414 1N5414 | 1N4942 1N4942 | 1N4948 1N4948 | 1N5055 1N5055 | 1N5062 1N5062 | 1N5024 1N5024 | 1N5027 1N5027 |
| APPLICATION | | | | | | | | | | | | | | | | | | | | | | | | | |
| Audio Power Amplifier | | | | | | | | | | | | | | | | | | | | | | | | | |
| Automotive | | | | | | | | | | | | | | | | | | | | | | | | | |
| Computer Systems | | | | | | | | | | | | | | | | | | | | | | | | | |
| Controlled Avalanche | | | | | | | | | | | | | | | | | | | | | | | | | |
| Domestic Appliances | | | | | | | | | | | | | | | | | | | | | | | | | |
| Fast Switching | | | | | | | | | | | | | | | | | | | | | | | | | |
| General Purpose | | | | | | | | | | | | | | | | | | | | | | | | | |
| High Current | | | | | | | | | | | | | | | | | | | | | | | | | |
| High Mechanical Strength | | | | | | | | | | | | | | | | | | | | | | | | | |
| High Surge | | | | | | | | | | | | | | | | | | | | | | | | | |
| High Voltage | | | | | | | | | | | | | | | | | | | | | | | | | |
| Low Leakage | | | | | | | | | | | | | | | | | | | | | | | | | |
| Low RFI | | | | | | | | | | | | | | | | | | | | | | | | | |
| Medical Equipment | | | | | | | | | | | | | | | | | | | | | | | | | |
| Micro Wave Ovens | | | | | | | | | | | | | | | | | | | | | | | | | |
| Military Applications | | | | | | | | | | | | | | | | | | | | | | | | | |
| Industrial Systems | | | | | | | | | | | | | | | | | | | | | | | | | |
| Photo Flash | | | | | | | | | | | | | | | | | | | | | | | | | |
| Power Supplies | | | | | | | | | | | | | | | | | | | | | | | | | |
| Switch Mode Power Supply | | | | | | | | | | | | | | | | | | | | | | | | | |
| Telecommunication | | | | | | | | | | | | | | | | | | | | | | | | | |
| Television Scanning | | | | | | | | | | | | | | | | | | | | | | | | | |
| TV Clamping, Damping | | | | | | | | | | | | | | | | | | | | | | | | | |



Plastic Rectifier

1 to 25 Amperes


50 V
to
15000 V

Principle of Construction

General Instrument has produced successfully for many years Plastic Rectifiers. The key factor of our 1 Amp Plastic Rectifier is the use of the cell concept. The small size and absence of leads allows many cells to be processed simultaneously in batch form. This method ensures accurate pretesting of the cells before final assembly, and allows General Instrument to produce high volume of 1 Amp Rectifiers economically.


The cell construction consists of the following steps:

1 – Diffusing a PN junction into a slice of silicon.




Diffused Slice

2 – Metallizing the slice of silicon.




Metallized Slice

3 – Scribing and breaking the slice into individual dies.



Scribed Wafer


4 – Soldering the die between two heat sinks.




Soldering die between Heat Sinks

5 – Cleaning the assembly by chemical etching, washing and drying.

6 – Passivating the finished cell with silastic.




Silastic Coated Cell



Cell Constructed Plastic Rectifier

7 – In addition to the cell-construction for high current rectifiers the double nail head construction is used.

In this construction the cell is soldered, between two nail headed leads and over-molding with an epoxy body.



Double Nail Head Plastic Rectifier

8 – The double nail head construction is used for high current plastic rectifiers.



Miniature Plastic Silicon Rectifiers 1 AMP

Type: 1N4001 thru 1N4007

Features:

- Low Cost
- Diffused Junction
- Low Leakage
- High Current Capability
- Easily Cleaned with Freon, Alcohol, Chlorothene and similar Solvents
- Silver Plated Axial Leads, Solderable per MIL-STD-202/208
- Case: Jedec DO 41

Plastic Power Rectifiers 1.2 to 5 AMP

Types: 1N5400 thru 1N5408
P300A thru P300M
BY251P thru BY255P
BY296P thru BY299P (Fast Recovery)
BY500-100 thru BY500-800 (Fast Recovery)
BYX55-350P and BYX55-600P

Features:

- High Surge Current Capability
- Void-Free Plastic DO 27A Package
- High Current Operation
- Typical I_R less than 1 μ A (1N5400, P300)
- Exceeds Environmental Standards of MIL-STD-19500/228
- High Temperature Soldering Guaranteed 350°C/10 Seconds/10 mm Lead Length at 2,25 kg Tension
- Controlled Soft Recovery guarantees low RFI and high Efficiency Switching Characteristics of BY296P thru BY299P and BY500-100 thru BY500-800.
- Silver Plated Axial Leads, Solderable per MIL-STD-202/208

High Current Plastic Silicon Rectifiers 6 to 25 AMP

Types: AR25A thru AR25M
P600A thru P600K

Features:

- High Current Lead Mounted (P600)
- Diffused Junction
- High Surge Current: 400 Ampere at $T_j = 175^\circ\text{C}$
- Low Leakage
- Tinned Copper Leads (P600)
- Silver Plated Copper (AR25)

High Voltage Plastic Rectifiers

Types: 1N1730 A thru 1N1734A
HVPR20 thru HVPR80
HVPR15-9 thru HVPR15-15
HVPR10-06 thru HVPR10-14

Features:

- Diffused Junction
- Low Forward Voltage Drop
- High Forward Overload Surge Rating
- Avalanche Operation
- Ideal for Magnetron Power Supply in Micro Wave Ovens.



QUICK GUIDE TO PLASTIC RECTIFIERS

| TYPE | 1N4001 thru 1N4007 | BYX55-350P* and BYX55-600P* | BY296P* thru BY299P* | BY500-100* thru BY500-800* | BY251P thru BY255P | 1N5400 thru 1N5408 | P300A thru P300M | P600A thru P600M | AR25A thru AR25M |
|------------------|--------------------------|-----------------------------------|----------------------------|----------------------------------|--------------------------|--------------------------|------------------------|------------------------|------------------------|
| CASE | DO41 | DO27A | DO27A | DO27C | DO27A | DO27A | DO27A | P600 | AR25 |
| I_o (A) | 1.0 | 1.2 | 2.0 | 5.0 | 3.0 | 3.0 | 3.0 | 6.0 | 25 |
| @ T_A (°C) | 75 | 55 | 55 | 45 | 75 | 105 | 105 | 60 | 150 T_c |
| $V_R = 50$ (V) | 1N4001 | | | | | 1N5400 | P300A | P600A | AR25A |
| $V_R = 100$ (V) | 1N4002 | | BY296P | BY500-100 | | 1N5401 | P300B | P600B | AR25B |
| $V_R = 200$ (V) | 1N4003 | | BY297P | B4500-200 | BY251P | 1N5402 | P300D | P600D | AR25D |
| $V_R = 300$ (V) | | | | | | 1N5403 | | | |
| $V_R = 400$ (V) | 1N4004 | BYX55-350P | BY298P | BY500-400 | BY252P | 1N5404 | P300G | P600G | AR25G |
| $V_R = 500$ (V) | | | | | | 1N5405 | | | |
| $V_R = 600$ (V) | 1N4005 | | | BY500-600 | BY253P | 1N5406 | P300J | P600J | AR25J |
| $V_R = 800$ (V) | 1N4006 | BYX55-600P | BY299P | BY500-800 | BY254P | 1N5407 | P300K | P600K | AR25K |
| $V_R = 1000$ (V) | 1N4007 | | | | | 1N5408 | P300M | | |
| $V_R > 1000$ (V) | | | | | BY255P | | | | |
| SURGE (A) | 30 | 40 | 70 | 200 | 100 | 200 | 200 | 400 | 400 |
| V_F (V) | 1.1 | 1.25 | 1.3 | 1.25 | 1.1 | 1.2 | 1.1 | 1.25 | 1.0 |
| Page | 15 | 21 | 22 | 23 | 17 | 16 | 18 | 19 | 20 |

* Fast Recovery



QUICK GUIDE TO HV PLASTIC RECTIFIERS

| TYPE | 1N1730A thru 1N1734A | HVPR20 thru HVPR80 | HVPR15 | HVPR10-06 thru HVPR10-14 | TYPE |
|-------------------|----------------------------|--------------------------|-----------|--------------------------------|-------------------|
| I_o (A) | 0.35 | | | | I_o (A) |
| @ T_A (°C) | 25 | | | | @ T_A (°C) |
| SURGE (A) | 6 | | | | SURGE (A) |
| $V_R = 1000$ (V) | 1N1730A | | | | $V_R = 1000$ (V) |
| $V_R = 1500$ (V) | 1N1731A | | | | $V_R = 1500$ (V) |
| $V_R = 2000$ (V) | 1N1732A | HVPR20 | | | $V_R = 2000$ (V) |
| $V_R = 3000$ (V) | 1N1733A | HVPR30 | | | $V_R = 3000$ (V) |
| $V_R = 4000$ (V) | | HVPR40 | | | $V_R = 4000$ (V) |
| $V_R = 5000$ (V) | 1N1734A | HVPR50 | | | $V_R = 5000$ (V) |
| $V_R = 6000$ (V) | | HVPR60 | | HVPR10-06 | $V_R = 6000$ (V) |
| $V_R = 8000$ (V) | | HVPR80 | HVPR15-9 | HVPR10-08 | $V_R = 8000$ (V) |
| $V_R = 10000$ (V) | | | HVPR15-11 | HVPR10-10 | $V_R = 10000$ (V) |
| $V_R = 12000$ (V) | | | HVPR15-13 | HVPR10-12 | $V_R = 12000$ (V) |
| $V_R = 14000$ (V) | | | | HVPR10-14 | $V_R = 14000$ (V) |
| $V_R = 15000$ (V) | | | HVPR15-15 | | $V_R = 15000$ (V) |
| Page | 24 | 25 | 27 | 26 | Page |



1 A Plastic Rectifier


50 to 1000 V

1N4001
thru
1N4007

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|--------|---------------------|--|
| 1N4001 | 35 V | 50 V |
| 1N4002 | 70 V | 100 V |
| 1N4003 | 140 V | 200 V |
| 1N4004 | 280 V | 400 V |
| 1N4005 | 420 V | 600 V |
| 1N4006 | 560 V | 800 V |
| 1N4007 | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 1.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 30 A |
| Maximum Forward Voltage at 1.0 A _{DC} | 1.1 V |
| Maximum Reverse Current at 25°C | 5.0 μA |
| Maximum Reverse Current at 75°C | 50.0 μA |
| Typical Reverse Recovery Time – Measured with I _F = 20 mA, i _r = 1 mA | 20 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 30 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





3 A Plastic Rectifier


50 to 1000 V

1N5400
thru
1N5408

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|--------|---------------------|--|
| 1N5400 | 35 V | 50 V |
| 1N5401 | 70 V | 100 V |
| 1N5402 | 140 V | 200 V |
| 1N5403 | 210 V | 300 V |
| 1N5404 | 280 V | 400 V |
| 1N5405 | 350 V | 500 V |
| 1N5406 | 420 V | 600 V |
| 1N5407 | 560 V | 800 V |
| 1N5408 | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current at 105°C | 3.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 200 A |
| Maximum Forward Voltage at 3.0 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 5.0 μA |
| Maximum Reverse Current at 105°C | 500 μA |
| Typical Reverse Recovery Time – Measured with I _F = 0.5 A, I _R = 1.0 A, i _{rr} = 0.25 A | 5 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 60 pF |
| Typical Thermal Resistance | 25°C/W |
| Operating Temperature Range | –65 to +170°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





3 A Plastic Rectifier


200 to 1300 V

BY251P
thru
BY255P

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|--------|---------------------|--|
| BY251P | 140 V | 200 V |
| BY252P | 280 V | 400 V |
| BY253P | 420 V | 600 V |
| BY254P | 560 V | 800 V |
| BY255P | 910 V | 1300 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 3.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 100 A |
| Maximum Forward Voltage at 3.0 A _{DC} | 1.1 V |
| Maximum Reverse Current at 25°C | 5.0 μA |
| Maximum Reverse Current at 55°C | 100 μA |
| Typical Reverse Recovery Time – Measured with I _F = 0.5 A, I _R = 1.0 A, i _{rr} = 0.25 A | 3 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 60 pF |
| Typical Thermal Resistance | 25°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





3 A Plastic Rectifier


500 to 1000 V

P300
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|-------|---------------------|---|
| P300A | 35 V | 50 V |
| P300B | 70 V | 100 V |
| P300D | 140 V | 200 V |
| P300G | 280 V | 400 V |
| P300J | 420 V | 600 V |
| P300K | 560 V | 800 V |
| P300M | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 3.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 200 A |
| Maximum Forward Voltage at 9.4 A _{DC} | 1.1 V |
| Maximum Reverse Current at 25°C | 5.0 μA |
| Maximum Reverse Current at 100°C | 25.0 μA |
| Typical Reverse Recovery Time – Measured with I _F = 0.5 A, I _R = 1.0 A, i _{rr} = 0.25 A | 5.0 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 50.0 pF |
| Typical Thermal Resistance | 25°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





6 A Plastic Rectifier


50 to 800 V

P600
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|-------|---------------------|--|
| P600A | 35 V | 50 V |
| P600B | 70 V | 100 V |
| P600D | 140 V | 200 V |
| P600G | 280 V | 400 V |
| P600J | 420 V | 600 V |
| P600K | 560 V | 800 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 6 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 400 A |
| Maximum Forward Voltage at 6.0 A _{DC} | 0.9 V |
| Maximum Reverse Current at 25°C | 25 µA |
| Maximum Reverse Current at 100°C | 100 µA |
| Typical Reverse Recovery Time – Measured with I _F = 0.5 A, I _R = 1.0 A, i _{tr} = 0.25 A | 5 µs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 220 pF |
| Typical Thermal Resistance | 10°C/W |
| Operating Temperature Range | –65 to +170°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





25 A Button Rectifier


50 to 1000 V

AR25
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|-------|---------------------|--|
| AR25A | 35 V | 50 V |
| AR25B | 70 V | 100 V |
| AR25D | 140 V | 200 V |
| AR25G | 280 V | 400 V |
| AR25J | 420 V | 600 V |
| AR25K | 560 V | 800 V |
| AR25M | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 25 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 400 A |
| Maximum Forward Voltage at 25 A _{DC} | 1.0 V |
| Maximum Reverse Current at 25°C | 25.0 µA |
| Maximum Reverse Current at 100°C | 250 µA |
| Typical Reverse Recovery Time – Measured with $I_F = 0.5$ A, $I_R = 1.0$ A, $t_{rr} = 0.25$ A | 5 µs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 300 pF |
| Typical Thermal Resistance | 2.5°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1.2 A Plastic Rectifier


350 and 600 V / Fast Recovery

BYX55P

VOLTAGE RATINGS

| Type | Maximum Recurrent Peak Reverse Voltage |
|------------|---|
| BYX55-350P | 350 V |
| BYX55-600P | 600 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 1.2 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 40 A |
| Maximum Forward Voltage at 5.0 A _{DC} | 1.25 V |
| Maximum Reverse Current at 25°C | 5 µA |
| Maximum Reverse Current at 100°C | 200 µA |
| Maximum Reverse Recovery Time – Measured with I _F = 1.0 A, V _R = 50 V | 750 n |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 30 pF |
| Typical Thermal Resistance | 25°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





2 A Plastic Rectifier


100 to 800 V / Fast Recovery

BY296P
thru
BY299P

VOLTAGE RATINGS

| Type | Maximum Recurrent Peak Reverse Voltage |
|--------|---|
| BY296P | 100 V |
| BY297P | 200 V |
| BY298P | 400 V |
| BY299P | 800 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 2.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 70 A |
| Maximum Forward Voltage at 3.0 A _{DC} | 1.3 V |
| Maximum Reverse Current at 25°C | 10 μ A |
| Maximum Reverse Current at 100°C | 200 μ A |
| Maximum Reverse Recovery Time – Measured with $I_F = 0.5$ A, $I_R = 1.0$ A, $i_{rr} = 0.25$ A | 500 ns |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 40 pF |
| Typical Thermal Resistance | 25°C/W |
| Operating Temperature Range | –65 to +150°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





5 A Plastic Rectifier

100 to 800 V / Soft Recovery


**BY500
Series**

HIGH EFFICIENCY LOW NOISE SWITCHING RECTIFIER

CASE OUTLINE

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|------------------|---------------------|--|
| BY500-100 | 70 V | 100 V |
| BY500-200 | 140 V | 200 V |
| BY500-400 | 280 V | 400 V |
| BY500-600 | 420 V | 600 V |
| BY500-800 | 560 V | 800 V |

DO-27C



Especially designed for applications such as Switch Mode Power Supplies, Inverters, Converters, Choppers, TV Scanning, Ultrasonic-Systems, speed controlled DC Motors, low RF Interference and free Wheeling Rectifiers.

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 5 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 200 A |
| Maximum Forward Voltage at 3.0 A _{DC} | 1.25 V |
| Maximum Reverse Current at 25°C | 10 µA |
| Maximum Reverse Current at 100°C | 1 mA |
| Typical Reverse Recovery Time – Measured with I _F = 1 A, V _R = 30 V | 200 ns |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 12.0 V _{DC} | 30 pF |
| Typical Thermal Resistance | 25°C/W |
| Operating Temperature Range | –65 to +125°C |
| Storage Temperature Range | –65 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





HV Plastic Rectifier


1000 to 5000 V

1N1730A
thru
1N1734A

VOLTAGE RATINGS

| Type | Maximum Forward Voltage at 0.4 A _{DC} | Maximum Recurrent Peak Reverse Voltage |
|-----------|--|--|
| 1N1730A* | 3.0 V | 1000 V |
| 1N1731A* | 3.0 V | 1500 V |
| 1N1732A** | 3.0 V | 2000 V |
| 1N1733A** | 6.0 V | 3000 V |
| 1N1734A** | 8.0 V | 5000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current at 25°C | 0.35 A |
| Maximum Average Forward Rectified Current at 100°C | 0.2 A |
| Maximum Average Forward Rectified Current at 175°C | 0.05 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 6.0 A |
| Maximum Reverse Current at 25°C | 1.0 µA |
| Maximum Reverse Current at 150°C | 12.0 µA |
| Operating Temperature Range | -65 to +200°C |
| Storage Temperature Range | -65 to +200°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





HV Plastic Rectifier


2000 to 8000 V

**HVPR
Series**

VOLTAGE RATINGS

| Type | Maximum Recurrent Peak Reverse Voltage |
|--------|---|
| HVPR20 | 2000 V |
| HVPR30 | 3000 V |
| HVPR40 | 4000 V |
| HVPR50 | 5000 V |
| HVPR60 | 6000 V |
| HVPR80 | 8000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 0.25 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 30 A |
| Maximum Forward Voltage at 0.25 A _{DC} | 8 V |
| Maximum Reverse Current at 25°C | 10 μ A |
| Maximum Reverse Current at 125°C | 100 μ A |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 100 V _{DC} | 5 pF |
| Typical Thermal Resistance | 35 °C/W |
| Operating Temperature Range | -40 to +125°C |
| Storage Temperature Range | -50 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





HV Plastic Rectifier


6000 to 14000 V

**HVPR10
Series**

VOLTAGE RATINGS

| Type | Maximum Recurrent Peak Reverse Voltage |
|------------------|---|
| HVPR10-06 | 6000 V |
| HVPR10-08 | 8000 V |
| HVPR10-10 | 10000 V |
| HVPR10-12 | 12000 V |
| HVPR10-14 | 14000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.


| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 0.75 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 250 A |
| Maximum Forward Voltage at 0.75 A _{DC} | 14 V |
| Maximum Reverse Current at 25°C | 5 μ A |
| Operating Temperature Range | -20 to +125°C |
| Storage Temperature Range | -20 to +125°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 - Typical forward characteristic



Fig. 2 - Forward derating curve





Glass Rectifier

0.4 to 3 Amperes

50 V
to
5000 V


Device Design

The Glass-Amp II is a hermetically sealed, cavity-free, diffused junction rectifier with unsurpassed operating and surge characteristics at high temperature.

Cavity-free construction with a specially developed extremely pure glass in direct contact with the silicon junction plus durable heat sink design obviate the need for solder joints and compression contact parts. The carefully matched expansion characteristics of the glass and metal parts in combination with the direct contact of the glass and silicon junction make the active rectifying elements impervious to surface contamination, moisture or other external chemical agents. Further, the long term degradation associated with organic junction protection is avoided.


There are many steps necessary to produce such a device :

1 – Diffuse a PN junction into a slice of silicon




Diffused Slice

2 – Evaporate aluminium on both sides of the slice to make metallurgical contact




Metallized Slice

3 – Sandblast the slice to produce a round beveled die




Sandblasted Round Dice

- 4 – Braze the die between two molybdenum heat sinks to which leads have been attached at approximately 700°C.



- 5 – Clean the assembly by chemically etching, washing and drying.
- 6 – Apply glass in the form of a frit to the die and molybdenum assembly.

- 7 – Melt the glass by heating in an oven to approximately 600°C.



Glass Passivated Rectifier

- 8 – Perform finishing operations such as lead tinning, electrical testing and marking.

Package Design

The small size of the glass package with its capability up to 3 Ampere permits greater packing densities in electronic assemblies and equipment, while increasing reliability. Furthermore, only high temperature brazing operations are used to withstand the 600°C required to melt and fuse the glass. This technique eliminates solder construction and tremendously enhances mechanical strength and temperature cycling capability, increasing operating and storage temperature range while reducing thermal resistance.

Reliability

Specified reliability data on Glass-Amp II devices are available from the General Instrument Semiconductor Components Division Reliability Department. The basic design of the Glass-Amp II rectifier and the strict positive controls over materials and manufacturing processes provide assurance of failure-free performance under the most severe conditions. Processing facilities have been geared to follow the procedural requirements of Military Standard 750. Glass-Amp II rectifiers are capable of withstanding environmental extremes in excess of MIL-S-19500/286 and of meeting the requirements of MIL-S-19500E, MIL-STD-883, MIL-Q-9858 and MIL-I-45208. Assurance of production uniformity and reliability is provided by a test technique called „Operational Load Line Testing”, which has proven product reliability with over 1 Billion Glass-Amp rectifiers now in use.

**Glass Passivated Silicon Diodes 0.4 AMP**

Type: 1N645 thru 1N649

Features:

- High Temperature Metallurgically Bonded
- High Efficiency and Rectification Ratio
- Ideally Suited for Miniaturized Equipment
- Case: One Piece Glass, Hermetically Sealed
- Tin Plated Axial Leads, Solderable per MIL-STD-202/208
- Operating from -65°C to $+175^{\circ}\text{C}$
- Low Leakage

Glass Passivated Silicon Rectifiers 1 to 3 AMP

Types: 1N3611 thru 1N3614
1N4245 thru 1N4249
1N5059 thru 1N5062
1N5624 thru 1N5627
G1A thru G1M
G2A thru G2M
G3A thru G3M

Features:

- Glass Passivated Junction
- High Mechanical Strength
- Storage up to 200°C
- Voidless Construction
- Hermetically Sealed
- Avalanche Operation
- Low Leakage
- High Conductance
- Tin Plated Axial Leads, Solderable per MIL-STD-202/208

Glass Passivated Fast Recovery Silicon Rectifiers 1 to 3 AMP

Types: 1N4942 thru 1N4948
1N5614 thru 1N5622
1N5615 thru 1N5623
RG1A thru RG1M
RG3A thru RG3M

Features:

- Glass Passivated Junction
- High Rectification Efficiency to 100 kHz
- High Mechanical Strength
- Low Leakage
- Hermetically Sealed
- Storage up to 200°C
- Tin Plated Axial Leads, Solderable per MIL-STD-202/208

Glass Passivated High Voltage Silicon Rectifiers 0.15 to 1.5 AMP

Types: CG1, DG1
HVG-2 thru HVG-5
BY228

Features:

- All Advantages of a Hermetically Sealed Glass Passivated Junction
- Especially designed for Clamper/Damper Applications in Television Circuits
- Low Leakage
- High Mechanical Strength
- Tin Plated Axial Leads, Solderable per MIL-STD-202/208



QUICK GUIDE TO GLASS PASSIVATED RECTIFIERS

| TYPE | 1N645 thru 1N649 | 1N3611 thru 1N3614 | 1N4245 thru 1N4249 | 1N4942* thru 1N4948* | RG 1 A* thru RG 1 M* | 1N5059 thru 1N5062 | 1N5614 thru 1N5622 | 1N5615* thru 1N5623* | TYPE |
|------------------|------------------------|--------------------------|--------------------------|----------------------------|----------------------------|--------------------------|--------------------------|----------------------------|------------------|
| CASE | GPD | GPR | GPR | GPR | GPR | GPR | GPR | GPR | CASE |
| I_o (A) | 0.4 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | I_o (A) |
| @ T_A (°C) | 25 | 100 | 55 | 55 | 55 | 55 | 55 | 55 | @ T_A (°C) |
| $V_R = 50$ (V) | | | | | RG 1 A | | | | $V_R = 50$ (V) |
| $V_R = 100$ (V) | | | | | RG 1 B | | | | $V_R = 100$ (V) |
| $V_R = 200$ (V) | 1N645 | 1N3611 | 1N4245 | 1N4942 | RG 1 D | 1N5059 | 1N5614 | 1N5615 | $V_R = 200$ (V) |
| $V_R = 300$ (V) | 1N646 | | | 1N4943 | | | | | $V_R = 300$ (V) |
| $V_R = 400$ (V) | 1N647 | 1N3612 | 1N4246 | 1N4944 | RG 1 G | 1N5060 | 1N5616 | 1N5617 | $V_R = 400$ (V) |
| $V_R = 500$ (V) | 1N648 | | | 1N4945 | | | | | $V_R = 500$ (V) |
| $V_R = 600$ (V) | 1N649 | 1N3613 | 1N4247 | 1N4946 | RG 1 J | 1N5061 | 1N5618 | 1N5619 | $V_R = 600$ (V) |
| $V_R = 800$ (V) | | 1N3614 | 1N4248 | 1N4947 | RG 1 K | 1N5062 | 1N5620 | 1N5621 | $V_R = 800$ (V) |
| $V_R = 1000$ (V) | | | 1N4249 | 1N4948 | RG 1 M | | 1N5622 | 1N5623 | $V_R = 1000$ (V) |
| $V_R > 1000$ (V) | | | | | | | | | $V_R > 1000$ (V) |
| SURGE (A) | 5 | 20 | 25 | 30 | 30 | 50 | 50 | 50 | SURGE (A) |
| V_F (V) | 1.0 | 1.1 | 1.2 | 1.3 | 1.3 | 1.2 | 1.2 | 1.2 | V_F (V) |
| Page | 33 | 34 | 35 | 41 | 44 | 36 | 42 | 43 | Page |



QUICK GUIDE TO GLASS PASSIVATED RECTIFIERS

| TYPE | G 1 A thru G 1 M | CG 1 and DG 1 | BY228 | G 2 A thru G 2 M | RG 3 A* thru RG 3 M* | G 3 A thru G 3 M | 1N5624 thru 1N5627 | TYPE |
|------------------|------------------------|---------------------|-------|------------------------|----------------------------|------------------------|--------------------------|------------------|
| CASE | GPR | GPR | GPR 3 | GPR | GPR 3 | GPR 3 | GPR 3 | CASE |
| I_o (A) | 1.0 | 1.5 | 2.5 | 2.0 | 3.0 | 3.0 | 3.0 | I_o (A) |
| @ T_A (°C) | 100 | 55 | 55 | 75 | 55 | 70 | 70 | @ T_A (°C) |
| $V_R = 50$ (V) | G 1 A | | | G 2 A | RG 3 A | G 3 A | | $V_R = 50$ (V) |
| $V_R = 100$ (V) | G 1 B | | | G 2 B | RG 3 B | G 3 B | | $V_R = 100$ (V) |
| $V_R = 200$ (V) | G 1 D | | | G 2 D | RG 3 D | G 3 D | 1N5624 | $V_R = 200$ (V) |
| $V_R = 300$ (V) | | | | | | | | $V_R = 300$ (V) |
| $V_R = 400$ (V) | G 1 G | | | G 2 G | RG 3 G | G 3 G | 1N5625 | $V_R = 400$ (V) |
| $V_R = 500$ (V) | | | | | | | | $V_R = 500$ (V) |
| $V_R = 600$ (V) | G 1 J | | | G 2 J | RG 3 J | G 3 J | 1N5626 | $V_R = 600$ (V) |
| $V_R = 800$ (V) | G 1 K | | | G 2 K | RG 3 K | G 3 K | 1N5627 | $V_R = 800$ (V) |
| $V_R = 1000$ (V) | G 1 M | | | G 2 M | RG 3 M | G 3 M | | $V_R = 1000$ (V) |
| $V_R > 1000$ (V) | | CG 1/DG 1 | BY228 | | | | | $V_R > 1000$ (V) |
| SURGE (A) | 50 | 50 | 100 | 50 | 100 | 125 | 125 | SURGE (A) |
| V_F (V) | 1.1 | 1.0 | 1.3 | 1.1 | 1.3 | 1.1 | 1.0 | V_F (V) |
| Page | 37 | 46 | 47 | 38 | 45 | 40 | 39 | Page |

* Fast Recovery



0.4 A Glass Diode


225 to 600 V

1N645
thru
1N649

VOLTAGE RATINGS

| Type | Maximum Recurrent Peak Reverse Voltage |
|-------|---|
| 1N645 | 225 V |
| 1N646 | 300 V |
| 1N647 | 400 V |
| 1N648 | 500 V |
| 1N649 | 600 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 400 mA |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 5 A |
| Maximum Forward Voltage at 0.4 A _{DC} | 1.0 V |
| Maximum Reverse Current at 25°C | 0.2 μA |
| Maximum Reverse Current at 100°C | 15 μA |
| Maximum Reverse Recovery Time – Measured with $I_F = 20$ mA, $i_{rr} = 1$ mA | 20 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 100°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +200°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Glass Rectifier


200 to 800 V

1N3611
thru
1N3614

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|--------|---------------------|--|
| 1N3611 | 140 V | 200 V |
| 1N3612 | 280 V | 400 V |
| 1N3613 | 420 V | 600 V |
| 1N3614 | 560 V | 800 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current @100°C | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 30 A |
| Maximum Forward Voltage at 2.0 A _{DC} | 1.1 V |
| Maximum Reverse Current at 25°C | 1.0 μA |
| Maximum Reverse Current at 150°C | 300 μA |
| Maximum Reverse Recovery Time – Measured with I _F = 20 A, i _r = 1 mA | 20 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +300°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Glass Rectifier


200 to 1000 V

1N4245
thru
1N4249

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|--------|---------------------|--|
| 1N4245 | 140 V | 200 V |
| 1N4246 | 280 V | 400 V |
| 1N4247 | 420 V | 600 V |
| 1N4248 | 560 V | 800 V |
| 1N4249 | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 25 A |
| Maximum Forward Voltage at 1.0 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 1.0 μA |
| Maximum Reverse Current at 125°C | 25 μA |
| Typical Reverse Recovery Time – Measured with I _F = 0.5 A, I _R = 1.0 A, i _{rr} = 0.25 A | 2 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | –65 to +160°C |
| Storage Temperature Range | –65 to +200°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Glass Rectifier


200 to 800 V

1N5059
thru
1N5062

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|--------|---------------------|--|
| 1N5059 | 140 V | 200 V |
| 1N5060 | 280 V | 400 V |
| 1N5061 | 420 V | 600 V |
| 1N5062 | 560 V | 800 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage at 1.0 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 5.0 μ A |
| Maximum Reverse Current at 75°C | 100 μ A |
| Typical Reverse Recovery Time — Measured with $I_F = 0.5$ A, $I_R = 1.0$ A, $i_{rr} = 0.25$ A | 2 μ s |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 20 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | −65 to +175°C |
| Storage Temperature Range | −65 to +175°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





1 A Glass Rectifier


50 to 1000 V

G1
Series

VOLTAGE RATINGS

| Type | Maximum Forward Voltage at 1.0 A _{DC} | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|------|--|---------------------|--|
| G1A | 1.2 V | 35 V | 50 V |
| G1B | 1.2 V | 70 V | 100 V |
| G1D | 1.1 V | 140 V | 200 V |
| G1G | 1.1 V | 280 V | 400 V |
| G1J | 1.1 V | 420 V | 600 V |
| G1K | 1.1 V | 560 V | 800 V |
| G1M | 1.1 V | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Reverse Current at 25°C | 1.0 μ A |
| Maximum Reverse Current at 100°C | 100 μ A |
| Typical Reverse Recovery Time -- Measured with $I_F = 0.5$ A, $I_R = 1.0$ A, $t_r = 0.25$ A | 2 μ s |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 14 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +300°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 -- Typical forward characteristic





Fig. 2 -- Forward derating curve





2 A Glass Rectifier


50 to 1000 V

G2
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|------|---------------------|--|
| G2A | 35 V | 50 V |
| G2B | 70 V | 100 V |
| G2D | 140 V | 200 V |
| G2G | 280 V | 400 V |
| G2J | 420 V | 600 V |
| G2K | 560 V | 800 V |
| G2M | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 2 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage at 2.0 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 0.2 μ A |
| Maximum Reverse Current at 100°C | 10 μ A |
| Maximum Reverse Recovery Time – Measured with $I_F = 0.5$ A, $I_R = 1.0$ A, $i_{rr} = 0.25$ A | 2 μ s |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 14 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +300°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





3 A Glass Rectifier


200 to 800 V

1N5624
thru
1N5627

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|--------|---------------------|--|
| 1N5624 | 140 V | 200 V |
| 1N5625 | 280 V | 400 V |
| 1N5626 | 420 V | 600 V |
| 1N5627 | 560 V | 800 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 3 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 125 A |
| Maximum Forward Voltage at 3.0 A _{DC} | 1.0 V |
| Maximum Reverse Current at 25°C | 1.0 μA |
| Maximum Reverse Current at 100°C | 100 μA |
| Typical Reverse Recovery Time – Measured with I _F = 0.5 A, I _R = 1.0 A, i _{rr} = 0.25 A | 3 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 30 pF |
| Typical Thermal Resistance | 35°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +300°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





3 A Glass Rectifier

50 to 1000 V


G3
Series

VOLTAGE RATINGS

| Type | Maximum Forward Voltage at 3.0 A _{DC} | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|------|--|---------------------|--|
| G3A | 1.2 V | 35 V | 50 V |
| G3B | 1.2 V | 70 V | 100 V |
| G3D | 1.1 V | 140 V | 200 V |
| G3G | 1.1 V | 280 V | 400 V |
| G3J | 1.1 V | 420 V | 600 V |
| G3K | 1.1 V | 560 V | 800 V |
| G3M | 1.1 V | 700 V | 1000 V |

CASE OUTLINE

GPR-3



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 3 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 125 A |
| Maximum Reverse Current at 25°C | 1 μ A |
| Maximum Reverse Current at 100°C | 100 μ A |
| Typical Reverse Recovery Time – Measured with $I_F = 0.5$ A, $I_R = 1.0$ A, $i_{rr} = 0.25$ A | 3 μ s |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 30 pF |
| Typical Thermal Resistance | 25°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +300°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Glass Rectifier


200 to 1000 V / Fast Recovery

1N4942
thru
1N4948

VOLTAGE AND REVERSE RECOVERY RATINGS

| Type | Maximum Reverse Recovery Time $I_F = .5 \text{ A}$, $I_R = 1 \text{ A}$, $i_{rr} = .25 \text{ A}$ | Maximum Recurrent Peak Reverse Voltage |
|--------|--|---|
| 1N4942 | 150 ns | 200 V |
| 1N4943 | 150 ns | 300 V |
| 1N4944 | 150 ns | 400 V |
| 1N4945 | 150 ns | 500 V |
| 1N4946 | 150 ns | 600 V |
| 1N4947 | 250 ns | 800 V |
| 1N4948 | 500 ns | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|-------------------|
| Maximum Average Forward Rectified Current | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 30 A |
| Maximum Forward Voltage at 1 A _{DC} | 1.3 V |
| Maximum Reverse Current at 25°C | 1.0 μA |
| Maximum Reverse Current at 100°C | 100 μA |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 20 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +200°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





1 A Glass Rectifier


200 to 1000 V

1N5614
even thru
1N5622

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|--------|---------------------|--|
| 1N5614 | 140 V | 200 V |
| 1N5616 | 280 V | 400 V |
| 1N5618 | 420 V | 600 V |
| 1N5620 | 560 V | 800 V |
| 1N5622 | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|----------------|
| Maximum Average Forward Rectified Current | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage at 1.0 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 0.5 μA |
| Maximum Reverse Current at 100°C | 25 μA |
| Typical Reverse Recovery Time – Measured with I _F = 0.5 A, I _R = 1.0 A, i _{rr} = 0.25 A | 2 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 12.0 V _{DC} | 20 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | –193 to +200°C |
| Storage Temperature Range | –193 to +200°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Glass Rectifier


200 to 1000 V / Fast Recovery

1N5615
odd thru
1N5623

VOLTAGE AND REVERSE RECOVERY RATINGS

| Type | Maximum Reverse Recovery Time $I_F = .5\text{ A}$, $I_R = 1\text{ A}$, $t_{rr} = .25\text{ A}$ | Maximum Recurrent Peak Reverse Voltage |
|--------|---|---|
| 1N5615 | 150 ns | 200 V |
| 1N5617 | 150 ns | 400 V |
| 1N5619 | 250 ns | 600 V |
| 1N5621 | 300 ns | 800 V |
| 1N5623 | 500 ns | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|----------------|
| Maximum Average Forward Rectified Current | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage at 1.0 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 0.5 μA |
| Maximum Reverse Current at 100°C | 25 μA |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 20 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | −193 to +200°C |
| Storage Temperature Range | −193 to +200°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Glass Rectifier


50 to 1000 V / Fast Recovery

RG1
Series

VOLTAGE AND REVERSE RECOVERY RATINGS

| Type | Maximum Reverse Recovery Time $I_F = .5\text{ A}$, $I_R = 1\text{ A}$, $t_{rr} = .25\text{ A}$ | Maximum Recurrent Peak Reverse Voltage |
|------|---|---|
| RG1A | 150 ns | 50 V |
| RG1B | 150 ns | 100 V |
| RG1D | 150 ns | 200 V |
| RG1G | 150 ns | 400 V |
| RG1J | 150 ns | 600 V |
| RG1K | 250 ns | 800 V |
| RG1M | 500 ns | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 30 A |
| Maximum Forward Voltage at 1.0 A _{DC} | 1.3 V |
| Maximum Reverse Current at 25°C | 1.0 μA |
| Maximum Reverse Current at 100°C | 100 μA |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 20 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +300°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





3 A Glass Rectifier

50 to 1000 V / Fast Recovery


RG3
Series

VOLTAGE AND REVERSE RECOVERY RATINGS

CASE OUTLINE

| Type | Maximum Reverse Recovery Time $I_F = .5 \text{ A}$, $I_R = 1 \text{ A}$, $t_{rr} = .25 \text{ A}$ | Maximum Recurrent Peak Reverse Voltage |
|------|--|---|
| RG3A | 150 ns | 50 V |
| RG3B | 150 ns | 100 V |
| RG3D | 150 ns | 200 V |
| RG3G | 150 ns | 400 V |
| RG3J | 150 ns | 600 V |
| RG3K | 250 ns | 800 V |
| RG3M | 500 ns | 1000 V |

GPR-3



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|-------------------|
| Maximum Average Forward Rectified Current | 3 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 100 A |
| Maximum Forward Voltage at 3.0 A _{DC} | 1.3 V |
| Maximum Reverse Current at 25°C | 2.0 μA |
| Maximum Reverse Current at 100°C | 100 μA |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 35 pF |
| Typical Thermal Resistance | 25°C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +300°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





1.5 A Glass Rectifier


Clamper/Damper

CG1
DG1

VOLTAGE AND RECOVERY RATINGS

| Type | Typical Forward Recovery Voltage | Maximum Reverse Recovery Time | Maximum Recurrent Peak Reverse Voltage |
|------|----------------------------------|-------------------------------|--|
| CG1 | 30 V | 15 μ s | 1400 V |
| DG1 | 25 V | 20 μ s | 1400 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 1.5 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Reverse Current at 25°C | 5.0 μ A |
| Maximum Reverse Current at 125°C | 100 μ A |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | -65 to +125°C |
| Storage Temperature Range | -65 to +200°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1.5 A Glass Rectifier

1500 V

BY228

VOLTAGE RATINGS

Type


BY228

Maximum Recurrent
Peak Reverse Voltage

1500 V

CASE OUTLINE

GPR-3



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 2.5 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 100 A |
| Maximum Forward Voltage at 5 A _{DC} | 1.5 V |
| Maximum Reverse Current at 25°C | 5 µA |
| Maximum Reverse Current at 125°C | 200 µA |
| Maximum Reverse Recovery Time | 20 µs |
| Typical Thermal Resistance | 25 °C/W |
| Operating Temperature Range | -65 to +140°C |
| Storage Temperature Range | -65 to +200°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





HV Glass Rectifier


2000 to 5000 V

HVG
Series

VOLTAGE RATINGS

| Type | Maximum Forward Voltage at 0.1 A _{DC} | Maximum Recurrent Peak Reverse Voltage |
|------|--|--|
| HVG2 | 3.0 V | 2000 V |
| HVG3 | 4.0 V | 3000 V |
| HVG4 | 6.0 V | 4000 V |
| HVG5 | 8.0 V | 5000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 0.3 to 0.15 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 25 to 8 A |
| Maximum Reverse Current at 25°C | 5 μA |
| Maximum Reverse Current at 100°C | 25 μA |
| Typical Thermal Resistance | 50 °C/W |
| Operating Temperature Range | -65 to +150°C |
| Storage Temperature Range | -65 to +200°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve






LIST OF APPROVED JAN-JANTX DEVICES

| Unit | Package | | JANTX AVAILABLE | Package |
|--|--|-----|-----------------|---------|
| | GPR | GPD | | |
| 1N483B 1N485B 1N486B 1N645 1N647 1N649 1N645-1 1N647-1 1N649-1 1N3611 1N3612 1N3613 1N3614 1N3957 1N4245 1N4246 1N4247 1N4248 1N4249 1N4942 1N4944 1N4946 1N4947 1N4948 1N5624* 1N5625* 1N5626* 1N5627* | | | | |


Environmental test conditions and further information see page 107.

GRAPHIC REPRESENTATION OF SUPERECTIFIER'S SUPERIORITY


GI SUPERECTIFIER




DOUBLE NAIL HEAD



DOUBLE SLUG



DOUBLE PLUG





Superectifier

0.4 to 3 Amperes

50 V
to
1600 V

Introduction

No other 1 to 3 Amp rectifier – plastic, glass, or metal – can match (or even approach) SUPERECTIFIER's combination of features ... the result of General Instrument's unique glass-plastic construction:

- Brazed at greater than 600°C at both leads and cell – eliminates all soft solders
- Exclusive UL recognized *flame-retardant* epoxy molding compound rated 94V-0, the highest available
- Patented glass passivation
- Reliability proved equal to military requirements
- Hermetically sealed construction
- Cost effective construction


General instrument's SUPERECTIFIER is exactly that ... a super rectifier. There is nothing else in the world like it.

In cell construction, most other rectifiers rated up to 3 Amps are soft soldered or are only pressure contacted. SUPERECTIFIER is made into an entirely solid unit with its leads and cell brazed at temperatures greater than 600°C. All other rectifiers fail at half that temperature.

In cell protection, conventional plastic rectifiers use either varnish, silicon rubber or a thin film of silicon oxide to protect the junction. SUPERECTIFIER uses a patented glass passivation to seal its junction hermetically.

In device encapsulation, again SUPERECTIFIER is the only one that won't go up in flames. It is one of the few rectifier using an exclusive flame-RETARDANT molding compound, rated UL 94V-0, the highest rating available. Other plastic rectifiers use flame-ENHANCING compounds. Here again, SUPERECTIFIER's superiority is manifest. With this construction it exceeds environmental standards of MIL-STD-19500/228.

In summary, SUPERECTIFIER is the world's only rectifier with totally brazed construction, with a patented glass passivated junction, and with flame-retardant molding encapsulation.



**Glass Passivated Junction Plastic Rectifiers 0.4 to 1.75 AMP**

Types: 1N645GP thru 1N649GP
1N3611GP thru 1N3614GP
1N4001GP thru 1N4007GP
1N4245GP thru 1N4249GP
1N5059GP thru 1N5062GP
1N5391GP thru 1N5399GP
GP10A thru GP10M
GP15A thru GP15M
BY126GP and BY127GP
BY226GP and BY227GP
BY133GP thru BY135GP

Features:

- High Temperature Metallurgically Bonded
- Plastic Package has Underwriters Laboratory Classification 94V-0
- Glass Passivated Junction
- No Thermal Runaway
- Exceeds Environmental Standards of MIL-STD-19500/228
- High Temperature Soldering Guaranteed 350°C / 10 Second / 10 mm Lead Length at 2.25 kg Tension
- Tin Plated Axial Leads, Solderable per MIL-STD-202/208

Glass Passivated Junction Plastic Rectifiers 2 to 3 AMP

Types: 1N5624GP thru 1N5627GP
GP20A thru GP20M
GP30A thru GP30M

Features:

- High Temperature Metallurgically Bonded
- Plastic Package has Underwriters Laboratory Classification 94V-0
- Glass Passivated Junction in DO 27 Package
- 2.0 Ampere (GP20) and 3.0 Ampere Operation (GP30) at 55°C Ambient Temperature with no Thermal Runaway
- Typical I_R less than 1 μ A
- Exceeds Environmental Standards of MIL-STD-19500/228
- Tin Plated Axial Leads, Solderable per MIL-STD-202/208
- High Temperature Soldering Guaranteed 350°C / 10 Second / 10 mm Lead Length at 2.25 kg Tension

Glass Passivated Junction Plastic Fast Recovery Rectifiers 0.4 to 3 AMP

Types: 1N4942GP thru 1N4948GP
 RGP01-10 thru RGP01-16
 RGP10A thru RGP10M
 RGP15A thru RGP15M
 RGP30A thru RGP30M
 BA157GP thru BA159GP
 BY206GP and BY207GP

- Features:
- High Temperature Metallurgically Bonded
 - High Rectification Efficiency to 100 kHz
 - No Thermal Runaway
 - Exceeds Environmental Standards of MIL-STD-19500/228
 - Includes all Advantages of the SUPERECTIFIER Design
 - Tin Plated Axial Leads, Solderable per MIL-STD-202/208

Glass Passivated Junction Plastic Controlled Avalanche Rectifiers 1.5 AMP

Type: AGP15-200 thru AGP15-800

- Features:
- High Capability for Absorption of Peak Reverse Power
 - Designed for Rectifier Applications where Inductive Loads may be switched on and off periodically
 - All Advantages of the SUPERECTIFIER Design
 - Tin Plated Axial Leads, Solderable per MIL-STD-202/208

Glass Passivated Junction Plastic Zener Rectiflers 160 to 200 VOLTS

Types: ZGP10-160 thru ZGP10-200

- Features:
- Reliable SUPERECTIFIER Construction
 - Zener Voltages available in 5 %, 10 % and 20 % Tolerances
 - High Capability for Absorption of Peak Reverse Power
 - Tin Plated Axial Leads, Solderable per MIL-STD-202/208



QUICK GUIDE TO SUPERECTIFIERS

| TYPE | 1N645GP thru 1N649GP | BY206GP* thru BY207GP* | BA157GP* thru BA159GP* | GP10A thru GP10M | 1N3611GP thru 1N3614GP | 1N4001GP thru 1N4007GP | 1N4245GP thru 1N4249GP | 1N4942GP* thru 1N4948GP* | RGP10A* thru RGP10M* | BY133GP thru BY135GP | 1N5059GP thru 1N5062GP |
|---------------------------|----------------------------|------------------------------|------------------------------|------------------------|------------------------------|------------------------------|------------------------------|--------------------------------|----------------------------|----------------------------|------------------------------|
| CASE | DO41 | DO41 | DO41 | DO41 | DO41 | DO41 | DO41 | DO41 | DO41 | DO15 | DO15 |
| I _o (A) | 0.4 | 0.4 | 0.5 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
| @T _A (°C) | 25 | 55 | 55 | 55 | 100 | 75 | 55 | 55 | 55 | 75 | 55 |
| V _R = 50 (V) | | | | GP10A | | 1N4001GP | | | RGP10A | | |
| V _R = 100 (V) | | | | GP10B | | 1N4002GP | | | RGP10B | | |
| V _R = 200 (V) | 1N645GP | | | GP10D | 1N3611GP | 1N4003GP | 1N4245GP | 1N4942GP | RGP10D | BY135GP | 1N5059GP |
| V _R = 300 (V) | 1N646GP | | | | | | | 1N4943GP | | | |
| V _R = 400 (V) | 1N647GP | BY206GP | BA157GP | GP10G | 1N3612GP | 1N4004GP | 1N4246GP | 1N4944GP | RGP10G | | 1N5060GP |
| V _R = 500 (V) | 1N648GP | | | | | | | 1N4945GP | | | |
| V _R = 600 (V) | 1N649GP | BY207GP | BA158GP | GP10J | 1N3613GP | 1N4005GP | 1N4247GP | 1N4946GP | RGP10J | BY134GP | 1N5061GP |
| V _R = 800 (V) | | | BA159DGP | GP10K | 1N3614GP | 1N4006GP | 1N4248GP | 1N4947GP | RGP10K | | 1N5062GP |
| V _R = 1000 (V) | | | BA159GP | GP10M | 1N3957GP | 1N4007GP | 1N4249GP | 1N4948GP | RGP10M | | |
| V _R > 1000 (V) | | | | | | | | | | BY133GP | |
| SURGE (A) | 20 | 15 | 20 | 30 | 30 | 30 | 25 | 30 | 30 | 50 | 50 |
| V _F (V) | 1.2 | 1.3 | 1.3 | 1.1 | 1.1 | 1.1 | 1.2 | 1.3 | 1.3 | 1.2 | 1.2 |
| Page | 55 | 70 | 71 | 59 | 56 | 57 | 58 | 72 | 73 | 61 | 60 |



QUICK GUIDE TO SUPERECTIFIERS

| TYPE | AGP15-200 thru AGP15-800 | GP15A thru GP15M | 1N5391GP thru 1N5399GP | RGP15A* thru RGP15M* | BY126GP thru BY127GP | BY226GP thru BY227GP | GP20A thru GP20M | 1N5624GP thru 1N5627GP | GP30A thru GP30M | RGP30A* thru RGP30M* |
|---------------------------|--------------------------------|------------------------|------------------------------|----------------------------|----------------------------|----------------------------|------------------------|------------------------------|------------------------|----------------------------|
| CASE | DO15 | DO15 | DO15 | DO15 | DO27 | DO27 | DO27 | DO27A | DO27A | DO27A |
| I _o (A) | 1.5 | 1.5 | 1.5 | 1.5 | 1.5 | 1.75 | 2.0 | 3.0 | 3.0 | 3.0 |
| @T _A (°C) | 55 | 55 | 70 | 55 | 55 | 55 | 55 | 70 | 55 | 55 |
| V _R = 50 (V) | | GP15A | 1N5391GP | RGP15A | | | GP20A | | GP30A | RGP30A |
| V _R = 100 (V) | | GP15B | 1N5392GP | RGP15B | | | GP20B | | GP30B | RGP30B |
| V _R = 200 (V) | AGP15-200 | GP15D | 1N5393GP | RGP15D | | | GP20D | 1N5624GP | GP30D | RGP30D |
| V _R = 300 (V) | | | 1N5394GP | | | | | | | |
| V _R = 400 (V) | AGP15-400 | GP15G | 1N5395GP | RGP15G | | | GP20G | 1N5625GP | GP30G | RGP30G |
| V _R = 500 (V) | | | 1N5396GP | | | | | | | |
| V _R = 600 (V) | AGP15-600 | GP15J | 1N5397GP | RGP15J | BY126GP | BY226GP | GP20J | 1N5626GP | GP30J | RGP30J |
| V _R = 800 (V) | AGP15-800 | GP15K | 1N5398GP | RGP15K | | | GP20K | 1N5627GP | GP30K | RGP30K |
| V _R = 1000 (V) | | GP15M | 1N5399GP | RGP15M | | | GP20M | | GP30M | RGP30M |
| V _R > 1000 (V) | | | | | BY127GP | BY227GP | | | | |
| SURGE (A) | 50 | 50 | 50 | 50 | 50 | 60 | 65 | 125 | 125 | 125 |
| V _F (V) | 1.2 | 1.1 | 1.4 | 1.3 | 1.3 | 1.3 | 1.1 | 1.0 | 1.1 | 1.3 |
| Page | 76 | 63 | 62 | 74 | 64 | 65 | 66 | 67 | 68 | 75 |

* Fast Recovery



0.4 A Superectifier

225 to 600 V


1N645GP
thru
1N649GP

VOLTAGE RATINGS

| Type | Maximum Recurrent Peak Reverse Voltage |
|---------|---|
| 1N645GP | 225 V |
| 1N646GP | 300 V |
| 1N647GP | 400 V |
| 1N648GP | 500 V |
| 1N649GP | 600 V |

CASE OUTLINE

DO-41



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 400 mA |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 20 A |
| Maximum Forward Voltage at 0.4 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 0.5 μA |
| Maximum Reverse Current at 150°C | 25 μA |
| Typical Reverse Recovery Time – Measured with I _F = 20 mA, i _{rr} = 1 mA | 20 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Superelectifier

200 to 1000 V


1N3611GP
1N3612GP
1N3613GP
1N3614GP
1N3957GP

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|----------|---------------------|--|
| 1N3611GP | 140 V | 200 V |
| 1N3612GP | 280 V | 400 V |
| 1N3613GP | 420V | 600 V |
| 1N3614GP | 560 V | 800 V |
| 1N3957GP | 700 V | 1000 V |

CASE OUTLINE

DO-41



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 30 A |
| Maximum Forward Voltage at 1.0 A _{DC} | 1.0 V |
| Maximum Reverse Current at 25°C | 1.0 μ A |
| Maximum Reverse Current at 150°C | 300 μ A |
| Typical Reverse Recovery Time – Measured with $I_F = 20$ mA, $i_{rr} = 1$ mA | 20 μ s |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Superrectifier

50 to 1000 V


1N4001GP
thru
1N4007GP

VOLTAGE RATINGS

| Type | Maximum Forward Voltage at 1.0 A _{DC} | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|----------|--|---------------------|--|
| 1N4001GP | 1.1 V | 35 V | 50 V |
| 1N4002GP | 1.1 V | 70 V | 100 V |
| 1N4003GP | 1.1 V | 140 V | 200 V |
| 1N4004GP | 1.1 V | 280 V | 400 V |
| 1N4005GP | 1.1 V | 420 V | 600 V |
| 1N4006GP | 1.2 V | 560 V | 800 V |
| 1N4007GP | 1.2 V | 700 V | 1000 V |

CASE OUTLINE

DO-41



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 30 A |
| Maximum Reverse Current at 25°C | 5 μ A |
| Maximum Reverse Current at 125°C | 50 μ A |
| Typical Reverse Recovery Time – Measured with $I_F = 20$ mA, $I_R = 1$ mA | 20 μ s |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Superectifier

200 to 1000 V


1N4245GP
thru
1N4249GP

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|----------|---------------------|--|
| 1N4245GP | 140 V | 200 V |
| 1N4246GP | 280 V | 400 V |
| 1N4247GP | 420 V | 600 V |
| 1N4248GP | 560 V | 800 V |
| 1N4249GP | 700 V | 1000 V |

CASE OUTLINE

DO-41



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 25 A |
| Maximum Forward Voltage at 1.0 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 1.0 μA |
| Maximum Reverse Current at 125°C | 25 μA |
| Typical Reverse Recovery Time – Measured with I _F = 20 mA, i _{rr} = 1 mA | 20 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Superectifier

50 to 1000 V

GP10


Series

VOLTAGE RATINGS

| Type | Maximum Forward Voltage at 1.0 A _{DC} | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|-------|--|---------------------|--|
| GP10A | 1.1 V | 35 V | 50 V |
| GP10B | 1.1 V | 70 V | 100 V |
| GP10D | 1.1 V | 140 V | 200 V |
| GP10G | 1.1 V | 280 V | 400 V |
| GP10J | 1.1 V | 420 V | 600 V |
| GP10K | 1.2 V | 560 V | 800 V |
| GP10M | 1.2 V | 700 V | 1000 V |

CASE OUTLINE

DO-41



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 30 A |
| Maximum Reverse Current at 25°C | 5 μ A |
| Maximum Reverse Current at 55°C | 100 μ A |
| Typical Reverse Recovery Time – Measured with $I_F = 20$ mA, $i_{rr} = 1$ mA | 20 μ s |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Superectifier

200 to 800 V


1N5059GP
thru
1N5062GP

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|----------|---------------------|--|
| 1N5059GP | 140 V | 200 V |
| 1N5060GP | 280 V | 400 V |
| 1N5061GP | 420 V | 600 V |
| 1N5062GP | 560 V | 800 V |

CASE OUTLINE

DO-15



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage at 1.0 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 5.0 μA |
| Maximum Reverse Current at 75°C | 100 μA |
| Typical Reverse Recovery Time — Measured with $I_F = 0.5$ A, $I_R = 1.0$ A, $t_r = 0.25$ A | 2 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 20 pF |
| Typical Thermal Resistance | 40°C/W |
| Operating Temperature Range | −65 to +175°C |
| Storage Temperature Range | −65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





1 A Superectifier

200 to 1300 V


BY133GP
thru
BY135GP

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|---------|---------------------|--|
| BY133GP | 910 V | 1300 V |
| BY134GP | 420 V | 600 V |
| BY135GP | 140 V | 200 V |

CASE OUTLINE

DO-15



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage at 2.0 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 5.0 μA |
| Maximum Reverse Current at 75°C | 100 μA |
| Typical Reverse Recovery Time – Measured with I _F = 0.5 A, I _R = 1.0 A, i _{rr} = 0.25 A | 2.5 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 25 pF |
| Typical Thermal Resistance | 40°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1,5 A Superectifier


50 to 1000 V

1N5391GP
thru
1N5399GP

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|----------|---------------------|--|
| 1N5391GP | 35 V | 50 V |
| 1N5392GP | 70 V | 100 V |
| 1N5393GP | 140 V | 200 V |
| 1N5394GP | 210 V | 300 V |
| 1N5395GP | 280 V | 400 V |
| 1N5396GP | 350 V | 500 V |
| 1N5397GP | 420 V | 600 V |
| 1N5398GP | 560 V | 800 V |
| 1N5399GP | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1.5 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage at 1.5 A _{DC} | 1.4 V |
| Maximum Reverse Current at 25°C | 5 µA |
| Maximum Reverse Current at 150°C | 300 µA |
| Typical Reverse Recovery Time – Measured with I _F = 0.5 A, I _R = 1.0 A, i _{rr} = 0.25 A | 2 µs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 25 pF |
| Typical Thermal Resistance | 40°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1,5 A Superrectifier


50 to 1000 V

GP15
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|-------|---------------------|--|
| GP15A | 35 V | 50 V |
| GP15B | 70 V | 100 V |
| GP15D | 140 V | 200 V |
| GP15G | 280 V | 400 V |
| GP15J | 420 V | 600 V |
| GP15K | 560 V | 800 V |
| GP15M | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 1.5 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage at 1.5 A _{DC} | 1.1 V |
| Maximum Reverse Current at 25°C | 5 μA |
| Maximum Reverse Current at 55°C | 100 μA |
| Typical Reverse Recovery Time — Measured with $I_F = 0.5$ A, $I_R = 1.0$ A, $i_{rr} = 0.25$ A | 2 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 25 pF |
| Typical Thermal Resistance | 40°C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





1.5 A Superectifier


650 to 1250 V

BY126GP
BY127GP

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|---------|---------------------|--|
| BY126GP | 450 V | 650 V |
| BY127GP | 850 V | 1250 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1.5 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage at 5.0 A _{DC} | 1.5 V |
| Maximum Reverse Current at 25°C | 5.0 μA |
| Maximum Reverse Current at 55°C | 100 μA |
| Typical Reverse Recovery Time – Measured with I _F = 0.5 A, I _R = 1.0 A, i _{rr} = 0.25 A | 2.5 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 40 pF |
| Typical Thermal Resistance | 30°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1.75 A Superectifier

650 to 1250 V


BY226GP

BY227GP

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|---------|---------------------|--|
| BY226GP | 450 V | 650 V |
| BY227GP | 850 V | 1250 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1.75 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 60 A |
| Maximum Forward Voltage at 5.0 A _{DC} | 1.5 V |
| Maximum Reverse Current at 25°C | 5.0 μA |
| Maximum Reverse Current at 55°C | 100 μA |
| Typical Reverse Recovery Time – Measured with I _F = 0.5 A, I _R = 1.0 A, I _{rr} = 0.25 A | 2.5 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 40 pF |
| Typical Thermal Resistance | 30°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





2 A Superrectifier


50 to 1000 V

GP20
Series

VOLTAGE RATINGS

| Type | Maximum Forward Voltage at 2.0 A _{DC} | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|-------|--|---------------------|--|
| GP20A | 1.2 V | 35 V | 50 V |
| GP20B | 1.2 V | 70 V | 100 V |
| GP20D | 1.1 V | 140 V | 200 V |
| GP20G | 1.1 V | 280 V | 400 V |
| GP20J | 1.1 V | 420 V | 600 V |
| GP20K | 1.1 V | 560 V | 800 V |
| GP20M | 1.1 V | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 2.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 65 A |
| Maximum Reverse Current at 25°C | 5 μ A |
| Maximum Reverse Current at 55°C | 100 μ A |
| Typical Reverse Recovery Time – Measured with $I_F = 0.5$ A, $I_R = 1.0$ A, $t_{rr} = 0.25$ A | 2.5 μ s |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 40 pF |
| Typical Thermal Resistance | 30°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





3 A Superectifier


200 to 800 V

1N5624GP
thru
1N5627GP

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|----------|---------------------|--|
| 1N5624GP | 140 V | 200 V |
| 1N5625GP | 280 V | 400 V |
| 1N5626GP | 420 V | 600 V |
| 1N5627GP | 560 V | 800 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 3.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 125 A |
| Maximum Forward Voltage at 3.0 A _{DC} | 1.0 V |
| Maximum Reverse Current at 25°C | 5.0 µA |
| Maximum Reverse Current at 100°C | 100 µA |
| Typical Reverse Recovery Time – Measured with I _F = 0.5 A, I _R = 1.0 A, i _{rr} = 0.25 A | 3 µs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 60 pF |
| Typical Thermal Resistance | 25°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





3 A Superrectifier


50 to 1000 V

GP30
Series

VOLTAGE RATINGS

| Type | Maximum Forward Voltage at 3.0 A _{DC} | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|-------|--|---------------------|--|
| GP30A | 1.2 V | 35 V | 50 V |
| GP30B | 1.2 V | 70 V | 100 V |
| GP30D | 1.1 V | 140 V | 200 V |
| GP30G | 1.1 V | 280 V | 400 V |
| GP30J | 1.1 V | 420 V | 600 V |
| GP30K | 1.1 V | 560 V | 800 V |
| GP30M | 1.1 V | 720 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 3 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 125 A |
| Maximum Reverse Current at 25°C | 5 µA |
| Maximum Reverse Current at 55°C | 100 µA |
| Typical Reverse Recovery Time – Measured with $I_F = 0.5$ A, $I_R = 1.0$ A, $i_{rr} = 0.25$ A | 3 µs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 60 pF |
| Typical Thermal Resistance | 25°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





Photoflash Rectifier

1000 to 1600 V


RGP01
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|----------|---------------------|--|
| RGP01-10 | 700 V | 1000 V |
| RGP01-12 | 840 V | 1200 V |
| RGP01-14 | 980 V | 1400 V |
| RGP01-16 | 1120 V | 1600 V |

CASE OUTLINE

DO-41



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 100 mA |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 20 A |
| Maximum Forward Voltage at 0.1 A _{DC} | 1.5 V |
| Maximum Reverse Current at 25°C | 5 μA |
| Maximum Reverse Current at 55°C | 100 μA |
| Maximum Reverse Recovery Time – Measured with I _F = 10 mA, I _R = 10 mA, i _{rr} = 1 mA | 1 μs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





0.4 A Superectifier


350 and 600 V / Fast Recovery

BY206GP
BY207GP

VOLTAGE RATINGS

| Type | Maximum Recurrent Peak Reverse Voltage |
|---------|---|
| BY206GP | 350 V |
| BY207GP | 600 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 0.4 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 15 A |
| Maximum Forward Voltage at 2.0 A _{DC} | 1.5 V |
| Maximum Reverse Current at 25°C | 5.0 µA |
| Maximum Reverse Current at 100°C | 100 µA |
| Typical Reverse Recovery Time – Measured with I _F = 0.4 A, V _R = 50 V | 1 µs |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | –65 to +175°C |
| Storage Temperature Range | –65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





0.5 A Superectifier

400 to 1000 V / Fast Recovery


BA157GP
thru
BA159GP

VOLTAGE AND REVERSE RECOVERY RATINGS

| Type | Maximum Reverse Recovery Time $I_F = .5 \text{ A}$, $I_R = 1 \text{ A}$, $t_{rr} = .25 \text{ A}$ | Maximum Recurrent Peak Reverse Voltage |
|----------|--|---|
| BA157GP | 150 ns | 400 V |
| BA158GP | 250 ns | 600 V |
| BA159DGP | 500 ns | 800 V |
| BA159GP | 500 ns | 1000 V |

CASE OUTLINE

DO-41



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 0.5 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 20 A |
| Maximum Forward Voltage at 1.0 A _{DC} | 1.5 V |
| Maximum Reverse Current at 25°C | 5.0 μA |
| Maximum Reverse Current at 55°C | 100 μA |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





1 A Superelectifier


200 to 1000 V / Fast Recovery

1N4942GP
thru
1N4948GP

VOLTAGE AND REVERSE RECOVERY RATINGS

| Type | Maximum Reverse Recovery Time $I_F = .5 \text{ A}, I_R = 1 \text{ A}, t_{rr} = .25 \text{ A}$ | Maximum Recurrent Peak Reverse Voltage |
|----------|--|---|
| 1N4942GP | 150 ns | 200 V |
| 1N4944GP | 150 ns | 400 V |
| 1N4946GP | 150 ns | 600 V |
| 1N4947GP | 250 ns | 800 V |
| 1N4948GP | 500 ns | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 25 A |
| Maximum Forward Voltage at 1.0 A _{DC} | 1.3 V |
| Maximum Reverse Current at 25°C | 1.0 μA |
| Maximum Reverse Current at 150°C | 200 μA |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





1 A Superectifier

50 to 1000 V / Fast Recovery


RGP10
Series

VOLTAGE AND REVERSE RECOVERY RATINGS

| Type | Maximum Reverse Recovery Time $I_F = .5 \text{ A}, I_R = 1 \text{ A}, i_{rr} = .25 \text{ A}$ | Maximum Recurrent Peak Reverse Voltage |
|--------|--|---|
| RGP10A | 150 ns | 50 V |
| RGP10B | 150 ns | 100 V |
| RGP10D | 150 ns | 200 V |
| RGP10G | 150 ns | 400 V |
| RGP10J | 250 ns | 600 V |
| RGP10K | 500 ns | 800 V |
| RGP10M | 500 ns | 1000 V |

CASE OUTLINE

DO-41



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|-------------------|
| Maximum Average Forward Rectified Current | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 30 A |
| Maximum Forward Voltage at 1 A _{DC} | 1.3 V |
| Maximum Reverse Current at 25°C | 5 μA |
| Maximum Reverse Current at 55°C | 100 μA |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 15 pF |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 -- Typical forward characteristic





Fig. 2 -- Forward derating curve





1,5 A Superectifier


50 to 1000 V / Fast Recovery

RGP15
Series

VOLTAGE AND REVERSE RECOVERY RATINGS

| Type | Maximum Reverse Recovery Time $I_F = .5 \text{ A}, I_R = 1 \text{ A}, I_{rr} = .25 \text{ A}$ | Maximum Recurrent Peak Reverse Voltage |
|--------|--|---|
| RGP15A | 150 ns | 50 V |
| RGP15B | 150 ns | 100 V |
| RGP15D | 150 ns | 200 V |
| RGP15G | 150 ns | 400 V |
| RGP15J | 250 ns | 600 V |
| RGP15K | 500 ns | 800 V |
| RGP15M | 500 ns | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------|
| Maximum Average Forward Rectified Current | 1.5 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage at 1.5 A _{DC} | 1.3 V |
| Maximum Reverse Current at 25°C | 5 μA |
| Maximum Reverse Current at 55°C | 100 μA |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 25 pF |
| Typical Thermal Resistance | 40°C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





3 A Superelectifier


50 to 1000 V / Fast Recovery

RGP30
Series

VOLTAGE AND REVERSE RECOVERY RATINGS

| Type | Maximum Reverse Recovery Time $I_F = .5 \text{ A}$, $I_R = 1 \text{ A}$, $i_{rr} = .25 \text{ A}$ | Maximum Recurrent Peak Reverse Voltage |
|--------|--|---|
| RGP30A | 150 ns | 50 V |
| RGP30B | 150 ns | 100 V |
| RGP30D | 150 ns | 200 V |
| RGP30G | 150 ns | 400 V |
| RGP30J | 250 ns | 600 V |
| RGP30K | 500 ns | 800 V |
| RGP30M | 500 ns | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|-------------------|
| Maximum Average Forward Rectified Current | 3 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 125 A |
| Maximum Forward Voltage at 3 A _{DC} | 1.3 V |
| Maximum Reverse Current at 25°C | 5 μA |
| Maximum Reverse Current at 55°C | 100 μA |
| Typical Junction Capacitance at 1.0 MHz and Reverse Voltage of 4.0 V _{DC} | 60 pF |
| Typical Thermal Resistance | 25°C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





1.5 A Superectifier


200 to 800 V / Avalanche

AGP15
Series

VOLTAGE RATINGS

| Type | Maximum Recurrent Peak Reverse Voltage | Min. Avalanche Breakdown Voltage | Max. Avalanche Breakdown Voltage |
|-----------|---|-------------------------------------|-------------------------------------|
| AGP15-200 | 200 V | 240 V | 500 V |
| AGP15-400 | 400 V | 450 V | 750 V |
| AGP15-600 | 600 V | 675 V | 1000 V |
| AGP15-800 | 800 V | 880 V | 1200 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 1.5 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage at 1.5 A | 1.1 V |
| Maximum Reverse Current at 25°C | 5.0 μ A |
| Maximum Reverse Current at 100°C | 100 μ A |
| Maximum Continuous Avalanche Power Dissipation | 500 mW |
| Maximum Peak Avalanche Power Dissipation 20 μ s Pulse | 500 W |
| Typical Thermal Resistance | 40°C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +175°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





Zener Superrectifier

160 to 200 V/1 Watt


**ZGP10
Series**

VOLTAGE AND DYNAMIC IMPEDANCE RATINGS

| Type | Maximum Dynamic Impedance | Reverse Current Measurement Voltage | Zener Voltage |
|------------------|---------------------------|-------------------------------------|---------------|
| ZGP10-160 | 1100 Ω | 120 V | 160 V |
| ZGP10-170 | 1200 Ω | 130 V | 170 V |
| ZGP10-180 | 1300 Ω | 140 V | 180 V |
| ZGP10-190 | 1400 Ω | 150 V | 190 V |
| ZGP10-200 | 1500 Ω | 160 V | 200 V |

CASE OUTLINE

DO-41



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

SUPERECTIFIER



| | |
|---|---------------|
| Maximum Average Forward Rectified Current | 1 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 30 A |
| Maximum Forward Voltage at 0.5 A _{DC} | 1.0 V |
| Maximum Reverse Current at 25°C | 0.5 μ A |
| Maximum Reverse Current at 100°C | 100 μ A |
| Maximum Non Recurrent Surge Power 20 μ s Pulse | 500 W |
| Typical Thermal Resistance | 50°C/W |
| Operating Temperature Range | −65 to +175°C |
| Storage Temperature Range | −65 to +175°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Non Recurrent Reverse Surge





Fig. 2 – Typical Reverse Characteristic





Bridge Rectifiers

0.5 to 35 Amperes

50 V
to
1000 V

Families of General Instrument Bridge Rectifiers

All types of rectifier cells, which are produced by GENERAL INSTRUMENT, are available in bridge configurations, molded in various plastic and metal packages.

The basic types of packages are

- Round Plastic Package (Fig. 1)
- IN-LINE Plastic Package (Fig. 2)
- Square Plastic/Metal Package for Chassis Mounting (Fig. 3)

These bridge families are available with different terminals, such as wire leads, FASTON or soldering lugs.




Fig. 1

| ITEM | DESCRIPTION |
|------|-----------------|
| 1 | Solder Preforms |
| 2 | Formed Leads |
| 3 | Case |
| 4 | Cell |

Round Bridge




Fig. 2

IN-LINE Bridge




Fig. 3

Chassis Mounted Bridge

Silicon Miniature Single-Phase Bridge Rectifiers 0.5 to 2 AMP

Types: WL005 (M) thru WL10 (M)
W005 (M) thru W10 (M)
2W005 thru 2W10
B40C500 (M) thru B250C500 (M)
B40C800 (M) thru B250C800 (M)
B40C1000 (M) thru B380C1000 (M)
B40C1500 thru B380C1500
B40C1500C thru B380C1500C

Features:

- Surge Overload Rating 50 and 100 Amperes Peak
- Ideal for Printed Circuit Board
- Reliable Low Cost Construction
- Silver Plated Copper Leads
- Available in Avalanche Characteristics

Silicon In-Line Single Phase Bridge Rectifiers 1.5 to 5 AMP

Types: KBP005 thru KBP10
2KBP005 thru 2KBP10
KBF005 thru KBF10
KBL005 thru KBL08
B40C3700/2200 thru B380C3700/2200
B40C5000/3300 thru B380C5000/3300

Features:

- Surge Overload Rating up to 200 Amperes Peak
- Ideal for Printed Circuit Board
- Reliable Low Cost Construction utilizing molded Plastic
- Available in Avalanche Characteristics
- Silver Plated Copper Leads

High Current Single Phase Bridge Rectifiers 3 to 35 AMP

Types: KBPC005 thru KBPC10 SUPERRECTIFIER Construction
KBPC1005 thru KBPC1110 SUPERRECTIFIER Construction
KBPC6005 thru KBPC610
KBPC6005t thru KBPC610t
KBPC8005 thru KBPC810 SUPERRECTIFIER Construction
KBPC10005 thru KBPC1010
KBPC25005 thru KBPC2510
KBPC35005 thru KBPC3510

Features:

- High Capability of Surge Overload Rating
- Insulated Case
- Low Forward Voltage Drop
- Tinned Copper Leads
- Simple Installation thru Screw hole
- Available in Avalanche and Fast Recovery Characteristics
- For all kind of DC Motors.



QUICK GUIDE TO BRIDGE RECTIFIERS

| I_o (A) | 1.0 | 1.5 | 1.5 | 2.0 | 2.0 | 2.5 | 4.0 | I_o (A) |
|------------------|-----------|-----------|---------|-------|---------|--------|--------|------------------|
| @ T_A (°C) | 50 | 25 | 50 | 25 | 50 | 50 | 50 | @ T_A (°C) |
| SURGE (A) | 30 | 50 | 50 | 50 | 50 | 150 | 200 | SURGE (A) |
| $V_R = 50$ (V) | WL005 (M) | W005 (M)* | KBP005* | 2W005 | 2KBP005 | KBF005 | KBL005 | $V_R = 50$ (V) |
| $V_R = 200$ (V) | WL02 (M) | W02 (M)* | KBP02 * | 2W02 | 2KBP02 | KBF02 | KBL02 | $V_R = 200$ (V) |
| $V_R = 400$ (V) | WL04 (M) | W04 (M)* | KBP04 * | 2W04 | 2KBP04 | KBF04 | KBL04 | $V_R = 400$ (V) |
| $V_R = 600$ (V) | WL06 (M) | W06 (M)* | KBP06 * | 2W06 | 2KBP06 | KBF06 | KBL06 | $V_R = 600$ (V) |
| $V_R = 800$ (V) | WL08 (M) | W08 (M)* | KBP08 * | 2W08 | 2KBP08 | KBF08 | KBL08 | $V_R = 800$ (V) |
| $V_R = 1000$ (V) | WL10 (M) | W10 (M)* | KBP10 * | 2W10 | 2KBP10 | KBF10 | KBL10 | $V_R = 1000$ (V) |
| Page | 87 | 88 | 90 | 89 | 91 | 92 | 93 | Page |

(M) indicates Miniature Package

* Also available in Avalanche Characteristic.



QUICK GUIDE TO BRIDGE RECTIFIERS

| I_o (A) | 3.0 | 3.0 | 6.0 | 6.0 | 8.0 | 10 | 25 | 35 | I_o (A) |
|------------------|-----------|------------|----------|-----------|------------|------------|------------|------------|------------------|
| @ T_C (°C) | 50 | 50 | 100 | 100 | 50 | 60 | 60 | 60 | @ T_C (°C) |
| SURGE (A) | 50 | 50 | 200 | 200 | 125 | 200 | 300 | 400 | SURGE (A) |
| $V_R = 50$ (V) | KBPC005 ■ | KBPC1005 ■ | KBPC6005 | KBPC6005t | KBPC8005 ■ | KBPC10-005 | KBPC25-005 | KBPC35-005 | $V_R = 50$ (V) |
| $V_R = 200$ (V) | KBPC02 ■ | KBPC102 ■ | KBPC602 | KBPC602 t | KBPC802 ■ | KBPC10-02 | KBPC25-02 | KBPC35-02 | $V_R = 200$ (V) |
| $V_R = 400$ (V) | KBPC04 ■ | KBPC104 ■ | KBPC604 | KBPC604 t | KBPC804 ■ | KBPC10-04 | KBPC25-04 | KBPC35-04 | $V_R = 400$ (V) |
| $V_R = 600$ (V) | KBPC06 ■ | KBPC106 ■ | KBPC606 | KBPC606 t | KBPC806 ■ | KBPC10-06 | KBPC25-06 | KBPC35-06 | $V_R = 600$ (V) |
| $V_R = 800$ (V) | KBPC08 ■ | KBPC108 ■ | KBPC608 | KBPC608 t | KBPC808 ■ | KBPC10-08 | KBPC25-08 | KBPC35-08 | $V_R = 800$ (V) |
| $V_R = 1000$ (V) | KBPC10 ■ | KBPC110 ■ | KBPC610 | KBPC610 t | KBPC810 ■ | KBPC10-10 | KBPC25-10 | KBPC35-10 | $V_R = 1000$ (V) |
| Page | 96 | 97 | 98 | 99 | 100 | 101 | 102 | 103 | Page |

■ SUPERECTIFIER construction also available in Avalanche and Fast Recovery Characteristics.



QUICK GUIDE TO BRIDGE RECTIFIERS

| I_o (A) | 0.5 | 0.8 | 1.0 | 1.5 | 1.5 | 3.7 | 5.0 | I_o (A) |
|---------------------|--------------|--------------|---------------|-----------|-------------|----------------|----------------|---------------------|
| @ T_A (°C) | 45 | 45 | 45 | 45 | 45 | 45 | 45 | @ T_A (°C) |
| SURGE (A) | 30 | 45 | 45 | 45 | 100 | 100 | 200 | SURGE (A) |
| $V_{RMS} = 40$ (V) | B40C500 (M) | B40C800 (M) | B40C1000 (M) | B40C1500 | B40C1500 C | B40C3700/2200 | B40C5000/3300 | $V_{RMS} = 40$ (V) |
| $V_{RMS} = 80$ (V) | B80C500 (M) | B80C800 (M) | B80C1000 (M) | B80C1500 | B80C1500 C | B80C3700/2200 | B80C5000/3300 | $V_{RMS} = 80$ (V) |
| $V_{RMS} = 125$ (V) | B125C500 (M) | B125C800 (M) | B125C1000 (M) | B125C1500 | B125C1500 C | B125C3700/2200 | B125C5000/3300 | $V_{RMS} = 125$ (V) |
| $V_{RMS} = 250$ (V) | B250C500 (M) | B250C800 (M) | B250C1000 (M) | B250C1500 | B250C1500 C | B250C3700/2200 | B250C5000/3300 | $V_{RMS} = 250$ (V) |
| $V_{RMS} = 380$ (V) | B380C500 (M) | B380C800 (M) | B380C1000 (M) | B380C1500 | B380C1500 C | B380C3700/2200 | B380C5000/3300 | $V_{RMS} = 380$ (V) |
| Page | 82 | 83 | 84 | 85 | 86 | 94 | 95 | Page |

(M) indicates Miniature Package



0.5 A Bridge Rectifier

40 to 380 V_{RMS}


B 40C 500
B 80C 500
B125C 500
B250C 500
B380C 500

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|---------------|---------------------|--|
| B 40C 500 (M) | 40 V | 100 V |
| B 80C 500 (M) | 80 V | 190 V |
| B125C 500 (M) | 125 V | 300 V |
| B250C 500 (M) | 250 V | 600 V |
| B380C 500 (M) | 380 V | 900 V |

M Indicates Miniature Package

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|----------------------|
| Maximum Average Forward Rectified Current natural cooling, $t_A = 45^\circ\text{C}$ C-Load | 0.5 A |
| R+L-Load | 0.6 A |
| Maximum Repetitive Peak Forward Current | 6 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 30 A |
| I^2t Rating for fusing ($t < 10$ ms) | 4.5 A ² s |
| Maximum Forward Voltage per Element | 1.25 V |
| Maximum Reverse Current at 25°C | 10 μA |
| Maximum Reverse Current at 125°C | 1 mA |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





0.8 A Bridge Rectifier

40 to 380 V_{RMS}


B 40C 800
B 80C 800
B125C 800
B250C 800
B380C 800

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|---------------|---------------------|--|
| B 40C 800 (M) | 40 V | 100 V |
| B 80C 800 (M) | 80 V | 190 V |
| B125C 800 (M) | 125 V | 300 V |
| B250C 800 (M) | 250 V | 600 V |
| B380C 800 (M) | 380 V | 900 V |

M indicates Miniature Package

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------------|
| Maximum Average Forward Rectified Current natural cooling, $t_A = 45^\circ\text{C}$ C-Load | 0.8 A |
| R+L-Load | 0.9 A |
| Maximum Repetitive Peak Forward Current | 10 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 45 A |
| I^2t Rating for fusing ($t < 10$ ms) | 10 A ² s |
| Maximum Forward Voltage per Element | 1.0 V |
| Maximum Reverse Current at 25°C | 10 μA |
| Maximum Reverse Current at 125°C | 1 mA |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Bridge Rectifier

40 to 380 V_{RMS}


B 40C 1000
B 80C 1000
B125C 1000
B250C 1000
B380C 1000

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|----------------|---------------------|--|
| B 40C 1000 (M) | 40 V | 100 V |
| B 80C 1000 (M) | 80 V | 190 V |
| B125C 1000 (M) | 125 V | 300 V |
| B250C 1000 (M) | 250 V | 600 V |
| B380C 1000 (M) | 380 V | 900 V |

M indicates Miniature Package

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------------|
| Maximum Average Forward Rectified Current natural cooling, $t_A = 45^\circ\text{C}$ C-Load | 1.0 A |
| R+L-Load | 1.2 A |
| Maximum Repetitive Peak Forward Current | 10 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 45 A |
| I^2t Rating for fusing ($t < 10$ ms) | 10 A ² s |
| Maximum Forward Voltage per Element | 1.0 V |
| Maximum Reverse Current at 25°C | 10 μA |
| Maximum Reverse Current at 125°C | 1 mA |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





1.5 A Bridge Rectifier


40 to 380 V_{RMS}

B 40C 1500
B 80C 1500
B125C 1500
B250C 1500
B380C 1500

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|------------|---------------------|--|
| B 40C 1500 | 40 V | 100 V |
| B 80C 1500 | 80 V | 190 V |
| B125C 1500 | 125 V | 300 V |
| B250C 1500 | 250 V | 600 V |
| B380C 1500 | 380 V | 900 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------------|
| Maximum Average Forward Rectified Current natural cooling, $t_A = 45^\circ\text{C}$ C-Load | 1.5 A |
| R+L-Load | 1.6 A |
| Maximum Repetitive Peak Forward Current | 10 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 45 A |
| I^2t Rating for fusing ($t < 10$ ms) | 10 A ² s |
| Maximum Forward Voltage per Element | 1.0 V |
| Maximum Reverse Current at 25°C | 10 μA |
| Maximum Reverse Current at 125°C | 1.0 mA |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





1.5 A Bridge Rectifier


40 to 380 V_{RMS}

B 40C 1500C
B 80C 1500C
B125C 1500C
B250C 1500C
B380C 1500C

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|-------------|---------------------|--|
| B 40C 1500C | 40 V | 100 V |
| B 80C 1500C | 80 V | 190 V |
| B125C 1500C | 125 V | 300 V |
| B250C 1500C | 250 V | 600 V |
| B380C 1500C | 380 V | 900 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------------|
| Maximum Average Forward Rectified Current natural cooling, $t_A = 45^\circ\text{C}$ C-Load | 1.5 A |
| R+L-Load | 1.6 A |
| Maximum Repetitive Peak Forward Current | 12 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 100 A |
| I^2t Rating for fusing ($t < 10$ ms) | 50 A ² s |
| Maximum Forward Voltage per Element | 0.95 V |
| Maximum Reverse Current at 25°C | 10 μA |
| Maximum Reverse Current at 125°C | 1 mA |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1 A Bridge Rectifier

50 to 1000 V


WL
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|-----------|---------------------|--|
| WL005 (M) | 35 V | 50 V |
| WL02 (M) | 140 V | 200 V |
| WL04 (M) | 280 V | 400 V |
| WL06 (M) | 420 V | 600 V |
| WL08 (M) | 560 V | 800 V |
| WL10 (M) | 700 V | 1000 V |

M indicates Miniature Package

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|----------------------|
| Maximum Average Forward Rectified Current | 1.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 30 A |
| Maximum Forward Voltage per Element at 1 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 10 μ A |
| Maximum Reverse Current at 100°C | 1.0 mA |
| I ² t Rating for fusing (t < 10 ms) | 4.5 A ² s |
| Typical Thermal Resistance R _{th J-A} | 25 °C/W |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





1.5 A Bridge Rectifier

50 to 1000 V


W
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|----------|---------------------|--|
| W005 (M) | 35 V | 50 V |
| W02 (M) | 140 V | 200 V |
| W04 (M) | 280 V | 400 V |
| W06 (M) | 420 V | 600 V |
| W08 (M) | 560 V | 800 V |
| W10 (M) | 700 V | 1000 V |

M indicates Miniature Package Suffix A indicates Avalanche Characteristic.

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|--------------------|
| Maximum Average Forward Rectified Current | 1.5 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage per Element at 1 A _{DC} | 1.0 V |
| Maximum Reverse Current at 25°C | 10 μA |
| Maximum Reverse Current at 100°C | 1.0 mA |
| I ² t Rating for fusing (t < 10 ms) | 5 A ² s |
| Typical Thermal Resistance R _{th J-A} | 25 °C/W |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





2 A Bridge Rectifier


50 to 1000 V

2W Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|-------|---------------------|--|
| 2W005 | 35 V | 50 V |
| 2W02 | 140 V | 200 V |
| 2W04 | 280 V | 400 V |
| 2W06 | 420 V | 600 V |
| 2W08 | 560 V | 800 V |
| 2W10 | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|--------------------|
| Maximum Average Forward Rectified Current | 2.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage per Element at 1 A _{DC} | 1.0 V |
| Maximum Reverse Current at 25°C | 10 µA |
| Maximum Reverse Current at 100°C | 1 mA |
| I ² t Rating for fusing (t < 10 ms) | 5 A ² s |
| Typical Thermal Resistance R _{th J-A} | 25 °C/W |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





1.5 A Bridge Rectifier

50 to 1000 V


KBP
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|--------|---------------------|--|
| KBP005 | 35 V | 50 V |
| KBP02 | 140 V | 200 V |
| KBP04 | 280 V | 400 V |
| KBP06 | 420 V | 600 V |
| KBP08 | 560 V | 800 V |
| KBP10 | 700 V | 1000 V |

Suffix A Indicates Avalanche Characteristic

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.


| | |
|--|--------------------|
| Maximum Average Forward Rectified Current | 1.5 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage per Element at 1 A _{OC} | 1.0 V |
| Maximum Reverse Current at 25°C | 10 µA |
| Maximum Reverse Current at 100°C | 1 mA |
| I ² t Rating for fusing (t < 10 ms) | 5 A ² s |
| Typical Thermal Resistance R _{th J-A} | 25 °C/W |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic



Fig. 2 — Forward derating curve





2 A Bridge Rectifier


50 to 1000 V

2KBP
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|---------|---------------------|--|
| 2KBP005 | 35 V | 50 V |
| 2KBP02 | 140 V | 200 V |
| 2KBP04 | 280 V | 400 V |
| 2KBP06 | 420 V | 600 V |
| 2KBP08 | 560 V | 800 V |
| 2KBP10 | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|--------------------|
| Maximum Average Forward Rectified Current | 2 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage per Element at 1 A _{DC} | 1.0 V |
| Maximum Reverse Current at 25°C | 10 µA |
| Maximum Reverse Current at 100°C | 1.0 mA |
| I ² t Rating for fusing (t < 10 ms) | 5 A ² s |
| Typical Thermal Resistance R _{thJ-A} | 25 °C/W |
| Operating Temperature Range | −55 to +125°C |
| Storage Temperature Range | −55 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





3 A Bridge Rectifier

50 to 1000 V


KBL Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|--------|---------------------|--|
| KBL005 | 35 V | 50 V |
| KBL02 | 140 V | 200 V |
| KBL04 | 280 V | 400 V |
| KBL06 | 420 V | 600 V |
| KBL08 | 560 V | 800 V |
| KBL10* | 700 V | 1000 V |

* Limited Production

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|----------------------|
| Maximum Average Forward Rectified Current | 3 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 200 A |
| Maximum Forward Voltage per Element at 3 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 10 µA |
| Maximum Reverse Current at 100°C | 1 mA |
| I ² t Rating for fusing (t < 10 ms) | 200 A ² s |
| Typical Thermal Resistance R _{th J-A} | 15 °C/W |
| Operating Temperature Range | -55 to +150°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





3 A Bridge Rectifier

50 to 1000 V


KBPC
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|---------|---------------------|--|
| KBPC005 | 35 V | 50 V |
| KBPC02 | 140 V | 200 V |
| KBPC04 | 280 V | 400 V |
| KBPC06 | 420 V | 600 V |
| KBPC08 | 560 V | 800 V |
| KBPC10 | 700 V | 1000 V |

Also available in Avalanche and Fast Recovery Characteristics.

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|-----------------------|
| Maximum Average Forward Rectified Current | 3.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage per Element at 1.5 A _{DC} | 1.1 V |
| Maximum Reverse Current at 25°C | 10 µA |
| Maximum Reverse Current at 100°C | 1 mA |
| I ² t Rating for fusing (t < 10 ms) | 12.5 A ² s |
| Typical Thermal Resistance R _{th J-C} | 12.5 °C/W |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 – Typical forward characteristic





Fig. 2 – Forward derating curve





3 A Bridge Rectifier

50 to 1000 V


KBPC1
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|-----------|---------------------|---|
| KBPC1 005 | 35 V | 50 V |
| KBPC1 02 | 140 V | 200 V |
| KBPC1 04 | 280 V | 400 V |
| KBPC1 06 | 420 V | 600 V |
| KBPC1 08 | 560 V | 800 V |
| KBPC1 10 | 700 V | 1000 V |

Also available in Avalanche and Fast Recovery Characteristics.

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|-----------------------|
| Maximum Average Forward Rectified Current | 3.0 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 50 A |
| Maximum Forward Voltage per Element at 1 A _{DC} | 1.0 V |
| Maximum Reverse Current at 25°C | 10 µA |
| Maximum Reverse Current at 100°C | 1 mA |
| I ² t Rating for fusing (t < 10 ms) | 12.5 A ² s |
| Typical Thermal Resistance R _{th J-C} | 15 °C/W |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





8 A Bridge Rectifier


50 to 1000 V

KBPC6
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|-----------|---------------------|--|
| KBPC6 005 | 35 V | 50 V |
| KBPC6 02 | 140 V | 200 V |
| KBPC6 04 | 280 V | 400 V |
| KBPC6 06 | 420 V | 600 V |
| KBPC6 08 | 560 V | 800 V |
| KBPC6 10 | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------------|
| Maximum Average Forward Rectified Current | 8 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 125 A |
| Maximum Forward Voltage per Element at 3 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 10 µA |
| Maximum Reverse Current at 100°C | 1 mA |
| I ² t Rating for fusing (t < 10 ms) | 78 A ² s |
| Typical Thermal Resistance R _{th J-C} | 5 °C/W |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +125°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





8 A Bridge Rectifier


50 to 1000 V

KBPC6t
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|------------|---------------------|--|
| KBPC6 005t | 35 V | 50 V |
| KBPC6 02t | 140 V | 200 V |
| KBPC6 04t | 280 V | 400 V |
| KBPC6 06t | 420 V | 600 V |
| KBPC6 08t | 560 V | 800 V |
| KBPC6 10t | 700 V | 1000 V |

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------------|
| Maximum Average Forward Rectified Current | 8 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 125 A |
| Maximum Forward Voltage per Element at 3 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 10 μ A |
| Maximum Reverse Current at 100°C | 1 mA |
| I ² t Rating for fusing (t < 10 ms) | 78 A ² s |
| Typical Thermal Resistance R _{th J-C} | 5 °C/W |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +125°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





8 A Bridge Rectifier

50 to 1000 V


**KBPC8
Series**

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|------------------|---------------------|---|
| KBPC8 005 | 35 V | 50 V |
| KBPC8 02 | 140 V | 200 V |
| KBPC8 04 | 280 V | 400 V |
| KBPC8 06 | 420 V | 600 V |
| KBPC8 08 | 560 V | 800 V |
| KBPC8 10 | 700 V | 1000 V |

Also available in Avalanche and Fast Recovery Characteristics.

CASE OUTLINE



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|---------------------|
| Maximum Average Forward Rectified Current | 8 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 125 A |
| Maximum Forward Voltage per Element at 3 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 10 µA |
| Maximum Reverse Current at 100°C | 1.0 mA |
| I ² t Rating for fusing (t < 10 ms) | 78 A ² s |
| Typical Thermal Resistance R _{th J-C} | 5 °C/W |
| Operating Temperature Range | -55 to +125°C |
| Storage Temperature Range | -55 to +150°C |

RATING AND CHARACTERISTIC CURVES



Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





10 A Bridge Rectifier

50 to 1000 V


KBPC10 Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|------------|---------------------|--|
| KBPC10 005 | 35 V | 50 V |
| KBPC10 02 | 140 V | 200 V |
| KBPC10 04 | 280 V | 400 V |
| KBPC10 06 | 420 V | 600 V |
| KBPC10 08 | 560 V | 800 V |
| KBPC10 10* | 700 V | 1000 V |

*Limited Production

CASE OUTLINE



Suffix indication: **D** Insulated Case **L** Position Lug **W** Wire Leads

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|--|----------------------|
| Maximum Average Forward Rectified Current | 10 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 200 A |
| Maximum Forward Voltage per Element at 5 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 10 µA |
| Maximum Reverse Current at 100°C | 1 mA |
| I ² t Rating for fusing (t < 10 ms) | 200 A ² s |
| Typical Thermal Resistance R _{th J-C} | 2.5 °C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +175°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





35 A Bridge Rectifier

50 to 1000 V


KBPC35
Series

VOLTAGE RATINGS

| Type | Maximum RMS Voltage | Maximum Recurrent Peak Reverse Voltage |
|------------|---------------------|--|
| KBPC35 005 | 35 V | 50 V |
| KBPC35 02 | 140 V | 200 V |
| KBPC35 04 | 280 V | 400 V |
| KBPC35 06 | 420 V | 600 V |
| KBPC35 08* | 560 V | 800 V |
| KBPC35 10* | 700 V | 1000 V |

*Limited Production

CASE OUTLINE



Suffix indication: D Insulated Case L Position Lug W Wire Leads

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature and 10 mm lead length unless otherwise specified.
Single-phase, half-wave, 50 Hz, resistive or inductive load.

| | |
|---|----------------------|
| Maximum Average Forward Rectified Current | 35 A |
| Peak Forward Surge Current, 10 ms Single Half Sine Wave | 400 A |
| Maximum Forward Voltage per Element at 17.5 A _{DC} | 1.2 V |
| Maximum Reverse Current at 25°C | 10 µA |
| Maximum Reverse Current at 100°C | 1.0 mA |
| I ² t Rating for fusing (t < 10 ms) | 800 A ² s |
| Typical Thermal Resistance R _{th J-C} | 2.5 °C/W |
| Operating Temperature Range | -65 to +175°C |
| Storage Temperature Range | -65 to +175°C |

RATING AND CHARACTERISTIC CURVES

Fig. 1 — Typical forward characteristic





Fig. 2 — Forward derating curve





Quality Assurance

Customer Information

Introduction

Quality and Reliability Engineering of the Discrete Semiconductor Division extends its services to the areas of materials and product analysis, reliability evaluation, quality inspection and development of new test methods.

Headquartered in New York, it assumes the responsibility for the development, implementation and administration of the Quality Assurance programs for all operations of the Division, both domestic and foreign.

Additionally at our manufacturing plants, rigid and extensive in-process quality controls are utilized such that the quality and reliability of our products are consistent and repeatable. The laboratories of our facilities are equipped with the latest high-level instrumentation and staffed with skilled technicians and engineers.

Professional expertise and the most modern scientific equipment maintains our position of excellence and leadership as the foremost producer of semiconductor devices, and assures that the quality levels of our products, from inspection and test of raw materials to final approval of completed devices, meet the highest standards of the industry.

We offer . . .

- Top-flight specialists and modern facilities.
- Experienced Test Engineers and Reliability Engineers.
- A fully equipped laboratory able to perform almost any type of scientific investigation.

Services of the Materials and Device Analysis Section

- Testing, inspection and evaluation of materials and products utilizing the facilities of the electrical, mechanical, high-reliability and chemical analysis departments of our laboratories.
- Research and development of testing methods.
- Inspection of materials to ensure compliance by suppliers and contractors to specifications.
- Failure analysis to determine the cause of breakdown in materials or components.
- Qualification testing of military devices in accordance with applicable military specifications. The laboratories are qualified to perform testing to MIL-S-19500, MIL-STD-750, MIL-STD-202, and also are qualified to MIL-STD-883 tests under MIL-M-38510. Qualification approvals (QPL listing) were awarded by the United States, Canadian and West German Departments of Defense.
- A continuing program of military reliability (JAN-TX) also is in progress to assure conformance to the requirements for aerospace and the military.



TEST CONDITIONS

Operational Life

Conditions: Rated voltage, rated current, for 1000 hours at 25°C.

Solderability

Conditions: 95 % coverage within 1.2 mm of device body.

DC Blocking

Conditions: Rated voltage for 1000 hours at 100°C in inert environment.

Temperature Cycling

Conditions: -65°C to +175°C.

Storage Life

Conditions: 100°C for 1000 hours in inert environment.

Shock

Conditions: 5 blows of 1500 g's.

Lead Pull

Conditions: Axial pull to destruction.

Vibration (Constant)

Conditions: 20 g's at 60 Hz \pm 20 Hz.

Lead Fatigue

Conditions: Number of 90-degree bends with 0.5 kg weight attached to lead.

Acceleration

Conditions: 20,000 g's.

Moisture Resistance

Conditions: 85°C, 85 % Relative Humidity for 10 days.

Salt Atmosphere

Conditions: 5 % solution for 24 hours at 35°C.

Flammability

Conditions: Encapsulating compound, General Instrument's proprietary formulas, GI-4B or GI-5A is self-extinguishing, recognized and registered by Underwriters' Laboratories, U.S.

Moisture Capabilities of Diodes, Rectifiers, and Bridges

Conditions: T_a = 25°C to 85°C in Operating Mode Suitability Tested by Reverse Leakage Current at Rated Voltage

| Device | Yearly Average | | 100 % RH 30 Days Continuous | 95 % RH 30 Days Continuous | Balance Occasional 100 % RH |
|--------------|-------------------|-------------------|--------------------------------|-------------------------------|--------------------------------|
| | \geq 95 % RH | \geq 85 % RH | | | |
| GPD | ■ | | ■ | | ■ |
| GPR | ■ | | ■ | | ■ |
| GP10 | | ■ | ■ | | ■ |
| GP15 | | ■ | ■ | | ■ |
| GP20 | ■ | | ■ | | ■ |
| GP30 | ■ | | ■ | | ■ |
| DO41 | | ■ | | ■ | ■ |
| WO/WL Series | ■ | | ■ | | ■ |
| KBP Series | ■ | | | ■ | ■ |
| KBPC Series | ■ | | ■ | | ■ |
| KBL Series | ■ | | | ■ | ■ |

Description of HI-REL Test Capabilities

- **Barometric Pressure:** This equipment simulates low atmospheric pressure encountered in non-pressurized environments up to 200,000 feet.
- **Humidity:** This equipment evaluates units in an accelerated manner, and monitors the effects of their resistance to high humidity and heat conditions. Typical RH of 90 to 98 % is achieved.
- **Salt (Spray) and Salt Atmosphere:** The equipment provides an accelerated laboratory corrosion test simulating the effects of seacoast atmospheres. Salt concentration and velocity per day can be maintained between 10,000 and 50,000 mgm/m²/day. Salt Atmosphere – Salt spray 5 % – 20 % salt solution.
- **Thermal Shock Temp.-Cycling:** This test determines the resistance of devices to exposure at extremely high and low temperatures. Chamber limits – 74°C to 250°C.
- **Mass Spectrometer Leak Detector (Fine Leak):** To determine the effectiveness (or the hermeticity) of the seal on devices with internal cavities which are evacuated or contain air or gas. Machine limits $1 \cdot 10^{-9}$ to $10 \cdot 10^{-6}$ atm.
- **Gross Leak:** Determine seal leak greater than $10 \cdot 10^{-6}$ ATM cc/Sec.
- **Constant Acceleration:** Determines the effects of a centrifugal force on devices up to 700,000 g under space environment (refrigerated vacuum).
- **Shock:** Subjects the devices to conditions resulting from sudden applied forces or abrupt changes in motion produced by rough handling, transportation or field operation from 10 to 4,500 g.
- **Vibration Fatigue:** Tests the effects of vibration within the frequency range of 60 Hz at 0–70 g.
- **Vibration Noise:** Measures the amount of electrical noise produced by the devices under vibration from 0–5 kHz and 0–70 g.
- **Vibration Variable Frequency:** Tests the effect of the devices to vibration in specified frequency ranges from 0–5 kHz at 0–70 g.
- **Non-Operating Life:** To determine the effects on devices at elevated temperatures. Temperature ranges up to 300°C.
- **Operating Life Test:** To operate the devices under intended condition to screen and eliminate marginal devices and eliminate mortality.
 - Steady State Operating Life.
 - Reverse Bias Operating Life.
 - Intermittent Operating Life.
- **Solderability – Lead Integrity (Lead Tension):** Determine the solderability on all devices from 0 to 400°C. Lead Tension – Designed to check the capabilities of the devices to withstand straight pulls.
- **Lead Integrity (bending stress):** Check the quality of leads, welds and seals of the devices to withstand bends under specific weights.
- **Lead Integrity (lead torque):** Check the devices, leads and seals for resistance to twisting motion. Equipment limits from .5 cmkg to 100 mkg.
- **Hi-Power Microscopic Inspection:** Examine internal and external construction of our devices up to 600 times.
- **Bond Strength:** This determines strength of lead bonding between the active area of the device and connecting package leads.

HI-Reliability, Military, JAN and JANTX Devices

Where application demand higher reliability parts than our normal commercial units, there are two categories of product screening which are available as a stock item: JAN and JANTX. When reliability classes are required for use in military applications, on other very critical areas which are not for military use but require same special processing the JAN and JANTX devices are available. Where possible it is advantageous to specify a JAN or JANTX device rather than a special screening procedure because the JAN and JANTX parts are already processed as a standard stock item and do not place an additional load on the factory as will a small speciality requirement.

Reliability of each individual JAN and JANTX lot is accepted when sample tested, versus a commercial lot where a product line is tested for reliability on a periodic basis. JAN devices are processed according to a sample basis, where JANTX devices have 100 % processing and conditioning prior to release to the customer. Both JAN and JANTX devices are lot accepted by undergoing tests including electrical, solderability, thermal shock, terminal strength, moisture resistance, shock, vibration, acceleration, salt atmosphere, surge, storage and operating life. JAN parts are inspected electrically and shipped to the customer. All JANTX devices go through an additional environmental screening consisting of:

- Stabilization Bake for a minimum of 24 hours.
- Temperature Cycling of 10 complete cycles.
- Acceleration of 20,000 G's.
- Fine Leak.
- Gross Leak.
- Initial Electrical with data.
- Operating Life Burn-In for a minimum of 96 hours.
- Post Electrical with data.
- Delta Calculations on leakage current and forward voltage drop.

These devices are being processed on a daily ongoing basis. This in turn makes for a hi-reliability 100 % screened part readily available as an off-the-self item. A list of available parts and their packages is seen on page 49 under Glass Passivated Rectifier.



REEL PACKAGING (Standard Specification)

| COMPONENT CASE TYPE * | UNITS PER REEL | COMPONENT SPACING "A" FIG. 1 | | TAPE SPACING "B" FIG. 1 | | APPROX. REEL DIMENSION "C" FIG. 4 | | MAX OFF ALIGNMENT "E" FIG. 1 | | APPROX. GROSS WEIGHT PER REEL PACKED | |
|-----------------------|----------------|------------------------------|------|-------------------------|------|-----------------------------------|----|------------------------------|-----|--------------------------------------|-----|
| | | in. | mm | in. | mm | in. | mm | in. | mm | lbs. | kg. |
| DO15 | 3500 | .200 | 5.04 | 2.0 | 50.8 | 2.8 | 71 | .047 | 1.2 | 5.06 | 2.3 |
| DO27 | 1200 | .375 | 9.5 | 2.0 | 50.8 | 2.8 | 71 | .047 | 1.2 | 3.52 | 1.6 |
| DO27A/C | 1200 | .375 | 9.5 | 2.0 | 50.8 | 2.8 | 71 | .047 | 1.2 | 5.06 | 2.3 |
| DO41 | 5000 | .200 | 5.04 | 2.0 | 50.8 | 2.8 | 71 | .047 | 1.2 | 5.76 | 2.6 |
| G1 | 4000 | .200 | 5.04 | 2.0 | 50.8 | 2.8 | 71 | .047 | 1.2 | 5.76 | 2.6 |
| G3 | 1500 | .375 | 9.5 | 2.0 | 50.8 | 2.8 | 71 | .047 | 1.2 | 4.8 | 2.2 |
| GPD | 4000 | .200 | 5.04 | 2.0 | 50.8 | 2.8 | 71 | .047 | 1.2 | 3.74 | 1.7 |




Fig. 1




Fig. 2




Fig. 3




Fig. 4



REEL PACKAGING (Metric Specification)

| COMPONENT CASE TYPE * | UNITS PER REEL | COMPONENT SPACING "A" FIG. 1 | | TAPE SPACING "B" FIG. 1 | | APPROX. REEL DIMENSION | | MAX OFF ALIGNMENT "E" FIG. 1 | | APPROX. GROSS WEIGHT PER REEL PACKED | |
|-----------------------|----------------|------------------------------|----|-------------------------|------|------------------------|----|------------------------------|-----|--------------------------------------|-----|
| | | in. | mm | in. | mm | in. | mm | in. | mm | lbs. | kg. |
| DO15 | 3500 | .197 | 5 | 2.062 | 52.4 | 2.8 | 71 | .047 | 1.2 | 5.06 | 2.3 |
| DO27 | 1200 | .394 | 10 | 2.062 | 52.4 | 2.8 | 71 | .047 | 1.2 | 3.52 | 1.6 |
| DO27A | 1200 | .394 | 10 | 2.062 | 52.4 | 2.8 | 71 | .047 | 1.2 | 5.06 | 2.3 |
| DO41 | 5000 | .197 | 5 | 2.062 | 52.4 | 2.8 | 71 | .047 | 1.2 | 5.76 | 2.6 |
| G1 | 4000 | .197 | 5 | 2.062 | 52.4 | 2.8 | 71 | .047 | 1.2 | 5.76 | 2.6 |
| G3 | 1500 | .394 | 10 | 2.062 | 52.4 | 2.8 | 71 | .047 | 1.2 | 4.8 | 2.2 |
| GPD | 4000 | .197 | 5 | 2.062 | 52.4 | 2.8 | 71 | .047 | 1.2 | 3.74 | 1.7 |

* Rectifier type numbers versus product families (GPD, G1 etc.) please see Numerical Index page 6/7



PACKAGING SPECIFICATIONS

Bulk Packaging Diodes and Rectifiers

| Device Type | Box Size | | Quantity No. of Pieces | Approx. Gross Weight | |
|--------------------------------|-------------------|-------------------|------------------------------|----------------------------|-------------|
| | in. | cm | | lbs. | kg |
| RECTIFIERS | | | | | |
| DO41, GP10, GPD | 8 x 3.5 x 1 | 20.3 x 8.8 x 2.54 | 1000 | .81/.83/.52 | .37/.38/.24 |
| GP15, G1 | 8 x 3.5 x 1 | 20.3 x 8.8 x 2.54 | 500 | 0.55 | 0.25 |
| DO27, P100, P300, GP20 | 12 x 3.2 x 2.5 | 30.4 x 8.1 x 6.3 | 1000 | 1.76/2.86/1.78 | .80/1.3/.81 |
| P600 | 12 x 3.2 x 2.5 | 30.4 x 8.1 x 6.3 | 500 | 2.64 | 1.2 |
| DO27A/C, GP30, GP25, G3 | 12 x 3.2 x 2.5 | 30.4 x 8.1 x 6.3 | 1000 | 2.86 | 1.3 |
| AR25 | Plastic Bag | | 200 | 7.26 | 3.3 |
| HVPR10-1 | 7 x 5 x 3.4 | 17.7 x 12.8 x 8.6 | 50 | 4.84 | 2.2 |
| HVPR15-4 | 7.8 x 7.8 x 1.8 | 19.8 x 19.8 x 4.5 | 100 | 2.86 | 1.3 |
| HVPR20-80 | 7.5 x 10 x 2.2 | 19 x 25.4 x 5.5 | 200 | 0.66 | 0.3 |
| BRIDGES | | | | | |
| B...C800 | 10.5 x 2.75 x 2.5 | 26.7 x 7 x 6.3 | 250 | 1.21 | 0.55 |
| B...C1000 | 10.5 x 2.75 x 2.5 | 26.7 x 7 x 6.3 | 250 | 1.21 | 0.55 |
| B...C1500 | 10.5 x 2.75 x 2.5 | 26.7 x 7 x 6.3 | 250 | 1.21 | 0.55 |
| W, WOM, WL, 2W | 10.5 x 2.75 x 2.5 | 26.7 x 7 x 6.3 | 250 | 1.21 | 0.55 |
| KBP | 8.3 x 6.5 x 2.3 | 21 x 16.5 x 5.8 | 200 | 0.77 | 0.35 |
| KBL | 9 x 6 x 2.2 | 22.8 x 15.2 x 5.5 | 200 | 3.08 | 1.3 |
| KBF | 6 x 6 x 2 | 15.2 x 15.2 x 5.1 | 100 | 1.54 | 0.7 |
| KBPC8 | 8.8 x 8.8 x 1.8 | 22.3 x 22.3 x 4.5 | 200 | 3.52 | 1.6 |
| KBPC | 8.8 x 8.8 x 1.2 | 21 x 22.3 x 3 | 200 | 2.86 | 1.3 |
| KBPC1, KBPC6 | 4.8 x 7.8 x 1.8 | 19.8 x 19.8 x 4.5 | 200 | 1.87/.66 | .85/.3 |
| KBPC3 | 8 x 6.3 x 2.2 | 20.3 x 16 x 5.5 | 50 | 3.74 | 1.7 |
| KBPC10/25/35 With Faston Term. | 10 x 6.3 x 1.7 | 25.4 x 16 x 4.3 | 50 | 3.08 | 1.4 |
| KBPC10/25/35 With Leads | 10 x 6.3 x 1.7 | 25.4 x 16 x 4.3 | 40 | 4.07 | 1.85 |

A. Tape and Reel Packaging of Axial Lead Units

Axial lead units are packed in accordance with EIA Standard RS-296-C plus specifications given below and the diagrams given below which are referred to in the specifications.

1. Reeling

- Component leads are positioned between tapes as shown in Fig. 1.
- A minimum of 30 cm of tape is provided before the first unit and after the last unit on the reel.
- 23 kg kraft paper is wound between layers of components and extended beyond the tape sufficiently to protect the components.
- A maximum of ten components may be omitted from any 3 m length and a maximum of two consecutive components may be missing if this omission is followed by six consecutive components.

2. Tolerances

- Bending of components leads is held to the off-alignment dimension shown in Column E and indicated by E in Fig. 1.
- The C dimension of Fig. 3 is between 3 mm and 6 mm greater than the length of the component involved. See F, Fig. 1.
- The units are held between an perpendicular to a colored tape and a white tape. Polarized units are oriented in one direction with the cathode lead being held by the colored type. The spacing between leads is shown in Column A in the table and A in Fig. 1.
- Units are centered between tapes 1.2 mm but individual units may deviate from center of row ± 0.7 mm. See Fig. 1.

NOTES



GENERAL INSTRUMENT EUROPE



EUROPEAN HEADQUARTERS

52 Rue de Faubourg · Saint Honoré · 75008 Paris
Tel.: 2665634 · Telex: 641078

EUROPEAN APPLICATION LABORATORY

Neumarkter Straße 61 · 8000 München 80
Tel.: 089/491004 · Telex: 05-24523

EUROPEAN SALES OFFICES

FRANCE

General Instrument France
11/13, Rue Gandon · 75013 Paris
Tel.: 5848731 · Telex: 260766

GERMANY, AUSTRIA AND SWITZERLAND

General Instrument Deutschland GmbH
Neumarkter Str. 61 · 8000 München 80
Tel.: 089/491004 · Telex: 05-24523

ITALY

C.P. Clare Elettronica SRL · Divisione Semiconduttori
Via Anfossi 32 · Milano
Tel.: 02/5465514, 02/5469187 · Telex: 320348

UNITED KINGDOM

General Instrument U.K.Ltd.
Cock Lane 2 · High Wycombe-Buckinghamshire
Tel.: 445311 · Telex: 83691

OTHER COUNTRIES

General Instrument Deutschland GmbH
Neumarkter Str. 61 · 8000 München 80
Tel.: 089/491004 · Telex: 05-24523

GENERAL INSTRUMENT CORPORATION

DISCRETE SEMICONDUCTOR DIVISION

600 West John Street, Hicksville, N.Y. 11802, (516) 733-3333
TWX: 510-221-1865

